

v1.0.0

REST API DOCUMENTATION

Genea Access Control API – v1.0.0

Genea Access Control Platform

REST / JSON

Bearer Auth

HID Hardware

Mercury Hardware

Support: acsupport@getgenea.com

© Genea Access Control API — Confidential

Introduction

The Genea Access Control API provides programmatic access to manage users, locations, doors, cards, schedules, access groups, controllers, and events. All endpoints use REST conventions with JSON payloads.

Authentication	Hardware Support
All requests require Bearer token authentication.	Genea supports two hardware platforms:
Authorization: {token_type} {api_token}	HID — VertX / Alio controllers
Content-Type: application/json	Mercury — LP / EP / MR controllers. Mercury endpoints are prefixed with /mercury/

COMMON VARIABLES

Variable	Description
{api_token}	Token-based authentication key for API access
{customer_uuid}	Unique identifier for your customer portal
{location_uuid}	Unique identifier for a specific location
{api_url}	Base URL for all API requests
{token_type}	Token prefix, typically "Bearer"
{user_uuid}	Unique identifier for a specific user

Table of Contents

01. User 14 endpoints

GET Me
GET List my locations
POST Create user
GET Get user
PUT Update user
DELETE Delete user
DELETE Delete avatar
PUT Upload avatar
GET List users
POST Add user in location
PUT Edit user in location
DELETE Delete user in location
PUT Update User Card Access
GET List my location v2

02. Location 5 endpoints

GET Get location
GET Get location settings
PUT Update location
PUT Upload location logo
PUT Update location settings

03. Tenant 4 endpoints

GET List tenants
GET Get tenants
POST Add tenant
PUT Update tenant

04. Door Group 5 endpoints

GET List door groups
GET Get door group
POST Add door group
PUT Update door group
DELETE Delete door group

05. Schedule 10 endpoints

HID
GET List schedules
GET Get schedule
POST Add schedule
PUT Update schedule
DELETE Delete schedule
Mercury
GET List schedules
GET Get Schedule
POST Add schedule
PUT Update schedule
DELETE Delete schedule

06. Access Group 10 endpoints

HID
GET List access groups
GET Get access group
POST Add access group

PUT Update access group
 DELETE Delete access group
 Mercury
 GET List access groups
 GET Get access group
 POST Add access group
 PUT Update access group
 DELETE Delete access group

07. Card Set

3 endpoints

HID
 GET List Card Sets
 Mercury
 GET List Card Formats
 GET Get Card Format

08. Card

13 endpoints

HID
 GET List Cards By Property
 GET List Cards By User
 GET Get card
 POST Add card – Mobile
 POST Add card – Physical
 PUT Update card
 DELETE Delete card
 Mercury
 GET List Cards
 GET Get card
 POST Add card – Physical
 POST Add card – Mobile
 PUT Update card
 DELETE Delete card

09. Controller

10 endpoints

HID
 GET List controllers
 GET Get controller
 POST Add controller
 PUT Update controller
 DELETE Delete controller
 Mercury
 GET List controllers
 GET Get controller
 POST Add controller
 PUT Update controller
 DELETE Delete controller

10. Interface

10 endpoints

HID
 GET List interfaces
 GET Get interface
 POST Add interface
 PUT Update interface
 DELETE Delete interface
 Mercury
 GET List interface panels
 GET Get interface panel
 POST Add interface panel
 PUT Update interface panel

DELETE Delete interface panel

11. AUX Relay Operations

3 endpoints

PUT AUX relay on
PUT AUX relay off
PUT AUX relay restart

12. Reader(Door)

15 endpoints

HID
GET List readers for location
GET Get reader
POST Add reader
PUT Update reader
DELETE Delete reader
 Mercury
GET List doors
GET Get door
POST Add door
PUT Update door - Basic
PUT Update Door - Hardware
PUT Update Door - Monitor
PUT Update Door - Rex
PUT Update Door - Access
PUT Update Door - Unlock Schedule
DELETE Delete door

13. Remote Operations

12 endpoints

HID
GET Get emergency status
PUT Door - Lock
PUT Door - Unlock
PUT Door - Quick Grant
PUT Emergency hold open
PUT Emergency hold close
 Mercury
GET Get emergency status
PUT Door - Lock
PUT Door - Unlock
PUT Door - Quick Grant
PUT Emergency hold open
PUT Emergency hold close

14. Event

3 endpoints

HID
GET List event
 Mercury
GET List audit event
GET List access event

15. Statistics

6 endpoints

GET Get today attendance
GET Get attendance - Monthly
GET Door scans - Busy doors
GET Hourly heatmap - Access grants
GET Hourly heatmap - Unique users
GET Early scans

16. Pin

10 endpoints

HID

- [GET](#) Get PIN
- [POST](#) Generate PIN
- [POST](#) Create PIN
- [PUT](#) Update PIN
- [DELETE](#) Delete PIN
- Mercury
- [GET](#) Get PIN
- [POST](#) Generate PIN
- [POST](#) Create PIN
- [PUT](#) Update PIN
- [DELETE](#) Delete PIN

17. VMS Copy

[1 endpoints](#)

- Cisco Meraki
- [GET](#) Meraki: Get Camera-Door Mappings

01. User

GET Me

GET `https://{{api_url}}/v1/user/me`

This api will return information about your profile.

GET List my locations

GET `https://{{api_url}}/user/me/locations`

This api will list all your locations.

POST Create user

POST `https://{{api_url}}/customer/{{customer_uuid}}/user`

This api will create new user in locations.

REQUEST BODY

```
{
  "name": "",
  "email": "",
  "department": "",
  "mobile_phone": "",
  "scim_external_id": "",
  "user_locations": [{
    "location_uuid": "",
    "tenant_uuid": "",
    "role": "",
    "access_group_uuids": [],
    "in_schedule_floor_group_uuid": "",
    "out_schedule_floor_group_uuid": ""
  }, {
    "location_uuid": "",
    "role": "",
    "access_group_uuids": []
  }]
}
```

GET Get user

GET `{{api_url}}/customer/{{customer_uuid}}/user/{{user_uuid}}`

This api will fetch the user details.

PUT Update user

PUT `https://{{api_url}}/customer/{{customer_uuid}}/user/{{user_uuid}}`

This api will update user details.

REQUEST BODY

```
{
  "name": "John Smith",
  "email": "john.smith@example.com",
  "mobile_phone": null,
  "department": "Sales",
  "is_sso_exempt": true,
  "allow_directory_sync": false
}
```

DELETE Delete user

DELETE `https://{{api_url}}/customer/{{customer_uuid}}/user/{{user_uuid}}`

This api will delete user from all locations.

DELETE Delete avatar

DELETE `https://{{api_url}}/customer/{{customer_uuid}}/user/{{user_uuid}}/avatar`

Delete user avatar

PUT Upload avatar

PUT `https://{{api_url}}/customer/{{customer_uuid}}/user/{{user_uuid}}/avatar`

Upload user avatar

Request notes:

The picture upload method accept multi-part forms. (Learn more about multi-part forms [here](#))

[Here](#) is small sample code written in Node.js

REQUEST BODY

avatar: [file]

GET List users

GET `https://{{api_url}}/customer/{{customer_uuid}}/user?user_email=&user_role=&user_department=&tena...`

This api will fetch the property's user details.

QUERY PARAMETERS

Parameter	Description
user_email	Search users by email.
user_role	Search users by specific roles.
user_department	Search users by department
tenant_name	Search user by tenant name

POST Add user in location

POST https://{api_url}/customer/{customer_uuid}/user/{user_uuid}/user_location

Add user to locations

REQUEST BODY

```
[
{
  "location_uuid": "",
  "role": "",
  "access_group_uuids": [],
  "in_schedule_floor_group_uuid": "",
  "out_schedule_floor_group_uuid": ""
},
{
  "location_uuid": "",
  "role": "",
  "access_group_uuids": []
}
]
```

PUT Edit user in location

PUT https://{api_url}/customer/{customer_uuid}/user/{user_uuid}/user_location

Add user to locations

REQUEST BODY

```
[
{
  "location_uuid": "",
  "role": "",
  "access_group_uuids": [],
  "in_schedule_floor_group_uuid": "",
  "out_schedule_floor_group_uuid": ""
},
{
  "location_uuid": "",
  "role": "",
  "access_group_uuids": []
}
]
```

DELETE Delete user in location

DELETE https://{api_url}/user_location/{user_location_uuid}

Remove user from location.

PUT Update User Card Access

This API will update (i.e. revoke/restore) user's card access on location level. Revoking the access at location level will suspend the user's all keys and access will not be granted to the user. Upon restoring the access, all keys will function normally.

Payload Parameters	Mandatory or Optional	Type	Description
is_card_access_revoked	Mandatory	boolean	true = To revoke access false = To restore access
location_uuids	Mandatory	Array	List of location_uuids in which user's card access needs to be updated

REQUEST BODY

```
{
  "is_card_access_revoked": true/false,
  "location_uuids": ["{{location_uuids}}"]
}
```

GET**List my location v2**

GET https://{{api_url}}/v2/user/me/locations?page=1&page_size=10&resource_name=USER&permission=READ&...

QUERY PARAMETERS

Parameter	Description
page	—
page_size	—
resource_name	—
permission	—
customer_uuid	—
visible_in_menu	—

SAMPLE RESPONSE — LIST MY LOCATION V2

```
{
  "meta": {
    "message": "User locations retrieved successfully.",
    "pagination": {
      "page": 1,
      "page_size": 10,
      "row_count": 1,
      "page_count": 1,
      "from": 1,
      "to": 1
    }
  },
  "data": [
    {
      "id": "43033",
      "uuid": "8d4067c0-c827-46d0-84ed-8724f224dbec",
      "role": "dev test",
      "status": "ACTIVE",
      "role_detail": {
        "name": "dev test",
        "uuid": "f8a88e86-6627-4db0-8fa0-5a919232daf8",
        "role_hierarchy": 0
      },
      "location": {
        "id": 3560,
        "uuid": "ce0ad974-7d4d-42a4-af09-b6d3222f99c1",
        "customer_uuid": "2abbb9a1-d102-4608-b798-e1c6128528e7",
        "name": "Genea",
        "client_id": 197,
        "type": "ENTERPRISE_SINGLE",
        "address_line1": "Krasnoyarsk Krai, Russia, 648483",
        "address_line2": "Suite 500",
        "city": "Kamrej",
        "state": "Krasnoyarsk Krai",
        "zip": "648483",
        "timezone": "America/New_York",
        "latitude": 62.07,
        "longitude": 100.259,
        "radius_mile": 1,
        "logo": "https://s3.amazonaws.com/dev-000-images.dev-secur.io/logo..."
      }
    }
  ]
}
```

02. Location

GET

Get location

GET https://{{api_url}}/location/{{location_uuid}}

This API will fetch location details.

GET

Get location settings

GET https://{{api_url}}/location/{{location_uuid}}/settings

This API will fetch location settings.

PUT

Update location

PUT https://{{api_url}}/location/{{location_uuid}}

This API will update location details.

REQUEST BODY

```
{
  "address_line1": "299 North Highland",
  "address_line2": "214"
}
```

PUT Upload location logo

PUT https://{{api_url}}/location/{{location_uuid}}/logo

Update location logo.

Request notes:

The picture upload method accept multi-part forms. (Learn more about multi-part forms [here](#))

[Here](#) is small sample code written in Node.js

REQUEST BODY

```
logo: [file]
```

PUT Update location settings

PUT https://{{api_url}}/location/{{location_uuid}}/settings

This API will update location settings.

REQUEST BODY

```
{
  "color": "#12578b",
  "suppress_fc_for_26_bits_keycard": true
}
```

03. Tenant

GET List tenants

GET https://{{api_url}}/location/{{location_uuid}}/tenant

This api will fetch all the tenants of location.

GET Get tenants

GET https://{{api_url}}/tenant/{{tenant_uuid}}

This api will fetch tenant details.

POST Add tenant

POST https://{{api_url}}/location/{{location_uuid}}/tenant

Create tenant.

REQUEST BODY

```
{
  "name": "Tenant 1"
  "address_line1": "299 North Highland Avenue NE",
  "address_line2": "101"
}
```

PUT Update tenant

PUT https://{{api_url}}/tenant/{{tenant_uuid}}

Update tenant details.

REQUEST BODY

```
{
  "name": "Tenant 1"
  "address_line1": "299 North Highland Avenue NE",
  "address_line2": "101"
}
```

04. Door Group

GET List door groups

GET https://{{api_url}}/location/{{location_uuid}}/door_group

This API will fetch all door groups of location.

Filter Options

property_id

Sorting options

updated_at

id

name

To apply sorting, order (ASC/DESC) and order_by(Anyone from sorting options) mandatory query params.

GET Get door group

GET https://{{api_url}}/door_group/{{door_group_id}}

This API will fetch door group details.

POST Add door group

POST https://{{api_url}}/location/{{location_uuid}}/door_group

Create door group.

REQUEST BODY

```
{
  "name": "Ground Floor",
  "description": "Receptionist Area",
  "doors": [1, 2, 3]
}
```

PUT Update door group

PUT https://{{api_url}}/door_group/{{door_group_id}}

Update door group.

REQUEST BODY

```
{
  "name": "Ground Floor",
  "description": "Receptionist Area",
  "doors": [1, 2]
}
```

DELETE Delete door group

DELETE https://{{api_url}}/door_group/{{door_group_id}}

Delete door group.

05. Schedule

HID

Schedule Related API for HID hardware.

GET List schedules

GET http://{{api_url}}/location/{{location_uuid}}/schedule?order_by=name&order=ASC

This API will fetch all schedules of location.

Filter options

property_id

Sorting options

updated_at

id

name

To apply sorting, order (ASC/DESC) and order_by (Anyone from sorting options) mandatory query params.

QUERY PARAMETERS

Parameter	Description
order_by	—
order	—

GET

Get schedule

GET https://{{api_url}}/schedule/{{schedule_id}}

This API will fetch schedule details.

POST

Add schedule

POST https://{{api_url}}/location/{{location_uuid}}/schedule

Create schedule.

REQUEST BODY

```
{
  "name": "Morning shift",
  "description": "Morning shift of working days",
  "days": [
    {
      "day_id": 1,
      "start": "09:30:00",
      "end": "18:00:00"
    },
    {
      "day_id": 2,
      "start": "09:30:00",
      "end": "13:00:00"
    },
    {
      "day_id": 2,
      "start": "13:45:00",
      "end": "15:45:00"
    },
    {
      "day_id": 3,
      "start": "08:00:00",
      "end": "15:00:00"
    },
    {
      "day_id": 4,
      "start": "09:30:00",
      "end": "18:00:00"
    },
    {
      "day_id": 5,
      "start": "10:30:00",
      "end": "19:00:00"
    }
  ]
}
```

PUT Update schedule**PUT** `https://{{api_url}}/schedule/{{schedule_id}}`

Update schedule.

REQUEST BODY

```
{
  "name": "Morning",
  "description": "Morning shift of working days",
  "days": [
    {
      "day_id": 1,
      "start": "09:30:00",
      "end": "18:00:00"
    },
    {
      "day_id": 2,
      "start": "09:00:00",
      "end": "18:00:00"
    }
  ]
}
```

DELETE Delete schedule**DELETE** `https://{{api_url}}/schedule/{{schedule_id}}`

Delete schedule.

Mercury

Schedule Related API for Mercury hardware.

GET List schedules**GET** `https://{{api_url}}/mercury/customer/{{customer_uuid}}/schedule`

This API will fetch all schedules of customer.

Filter options`location_uuid`**Sorting options**`name``updated_at`

To apply sorting, order (ASC/DESC) and order_by(Anyone from sorting options) mandatory query params.

GET Get Schedule**GET** `https://{{api_url}}/mercury/schedule/{{schedule_uuid}}`

This API will fetch schedule details.

POST Add schedule**POST** `https://{{api_url}}/mercury/customer/{{customer_uuid}}/schedule`

Create schedule.

REQUEST BODY

```
{
  "name": "Test Schedule",
  "description": "Test Schedule",
  "location_uuid": "{{location_uuid}}",
  "intervals": [{
    "start_time": "08:00:00",
    "end_time": "16:00:00",
    "monday": true,
    "tuesday": true,
    "wednesday": true,
    "thursday": true,
    "friday": false,
    "saturday": false,
    "sunday": false ,
    "holiday_group_uuids": ["{{holiday_group_uuid1}}", "{{holiday_group_uuid2}}"]
  },
  {
    "start_time": "08:00:00",
    "end_time": "10:00:00",
    "monday": false,
    "tuesday": false,
    "wednesday": false,
    "thursday": false,
    "friday": false,
    "saturday": false,
    "sunday": false ,
    "holiday_group_uuids": []
  }]
}
```

PUT Update schedule**PUT** `https://{{api_url}}/mercury/schedule/{{schedule_uuid}}`

Update schedule.

REQUEST BODY

```
{
  "name": "Test schedule",
  "description": "Test schedule",
  "intervals": [{
    "start_time": "10:00:00",
    "end_time": "09:00:00",
    "monday": false,
    "tuesday": false,
    "wednesday": false,
    "thursday": false,
    "friday": false,
    "saturday": false,
    "sunday": false ,
    "holiday_group_uuids": []
  }]
}
```

DELETE Delete schedule

DELETE https://{{api_url}}/mercury/schedule/{{schedule_uuid}}

Delete schedule.

06. Access Group

HID

Access Group Related API for HID hardware.

GET List access groups

GET https://{{api_url}}/location/{{location_uuid}}/access_group

This API will fetch all access groups of location.

Filter options

property_id

Sorting options

updated_at

id

name

To apply sorting, order (ASC/DESC) and order_by(Anyone from sorting options) mandatory query params.

GET Get access group

GET https://{{api_url}}/access_group/{{access_group_id}}

This API will fetch access group details.

POST Add access group**POST** https://{{api_url}}/location/{{location_uuid}}/access_group

Create access group.

REQUEST BODY

```
{
  "name": "Working Hours",
  "description": "description",
  "groups": [
    {
      "door_group_id": 1,
      "schedule_id": 1
    }
  ]
}
```

PUT Update access group**PUT** https://{{api_url}}/access_group/{{access_group_id}}

Update access group.

REQUEST BODY

```
{
  "name": "Working Hours",
  "description": "",
  "groups": [
    {
      "door_group_id": 3,
      "schedule_id": 4
    }
  ]
}
```

DELETE Delete access group**DELETE** https://{{api_url}}/access_group/{{access_group_id}}

Delete access group.

Mercury

Access Group Related API for Mercury hardware.

GET List access groups**GET** https://{{api_url}}/mercury/customer/{{customer_uuid}}/access_group

This API will fetch all access groups of customer.

Filter options

name

Filter options

location_uuid

type

Sorting options

name

updated_at

To apply sorting, order (ASC/DESC) and order_by(Anyone from sorting options) mandatory query params.

GET**Get access group****GET** https://{{api_url}}/mercury/access_group/{{access_group_uuid}}

This API will fetch access group details.

POST**Add access group****POST** https://{{api_url}}/mercury/customer/{{customer_uuid}}/access_group

Create access group.

REQUEST BODY

```
{
  "location_uuid": "{{location_uuid}}",
  "name": "Admin Access",
  "description": "All door access to admin",
  "sets": [
    { "door_uuid": "9d8ce624-679e-4bfb-b07b-174ac0257b2d", "schedule_uuid": "4902c47d-5044-4ee6-84b9-dd35dcd32bf0" }
  ]
}
```

PUT**Update access group****PUT** https://{{api_url}}/mercury/access_group/{{access_group_uuid}}

Update access group.

REQUEST BODY

```
{
  "name": "Admin Access",
  "description": "All door access to admin",
  "sets": [
    { "door_uuid": "9d8ce624-679e-4bfb-b07b-174ac0257b2d", "schedule_uuid": "4902c47d-5044-4ee6-84b9-dd35dcd32bf0" }
  ]
}
```

DELETE**Delete access group****DELETE** https://{{api_url}}/mercury/access_group/{{access_group_uuid}}

Delete access group.

07. Card Set

HID

CardSet Related API for HID hardware.

GET List Card Sets

GET https://{{api_url}}/location/{{location_uuid}}/cardset

This API will fetch all cardsets of location

Filter options

property_id

Mercury

Card Format Related API for Mercury hardware.

GET List Card Formats

GET https://{{api_url}}/mercury/customer/{{customer_uuid}}/card_format

This API will fetch all card formats of customer.

Filter options

name

GET Get Card Format

GET https://{{api_url}}/mercury/customer/{{customer_uuid}}/card_format

This API will fetch card format details.

08. Card

HID

Card Related API for HID hardware.

GET List Cards By Property

GET https://{{api_url}}/location/{{location_uuid}}/card

This API will fetch all cards of location.

Filter options	Mandatory or optional
page_size	mandatory

Filter options	Mandatory or optional
page	mandatory
property_id	optional
property_user_id	optional
card_number	optional
user_name	optional
card_status(PENDING_ACTIVATION,ACTIVE)	optional

sorting options	Mandatory or optional
order	mandatory
order_by	mandatory
id	optional
status	optional
type	optional
card_number	optional
start_date	optional
end_date	optional
updated_at	updated_at

Notes:

- For start_date , end_date and updated_at, Please use this date format (YYYY-MM-DD)
- To apply sorting, order (ASC/DESC) and order_by(Anyone from sorting options) mandatory query params.

GET**List Cards By User**

GET https://{{api_url}}user_location/{{user_location_uuid}}/card

This API will fetch all cards of user.

Filter options	Mandatory or optional
page_size	mandatory
page	mandatory
property_id	optional
property_user_id	optional
card_number	optional
user_name	optional
card_status(PENDING_ACTIVATION,ACTIVE)	

sorting_options	Mandatory or optional
order	mandatory
order_by	mandatory
id	optional
status	optional
type	optional
card_number	optional
start_date	optional
end_date	optional

Notes:

- For start_date , end_date and updated_at, Please use this date format (YYYY-MM-DD)
- To apply sorting, order (ASC/DESC) and order_by(Anyone from sorting options) mandatory query params.

GET**Get card****GET** https://{{api_url}}/card/{{card_id}}

This API will fetch card details.

POST**Add card - Mobile****POST** https://{{api_url}}/user_location/{{user_location_uuid}}/card

To create mobile card.

REQUEST BODY

```
{
  "type": "MOBILE",
  "start_date": "2019/05/01",
  "end_date": "2019/05/02"
}
```

POST**Add card - Physical****POST** https://{{api_url}}/user_location/{{user_location_uuid}}/card

To add physical card.

REQUEST BODY

```
{
  "card_set_id": 602,
  "type": "KEYCARD",
  "card_number": "12345",
  "start_date": "2017/05/01",
  "end_date": "2018/05/01"
}
```

PUT Update card**PUT** https://{{api_url}}/card/{{card_id}}

To update card.

REQUEST BODY

```
{
  "access_groups": [1],
  "start_date": "2017/05/01",
  "end_date": null
}
```

DELETE Delete card**DELETE** https://{{api_url}}/card/{{card_id}}

To delete card.

Mercury

Card Related API for Mercury hardware.

GET List Cards**GET** https://{{api_url}}/mercury/customer/{{customer_uuid}}/card

This API will fetch all cards of customer.

Filter options	Mandatory or optional
page_size	mandatory
page	mandatory
location_uuid	optional
card_type(MOBILE,KEYCARD,PIN)	(optional)
card_status(ACTIVE,PENDING_ACTIVATION,PENDING_DOWNLOAD,EXPIRED)	optional
card_number	optional
user_name	optional
user_uuid	optional
user_email	optional
tenant_name	optional
tenant_uuid	optional
tenant_address	optional

sorting options	Mandatory or optional
order	mandatory
order_by	mandatory
user_name	optional
card_type	optional
card_number	optional
card_status	optional
created_at	optional

Notes:

- To apply sorting, order (ASC/DESC) and order_by(Anyone from sorting options) mandatory query params.

GET Get card

GET `https://{{api_url}}/mercury/card/{{card_uuid}}`

This API will fetch card details.

POST Add card - Physical

POST `https://{{api_url}}/mercury/customer/{{customer_uuid}}/card/physical`

To create physical card.

REQUEST BODY

```
{
  "user_uuid": "{{user_uuid}}",
  "card_number": "1001",
  "activation_time": "2020-10-25T22:00:00",
  "deactivation_time": "2020-10-27T22:00:00",
  "is_passback_exempt": false,
  "is_pin_exempt": false
}
```

POST Add card - Mobile

POST `https://{{api_url}}/mercury/customer/{{customer_uuid}}/card/mobile`

To add mobile card.

REQUEST BODY

```
{
  "user_uuid": "{{user_uuid}}",
  "activation_time": "2020-10-25T22:00:00",
  "deactivation_time": "2020-10-27T22:00:00",
  "is_passback_exempt": false,
  "is_pin_exempt": false
}
```

PUT Update card

PUT https://{{api_url}}/mercury/card/{{card_uuid}}

To update card.

REQUEST BODY

```
{
  "activation_time": "2020-10-25T22:00:00",
  "deactivation_time": "2020-10-27T22:00:00",
  "is_passback_exempt": false,
  "is_pin_exempt": false
}
```

DELETE Delete card

DELETE https://{{api_url}}/mercury/card/{{card_uuid}}

To delete card.

09. Controller

HID

Controller Related API for HID hardware.

GET List controllers

GET https://{{api_url}}/location/{{location_uuid}}/controller

This API will fetch all controllers of location.

Filter options

property_id

Sorting options

updated_at

id

site_location

To apply sorting, order (ASC/DESC) and order_by (Any from sorting options) mandatory query params.

GET Get controller

GET https://{{api_url}}/controller/{{controller_id}}

This API will fetch controller details.

POST Add controller

POST https://{{api_url}}/location/{{location_uuid}}/controller

To add controller.

REQUEST BODY

```
{
  "site_location": "Genea 1st Floor",
  "model": "VertX V1000",
  "mac": "00:06:8E:00:6F:61"
}
```

PUT Update controller

PUT https://{{api_url}}/controller/{{controller_id}}

To update controller.

REQUEST BODY

```
{
  "site_location": "Genea Dev Lab West",
  "model": "VertX V1000",
  "mac": "00:06:8E:02:DA:1E"
}
```

DELETE Delete controller

DELETE https://{{api_url}}/controller/{{controller_id}}

To delete controller.

Mercury

Controller Related API for Mercury hardware.

GET List controllers

GET https://{{api_url}}/mercury/customer/{{customer_uuid}}/controller

This API will fetch all controllers of customer.

Filter options

model

name

mac

location_uuid

Sorting options

updated_at

name

To apply sorting, order (ASC/DESC) and order_by (Anyone from sorting options) mandatory query params.

GET Get controller

GET `https://{{api_url}}/mercury/controller/{{controller_uuid}}`

This API will fetch controller details.

POST Add controller

POST `https://{{api_url}}/mercury/customer/{{customer_uuid}}/controller`

To add controller.

REQUEST BODY

```
{
  "location_uuid":"{{location_uuid}}",
  "name":"1st Floor Controller",
  "description":"Controller to control all doors at 1st floor",
  "model":"LP1501",
  "mac":"00:00:00:00:00:A0",
  "timezone":"America/New_York"
}
```

PUT Update controller

PUT `https://{{api_url}}/mercury/controller/{{controller_uuid}}`

To update controller.

REQUEST BODY

```
{
  "name":"1st Floor Controller",
  "description":"Controller to control all doors at 1st floor",
  "model":"LP1501",
  "mac":"00:00:00:00:00:A0",
  "timezone":"America/New_York"
}
```

DELETE Delete controller

DELETE `https://{{api_url}}/mercury/controller/{{controller_uuid}}`

To delete controller.

10. Interface

HID

Interface Related API for HID hardware.

GET List interfaces

GET `https://{{api_url}}/location/{{location_uuid}}/interface`

Interfaces can be queried by controller_id or property_id

GET Get interface

GET https://{{api_url}}/interface/{{interface_id}}

This API will fetch interface details.

POST Add interface

POST https://{{api_url}}/controller/{{controller_id}}/interface

Create interface under controller.

REQUEST BODY

```
{
  "site_location": "1st Floor East",
  "model": "V100",
  "type": "a",
  "if": 0
}
```

PUT Update interface

PUT https://{{api_url}}/interface/{{interface_id}}

To update interface.

REQUEST BODY

```
{
  "controller_id": 1,
  "site_location": "Genea Lab East 2",
  "model": "eProx™ MCM Model 4025",
  "type": "a",
  "if": 16
}
```

DELETE Delete interface

DELETE https://{{api_url}}/interface/{{interface_id}}

To delete interface.

Mercury

Interface Panel Related API for Mercury hardware.

GET List interface panels

GET https://{{api_url}}/mercury/customer/{{customer_uuid}}/interface_panel

This API will fetch all interface panels of customer.

Filter options

model

name

location_uuid

controller_uuid

controller_name

address

Sorting options

updated_at

name

is_online

model

address

To apply sorting, order (ASC/DESC) and order_by(Anyone from sorting options) mandatory query params.

GET**Get interface panel****GET** https://{{api_url}}/mercury/interface_panel/{{interface_panel_uuid}}

This API will fetch interface panel details.

POST**Add interface panel****POST** https://{{api_url}}/mercury/controller/{{controller_uuid}}/interface_panel

Create interface panel under controller.

REQUEST BODY

```
{
  "name": "1st Floor Controller - panel 6",
  "description": "",
  "model": "MR52",
  "address": 6,
  "mspl_port_uuid": "{{mspl_port_uuid}}"
}
```

PUT**Update interface panel****PUT** https://{{api_url}}/mercury/interface_panel/{{interface_panel_uuid}}

To update interface panel.

REQUEST BODY

```
{
  "controller_uuid": "{{controller_uuid}}",
  "name": "1st Floor Controller - panel 2",
  "description": "",
  "model": "MR52",
  "address": 2,
  "mspl_port_uuid": "{{mspl_port_uuid}}"
}
```

DELETE Delete interface panel

DELETE `https://{{api_url}}/mercury/interface_panel/{{interface_panel_uuid}}`

To delete interface panel.

11. AUX Relay Operations

For AUX relay operations, you need to enter relay side into payload. value of relay_side must be "LEFT" or "RIGHT".

Steps to find relay side:

1. Go to control center.
2. Go to AUX relays.

You can find relay side under AUX relay label.

PUT AUX relay on

PUT `https://{{api_url}}/interface/{{interface_uuid}}/aux_relay/on`

To turn on AUX relay.

REQUEST BODY

```
{
  "relay_side": "LEFT"
}
```

PUT AUX relay off

PUT `https://{{api_url}}/interface/{{interface_uuid}}/aux_relay/off`

To turn off AUX relay.

REQUEST BODY

```
{
  "relay_side": "LEFT"
}
```

PUT AUX relay restart

PUT `https://{{api_url}}/interface/{{interface_uuid}}/aux_relay/timed_on`

To restart AUX relay.

REQUEST BODY

```
{
  "relay_side": "LEFT"
}
```

12. Reader(Door)

HID

Door Related API for HID hardware.

GET List readers for location

GET https://{{api_url}}/location/{{location_uuid}}/reader

This api will return readers collection for location.

GET Get reader

GET https://{{api_url}}/reader/{{reader_id}}

This api return reader details.

POST Add reader

POST https://{{api_url}}/interface/{{interface_id}}/reader

This api is to add reader under interface board.

REQUEST BODY

```
{
  "site_location": "East Front Door",
  "model": "iCLASS® R15",
  "a": 0,
  "am": 5,
  "elev": 0,
  "grant_access_time": 50,
  "door_held_time": 60,
  "scheduled_open_flag": false,
  "scheduled_open_schedule_id": null
}
```

PUT Update reader

PUT https://{{api_url}}/reader/{{reader_id}}

To update reader.

REQUEST BODY


```
{
  "interface_id":1,
  "site_location":"IQ GATE 2",
  "model":"MiniProx®",
  "a":0,
  "am":5,
  "elev":0,
  "grant_access_time":30,
  "door_held_time":50,
  "scheduled_open_flag":false,
  "scheduled_open_schedule_id":null
}
```

DELETE Delete reader

DELETE https://{{api_url}}/reader/{{reader_id}}

To delete reader.

Mercury

Door Related API for Mercury hardware.

GET List doors

GET https://{{api_url}}/mercury/customer/{{customer_uuid}}/door

This API will fetch all doors of customer.

Filter options

name

location_uuid

interface_panel_uuid

controller_uuid

controller_name

is_elevator_door

Sorting options

updated_at

name

controller_name

interface_panel_address

To apply sorting, order (ASC/DESC) and order_by(Anyone from sorting options) mandatory query params.

GET Get door

GET https://{{api_url}}/mercury/door/{{door_uuid}}

This api return door details.

POST Add door

POST https://{{api_url}}/mercury/customer/{{customer_uuid}}/door

This api is to add door.

REQUEST BODY

```
{
  "location_uuid": "{{location_uuid}}",
  "name": "Front Door",
  "description": "Front Door attached to Master controller",
  "is_elevator_door": false
}
```

PUT Update door – Basic

PUT https://{{api_url}}/mercury/door/{{door_uuid}}

To update door.

REQUEST BODY

```
{
  "name": "Front Door",
  "description": "Front Door attached to Master controller",
  "is_elevator_door": false
}
```

PUT Update Door – Hardware

PUT https://{{api_url}}/mercury/door/{{door_uuid}}/hardware

To update door hardware.

REQUEST BODY

```
{
  "reader_model": "HID_RP10",
  "reader_port_uuid": "{{reader_port_uuid}}",
  "door_strike_output_point_uuid": "{{door_strike_output_point_uuid}}",
  "door_position_input_point_uuid": "{{door_position_input_point_uuid}}",
  "rex1_input_point_uuid": "{{rex1_input_point_uuid}}",
  "rex2_input_point_uuid": "{{rex2_input_point_uuid}}"
}
```

PUT Update Door – Monitor

PUT https://{{api_url}}/mercury/door/{{door_uuid}}/monitor

To update door monitor.

REQUEST BODY

```
{
  "is_door_force_masked": true,
  "is_door_held_masked": false,
  "door_held_open_alarm_delay": 30,
  "door_held_open_pre_alarm_delay": 25
}
```

PUT Update Door – Rex

PUT https://{{api_url}}/mercury/door/{{door_uuid}}/rex

To update door rex settings.

REQUEST BODY

```
{
  "is_door_unlock_on_rex_enabled": true
}
```

PUT Update Door – Access

PUT https://{{api_url}}/mercury/door/{{door_uuid}}/access

To update door access settings.

Parameter options	value
door_access_mode	(CARD_OR_PIN, CARD, PIN, CARD_AND_PIN)

REQUEST BODY

```
{
  "door_access_mode": "CARD_OR_PIN",
  "door_access_time": 10
}
```

PUT Update Door – Unlock Schedule

PUT https://{{api_url}}/mercury/door/{{door_uuid}}/unlock_schedule

To update door unlock schedule settings.

REQUEST BODY

```
{
  "is_door_unlock_schedule_enabled": true,
  "door_unlock_schedule_uuid": "{{schedule_uuid}}",
  "is_first_person_in_enabled": true
}
```

DELETE Delete door

DELETE https://{{api_url}}/mercury/door/{{door_uuid}}

To delete reader.

13. Remote Operations

HID

Remote Operations Related API for HID hardware.

GET

Get emergency status

GET `https://{{api_url}}/location/{{location_uuid}}/emergency_hold/status`

Emergency hold open

PUT

Door - Lock

PUT `https://{{api_url}}/reader/{{reader_id}}/lock`

Door Lock

PUT

Door - Unlock

PUT `https://{{api_url}}/reader/{{reader_id}}/unlock`

Door Unlock

PUT

Door - Quick Grant

PUT `https://{{api_url}}/reader/{{reader_id}}/quick_grant`

Door Quick Grant

PUT

Emergency hold open

PUT `https://{{api_url}}/location/{{location_uuid}}/emergency_hold/open`

Emergency hold open

PUT

Emergency hold close

PUT `https://{{api_url}}/location/{{location_uuid}}/emergency_hold/close`

Emergency hold close

Mercury

Remote Operations Related API for Mercury hardware.

GET

Get emergency status

GET `https://{{api_url}}/mercury/location/{{location_uuid}}/emergency_hold/status`

Emergency hold open

PUT Door - Lock**PUT** `https://{{api_url}}/mercury/door/{{door_uuid}}/lock`

Door Lock

PUT Door - Unlock**PUT** `https://{{api_url}}/mercury/door/{{door_uuid}}/unlock`

Door Unlock

PUT Door - Quick Grant**PUT** `https://{{api_url}}/mercury/door/{{door_uuid}}/quick_unlock`

Door Quick Grant

PUT Emergency hold open**PUT** `https://{{api_url}}/mercury/location/{{location_uuid}}/emergency_hold/open`

Emergency hold open

PUT Emergency hold close**PUT** `https://{{api_url}}/mercury/location/{{location_uuid}}/emergency_hold/close`

Emergency hold close

14. Event

HID**GET List event****GET** `https://{{api_url}}/property/{{property_id}}/event`**List Events By Property Id**

This api will fetch all the events (ACCESS + AUDIT) of property.

Sorting (Optional):

You can sort data by adding `order` and `order_by` query parameters.

These are available sorting options.

- order options
 - ASC
 - DESC
 - asc
 - desc
- order_by options

- event_message
- event_time

Filtering (Optional):

You can use different filters as a query params for in this api to get your desire results.

Available Options:

- event_message : String value to apply filter on event message. It will search given string as a sub string in event message.
- card_number : String value to apply filter on card's number. It will search given number as a sub string in card's number.
- site_location : String value to apply filter on door's name. It will search given string as a sub string in interface, controller or reader's site location.
- actor_name : String value to apply filter on actor's name. It will search given string as a sub string in actor's name.
- start_date and end_date : To get events of perticular date range. It will give results from start date to end date. Date formate must be as YYYY-MM-DDTHH:MM.
- card_id : Card's primary id to get all events related to perticular card.
- subproperty_id : Subproperty's primary id to get all events related to perticular subproperty (office/unit).
- property_user_id : Property user's primary id to get all events related to perticular user in this property.

Pagination (Optional):

You can use pagination in this api by passing query params.

- page : Fetch records on given page.
- page_size : Number of records in each page.

NOTE: Do not pass unnecessary query params.

Mercury

GET List audit event

GET https://{{api_url}}/mercury/property/{{property_id}}/event

List Audit Events

This api will fetch all AUDIT events of location.

Sorting (Optional):

You can sort data by adding order and order_by query parameters.

These are available sorting options.

- order options
- ASC
- DESC
- asc
- desc
- order_by options
- event_message
- event_time

Filtering (Optional):

You can use different filters as a query params for in this api to get your desire results.

Available Options:

- **event_message** : String value to apply filter on event message. It will search given string as a sub string in event message.
- **actor_name** : String value to apply filter on actor's name. It will search given string as a sub string in actor's name.
- **start_date** and **end_date** : To get events of particular date range. It will give results from start date to end date. Date format must be as YYYY-MM-DDTHH:MM.

Pagination (Optional):

You can use pagination in this api by passing query params.

- **page** : Fetch records on given page.
- **page_size** : Number of records in each page.

NOTE: Do not pass unnecessary query params.

GET

List access event

GET `https://{{api_url}}/mercury/customer/{{customer_uuid}}/access_log?order=DESC&order_by=time&page=...`

List Access Events

This api will fetch all ACCESS events.

Sorting (Mandatory):

You can sort data by adding **order** and **order_by** query parameters.

These are available sorting options.

- **order** options
 - ASC
 - DESC
 - asc
 - desc
- **order_by** options
 - time

Filtering (Optional):

You can use different filters as a query params for in this api to get your desire results.

Available Options:

- **location_uuid** : String value to apply filter on event message. It will search event message by particular location.
- **event_message** : String value to apply filter on event message. It will search given string as a sub string in event message.
- **card_number** : String value to apply filter on card's number. It will search given number as a sub string in card's number.
- **access_group_name** : String value to apply filter on access group name. It will search given number as a sub string in access group name.
- **door_name** : String value to apply filter on door's name. It will search given string as a sub string in door's name.
- **user_name** : String value to apply filter on actor user's name. It will search given string as a sub string in actor user's name.
- **user_uuid** : uuid value to apply filter on user's uuid. It will search given string as a uuid in actor user's uuid.
- **user_department** : String value to apply filter on actor user's department. It will search given string as a sub string in actor user's department.
- **user_cost_center** : String value to apply filter on actor user's cost center. It will search given string as a sub string in actor user's cost center.

- **user_employee_number** : String value to apply filter on actor user's employee number. It will search given string as a sub string in actor user's employee number.
- **start_date** and **end_date** : To get events of particular date range. It will give results from start date to end date. Date format must be as YYYY-MM-DDTHH:MM.
- **tenant_name** : String value to apply filter on tenant's name. It will search given string as a sub string in tenant's name.
- **tenant_uuid** : uuid value to apply filter on tenant's uuid. It will search given string as a uuid in actor tenant's uuid.
- **elevator_name** : String value to apply filter on elevator's name. It will search given string as a sub string in elevator's name.
- **floor_name** : String value to apply filter on floor's name. It will search given string as a sub string in floor's name.

Pagination (Optional):

You can use pagination in this api by passing query params.

- **page** : Fetch records on given page.
- **page_size** : Number of records in each page.

NOTE: Do not pass unnecessary query params.

QUERY PARAMETERS

Parameter	Description
order	—
order_by	—
page	—
page_size	—
location_uuid	—

15. Statistics

GET

Get today attendance

GET `https://{{api_url}}/location/{{location_uuid}}/attendance/today`

Get today's attendance by location uuid.

SAMPLE RESPONSE — GET TODAY ATTENDANCE SAMPLE

```
{"meta":{"message":"Attendance details retrived successfully."},"data":{"total_active_property_users":4,"total_present_property_users":"0"}}
```

GET

Get attendance - Monthly

GET `https://{{api_url}}/location/{{location_uuid}}/attendance`

Get attendance details.

This API can be used to query attendance for a particular day, month or a year.

SAMPLE RESPONSE — GET MONTHLY ATTENDANCE SAMPLE

```
{
  "meta": {
    "message": "Attendance details retrived successfully."
  },
  "data": [
    {
      "total_active_property_users": 2,
      "present_property_users": 0,
      "month": 6,
      "year": 2018,
      "day": 29
    },
    {
      "total_active_property_users": 300,
      "present_property_users": 156,
      "month": 6,
      "day": 26,
      "year": 2018
    },
    {
      "total_active_property_users": 250,
      "present_property_users": 180,
      "month": 6,
      "day": 25,
      "year": 2018
    },
    {
      "total_active_property_users": 271,
      "present_property_users": 132,
      "month": 6,
      "day": 24,
      "year": 2018
    }
  ]
}
```

GET**Door scans - Busy doors**

GET https://{{api_url}}/location/{{location_uuid}}/door_scans/total

get total access grants per door till now

SAMPLE RESPONSE — DOOR SCANS - BUSY DOORS SAMPLE

```
{
  "meta": {
    "message": "Total door scans retrived successfully."
  },
  "data": [
    {
      "total_access_grants": 64,
      "site_location": "SK Right Door"
    },
    {
      "total_access_grants": 0,
      "site_location": "Door 1"
    },
    {
      "total_access_grants": 0,
      "site_location": "Door 2"
    },
    {
      "total_access_grants": 0,
      "site_location": "Door 3"
    },
    {
      "total_access_grants": 0,
      "site_location": "Door 4"
    }
  ]
}
```

GET**Hourly heatmap - Access grants**

GET https://{{api_url}}/location/{{location_uuid}}/heatmap/total_access_grants?at=2018/06/28

Get access grants heatmap by date

QUERY PARAMETERS

Parameter	Description
at	Date must be in YYYY/MM/DD format

SAMPLE RESPONSE — HOURLY - HEATMAP SAMPLE

```
{
  "meta": {
    "message": "Door scans heatmap retrived successfully."
  },
  "data": [
    {
      "total_access_grants": 0,
      "start_time": "00:00:00",
      "end_time": "01:00:00"
    },
    {
      "total_access_grants": 0,
      "start_time": "01:00:00",
      "end_time": "02:00:00"
    },
    {
      "total_access_grants": 0,
      "start_time": "02:00:00",
      "end_time": "03:00:00"
    },
    {
      "total_access_grants": 0,
      "start_time": "03:00:00",
      "end_time": "04:00:00"
    },
    {
      "total_access_grants": 0,
      "start_time": "04:00:00",
      "end_time": "05:00:00"
    },
    {
      "total_access_grants": 0,
      "start_time": "05:00:00",
      "end_time": "06:00:00"
    },
    {
      "total_access_grants": 0,
      "start_time": "06:00:00",
      "end_time": "07:00:00"
    },
    {
      "total_access_grants": 0,
      "start_time": "07:00:00",
      "end_time": "08:00:00"
    },
    {
      "total_access_grants": 0,
      "start_time": "08:00:00",
      "end_time": "09:00:00"
    },
    {
      "total_access_grants": 0,
      "start_time": "09:00:00",
      "end_time": "10:00:00"
    },
    {
      "total_access_grants": 0,
      "start_time": "10:00:00",
      "end_time": "11:00:00"
    },
    {
      "total_access_grants": 0,
      "start_time": "11:00:00",
      "end_time": "12:00:00"
    },
    {
      "total_access_grants": 0,
      "start_time": "12:00:00",
      "end_time": "13:00:00"
    },
    {
      "total_access_grants": 0,
      "start_time": "13:00:00",
      "end_time": "14:00:00"
    },
    {
      "total_access_grants": 0,
      "start_time": "14:00:00",
      "end_time": "15:00:00"
    },
    {
      "total_access_grants": 0,
      "start_time": "15:00:00",
      "end_time": "16:00:00"
    },
    {
      "total_access_grants": 0,
      "start_time": "16:00:00",
      "end_time": "17:00:00"
    },
    {
      "total_access_grants": 0,
      "start_time": "17:00:00",
      "end_time": "18:00:00"
    },
    {
      "total_access_grants": 0,
      "start_time": "18:00:00",
      "end_time": "19:00:00"
    }
  ]
}
```

GET**Hourly heatmap - Unique users**

GET https://{{api_url}}/location/{{location_uuid}}/heatmap/user_arrivals?at=2018/06/28

Get users count which are access granted in a hour.

heatmap by date

QUERY PARAMETERS

Parameter	Description
at	—

SAMPLE RESPONSE — HOURLY - HEATMAP SAMPLE

```
{
  "meta": {
    "message": "Door scans heatmap retrived successfully."
  },
  "data": [
    {
      "total_access_grants": "0",
      "start_time": "00:00:00",
      "end_time": "01:00:00"
    },
    {
      "total_access_grants": "0",
      "start_time": "01:00:00",
      "end_time": "02:00:00"
    },
    {
      "total_access_grants": "0",
      "start_time": "02:00:00",
      "end_time": "03:00:00"
    },
    {
      "total_access_grants": "0",
      "start_time": "03:00:00",
      "end_time": "04:00:00"
    },
    {
      "total_access_grants": "0",
      "start_time": "04:00:00",
      "end_time": "05:00:00"
    },
    {
      "total_access_grants": "0",
      "start_time": "05:00:00",
      "end_time": "06:00:00"
    },
    {
      "total_access_grants": "0",
      "start_time": "06:00:00",
      "end_time": "07:00:00"
    },
    {
      "total_access_grants": "0",
      "start_time": "07:00:00",
      "end_time": "08:00:00"
    },
    {
      "total_access_grants": "0",
      "start_time": "08:00:00",
      "end_time": "09:00:00"
    },
    {
      "total_access_grants": "0",
      "start_time": "09:00:00",
      "end_time": "10:00:00"
    },
    {
      "total_access_grants": "0",
      "start_time": "10:00:00",
      "end_time": "11:00:00"
    },
    {
      "total_access_grants": "0",
      "start_time": "11:00:00",
      "end_time": "12:00:00"
    },
    {
      "total_access_grants": "0",
      "start_time": "12:00:00",
      "end_time": "13:00:00"
    },
    {
      "total_access_grants": "0",
      "start_time": "13:00:00",
      "end_time": "14:00:00"
    },
    {
      "total_access_grants": "0",
      "start_time": "14:00:00",
      "end_time": "15:00:00"
    },
    {
      "total_access_grants": "0",
      "start_time": "15:00:00",
      "end_time": "16:00:00"
    },
    {
      "total_access_grants": "0",
      "start_time": "16:00:00",
      "end_time": "17:00:00"
    },
    {
      "total_access_grants": "0",
      "start_time": "17:00:00",
      "end_time": "18:00:00"
    },
    {
      "total_access_grants": "0",
      "start_time": "18:00:00",
      "end_time": "19:00:00"
    }
  ]
}
```

GET**Early scans**

GET https://{{api_url}}/location/{{location_uuid}}/door_scans/early?at=2018/06/25

Get early arrivals

QUERY PARAMETERS

Parameter	Description
at	—

SAMPLE RESPONSE — EARLY ARRIVAL OF THE DAY SAMPLE

```
{
  "meta": {
    "message": "Early scans retrived successfully."
  },
  "data": [
    {
      "arrival_at": "2016-10-11T14:00:02.000Z",
      "actor_user_name": "Jennifer Hopkins"
    },
    {
      "arrival_at": "2016-10-11T18:10:02.000Z",
      "actor_user_name": "Gordon"
    }
  ]
}
```

16. Pin

Create PIN for user.

HID

PIN Related API for HID hardware.

GET**Get PIN**

GET https://{{api_url}}/pin/{{pin_id}}

It will retrieve PIN details.

POST**Generate PIN**

POST https://{{api_url}}/user_location/{{user_location_uuid}}/generate_pin

It will generate unique pin for user.

REQUEST BODY

```
{
  "pin_size": 4
}
```

POST Create PIN

POST https://{{api_url}}/user_location/{{user_location_uuid}}/pin

It will create pin for user per property.

REQUEST BODY

```
{
  "pin": "9173",
  "start_date": "2018/04/08",
  "end_date": "2018/04/08",
  "passback_exempt": 0
}
```

PUT Update PIN

PUT https://{{api_url}}/pin/{{pin_id}}

It will update validity and other pin related fields.

REQUEST BODY

```
{
  "start_date": "2018/04/10",
  "end_date": "2018/04/12",
  "passback_exempt": 0
}
```

DELETE Delete PIN

DELETE https://{{api_url}}/pin/{{pin_id}}

It will delete pin.

Mercury

PIN Related API for Mercury hardware.

GET Get PIN

GET https://{{api_url}}/mercury/pin/{{pin_uuid}}

It will retrieve PIN details.

POST Generate PIN

POST https://{{api_url}}/mercury/customer/{{customer_uuid}}/generate_pin

It will generate unique pin for user.

REQUEST BODY

```
{
  "pin_size": 4
}
```

POST Create PIN

POST https://{{api_url}}/mercury/customer/{{customer_uuid}}/pin

It will create pin for user.

REQUEST BODY

```
{
  "user_uuid": "{{user_uuid}}",
  "activation_time": "2020-10-17T04:00:00.000Z",
  "deactivation_time": "2020-10-19T04:00:00.000Z",
  "is_passback_exempt": false,
  "pin": "1245"
}
```

PUT Update PIN

PUT https://{{api_url}}/mercury/pin/{{pin_uuid}}

It will update validity and other pin related fields.

REQUEST BODY

```
{
  "activation_time": "2020-10-17T04:00:00.000Z",
  "deactivation_time": "2020-10-19T04:00:00.000Z",
  "is_passback_exempt": false
}
```

DELETE Delete PIN

DELETE https://{{api_url}}/mercury/pin/{{pin_uuid}}

It will delete pin.

17. VMS Copy

Cisco Meraki**GET Meraki: Get Camera-Door Mappings**

GET https://{{api_url}}/v1/customer/{{customer_uuid}}/meraki/camera_door

List all the camera-door mapping for the specific customer in Cisco Meraki integration.

SAMPLE RESPONSE — MERAKI: GET CAMERA-DOOR MAPPINGS

```
{
  "meta": {
    "message": "Successful request"
  },
  "data": [
    {
      "uuid": "92c17a6f-1d82-4f43-83a1-81489198adbd",
      "customer_uuid": "2abbb9a1-d102-4608-b798-e1c6128528e7",
      "location_uuid": "2394b1c7-aa0c-482d-827d-b7874661df21",
      "door_camera_mappings": [
        {
          "door": {
            "uuid": "5fca84df-52a8-4757-b392-d6f4db9639e6",
            "name": "Front Entrance"
          },
          "cameras": [
            {
              "uuid": "d44df0d4-c47e-4209-b843-0b09139e61c2",
              "name": "Atlanta - Main Entrance",
              "model": "MV12W",
              "mac": "ac:17:c8:0b:06:7b",
              "serial": "Q2GV-B2PB-EXGG",
              "network_id": "L_781937485302206214",
              "created_at": "2023-03-07T07:17:45.206Z",
              "updated_at": "2023-03-24T12:23:38.016Z",
              "network_name": "Genea - Atlanta - Lab",
              "organization_id": "848960",
              "organization_name": "Genea"
            },
            {
              "uuid": "9cc3f020-77d3-43a2-bcd2-878222932112",
              "name": "Irvine - Server Room",
              "model": "MV22",
              ...
            }
          ]
        }
      ]
    }
  ]
}
```