

SeraPay Phase 1 - DevOps TLDR

PRODUCTION / DOCKER / EXECUTE IN ORDER

Required before the new image starts: add one runtime RPC variable and run the root database migrations.

1. Production runtime environment

Where: Existing SeraPay Docker/container runtime environment or secret store, beside DATABASE_URL.

Add:

```
ETHEREUM_RPC_URL=https://ethereum.publicnode.com
```

- Server/runtime only. Do not add it as a Docker build argument or prefix it with VITE_.
- No Privy or Sera API credential changes.
- Do not add SERA_PROVISIONAL_CONFIRMATIONS; backend default is 2.

2. Production database migration

Where: Existing deployment migration job or SeraPay source checkout with production DATABASE_URL available.

Run before starting the new image:

```
corepack enable
pnpm install --frozen-lockfile
pnpm run db:migrate
```

Applies all pending root migrations through `drizzle/0007_add_sera_provisional_settlement.sql`.

STOP deployment if the migration fails. Do not use scripts/post-merge.sh or pnpm db:push.

3. Application deployment

Where: Existing external deployment webhook/service.

Deploy image:

```
ghcr.io/sera-cx/sera-pay:latest
```

Keep the existing deploy/restart flow. Ensure the new container receives ETHEREUM_RPC_URL.

NO UPDATE REQUIRED

- | | |
|-----------------------------|---------------------------------|
| - Dockerfile | - Privy settings |
| - Frontend/Vite environment | - Sera API settings |
| - Ports or proxy | - Cron, PM2, or separate worker |

The settlement worker starts automatically inside the backend.