

OpenSearch Dashboards API Documentation

Auto-generated API reference for OpenSearch Dashboards (OSD) internal and public HTTP endpoints.

Table of Contents

- [Authentication](#)
- [Core APIs](#)
 - [Status](#)
 - [Saved Objects](#)
 - [UI Settings](#)
 - [Capabilities](#)
- [Plugin APIs](#)
 - [Application Config](#)
 - [Banner](#)
 - [Chat](#)
 - [Console \(Proxy\)](#)
 - [Data \(Search, Index Patterns, Autocomplete\)](#)
 - [Data Importer](#)
 - [Data Source](#)
 - [Data Source Management](#)
 - [Home](#)
 - [Index Pattern Management](#)
 - [Legacy Export/Import](#)
 - [Query Enhancements](#)
 - [Region Map \(Geospatial\)](#)
 - [Saved Objects Management](#)
 - [Share \(Short URLs\)](#)
 - [Telemetry](#)
 - [Usage Collection](#)
 - [Vis Augmenter](#)
 - [Vis Type Timeline](#)
 - [Vis Type Timeseries \(TSVB\)](#)
 - [Workspaces](#)
- [Common Patterns](#)

Authentication

All OSD API endpoints require authentication by default unless explicitly marked otherwise. When the OpenSearch Dashboards Security plugin is installed:

- Requests must include valid session cookies or authentication headers.
- Unauthenticated requests to /api/ routes receive a 401 Unauthorized response.

- The `/api/status` endpoint can optionally allow anonymous access via server configuration (`status.allowAnonymous: true`).

Common Headers:

Header	Description
<code>osd-xsrf: true</code>	Required for all non-GET requests to prevent CSRF attacks
<code>Content-Type: application/json</code>	Required for JSON request bodies
<code>Content-Type: multipart/form-data</code>	Required for file upload endpoints

Core APIs

Status

GET `/api/status`

Returns the overall health and status of the OpenSearch Dashboards server, including version info, plugin statuses, and OS/process metrics.

Authentication: Configurable (can allow anonymous access)

Query Parameters:

Parameter	Type	Default	Description
<code>v8format</code>	boolean	false	Use v8-style status format instead of legacy format

Example Request:

```
curl -X GET "http://localhost:5601/api/status"
```

Example Response:

```
{
  "name": "opensearch-dashboards",
  "uuid": "abc-123-def",
  "version": {
    "number": "2.19.0",
    "build_hash": "abc123",
    "build_number": 1234,
    "build_snapshot": false
  },
  "status": {
    "overall": { "state": "green", "title": "Green" }
  },
  "metrics": {
    "last_updated": "2026-03-19T00:00:00.000Z",
    "collection_interval_in_millis": 5000,
    "process": {
      "memory": { "heap": { "total_in_bytes": 1000000, "used_in_bytes": 500000, "size_limit": 2000000 } },
      "pid": 12345,
      "uptime_in_millis": 3600000
    },
    "os": {
      "load": { "1m": 1.5, "5m": 1.2, "15m": 1.0 },
      "memory": { "total_in_bytes": 8000000000, "free_in_bytes": 4000000000 }
    },
    "concurrent_connections": 5,
    "requests": { "total": 100, "disconnects": 0 }
  }
}
```

Saved Objects

The Saved Objects API manages persisted objects such as dashboards, visualizations, index patterns, and searches. All endpoints use the base path `/api/saved_objects/`.

GET `/api/saved_objects/{type}/{id}`

Retrieve a single saved object by type and ID.

Path Parameters:

Parameter Type	Description
type	string Saved object type (e.g., dashboard, visualization, index-pattern)
id	string Saved object ID

Example Request:

```
curl -X GET "http://localhost:5601/api/saved_objects/dashboard/my-dashboard-id" \
-H "osd-xsrf: true"
```

POST `/api/saved_objects/{type}/{id?}`

Create a new saved object. The id is optional; if omitted, one is auto-generated.

Path Parameters:

Parameter Type Required		Description
type	string Yes	Saved object type
id	string No	Custom ID (auto-generated if omitted)

Query Parameters:

Parameter	Type	Default	Description
overwrite	boolean	false	If true, overwrite an existing object with the same ID

Request Body:

Field	Type	Required	Description
attributes	object	Yes	The saved object's attributes (type-specific)
references	array	No	References to other saved objects [{name, type, id}]
migrationVersion	object	No	Migration version tracking
initialNamespaces	string[]	No	Initial namespace assignments
workspaces	string[]	No	Workspace assignments

Example Request:

```
curl -X POST "http://localhost:5601/api/saved_objects/index-pattern" \  
-H "osd-xsrf: true" \  
-H "Content-Type: application/json" \  
-d '{  
  "attributes": {  
    "title": "my-index-*",  
    "timeFieldName": "@timestamp"  
  }  
'
```

PUT /api/saved_objects/{type}/{id}

Update an existing saved object's attributes.

Request Body:

Field	Type	Required	Description
attributes	object	Yes	Updated attributes
version	string	No	Optimistic concurrency version
references	array	No	Updated references [{name, type, id}]

Example Request:

```
curl -X PUT "http://localhost:5601/api/saved_objects/index-pattern/my-id" \
-H "osd-xsrf: true" \
-H "Content-Type: application/json" \
-d '{
  "attributes": {
    "title": "updated-index-*"
  }
}'
```

DELETE /api/saved_objects/{type}/{id}

Delete a saved object.

Query Parameters:

Parameter	Type	Description
force	boolean	Force deletion even if the object has references

Example Request:

```
curl -X DELETE "http://localhost:5601/api/saved_objects/visualization/my-vis-id?force=true" \
-H "osd-xsrf: true"
```

GET /api/saved_objects/_find

Search for saved objects with filtering, pagination, and sorting.

Query Parameters:

Parameter	Type	Default	Description
type	string or string[]	<i>required</i>	Saved object type(s) to search
per_page	number	20	Results per page
page	number	1	Page number
search	string	-	Full-text search query
default_search_operator	OR or AND	OR	Search operator for multi-term queries
search_fields	string or string[]	-	Fields to search within
sort_field	string	-	Field to sort by
has_reference	object	-	Filter by reference {type, id}
fields	string or string[]	-	Fields to include in response
filter	string	-	OSD Query Language filter
namespaces	string or string[]	-	Namespace filter
workspaces	string or string[]	-	Workspace filter

Example Request:

```
curl -X GET "http://localhost:5601/api/saved_objects/_find?type=dashboard&search=sales&per_page=10" \
-H "osd-xsrf: true"
```

POST /api/saved_objects/_bulk_get

Retrieve multiple saved objects in a single request.

Request Body: Array of objects:

Field	Type	Required	Description
type	string	Yes	Saved object type
id	string	Yes	Saved object ID
fields	string[]	No	Specific fields to return

Example Request:

```
curl -X POST "http://localhost:5601/api/saved_objects/_bulk_get" \  
-H "osd-xsrf: true" \  
-H "Content-Type: application/json" \  
-d '[  
  {"type": "dashboard", "id": "dash-1"},  
  {"type": "visualization", "id": "vis-1"}  
'
```

POST /api/saved_objects/_bulk_create

Create multiple saved objects in a single request.

Query Parameters:

Parameter	Type	Default	Description
overwrite	boolean	false	Overwrite existing objects
workspaces	string or string[]	-	Workspace assignments

Request Body: Array of saved object definitions (same schema as single create, with type included in each item).

PUT /api/saved_objects/_bulk_update

Update multiple saved objects in a single request.

Request Body: Array of objects:

Field	Type	Required	Description
type	string	Yes	Saved object type
id	string	Yes	Saved object ID
attributes	object	Yes	Updated attributes
version	string	No	Optimistic concurrency version
references	array	No	Updated references
namespace	string	No	Namespace

POST /api/saved_objects/_export

Export saved objects as NDJSON. Supports exporting by type or by specific object references.

Request Body:

Field	Type	Description
type	string or string[]	Export all objects of these types
objects	array	Specific objects to export [{type, id}]
search	string	Search filter
includeReferencesDeep	boolean	Include all referenced objects recursively (default: false)
excludeExportDetails	boolean	Exclude export summary (default: false)
workspaces	string[]	Filter by workspaces

Response: NDJSON stream (application/ndjson)

Example Request:

```
curl -X POST "http://localhost:5601/api/saved_objects/_export" \  
-H "osd-xsrf: true" \  
-H "Content-Type: application/json" \  
-d '{"type": "dashboard", "includeReferencesDeep": true}' \  
-o export.ndjson
```

POST /api/saved_objects/_import

Import saved objects from an NDJSON file.

Content-Type: multipart/form-data

Query Parameters:

Parameter	Type	Default	Description
overwrite	boolean	false	Overwrite existing objects
createNewCopies	boolean	false	Generate new IDs for all imported objects
dataSourceId	string	-	Associate with a data source
workspaces	string or string[]	-	Assign to workspaces

Form Data:

Field	Type	Description
file	file	NDJSON file (.ndjson extension required)

Example Request:

```
curl -X POST "http://localhost:5601/api/saved_objects/_import?overwrite=true" \  
-H "osd-xsrf: true" \  
-F "file=@export.ndjson"
```

POST /api/saved_objects/_resolve_import_errors

Resolve errors from a previous import attempt by providing corrective actions (retries, overwrite decisions).

Content-Type: multipart/form-data

Query Parameters:

Parameter	Type	Default	Description
createNewCopies	boolean	false	Generate new IDs
dataSourceId	string	-	Data source ID
workspaces	string or string[]	-	Workspace assignments

Form Data:

Field	Type	Description
file	file	Original NDJSON file
retries	array	Retry instructions per failed object

POST /api/saved_objects/_log_legacy_import

(Deprecated) Logs a warning about legacy JSON imports. Returns {success: true}.

POST /internal/saved_objects/_migrate

(Internal) Trigger saved objects migration. Used during upgrade processes.

UI Settings

Manage user interface settings (advanced settings). All endpoints use the path prefix /api/opensearch-dashboards/settings.

GET /api/opensearch-dashboards/settings

Get all user-provided UI settings.

Query Parameters:

Parameter	Type	Description
scope	global, user, or workspace	Settings scope filter

Example Request:

```
curl -X GET "http://localhost:5601/api/opensearch-dashboards/settings" \
-H "osd-xsrf: true"
```

Example Response:

```
{
  "settings": {
    "dateFormat": { "userValue": "YYYY-MM-DD" },
    "defaultIndex": { "userValue": "my-index-*" }
  }
}
```

POST /api/opensearch-dashboards/settings/{key}

Set a single UI setting.

Path Parameters:

Parameter Type	Description
key	string Setting key (e.g., dateFormat, defaultIndex)

Query Parameters:

Parameter	Type	Description
scope	global or user	Settings scope

Request Body:

Field	Type	Description
value	any	The new setting value

Example Request:

```
curl -X POST "http://localhost:5601/api/opensearch-dashboards/settings/dateFormat" \  
-H "osd-xsrf: true" \  
-H "Content-Type: application/json" \  
-d '{"value": "YYYY-MM-DD HH:mm:ss"}'
```

POST /api/opensearch-dashboards/settings

Set multiple UI settings at once.

Request Body:

Field	Type	Description
changes	object	Key-value pairs of settings to update

DELETE /api/opensearch-dashboards/settings/{key}

Reset a UI setting to its default value.

Query Parameters:

Parameter	Type	Description
scope	global or user	Settings scope

Capabilities

POST /api/core/capabilities

Resolve UI capabilities for the current user based on registered applications.

Authentication: Optional

Request Body:

Field	Type	Description
applications	string[]	List of application IDs to resolve capabilities for

Example Request:

```
curl -X POST "http://localhost:5601/api/core/capabilities" \
-H "osd-xsrf: true" \
-H "Content-Type: application/json" \
-d '{"applications": ["discover", "dashboard", "visualize"]}'
```

Plugin APIs

Application Config

Manage application-level configuration key-value pairs.

GET /api/appconfig

Get all application configuration entries.

GET /api/appconfig/{entity}

Get a single configuration value by entity key.

POST /api/appconfig/{entity}

Set or update a configuration value.

Request Body:

Field	Type	Description
newValue	string	The new configuration value

DELETE /api/appconfig/{entity}

Delete a configuration entry.

Banner

GET /api/_plugins/_banner/content

Get the current banner configuration (content, color, icon, markdown settings, size).

Chat

AI-powered chat assistant using AG-UI protocol.

POST /api/chat/memory/sessions/search

Search conversation history sessions with pagination.

POST /api/chat/proxy

Proxy AI agent requests to AG-UI or ML Commons backend. Supports Server-Sent Events (SSE) streaming for real-time responses.

Console (Proxy)

The Console plugin provides a proxy to the OpenSearch cluster and related configuration endpoints.

POST /api/console/proxy

Proxy requests to the OpenSearch cluster. This is the primary endpoint used by the Dev Tools Console.

GET /api/console/opensearch_config

Get OpenSearch connection configuration visible to the Console.

GET /api/console/api_server

Get the Console's spec definitions for API autocompletion.

Data (Search, Index Patterns, Autocomplete)

The Data plugin provides core search, index pattern, and autocomplete functionality.

POST /internal/search/{strategy}/{id?}

(Internal) Execute a search using a registered strategy (e.g., opensearch, ppl, sql).

DELETE /internal/search/{strategy}/{id}

(Internal) Cancel an async search by strategy and ID.

POST /internal/_msearch

(Internal, Deprecated) Execute a multi-search request.

Query Parameters:

Parameter	Type	Description
data_source_id	string	Target data source

Request Body:

Field	Type	Description
searches	array	Array of {header: {index, preference?}, body} pairs

GET /api/index_patterns/_fields_for_wildcard

Get field capabilities for an index pattern.

Query Parameters:

Parameter	Type	Description
pattern	string	Index pattern (e.g., logs-*)
meta_fields	string or string[]	Meta fields to include
data_source	string	Data source ID

GET /api/index_patterns/_fields_for_time_pattern

Get fields for a time-based index pattern.

Query Parameters:

Parameter	Type	Description
pattern	string	Index pattern
interval	string	Time interval
look_back	number	Number of intervals to look back
meta_fields	string or string[]	Meta fields to include
data_source	string	Data source ID

POST /api/opensearch-dashboards/suggestions/values/{index}

Get autocomplete value suggestions for a field within an index.

Request Body:

Field	Type	Description
field	string	Field name
query	string	Partial value to autocomplete
boolFilter	object	Optional filter context
dataSourceId	string	Data source ID

GET /api/opensearch-dashboards/scripts/languages

Get supported scripting languages from OpenSearch.

POST /api/opensearch-dashboards/dql_opt_in_stats

Track DQL opt-in/opt-out telemetry.

Data Importer

POST /api/data_importer/_import_file

Import data from a file (CSV, JSON, NDJSON) into an OpenSearch index.

Content-Type: multipart/form-data

Query Parameters:

Parameter	Type	Required	Description
indexName	string	Yes	Target index name
createMode	boolean	Yes	Whether to create the index

fileExtension	string	Yes	File type extension
dataSource	string	No	Data source ID
delimiter	string	No	CSV delimiter character

POST /api/data_importer/_import_text

Import data from text content directly into an OpenSearch index.

GET /api/data_importer/_cat_indices

List available indices for import targeting.

POST /api/data_importer/_preview

Preview imported data before committing.

Data Source

Manage external OpenSearch data source connections.

POST /internal/data-source-management/validate

Test connection to a data source.

Request Body:

Field	Type	Description
id	string	Existing data source ID (optional for new connections)
dataSourceAttr.endpoint	string	OpenSearch endpoint URL
dataSourceAttr.auth	object	Authentication configuration

Auth Types:

- no_auth - No authentication
- username_password - Basic auth with {username, password}
- sigv4 - AWS SigV4 with {region, accessKey, secretKey, service}

Example Request:

```
curl -X POST "http://localhost:5601/internal/data-source-management/validate" \
-H "osd-xsrf: true" \
-H "Content-Type: application/json" \
-d '{
  "dataSourceAttr": {
    "endpoint": "https://my-opensearch:9200",
    "auth": {
      "type": "username_password",
      "credentials": {
        "username": "admin",
        "password": "admin"
      }
    }
  }
}'
```

POST /internal/data-source-management/fetchDataSourceMetaData

Fetch metadata (version, cluster info) from a data source.

Data Source Management

Async Query Jobs

POST /api/datasourcemangement/query/jobs

Execute an async direct query (PPL/SQL) job against a data connection.

Request Body:

Field	Type	Description
query	string	Query string
lang	string	Language (ppl, sql)
datasource	string	Data source name
sessionId	string	Optional session ID

GET /api/datasourcemangement/query/jobs/{queryId}/{dataSourceMDSId?}

Get the status and results of an async query job.

DELETE /api/datasourcemangement/query/jobs/{queryId}

Cancel or delete a running query job.

Direct Query Data Connections

GET /api/directquery/dataconnections

List all data connections.

GET /api/directquery/dataconnections/{name}

Get a data connection by name.

POST /api/directquery/dataconnections

Create a new data connection.

Request Body:

Field	Type	Description
name	string	Connection name
connector	string	Connector type (e.g., Prometheus, S3)
allowedRoles	string[]	Allowed roles
properties	object	Connection properties

POST /api/directquery/dataconnections/edit

Edit a data connection's roles.

POST /api/directquery/dataconnections/edit/status

Update a data connection's status.

DELETE /api/directquery/dataconnections/{name}

Delete a data connection.

Note: All /api/directquery/ routes also have MDS variants with /dataSourceMDSId={id} path suffix for multi-data-source environments.

DSL & PPL Proxy Routes

POST /api/directquery/dsl/search

Proxy DSL search queries to a data connection.

GET /api/directquery/dsl/cat.indices

Proxy cat indices request.

GET /api/directquery/dsl/indices.getFieldMapping

Proxy get field mapping request.

GET /api/directquery/dsl/indices.getFieldSettings

Proxy get field settings request.

POST /api/directquery/ppl/search

Execute a PPL query against a data connection.

Home

POST /api/home/hits_status

Check whether an index has any matching documents (used by the home page to detect data).

Request Body:

Field	Type	Description
index	string	Index pattern to search
query	object	OpenSearch query DSL

GET /api/sample_data

List available sample datasets and their install status.

Query Parameters:

Parameter	Type	Description
data_source_id	string	Data source ID

POST /api/sample_data/{id}

Install a sample dataset (flights, ecommerce, logs).

Query Parameters:

Parameter	Type	Description
now	string	Override current timestamp
data_source_id	string	Target data source

DELETE /api/sample_data/{id}

Uninstall a sample dataset.

Index Pattern Management

GET /internal/index-pattern-management/resolve_index/{query}

(Internal) Resolve index names matching a pattern. Used by the index pattern creation workflow.

Path Parameters:

Parameter	Type	Description
query	string	Index pattern query (supports wildcards)

Query Parameters:

Parameter	Type	Description
expand_wildcards	string	all, open, closed, hidden, or none
data_source	string	Data source ID

POST /internal/index-pattern-management/preview_scripted_field

(Internal) Preview a scripted field's output on sample documents.

Legacy Export/Import

GET /api/opensearch-dashboards/dashboards/export

Export dashboards and their dependencies in legacy format.

POST /api/opensearch-dashboards/dashboards/import

Import dashboards from legacy format.

Query Enhancements

POST /api/enhancements/search/{strategy}

Execute a search using a specific query strategy (SQL, PPL, etc.).

GET /api/enhancements/assist/languages

List supported query assist languages.

POST /api/enhancements/assist/generate

Generate a query using AI assistance with time range support.

GET /api/enhancements/jobs

POST /api/enhancements/jobs

DELETE /api/enhancements/jobs

Async query job management: check status, create jobs, and cancel running jobs.

GET /api/enhancements/connections

List available data connections.

GET /api/enhancements/connections/{id?}

Get a specific data connection by ID or the default connection.

GET /api/enhancements/remote_cluster/list

List remote cluster connections.

GET /api/enhancements/remote_cluster/indexes

Get indexes from a remote cluster.

POST /api/enhancements/resources

Resource discovery endpoint.

Region Map (Geospatial)

POST /api/geospatial/_indices

List indices matching a pattern (filtered to geospatial/map indices).

POST /api/geospatial/_search

Search a geospatial index for map data.

POST /api/geospatial/_mappings

Get field mappings for a geospatial index.

Saved Objects Management

Management UI-specific endpoints for browsing and managing saved objects.

GET /api/opensearch-dashboards/management/saved_objects/_find

Enhanced find endpoint with management-specific metadata injection.

Query Parameters: Same as core `_find` plus:

Parameter	Type	Description
sortOrder	string	Sort direction
fields	string or string[]	Fields to include in response

GET /api/opensearch-dashboards/management/saved_objects/{type}/{id}

Get a saved object with management metadata.

POST /api/opensearch-dashboards/management/saved_objects/scroll/counts

Get document counts per saved object type.

POST /api/opensearch-dashboards/management/saved_objects/scroll/export

Stream export all objects of given types.

GET /api/opensearch-dashboards/management/saved_objects/relationships/{type}/{id}

Get relationship graph for a saved object.

GET /api/opensearch-dashboards/management/saved_objects/_allowed_types

Get the list of saved object types that can be imported/exported.

Share (Short URLs)

POST /api/shorten_url

Create a shortened URL for sharing.

Request Body:

Field Type	Description
url string	The long URL to shorten (must be a valid internal OSD path)

Example Response:

```
{  
  "urlId": "abc123"  
}
```

GET /api/short_url/{urlId}

Retrieve the original URL from a shortened URL ID.

GET /goto/{urlId}

Redirect to the full URL from a short URL ID.

Telemetry

POST /api/telemetry/v2/optIn

Opt in or out of telemetry collection.

POST /api/telemetry/v2/clusters/_stats

Fetch telemetry usage statistics.

POST /api/telemetry/v2/clusters/_opt_in_stats

Report opt-in statistics.

PUT /api/telemetry/v2/userHasSeenNotice

Mark the telemetry notice as seen by the user.

Usage Collection

POST /api/ui_metric/report

Report batched UI interaction metrics for usage tracking.

GET /api/stats

Get aggregated cluster usage statistics.

Vis Augmenter

GET /api/vis_augmenter/stats

Get statistics about augmented visualizations.

Vis Type Timeline

GET /api/timeline/functions

List available Timeline functions.

POST /api/timeline/run

Execute a Timeline expression.

GET /api/timeline/validate/es

Validate an OpenSearch query used in Timeline expressions.

Vis Type Timeseries (TSVB)

GET /api/metrics/fields

Get available fields for an index pattern (used by TSVB).

Query Parameters:

Parameter	Type	Description
index	string	Index pattern
data_source	string	Data source ID

POST /api/metrics/vis/data

Execute a TSVB visualization query and return time-series data.

POST /api/metrics/vis/data-raw

Execute a TSVB query and return raw, unprocessed data.

Workspaces

Manage workspaces for organizing saved objects and access control.

Base URL: /api/workspaces

POST /api/workspaces/_list

List workspaces with optional search and pagination.

Request Body:

Field	Type	Default	Description
search	string	-	Search query
sortOrder	string	-	Sort direction
perPage	number	20	Results per page
page	number	1	Page number
sortField	string	-	Field to sort by
searchFields	string[]	-	Fields to search
permissionModes	string[]	-	Filter by permission mode

GET /api/workspaces/{id}

Get a workspace by ID.

POST /api/workspaces

Create a new workspace.

Request Body:

Field	Type	Required	Description
attributes.name	string	Yes	Workspace name (max 40 chars)
attributes.features	string[]	Yes	Use case feature configurations (exactly one use case required)
attributes.description	string	No	Description (max 200 chars)
attributes.color	string	No	Hex color code
attributes.icon	string	No	Icon identifier
settings.permissions	object	No	Permission mappings by mode and principal type
settings.dataSources	string[]	No	Associated data source IDs
settings.dataConnections	string[]	No	Associated data connection IDs

Example Request:

```
curl -X POST "http://localhost:5601/api/workspaces" \  
-H "osd-xsrf: true" \  
-H "Content-Type: application/json" \  
-d '{  
  "attributes": {  
    "name": "Analytics Team",  
    "features": ["use-case-observability"],  
    "description": "Shared workspace for the analytics team",  
    "color": "#54B399"  
  },  
  "settings": {  
    "dataSources": ["ds-id-1"]  
  }  
}'
```

PUT /api/workspaces/{id}

Update a workspace.

DELETE /api/workspaces/{id}

Delete a workspace and all associated metadata.

POST /api/workspaces/_associate

Associate saved objects with a workspace.

Request Body:

Field	Type	Description
workspaceId	string	Target workspace ID
savedObjects	array	Objects to associate [{id, type}]

POST /api/workspaces/_dissociate

Remove saved objects from a workspace.

Request Body: Same schema as _associate.

POST /api/workspaces/_duplicate_saved_objects

Duplicate saved objects from one workspace to another.

Common Patterns

Error Responses

All API endpoints return errors in a consistent format:

```
{
  "statusCode": 400,
  "error": "Bad Request",
  "message": "Detailed error description"
}
```

Common HTTP status codes:

- 400 - Bad Request (invalid parameters or body)
- 401 - Unauthorized (missing or invalid credentials)
- 403 - Forbidden (insufficient permissions)
- 404 - Not Found
- 409 - Conflict (version mismatch or duplicate)

- 413 - Payload Too Large (file upload exceeds limit)
- 500 - Internal Server Error

CSRF Protection

All state-changing requests (POST, PUT, DELETE) must include the `osd-xsrf` header:

```
osd-xsrf: true
```

Requests without this header will be rejected with a 400 error.

Pagination

List/find endpoints follow a consistent pagination pattern:

```
{
  "page": 1,
  "per_page": 20,
  "total": 150,
  "saved_objects": [...]
}
```

Internal vs Public APIs

- **/api/** - Public APIs intended for external consumption. Stable between minor versions.
- **/internal/** - Internal APIs used by OSD's own UI. May change without notice between versions. Do not depend on these in external integrations.

Workspace-Aware Requests

Many endpoints accept workspace context via:

- Query parameter: `?workspaces=workspace-id`
- Request body field: `"workspaces": ["workspace-id"]`

When workspace isolation is enabled, requests are scoped to the specified workspace.

Data Source-Aware Requests

Endpoints that interact with OpenSearch data often accept a `dataSource` or `data_source` parameter to target a specific remote OpenSearch cluster instead of the local one.