FORMULARIO DE PRESENTACION DE PROPUESTAS

## NOMBRE DE LA EMPRESA:

No de NIT o C.L.:	132751031	170101701	N° Telefono de Contacto:	2422102 - 71561322
NOMBRE DE LA EMPRESA:	INMEDENT SRL	NOMBRE DEL REPRESENTANTETEN AL ORDER	THE THE THE TAKE THE TAKE OF T	IVAN RIOS CAMACHO

Nota: Llenar unicamente las columnas "el precio unitario ofertado" y "precio total ofe

-	a commission of the commission	tecto utilitario ofert	ado y precio	The continuation of the co	or su empresa/nersona
Š	DETALLE	CANTIDAD	UNIDAD	PRECIO UNITARIO OFFRTADO PRECIO TOTAL OFFRTADO	TAI OFFDTADO
*	Tros and a strain of the second		-	O CINCIO LIVERIO IO	JAL OFENIADO
7	LEKINDIMETRO DIGITAL	25	PIEZA	200	C C C C C C C C C C C C C C C C C C C
		And in case of the supplemental and the supplementa	Section of the sectio	270	/.450,00
	TOTAL			298.00	7 450 00

Lie-Tuan Rios Camacho REPRESENTANTE LEGAL INMEDENT S.R.L.

# TERMÓMETRO INFRARROJO

Medición de Temperatura 37.5°C = T<38.0°C Temperature indicator Red 38.0°C = 1 T<37.5T Green Orange Pantalla LCD 376 到時 3801 Σ -

Puede guardar hasta 32 mediciones

Encendido/Cambio de Modo

Model STSTEMAN (PROTEST)

INMEDENT S.R.L.

Huan

Ivan Rios Camacho REPRESENTANTE LEGAL INMEDENT S.R.L.

### **TERMOMETRO INFRAROJOFT-100B**

### NOMBRE DEL PRODUCTO:

TERMOMETRO INFRAROJO (sin contacto)

### MODELO:

YS-TWA-1(FT-100B)

### **CARACTERISTICAS**

Innovadora tecnología de infrarroja, que puede medir rápidamente la temperatura corporal y la temperatura del ambiente sin contacto alguno.

Se puede obtener resultados inmediatos y precisos con la energía térmica emitida en la frente.

Alta confiabilidad: Este producto pasa los exámenes de confiabilidad y vida interna de fábrica.

Alta precisión: este producto ha pasado los estándares de rendimiento del termómetro infrarrojo de la unión europea y china para requerimientos clínicos de medición, la precisión de medición clínica no es mayor que  $\pm\,0.2^{\circ}$ C (0.4°F).

### **ESPECIFICACIONES TECNICAS**

- Lugar de medición: en la frente
- Rango de medición:
  - Modo temperatura corporal: 28.0 42.9 °C
  - 2. Modo temperatura ambiente: 28.0 50.0 °C
- Resolución de la pantalla: 0.1°c / 0.1°f
- Condiciones de almacenamiento: temperatura -20-50°c, humedad ≤ 9
- Requerimiento de energía: 2 BATERÍAS AAA
- Condiciones de operación: rango de temperatura 10-40°c, humedad ≤ 85% rh 0% rh
- Medias: 135\*36\*40mm
- Peso: sobre 67g (sin baterías)
- Modo de operación: operación continua
- Tiempo de vida de la batería: ≥1000 repeticiones
- Tiempo de vida del producto: 5 años
- Versión de software: v1.1
- Grados Centígrados y Grados Fahrenheit
- Modo de funcionamiento: Corporal y Ambiente
- Capacidad de almacenamiento: 32 mediciones

### TERMOMETRO INTELIGENTE

Cuenta con rangos de medición que reflejan en tres colores diferentes en la pantalla, que nos pueden alertar la temperatura, con 4 segundos de duración.

COLOR VERDE. - cuando la temperatura es menor a 37.5 grados centígrados, con sonido prolongado.

Tuan Rius Cumuris R. R. A. Tuan Rius Antie Regarden de la companya de la companya

<u>COLOR NARANJA.</u> - cuando la temperatura esta entre 37.5 – 38 grados centígrados, con sonido de 3 timbres cortos.

<u>COLOR ROJO. -</u> cuando la temperatura es superior a 38 grados centígrados, con sonido de 3 timbres cortos.



TUAN RIOS CUMUCHU

INAN REPRESENTANTE LEGAL

REPRESENTANTE LEGAL

REPRESENTANTE LEGAL

\$5 FF	口外人体表際保管快速布拉供说明	報が小器	± 1mm
<b>新型</b>	FT~1008	単圏	知識學
村原	BDS共耳统	194回	190202
ill th	Co Mr3 Vig send	1683	日本の日
版本	Mar.2020, ver. 1	支票權仍	5
RT	45*140mm		

Univerteating Library detaution to the control of t		The state of the s	OF SAME OF THE PARTY OF THE PAR	Committee of the second	The state of the s		
The control of the	Titom	Catalog	1.Summary of infrared thermometer	a Donut measure the otes of surred strate or	4.Temperature measurement mode and	High accuracy	LCD dienlaw
The control of the co	4	L. Montaging of mittaged thermometer 1	Trickle by the trickle by the series of the	serving body retipes still a fact mice at scareed	Tange description The inflated the monetar has the following	Das productives passed the softweet themselve performance standards of the European Union and	
1 Control Cont	UniverHealth	3 intended and	traditional between temporates and merundale inflational between temporature and merundale inflation of refittion.	County, memory of the site of the dived temperature, of the parties is travers on temperature.	mediculement mode : 1) Foreitzhd temperature meast senetet	Chies for measuring direct requirement, reconcing the oil Precion is no more	- Chinamin
Some description of the property of the production of the property of the production		breaparnees wade and		<ul> <li>Durset masser of that perfect is treated with certain drug triangules.</li> </ul>	mode-mesticas the per cartara of human forthead's temperature accentishtaing place of	- Shares O.J. C (O.416)	Trumpy visual
Supplied to the property of the control based places and the control based places are and delivered to the control		carige description	temperature, is emple proper use, please be sure		Tadificand Instituty Gistropmict has a decailed them senten.	Humanization design When the texture has exceede the case, LCD will-	Fritzman
So Contact interaction with the contact interaction with the contraction of the contact interaction with the contraction of the		5 feeture 3	All wider to car this product correctly please read	Numeronette schedule or coulten priene near the		depty the Louar Hipponest. What operating enhippenent percels the designed consideration	
1 Chartest and the control of the co		is Overall detachban	ere user may all before use -	data please don't take metalics meet of body	Normal temperature range for different meetaring position Normal forecast	LCD will display the fire prompt. When the	7.Operation
Substitution of Michigan to Michigan the Community (Michigan to Michigan the Community) and the Community (Michigan to Michigan the Community) and the Community (Michigan the Community) (Michigan the Community) and the Community (Michigan the Community) (Mich		7 Operation material Preparation S	condition conditions the salety precomposes before	this extracts spatning electron against the feeting unwanted as man overe.	temperaturis range for different ages	for voltage icinable the hardware self-see	an the stanctor
Supported the control of the control	Infrared Thermometer	Contract our service	without has a second the selection of the side for easy checking			LCD will display the first or fire protect	the preside it with
1. Supply of Common and the Common a		The Confession		4 this trustment for entry a personal device, please do not user for others.	la hydrother C1	Power savina function	distribution of the
1. Sciences as the control of the co	ICCD MANHIAL	-		The State and Editory output when reagaining	NAME OF TAXABLE PARTY.		the instruction
14. Control control of the control o	JUNEAU AND			use technical apecifications.  The moreotopic/ABS) had passed the ISO 10999-5	147.003		the [M] tay to
1. Somewhat to the control of the co		15. Votalenthaming a		and SG 18948-12 standard hest, my towardly allumy and initiation mention They are compliant dates with	10.6-20.7	-	Summer and ob-
1. Submered to the control of the co		14 Sperifications		the NUD requirements, Based on the current	The same of the sa	Description of the second of t	thesistens in T
1. Storender of the first of the control of the con				Intelligence are sentenced.	Nages	bidence the topperature rang Whier the corner	the target temp
The foreign of the contract of	The same of the sa		-	EMI PRESENT LO ANTINCHES OF STORE THE PARENT.	Herpalitical Co	light different color to indicate the temperature	Dispussion
1 Committee of the control of the co			temperature.	manual circumstances and makessi the device and	284-381	conge as below:	Ne conspand
13. Work desiration 13. Work and application of the control of the	30.00		-	The device is not arounded for MIRNT 9 autpor-		Security Second	After about 3 so
15 Genomes 13 defined by completion of production of the completion of the completio	3034	- Mode		outside a Newthown feolity.	1	Trees + becames 1 lange	and The Luize
The standard product of the standard control of the st				Recommendations (S)  1. Don't use first themposites for other manages	7	SEE T Change Synamb Labor	Tenipositar ag
The state of the s				2. Raforbiddes to lawe desproduct expressed to	MOTE The no mol tensor they and difference	There's find Amenda Labori	As in the measur key for neare the
The contraction of the contrac			Be such to fellow doctor's instruction     Kery for festionistic out of reschaft of coldner	temperature.	between the different tody particls afflarent To	1	intertaction all i
The control of the co	The state of the s		For accidental smallow of bactery or other consequents, please consult the ductor street	ti	ments 2 thrones at the same foreboard pooleder and an		Note in the rand
Middle Component of the Component of t				37	THE POSTERIOR COLOR	Memory mode The front strategies don't 32 termination	during use if the
Hardware a contraction of the co					NOTE Secavish the far sheed temperatury is	400	it will be thesis.
The controlled and the controlle			100	-	attacked obviously by the external execumentings andhornest, at convertion and side, etc., se		the display on the
Second Continued of the continued of t					advise that you take the forehead tumpor stuer		toff been sharts
- Section manus supported to produce a control of the component block of the component bloc					the special and found		record query mi
And the properties will be a served to the properties of the prope			100		SFeature	Main component including	tonesponding c
The control of the act of the control of the contro			A After doing some everons, eating and backing.		High refinibility		faers. 2. In the standing
A Wide target of temperature and temperature a			Not an experienced.  Define a residual entered.		or errol fife or directally best, ho life and 1028h.		key for more than
All the transfer and the state felocos is a first arrival temperature have forther — (7) in the state felocos is a first arrival temperature have forther arrival temperature for the state felocos and the state felocos are a first arrival temperature for the state felocos are a first arrival temperature for the state felocos are a first arrival temperature for the state felocos are a first arrival temperature for the state felocos are a first arrival temperature for the state felocos are a first arrival temperature for the state felocos are a first arrival temperature felocos are a first arrival temp			<ul> <li>When appoint temperature cycles a left to make aux the mengarement data reliable and stable</li> </ul>				Instrument with
A SECOND CONTRACTOR OF THE PROPERTY OF THE PRO			the themsomerer should be placed indoors for about 30 minutes before solver.		wide range of temperature	E T	templicature has
Subsidial Investments of the end, as a reference for the last of the end, as a reference of the last of the end, as a reference of the end of t			* There is no shoulder standard for temperature of hydratego plants for to collect the parenting of		N. O'C-42-3"C 42,4"Y-185-275;	Batary Cores	Section of the
	2004		undersides the uperature as the usual, as a reference for travity as because to seek				Terraporature us in
	WODEL: FI-100B						the kinds where the
						,	
	The same of the sa	The state of the s					

	M Date of manufacture		STABLEC (WEEE)	Kesp dry	,	as =	-	1	Stacking layer limit		regarding EMC and means to be inscalled and you and selve gening a concluding to the EMC informations	ACCOMMEND DOCUMENTS.  2) Vindess to ennancities equiences such as wirders traine network dedices. Inchlegisches	SOURCE, SCHOOL BOTS BY ONE TO SEE STATIONE STATIONE WAS CONTINUED BY SOURCE AND SELECT TO SELECT SECURITY OF SELECT SELECT SECURITY SELECT SEL	from the equipment of the people of the pools of the formal light of the people of the formal of the	19. Guerantee	We grant you a government of an in care of part of the care of part of the care of the car	guarden der betrate geben der	dams excludes a grantee dam may be submy the submy the submy the submy the test surch as even in former as	your delective tradument sed and with sufficient portrage to the distribution	The state of the s	Meritonic Could State Speech School Dated	Heighton 331.25, Zhesang, Chosa EC REP	in the Exception Continuing Profess Google Belleman St. 44225 December	Germany
16.Disposal	At the and of the product lifecycle, do	not throw this product late the reprint	collection point for the recycling of electronic equipment.	parameters are secrete to appear to the parameters of the control	Durango ya bir ngararer and son med cas be Naranful to kuman health.	NOTES: Handing at bothery and wasted medical., plante	acc according to the rather take to proposed to handle. Take out the lightery if you are not going to use the	soft far a lang time.	To produce the environment of depose of employ bettery at your total attacle or an appropriate collection after according to	national ar local regulations.	17. Normalized symbols	Menufacturer		Till Fo low operating instructions	Ceutioni Consult socompanying	ZIS documents.	-	Type BF applied parts		LOT Batch code		IP22 device of the device: this device: this markes of soid foreign objects		
-	decilial incordance that the JA-115 ath fallowing spektonds standards	EN 960 Symbols for use in the labeling of	-	EN SOURT 1 Man Both of the Sharest Part P 7 8 1 September 1 Septem	-	have safely and recent to performance-Culture of structed Mechanismer-be contrativity	-	-		-		Dougle 2016ty and glocental Derformance-Collateral styrulard Regularisers for medical derpical seguptives and results described	systems there in home healthcare	EN 12477-3 Charch themanipers-Pert 5: Purfamence of emission and familiarious testings in transmiss	Service) (Carutard Specification for Infrared	Deformation of Patent	C software-Software		devices application of engineering to mentical	-	PERSON MANAGEMENT, Buddaniese Teuthologiesese	7		
14. Specifications	statum infrared Thempumetat	Bods Frittin	Madantement body temperature purinds or Frank Brespenser temperatures Madantement	Silve Poster suispily Doug, 2" AAA instrains	Menaving Indeptendent ands 200-12/C	Messecting 25 2 CES 47 ecolog 35.5 C-42 (F.C. 8 course) (35.6 T-107.6 P); (A blane (on e. 6) 3 T-2 S 3 F supp.	42.9°C(197.8°F108_1°F)	Party.	0.4°C/S 1°F Terretactors angle Design	Storage Temperature-29-50°C candidon Huma Style Spira, RH	1.55*54*4(mms	Weight about 17 gradings ton erres fightedy a 3b.07 G(100 479)	T	Uniderstand State of the second of the secon	Machine Type SP actitadose, industrie the	T	Commission operation	Batterythe 271000 Notes	Productics Sympto	-	Note: Not jet, esded to be startlized. Not for use in and CNY GER RICH ENVIRONMENT.	*The above specifications are subject to that government of the specifications.		
13. Trouble-shooting	Thattee Cheditals of station S trementation in the contraction of stations	N. Tepperant Detrofferen aman på Naphranaper	A MAN & BOOK OF	Post beliary control Tuliperater a flambeliar		The state of the s	A CAMPAGE AND A	And the second of the second o	Total to the second of the sec	demonstrate ways has	Con Con Service Con	1	SECURITY ST	The haddeness of Sest-ding the presiding the part of t	ASS SERVICES CONTROL C	Shalffery Newwell	ErrE ErrE and the test to the transport	Control belief, houses of American States						
-	Sort use other non-reconstructed methods to more displace.	con-switching don't use the shaster clearer to	Maintenance	to the contract and production of the production of the contract of the product favor and areas of the product favor and areas on the product favor and areas on.	2) The discrete and actempt any repain to the	Deficial of July Cf. Its accounted Ploade Cartol the relative for Paper and Programme State of the State of t	dam to watering.	palpment is allowd	ACARDENSION  * Service and the comment of the comment of the comment of the distance of the comment of the comm	readiation is not required for doubt the accessory of acquering those contact	distributor of meastracturer, the contact enformation see has page.	11. Storage 12. Durit pail the themsewerer under the satisfaire. Not it services that and extract evolutions or	Lampalate which staying get to truck with five or is referenced with the or is	2) Take out the bartary if don't use the davice in a long thm.	12 Accessories	Children		Spiritual Catal Manual				***************************************		•
4. In the forector setting mode, each three the Callery is present the setting functions are converted	South of the state of the state of the second section in the second section of the state of the	the first place of the second	the fire to up or state and a setting of the functions of the south peep the fall her, the south setting in the south setting.	Annual of the Control	nothe press the [4] key, the activation profession for the first parties of the principle of the first parties of the LCD or the first parties of the LCD or the LCD	inglights the current blane, politifications for the properties. Each may proud it is fifth, lengther hamperature admin one distressments by \$0.1 %.	A the languages days part a count of the function of the funct	to LCD displays the country about to the state of the country of the passible fact that he contract the country of the passible fact that the contract the country of the c	Althrighment receives by (a) "c.  A for the beingeness about point "setting of the binding metals medic area the [[]] key Tae i D  disclay teneorism of the instrument enters	-	Dates being therity the LCO disable of tened off,	Teste-color backlight flanction for haddingto fam (CD vill light officent rates or indices the temperature range as before table.	-	Store - Average Visco Verice - Vespons a Average	Not destroy hours	&Care and desping	the standarders. It has to be then and arranged to	the state of the s	Nery gently ware the particle aith a cuttor segui-	neman rate after the slock-offers completely ned out	ten the unit body:	the a colt, say defit for drain the themson unter- inably and with body. If may obtactive a soft with alcohol to dearning		9

Dan Rios oungachu Bar Ries friend Ante J. R. A.



### EC Certificate Directive 93/42/EEC Annex V Production Quality Assurance Medical Devices

Registration No.: DD

Report No.:

Manufacturer:

Products:

- Digital Thermometers

- Blood Pressure Monitors - Infrared Ear Thermometers

- Infrared Forehead Thermometers

- Infrared Ear / Forehead Thermometers

Replaces Approval, Registration No.: DD

**Expiry Date:** 

2023-11-06

The Notified Body hereby declares that the requirements of Annex V of the directive 93/42/EEC have been met for the listed products. The above named manufacturer has established and applies a quality assurance system, which is subject to periodic surveillance, defined by Annex V, section 4 of the aforementioned directive. For placing on the market of class IIb and class III devices covered by this certificate an EC type-examination certificate according to Annex III is required.

Effective Date:

2019-08-08

Date:

2019-08-08

TÜV Rheinland LGA Products GmbH - Tillystraße 2 - 90431 Nürnberg
TÜV Rheinland LGA Products GmbH is a Notified Body according to Directive 93/42/EEC
concerning medical devices with the identification number 0197.