Probabilistic System Identification and State Estimation via Normalizing Flows

genehmigte Dissertation
zur Erlangung des akademischen Grades der Doktor-Ingenieurin (Dr.-Ing.).
an der
Fakultät für Angewandte Informatik
der
Universität Augsburg

vorgelegt von
Yi Zhang
aus
Tangshan, China

2026

Dekan: Prof. Dr. Jörg Hähner
Doktorvater: Prof. Dr.-Ing. Lars Mikelsons

I dedicate this thesis to my family.

Contents

Acronyms **i**

List of Figures **ii**

List of Tables **v**

I Introduction **1**

1 Motivation . . . 1

2 Background and Preliminaries . . . 5

2.1 Notations . . . 6

2.2 Bayesian Inference . . . 6

2.2.1 Bayes' rule . . . 6

2.2.2 Markov Chain Monte Carlo . . . 7

2.2.3 Variational Inference . . . 7

2.3 Deep Probabilistic Models . . . 7

2.3.1 Deep Gaussian Process . . . 7

2.3.2 Bayesian Neural Networks . . . 7

2.3.3 Variational Autoencoder . . . 7

2.4 Normalizing Flows . . . 7

2.4.1 Basics . . . 7

2.4.2 Discrete Normalizing Flows . . . 7

2.4.3 Continuous Normalizing Flows . . . 7

2.5 From Inference to Control . . . 7

2.5.1 Bayesian System Identification . . . 7

2.5.2 Bayesian State Estimation . . . 7

2.5.3 Model Predictive Control . . . 7

3 Literature Review 7
4 Objectives and Contributions 8
5 Outline 8

II Methodologies **9**
1 Parameter Identification 9
2 Dynamics Identification 9
3 State Estimation 9
4 Model Predictive Control 9

III Experiments and Results **11**
1 Parameter Identification 11
2 Dynamics Identification 11
3 State Estimation 11
4 Model Predictive Control 11
5 Reinforcement Learning 11

IV Discussion and Conclusion **13**

V Abstract **15**

VI Zusammenfassung **17**

Bibliography **18**

Own Contributions and Publications **19**
Own share in data acquisition and data analysis 19
Own Publications 19

Curriculum Vitae **22**

Appendix **25**

Acknowledgement **27**

Eidesstattliche Versicherung (Affidavit) in German **29**

Angabe zu verwendeten KI-basierter Elektronischer Hilfsmittel **31**

Acronyms

DGM Deep Generative Model

VAE Variational Autoencoder

NF Normalizing Flow

BNN Bayesian Neural Network

RNN Recurrent Neural Network

NARX Nonlinear Autoregressive eXogenous

MPC Model Predictive Control

DGP Deep Gaussian Process

PDF Probability Density Function

List of Figures

List of Tables

Chapter I

Introduction

1 Motivation

In this seemingly certain world, uncertainty lingers like a shadow, yet from the uncertain, we often find certainty.

The paradoxical relationship between certainty and uncertainty manifests across disciplines, demonstrating how truth often arises from navigating ambiguity. Quantum mechanics redefines predictability under randomness in the subatomic world, where Newtonian deterministic physics collapses. This uncertainty led to groundbreaking laws (e.g. Heisenberg's Uncertainty Principle), which now underpin modern technologies like quantum computing and all forms of spectroscopy. An example of medical diagnosis is that a patient presents vague symptoms, such as fatigue or pain, which could indicate anything from stress to cancer. Doctors converge on the cause through iterative hypothesis-testing approaches. Climate science also epitomizes how we manage uncertainty. Climate models incorporate a wide range of sources of variability and uncertainty. A common way to address it is to combine the results of a collection of different simulation models. By running multi-model ensembles, scientists can identify consistent patterns across the uncertainty.

From quantum randomness to medical diagnosis to climate models, uncertainty does not destroy the deterministic systems, but provides us accessibility to identify the systems. This perspective supports the use of ***probabilistic inference*** methods, which offer a rigorous framework for representing uncertainty and reasoning from uncertainty. In statistics, modeling uncertainty of variables from given data samples, using a probability distribution rather than just a point estimate is known as inference. The estimated distribution facilitates uncertainty quantification and provides a measure of reliability of the results, making it particularly well-suited for real-world applications.

The mathematical foundation of probabilistic inference is Bayes' rule: beliefs about unknown variables (the prior) are updated using observed data (likelihood), yielding the posterior distribution. A simplified formulation is:

$$\text{posterior} = \text{prior} \times \text{likelihood} \;/\; \text{total evidence or marginal likelihood.} \tag{I.1}$$

For example, we can illustrate Bayes' rule using the medical diagnosis scenario: the objective is to obtain the probability of a disease given a positive test result:

$$P(\text{Disease}|\text{Positive}) = \frac{P(\text{Positive}|\text{Disease}) \times P(\text{Disease})}{P(\text{Positive})},$$
$$P(\text{Positive}) = P(\text{Positive}|\text{Disease}) \times P(\text{Disease}) + P(\text{Positive}|\overline{\text{Disease}}) \times P(\overline{\text{Disease}}),$$

where $\overline{\text{Disease}}$ denotes "No Disease". In the Bayesian context, probabilistic inference is the process of obtaining the posterior distribution of target variables from observed data. This perspective extends naturally to modern machine learning, where predictions, structures, and policies can all be understood as random variables and probability distributions (Murphy, 2022).

Especially in modern Deep Generative Models (DGMs), probabilistic inference plays an essential role (Murphy, 2023). By learning joint distributions over data and latent variables, they allow both inference (discovering hidden structure from observed data) and generation (synthesizing new data from latent variables). The inference and generation functions are parameterized with deep learning architectures. However, an exhaustive calculation of the marginal likelihood in Bayes' rule I.1 is impossible, because all possible values of the latent variables are rarely obtainable in complex and high-dimensional models. This results in the intractability of the posterior over latent variables given observed data, which is called the "intractable posterior" problem. To fully unfold the potential of DGMs, this issue has to be at first addressed. Variational Autoencoders (VAEs) (Kingma and Welling, 2019) tackle this problem by introducing an inference network as a tractable approximation to the posterior. Normalizing Flows (NFs) (Rezende and Mohamed, 2016) construct bijective transformations between observed data and latent variables, making exact computation of posteriors possible. Diffusion models (Ho et al., 2020) avoid calculating posterior over latent variables by designing it as a simple Gaussian distribution, framing both inference and generation as iterative denoising from noise via learned transformations.

To sum up, DGMs are inherently probabilistic; through probabilistic modeling and inference, they are powerful in extracting latent information and representing uncertainty in complex data. These capabilities are proven in numerous applications in images, text, and speech. The same principles extend naturally to scientific and engineering domains. One prominent example is: how can probabilistic inference in DGMs empower the identification and modeling of complex, stochastic, nonlinear dynamical systems? In control theory, this process of building mathematical models of dynamical systems from observed input-output data is called ***system identification***. Interpreting system identification in probabilistic terms, dynamics identification is inferring the posterior of the

next states based on the previous states and system inputs, while parameter identification is estimating the posterior over system parameters given observations.

Classic methods for system identification rely on linearized models or pre-specified nonlinear structures. Model parameters are then estimated from observed data using estimation techniques such as the least squares method and Bayesian estimation. Subsequently, a validation process is employed to assess and select the most appropriate model structure. Although these methods offer strong physical interpretability and are often data-efficient, they exhibit several limitations: parameter estimation can be computationally inefficient with large amounts of data; results are sensitive to the choice of model structures and dependent on expert knowledge; uncertainty is difficult to handle and quantify; and they are generally inapplicable to partially observable systems and high-dimensional and raw data.

Despite the demand for uncertainty quantification, deep learning methods are suitable for system identification thanks to their strength in representing information from complex data, flexibility of function approximation, scalability in high-dimensional data, and compatibility with optimization techniques. Taking uncertainty quantification into account, a simple yet effective technique is Gaussian Process Regression (Särkkä, 2019), which involves assigning a Gaussian process prior to the latent regressor and performing statistical conditioning based on the available observations. This method has gained widespread adoption due to its usability and adaptability. Nonetheless, its significant computational and memory requirements limit its feasibility when dealing with large datasets. Another straightforward approach to combine the advantages of deep learning methods and the possibility of uncertainty modeling is the Bayesian Neural Network (BNN) (Goan and Fookes, 2020). Unlike standard neural networks that produce point estimates, BNNs assign probability distributions over the network weights, thereby inducing distributions for outputs. However, BNNs reveal expressiveness limitations because the approximate inference may not reliably capture true posterior behavior (Foong et al., 2020). Therefore, the adaptation and application of DGMs are crucial for achieving rich representational capacity, flexible modeling frameworks, and the ability to effectively handle large-scale data.

Different DGMs have been investigated in system identification applications. VAEs are flexible to cooperate with time series modeling architectures such as Recurrent Neural Network (RNN) (Girin et al., 2021) and Nonlinear Autoregressive eXogenous (NARX) (Paniagua and López, 2024), which is beneficial in uncovering the time-dependent features from data. However, because the VAE models the output as a Gaussian characterized by means and variances, joint optimization of both mean and variance in the VAE leads to the well-known problem of shrinkage or underestimation of variance (Mattei and Frellsen, 2018). Unlike VAEs, NFs are restricted in their architectural choices due to the requirement

of invertibility, which limits their direct applicability to time series modeling. On the other side, NFs provide exact and expressive density estimation capabilities, qualifying them for capturing uncertainty in data and enhancing the representational capacity of probabilistic forecasts. Diffusion models release the architectural constraints and manifest the strength in generating high-quality and coherent predictions. Nonetheless, their iterative sampling procedure incurs substantial computational overhead. Balancing expressiveness, computational efficiency, and sample quality, ***normalizing flows*** are chosen in this work as the generative backbone of probabilistic system identification.

Based on the results of system identification, ***state estimation*** is the process of inferring the value of hidden, time-varying state variables of a dynamical system from a history of noisy and potentially partial observations and known control inputs. Because of the noise in the sensors (measurement noise) and unmodeled disturbances in the system itself (process noise), state estimation is naturally probabilistic. Thus, estimating the target states is computing the posterior distribution of target states. The traditional method for state estimation is the Luenberger State Observer, which assumes the systems are deterministic and both the system dynamics and measurement models are linear and time-invariant. Taking stochasticity into account, Kalman Filter is the most widely applied method. Beyond system linearity, a Kalman filter assumes the process and measurement noises are additive Gaussian noise with zero mean. In order to handle nonlinear systems, Extended Kalman Filter linearizes the nonlinear functions around the state estimate. However, the linearization introduces errors, leading to wrong estimation or even divergence. An improved modification is the Unscented Kalman Filter, which carefully selects the means and variances and propagates them through the nonlinear functions. Nevertheless, it is computationally inefficient and still only compatible with Gaussian noises.

Through relaxing the need for precise modeling of dynamical systems and avoiding restrictive assumptions about uncertainty–while preserving expressiveness, modeling flexibility, and scalability to large datasets–the chosen architecture for probabilistic system identification, NF, also provides a foundation for accurate, efficient and reliable probabilistic state estimation. From a data-centric perspective, parameter identification involves mapping time series to discrete data points; dynamics identification operates either between data points or across entire time series; and state estimation entails inferring data points or reconstructing time series from temporal data. In order to address these tasks, it is necessary to extend normalizing flows, given the limited research currently available in this area. Bridging this gap not only broadens the applicability of NFs but also contributes to advancing probabilistic inference techniques for complex temporal systems.

Having explored system identification and state estimation through probabilistic inference, we can advance toward data-driven control by leveraging data as a central source of insight into system behavior, enabling more adaptive, scalable, and robust control strate-

gies. This is especially advantageous in situations where analytical models are incomplete, uncertain, or impractical to derive. One unmediated application is model-free control, which obtains control inputs directly from observations and reference trajectories. This enables fast path planning without requiring an explicit system model. Furthermore, for more reliable and interpretable control, a preferable approach is to employ the identified dynamics within a Model Predictive Control (MPC) framework. This integration of learned models with numerical solvers and optimization routines allows for anticipatory decision-making based on predicted system behavior. Notably, in cases where simulation models are complex and the Jacobian of dynamics is analytically intractable, learning-based representations offer differentiable approximations that are inherently compatible with gradient-based solvers and optimizers. This compatibility facilitates efficient and scalable MPC implementations.

In summary, this work is motivated by three key considerations:

- Probabilistic inference provides a principled framework for modeling uncertainty and extracting knowledge from uncertainty, enabling system identification and state estimation based solely on observations in situations. This is particularly valuable in scenarios where first-principles models are unavailable, incomplete, or prohibitively complex.

- System identification and state estimation are required to be expressive for representing complex models, capable of modeling uncertainty, and scalable to large data sets. Deep Generative Models (DGMs), in particular Normalizing Flows (NFs), fulfill these criteria. However, existing architectures must be further developed to adapt to sequential data more flexibly.

- The results of probabilistic system identification can be integrated in Model Predictive Control (MPC), paving the way for interpretable, reliable, and robust control strategies. This fusion of learned models with optimization-based control frameworks holds promise for advancing autonomous decision-making in complex, uncertain environments.

2 Background and Preliminaries

This section introduces the necessary fundational concepts and methodologies for understanding the rest of this work. Before the main contents, we explain the unified notations applied in this whole work. We first review classical Bayesian inference methods. Then we introduce deep probabilistic models, including Deep Gaussian Process (DGP), Bayesian Neural Network (BNN), and Variational Autoencoder (VAE). Next, we present the core

methods of this work, Normalizing Flows (NFs), a powerful class of generative models for flexible density estimation. Finally, we bridge probabilistic inference to control methods, covering system identification, state estimation, and model predictive control.

2.1 Notations

In general, scalars are denoted by lowercase letters, e.g., x, vectors by bold lowercase letters, e.g., $\boldsymbol{x}$, and matrices by bold uppercase letters, e.g., $\boldsymbol{X}$.

Random variables are denoted by vectors, multiple dimensional sequences are denoted by matrics, and stochastic processes are denoted by uppercase letters, e.g., $X(t)$, where (t) means it is a function of time. A set of mixed or unspecified data types is denoted by calligraphic letters, e.g., $\mathcal{D}$. A time series of length T is denoted by $\boldsymbol{x}_{1:T}$, where the subscript indicates the time step. When a single dimension in the time series is mentioned, the superscript $[i]$ is used to indicate the i-th dimension, e.g., $\boldsymbol{x}[i]$. The estimation of a variable is denoted by a hat, e.g., $\hat{\boldsymbol{x}}$. The processed value of a variable is denoted by a tilde, e.g., $\tilde{\boldsymbol{x}}$.

The Probability Density Function (PDF) of a random variable is denoted by $p(\cdot)$, joint PDF is denoted by $p(\cdot, \cdot)$, conditional PDF is denoted by $p(\cdot|\cdot)$. The expectation of a function $f(x)$ with respect to the PDF of x, $p(x)$, is denoted by $\mathbb{E}_{p(x)}[f(x)]$. The covariance between two random variables $\boldsymbol{x}$ and $\boldsymbol{y}$ is denoted by $\mathrm{Cov}[\boldsymbol{x}, \boldsymbol{y}]$. The variance of a random variable $\boldsymbol{x}$ is denoted by $\mathrm{Var}[\boldsymbol{x}]$. The identity matrix is denoted by $\boldsymbol{I}$. The determinant of a matrix $\boldsymbol{J}$ is denoted by $\det|\boldsymbol{J}|$, where $\boldsymbol{J}$ denotes a Jacobian matrix. The trace of a matrix $\boldsymbol{X}$ is denoted by $\mathrm{tr}(\boldsymbol{X})$. The transpose of a matrix $\boldsymbol{X}$ is denoted by $\boldsymbol{X}^\top$.

2.2 Bayesian Inference

This chapter refers to the book *Bayesian Data Analysis* (Gelman et al., 2013).

2.2.1 Bayes' rule

Denoting $\boldsymbol{\theta}$ as the target variables and $\mathcal{D}$ as the observed data samples, Bayes' rule is:

$$p(\boldsymbol{\theta}|\mathcal{D}) = \frac{p(\mathcal{D}|\boldsymbol{\theta})p(\boldsymbol{\theta})}{p(\mathcal{D})} = \frac{p(\mathcal{D}|\boldsymbol{\theta})p(\boldsymbol{\theta})}{\int p(D|\boldsymbol{\theta}')p(\boldsymbol{\theta}')d\boldsymbol{\theta}'}. \tag{I.2}$$

$p(\boldsymbol{\theta})$ is the initial distribution of the variables before any data samples are considered, which is called the prior distribution. $p(\mathcal{D}|\boldsymbol{\theta})$ is the likelihood of expected data given the setting of parameters $\boldsymbol{\theta}$. $p(\mathcal{D})$ is called the marginal likelihood of expected data across all possible parameter settings, which is often regarded as constant. $p(\boldsymbol{\theta}|\mathcal{D})$ is the posterior distribution of the target parameter after being updated by the observed

data. For example, the probability of a disease θ_1 given a test result $\mathcal{D}_1$, $p(\theta_1|\mathcal{D}_1)$ can be narrowed down from the prior belief $p(\theta_1)$ and all known likelihoods of test results $p(\mathcal{D}_i|\theta_i)$. In the Bayesian context, probabilistic inference is the process of obtaining the posterior distribution $p(\boldsymbol{\theta}|\mathcal{D})$.

2.2.2 Markov Chain Monte Carlo

2.2.3 Variational Inference

2.3 Deep Probabilistic Models

2.3.1 Deep Gaussian Process

2.3.2 Bayesian Neural Networks

2.3.3 Variational Autoencoder

2.4 Normalizing Flows

2.4.1 Basics

2.4.2 Discrete Normalizing Flows

Coupling layers

Autoregressive flows

2.4.3 Continuous Normalizing Flows

Neural ODEs

FFJORD

2.5 From Inference to Control

2.5.1 Bayesian System Identification

2.5.2 Bayesian State Estimation

2.5.3 Model Predictive Control

3 Literature Review

Bayesian system identification
- Bayesian state estimation
- Applications of DGMs in system identification and state estimation

Normalizing flow in density estimation
Data-driven control theory and RL

4 Objectives and Contributions

5 Outline

Chapter II

Methodologies

1 Parameter Identification

BayesFlow Stochastic BayesFlow

2 Dynamics Identification

IMFlow NFNeuralSDE

3 State Estimation

IMFlow ability limited

limitation for bayesflow for identifying highly dynamical data

transformer-bayesian neural network better for identification of battery state-of-health

Luenberger Observer with NFNeuralSDE

4 Model Predictive Control

mpc with IMFlow mpc with identified dynamics using NFNeuralSDE

Chapter III

Experiments and Results

1 Parameter Identification

von der pol single track car quadcopter

2 Dynamics Identification

synthetic data physics-based real-world

3 State Estimation

4 Model Predictive Control

car quadcopter

5 Reinforcement Learning

car quadcopter

Chapter IV

Discussion and Conclusion

Chapter V

Abstract

Chapter VI

Zusammenfassung

Own Contributions

This chapter gives an overview of my contributions in distinction to team efforts.

Own share in data acquisition and data analysis

Own share in Data Acquisition.

Own share in Data Analysis.

Own Publications

In this section, all publications that I was a part of and contributed to during my Ph.D. work are listed. It is subdivided into *First Authorships* and *Co-Authorships*.

First Authorships - Peer Reviewed International Journal Publications

Y. Zhang, L. Mikelsons. **Advanced Modeling and Simulation in Engineering and Science**. *Sensitivity-guided iterative parameter identification and data generation with BayesFlow and PELS-VAE for model calibration*. doi:10.1186/s40323-023-00246-y.

First Authorships - Peer Reviewed International Conference Publications

Y. Zhang, L. Mikelsons. **2023 IEEE/ASME International Conference on Advanced Intelligent Mechatronics (AIM)**. *Solving Stochastic Inverse Problems with Stochastic BayesFlow*. doi:10.1109/AIM46323.2023.10196190.

Y. Zhang, L. Mikelsons. **2024 IEEE 63rd Conference on Decision and Control(CDC)**. *Inverse Modeling with Conditional Normalizing Flows for Data-Driven Model Predictive*

Control. doi:10.1109/CDC56724.2024.10886862.

Co-Authorships

M.E. Heringhaus, Y. Zhang, A. Zimmermann, L. Mikelsons. **Sensors 2022**. *Towards Reliable Parameter Extraction in MEMS Final Module Testing Using Bayesian Inference*. doi:10.3390/s22145408.

Bibliography

Andrew Y. K. Foong, David R. Burt, Yingzhen Li, and Richard E. Turner. On the expressiveness of approximate inference in bayesian neural networks, 2020. URL https://arxiv.org/abs/1909.00719.

Andrew Gelman, John B. Carlin, Hal S. Stern, David B. Dunson, Akti Vehtari, and Donald B. Rubin. *Bayesian Data Analysis*. Chapman & Hall/CRC Texts in Statistical Science Series. CRC, Boca Raton, Florida, third edition, 2013. ISBN 9781439840955 1439840954. URL https://stat.columbia.edu/~gelman/book/.

Laurent Girin, Simon Leglaive, Xiaoyu Bie, Julien Diard, Thomas Hueber, and Xavier Alameda-Pineda. Dynamical variational autoencoders: A comprehensive review. *Foundations and Trends® in Machine Learning*, 15(1–2):1–175, 2021. ISSN 1935-8245. doi: 10.1561/2200000089. URL http://dx.doi.org/10.1561/2200000089.

Ethan Goan and Clinton Fookes. *Bayesian Neural Networks: An Introduction and Survey*, page 45–87. Springer International Publishing, 2020. ISBN 9783030425531. doi: 10.1007/978-3-030-42553-1_3. URL http://dx.doi.org/10.1007/978-3-030-42553-1_3.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models, 2020. URL https://arxiv.org/abs/2006.11239.

Diederik P. Kingma and Max Welling. An introduction to variational autoencoders. *Foundations and Trends® in Machine Learning*, 12(4):307–392, 2019. ISSN 1935-8245. doi: 10.1561/2200000056. URL http://dx.doi.org/10.1561/2200000056.

Pierre-Alexandre Mattei and Jes Frellsen. Leveraging the exact likelihood of deep latent variable models. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, NIPS'18, page 3859–3870, Red Hook, NY, USA, 2018. Curran Associates Inc.

Kevin P. Murphy. *Probabilistic Machine Learning: An introduction*. MIT Press, 2022. URL http://probml.github.io/book1.

Kevin P. Murphy. *Probabilistic Machine Learning: Advanced Topics*. MIT Press, 2023. URL http://probml.github.io/book2.

Jose L. Paniagua and Jesús A. López. Nonlinear system identification using modified variational autoencoders. *Intelligent Systems with Applications*, 22:200344, 2024. ISSN 2667-3053. doi: https://doi.org/10.1016/j.iswa.2024.200344. URL https://www.sciencedirect.com/science/article/pii/S2667305324000206.

Danilo Jimenez Rezende and Shakir Mohamed. Variational inference with normalizing flows, 2016. URL https://arxiv.org/abs/1505.05770.

Simo Särkkä. The use of gaussian processes in system identification, 2019. URL https://arxiv.org/abs/1907.06066.



YI ZHANG

PhD in Applied Computer Science

Augsburg | 015236410279 | zhangyi1353173@yahoo.com
https://www.linkedin.com/in/yi-zhang-2020/

Soon-to-graduate PhD specializing in probabilistic deep learning for real-world industrial applications. Experienced in bridging state-of-the-art AI research with practical deployment, with a focus on developing reliable, robust, and efficient system identification and state estimation methods – essential for system observation, control, and decision making

Education

University of Augsburg 04.2021-03.2026 (estimated)
Doctor of Engineering in Applied Computer Science
Title of Dissertation: Probabilistic System Identification and State Estimation for Dynamical Systems via Normalizing Flows
https://www.uni-augsburg.de/de/fakultaet/fai/informatik/prof/imech/team/yi-zhang/

University of Stuttgart 10.2017 – 09.2020
Master of Science in Electrical and Electronics Engineering
Major: Signal processing, Machine Learning
Master Thesis: Feature Selection using Attention Mechanism in Deep Learning
Grade: 1.6

TH Aschaffenburg University of Applied Science 09.2016 – 09.2017
Bachelor of Engineering in Mechatronics (Exchange Program)
Major: Drive technology and robotics, Application of micro-electrotechnology
Bachelor Thesis: Algorithms for avoiding singularity in industrial robots
Grade: 1.5

University of Tongji, Shanghai 09.2013 – 09.2016
Bachelor of Engineering in Mechatronics
Grade: 1.8

Experience

Trumpf Werkzeugmaschinen GmbH, Ditzingen 05.2019 – 10.2019
Intern in R&D Pre-development Production Platform MT
- Support in the development of a prediction model for process-reliable part removal on a fully automated laser cutting machine
- Further development and implementation of a novel computer vision approach for teaching a finite element structure simulation through U-Net architectures, with Keras
- Evaluation and training of the models as well as realization and identification of improvement potentials to increase model accuracy

Publications

Zhang, Y. and Mikelsons, L., IMFlow: Inverse Modeling with Conditional Normalizing Flows for Data-Driven Model Predictive Control, 2024 IEEE 63rd Conference on Decision and Control (CDC), Milan, Italy, 2024, pp. 3353-3359, doi: 10.1109/CDC56724.2024.10886862.
Zhang, Y. and Mikelsons, L., Solving Stochastic Inverse Problems with Stochastic BayesFlow, 2023 IEEE/ASME International Conference on Advanced Intelligent Mechatronics (AIM), Seattle, WA, USA, 2023, pp. 966-972, doi: 10.1109/AIM46323.2023.10196190.
Zhang, Y. and Mikelsons, L., Sensitivity-guided iterative parameter identification and data generation with BayesFlow and PELS-VAE for model calibration. Adv. Model. and Simul. in Eng. Sci. 10, 9 (2023). doi: 10.1186/s40323-023-00246-y.
Heringhaus, M.E.; Zhang, Y.; Zimmermann, A.; Mikelsons, L., Towards Reliable Parameter Extraction in MEMS Final Module Testing Using Bayesian Inference. Sensors 2022, 22, 5408. doi: 10.3390/s22145408

Programming Languages

Python, Julia
MATLAB/Simulink, C++

Languages

English: Professional Proficiency
German: Professional Proficiency
Chinese: Native Proficiency

Technical Skills

Machine Learning/Deep Learning
Reinforcement Learning
Mathematics & Statistics
Data processing & -analysis
ML-Frameworks: PyTorch, Jax, TensorFlow/Keras

Problem-solving expertise

Implementation and optimization of algorithms
Interdisciplinary work
Creativity & critical thinking
Ability to think abstractly

Soft Skills

Explanation of complex concepts
Collaboration with researchers and industry partners
Independence & personal responsibility
Time management & prioritisation
Teamwork & collaboration
Openness to feedback
Curiosity & lifelong learning
Perseverance

Third-party funded projects

PHyMoS 04.2021 – 02.2024
(https://phymos.de/)
OpenScaling 11.2023 – 10.2026
(https://openscaling.org/)

Appendix

Acknowledgement

Eidesstattliche Versicherung

Statutory Declaration

1. Bei der eingereichten Dissertation zu dem Thema ***Probabilistic System Identification and State Estimation via Normalizing Flows*** handelt es sich um meine eigenständig erbrachte Leistung.
   *I herewith formally declare that I have written the submitted dissertation **Probabilistic System Identification and State Estimation via Normalizing Flows** independently.*
2. Ich habe nur die angegebenen Quellen und Hilfsmittel benutzt und mich keiner unzulässigen Hilfe Dritter bedient. Insbesondere habe ich wörtlich oder sinngemäß aus anderen Werken übernommene Inhalte als solche kenntlich gemacht.
   I did not use any third party support except for the quoted literature and other sources mentioned in the text. Content from other work, either literally or in content, has been declared as such.
3. Die Arbeit oder Teile davon habe ich bislang nicht an einer Hochschule des In- oder Auslands als Bestandteil einer Prüfungs- oder Qualifikationsleistung vorgelegt.
   The thesis has not been submitted to any examination body in this, or similar, form.
4. Die Richtigkeit der vorstehenden Erklärungen bestätige ich.
   I confirm the correctness of the aforementioned declarations.
5. Die Bedeutung der eidesstattlichen Versicherung und die strafrechtlichen Folgen einer unrichtigen oder unvollständigen eidesstattlichen Versicherung sind mir bekannt. Ich versichere an Eides statt, dass ich nach bestem Wissen die reine Wahrheit erklärt und nichts verschwiegen habe.
   I am aware of the legal consequences of this declaration. To the best of my knowledge I have told the pure truth and not concealed anything.

Augsburg, 29.08.2025 _____

Angabe zu verwendeten KI-basierter Elektronischer Hilfsmittel

Information on the use of AI-based tools

Zur Dokumentation der verwendeten Hilfsmittel ist der schriftlichen Ausarbeitung ein besonderer Anhang hinzugefügt, der eine Liste und Beschreibung aller verwendeter KI-basierter Hilfsmittel enthält. Der besondere Anhang zur Dokumentation der verwendeten Hilfsmittel erfüllt folgende Kriterien:

To document the tools used, a special appendix has been added to the written report, which contains a list and description of all AI-based tools used. The special appendix to document the tools used meets the following criteria:

1. Auflistung der Ziele, für die die KI-basierten Hilfsmittel in der vorliegenden Arbeit eingesetzt wurden.
   List of the goals for which the AI-based tools were used in this work.

2. Dokumentation der Verwendungsweise der KI-basierten Hilfsmittel.
   Documentation of how AI-based tools are used.

3. Nennung der Kapitel und Abschnitte der vorliegenden Arbeit, in denen die KI-basierten Hilfsmittel eingesetzt wurden, um Inhalte zu erzeugen.
   Identification of the chapters and sections of this work in which AI-based tools were used to generate content.

Der Gebrauch dieser Hilfsmittel inklusive Art, Ziel und Umfang des Gebrauchs wurde mit meinem offiziellen Betreuer **Prof.Dr.Ing. Lars Mikelsons** abgesprochen.

*The use of these aids, including the type, purpose and extent of use, has been agreed with my official supervisor **Prof.Dr.Eng. Lars Mikelsons**.*

Mir ist bewusst, dass insbesondere der Versuch einer nicht dokumentierten Nutzung KI- basierter Hilfsmittel als Täuschungsversuch zu werten ist:

I am aware that in particular the attempt to use AI-based tools without documentation is to be regarded as an attempt at deception:

Gem. § 16 Abs. 2 der Promotionsordnung „Dr. med. / dent.“: „Ergibt sich vor Aushändigung der Promotionsurkunde, dass der Kandidat/die Kandidatin bei einer Promotionsleistung getäuscht hat, so können einzelne oder alle Promotionsleistungen für ungültig erklärt werden. In schweren Fällen kann die Zulassung zum Promotionsverfahren zurückgenommen werden.“

According to § 16 paragraph 2 of the doctoral regulations for "Dr. med. / dent.": "If it emerges before the doctoral certificate is issued that the candidate has cheated in a doctoral achievement, individual or all doctoral achievements can be declared invalid. In serious cases, admission to the doctoral process can be withdrawn.

Und § 16 Abs. 2 der Promotionsordnung „Dr. sc. hum.“: „Ergibt sich vor Aushändigung der Promotionsurkunde, dass der Doktorand / Doktorandin bei einer Promotionsleistung getäuscht hat, so kann der Promotionsausschuss diese Promotionsleistung oder alle bisher erbrachten Promotionsleistungen für ungültig erklären. In besonders schweren Fällen kann der Promotionsausschuss die Annahme als Doktorand / Doktorandin endgültig widerrufen.“

And § 16 paragraph 2 of the doctoral regulations “Dr. sc. hum.”: “If it emerges before the doctoral certificate is issued that the doctoral candidate has cheated in a doctoral achievement, the doctoral committee can declare this doctoral achievement or all doctoral achievements to date invalid. In particularly serious cases, the doctoral committee can permanently revoke the acceptance as a doctoral candidate.”

Augsburg, 29.08.2025 _____