

ITEM-ID..... : 0015469 SPEC REVISION: AC
EFFECTIVE DATE : 8/12/86 SPEC STATUS : CURRENT
EXPIRATION DATE: DOM-EXPORT : BOTH
DESCRIPTION... : CP, REF 754 27.0X6000 (K-C)
GRADE : 754 DIS BRAND .. : VARIES

PRINTED : NO
CERTIFIED FOR MACHINES: MARK 9 MARK 9N PROTOS

* REMARKS *

SEE 754 GENERIC SPECIFICATION FOR FURTHER INFORMATION.

* PHYSICAL *	TARGET	REJECT LIMITS			
		-- BOBBIN --		-- PALLET --	
		LOW	HIGH	LOW	HIGH
TENSILE STRENGTH, DRY, LBS/WIDTH:	0.00	0.00		4.50	

* BOBBIN SUPPLIER INSTRUCTIONS *

WIRE SIDE DIRECTION	IN				
BOBBIN WIDTH, MM	27.00	26.80	27.20		
BOBBIN LENGTH, METERS	6000	6000			
CORE INSIDE DIAMETER, IN. ...	4.718750	4.703125	4.734375		
OUTSIDE DIAMETER, IN. ..			22.000000		
SPLICE INSTRUCTIONS					
LAP WIDTH, MM.			4.00000		
OVERLAP TAIL, MM.			1.00000		
SPLICES PER ROLL			4		
LAP WEAVE, IN.031250	.031250		
SPLICE ADHESIVE TYPE	MUST BE APPROVED BY RJRT				

* STACKING INSTRUCTIONS *

BOBBINS PER STACK	54
STACKS PER PALLET	4
BOBBINS PER PALLET	216

* PALLET INSTRUCTIONS *

PALLET LENGTH, IN.	0.00	51.00
PALLET WIDTH, IN.	0.00	51.00
PALLET HEIGHT, IN.	0.00	70.00
PALLET WEIGHT, LBS.	0.00	0.00

