



LC10P driver

AC Servo Motor Kit

Support 7 control modes/frequency division feedback function/
485 bus, ModbusRTU protocol, Support 17/23-bit servo motor, Adapt
to 40/60/80 series servo motor.



40/60/80 Series AC Servo Motor

	40 Series		60 Series			80 Series		
Motor model	LCMT-005 SLC17□□ -40M00130B	LCMT-01 SLC17□□ -40M00330B	LCMT-02 SLC17□□ -60M00630B	LCMT-04 SLC17□□ -60M01330B	LCMT-06 SLC17□□ -60M01930B	LCMT-07 SLC17□□ -80M02430B	LCMT-10 SLC17□□ -80M03230B	LCMT-10 SLC17□□ -80M04025B
Rated power(KW)	0.05	0.1	0.2	0.4	0.6	0.75	1.0	1.0
Rated voltage(V)	220	220	220	220	220	220	220	220
Rated current(A)	0.8	1.1	1.6	2.5	3.3	4.5	5.8	4.6
Rated speed(rpm)	3000	3000	3000	3000	3000	3000	3000	2500
Holding torque (N.m)	0.16	0.32	0.637	1.27	1.91	2.39	3.2	4.0
Peak torque (N.m)	0.48	0.95	1.91	3.81	5.71	7.17	7.96	11.46
Voltage constant (V/1000r/min)	19	20	29.3	31.2	34.5	32.8	32.5	50.8
Torque coefficient (N.m/A)	0.2	0.29	0.4	0.5	0.75	0.53	0.55	0.83
Rotor inertia (Kg.m ²)	0.053 x10 ⁻⁴	0.06 x10 ⁻⁴	0.3 x10 ⁻⁴	0.52 x10 ⁻⁴	0.58 x10 ⁻⁴	1.5 x10 ⁻⁴	1.55 x10 ⁻⁴	2.2 x10 ⁻⁴
Resistance (Ω)	19.7	10.5	8.9	3.5	3.4	1.2	1.17	2.3
Inductance (mH)	41	8.9	13.5	5.8	6.4	4.2	3.9	9.6
Mechanical time-constant (Ms)	2.0	0.85	1.52	1.66	1.88	3.5	3.33	4.2
Weight(Kg)	0.6	0.8	0.72	1.06	1.2	2.05	2.15	2.75
Motor Length (mm)	68.5	86.5	72	90	110	96	111	116
Brake Motor Length(mm)	101.5	119.5	102	120	140	133	133	155.5
Encoder line number(PPR)	17-bit incremental/17-bit absolute; 23-bit incremental/23-bit absolute encoder							
Insulation class	CLASS F							
Safety class	IP65							



Shenzhen Xinlichuan Electric Co., Ltd.
Address: F/10, Building S8, Tian'an Digital Park, Yantian, Fenggang Town, Dongguan



LC30P driver

AC Servo Motor Kit

Support 7 control modes/frequency division feedback function/
485 bus, ModbusRTU protocol, Support 17/23-bit servo motor, Adapt
to 110/130 series servo motor.



Shenzhen Xinlichuan Electric Co., Ltd.
Address: F/10, Building S8, Tian'an Digital Park, Yantian, Fenggang Town, Dongguan

110/130 Series AC Servo Motor

	110 Series			130 Series												
Motor model	LCMT-12L □□-110 M04030	LCMT-15L □□-110 M05030	LCMT-18L □□-110 M06030	LCMT-10L □□-130 M04025	LCMT-13L □□-130 M05025	LCMT-15L □□-130 M06025	LCMT-20L □□-130 M07725	LCMT-15M □□-130 M10015	LCMT-26M □□-130 M10025	LCMT-23M □□-130 M15015	LCMT-38M □□-130 M15025					
Rated power(KW)	1.2	1.5	1.8	1.0	1.3	1.5	2.0	1.5	2.6	2.3	3.8					
Rated voltage(V)	220	220	220	220	220	220	220	220	220	220	220					
Rated current(A)	5.0	6.0	6.0	4.0	5.0	6.0	7.5	6.0	10	9.5	13.5					
Rated speed(rpm)	3000	3000	3000	2500	2500	2500	2500	1500	2500	1500	2500					
Holding torque (N.m)	4.0	5.0	6.0	4.0	5.0	6.0	7.7	10	10	15	15					
Peak torque (N.m)	12	15	18	12	16	18	22	25	25	30	30					
Voltage constant (V/1000r/min)	54	62	60	72	68	65	68	103	70	114	67					
Torque coefficient (N.m/A)	0.8	0.83	1.0	1.0	1.0	1.0	1.03	1.67	1.0	1.58	1.1					
Rotor inertia (Kg.m ²)	0.54x10 ⁻³	0.63x10 ⁻³	0.76x10 ⁻³	0.85x10 ⁻³	1.06x10 ⁻³	1.26x10 ⁻³	1.53x10 ⁻³	1.94x10 ⁻³	1.94x10 ⁻³	2.77x10 ⁻³	2.77x10 ⁻³					
Resistance (Ω)	1.09	1.03	0.81	2.76	1.84	1.21	1.01	1.29	0.73	0.64	0.49					
Inductance (mH)	3.3	3.43	2.59	6.42	4.9	3.87	2.94	5.07	2.45	4.45	1.68					
Mechanical time-constant (ms)	3.0	3.33	3.2	2.32	2.66	3.26	3.80	3.93	3.36	4.05	3.43					
Weight(Kg)	5.5	6.1	6.7	7.7	8.2	8.9	10	11.5	11.5	14.4	14.4					
Motor Length(mm)	189	204	219	166	171	179	192	213	209	241	231					
Brake Motor Length(mm)	263	278	293	223	228	236	249	294	290	322	312					
Encoder linewidth (PPR)	17-bit incremental/17-bit absolute; 23-bit incremental/23-bit absolute encoder															
Insulation class	CLASS B(130°C)															
Safety class	IP65															
Use Environment	Ambient temperature: -20°C~ 50°C; Ambient humidity: Relative humidity <90% (without conditions)															
Motor winding socket	Winding lead	U			V			W			PE					
	Outlet number	2			3			4			1					
Encoder socket	Winding lead	5V	0V	A+	B+	Z+	A-	B-	Z-	U+	V+	W+	U-	V-	W-	PE
	Outlet number	2	3	4	5	6	7	8	9	10	11	12	13	14	5	1



LC10E driver

AC Servo Motor Kit

Support PP/PV/PT/HM/CSP/CSV/CST mode Built-in 35 reset modes
Support 17bit/23-bit servo motor Adapt to 40/60/80 series servo motor.



EtherCAT

40/60/80 Series AC Servo Motor

	40 Series		60 Series			80 Series		
Motor model	LCMT-005 SLC17□□ -40M00130B	LCMT-01 SLC17□□ -40M00330B	LCMT-02 SLC17□□ -60M00630B	LCMT-04 SLC17□□ -60M01330B	LCMT-06 SLC17□□ -60M01930B	LCMT-07 SLC17□□ -80M02430B	LCMT-10 SLC17□□ -80M03230B	LCMT-10 SLC17□□ -80M04025B
Rated power(KW)	0.05	0.1	0.2	0.4	0.6	0.75	1.0	1.0
Rated voltage(V)	220	220	220	220	220	220	220	220
Rated current(A)	0.8	1.1	1.6	2.5	3.3	4.5	5.8	4.6
Rated speed(rpm)	3000	3000	3000	3000	3000	3000	3000	2500
Holding torque (N.m)	0.16	0.32	0.637	1.27	1.91	2.39	3.2	4.0
Peak torque (N.m)	0.48	0.95	1.91	3.81	5.71	7.17	7.96	11.46
Voltage constant (V/1000r/min)	19	20	29.3	31.2	34.5	32.8	32.5	50.8
Torque coefficient (N.m/A)	0.2	0.29	0.4	0.5	0.75	0.53	0.55	0.83
Rotor inertia (Kg.m²)	0.053 x10 ⁻⁴	0.06 x10 ⁻⁴	0.3 x10 ⁻⁴	0.52 x10 ⁻⁴	0.58 x10 ⁻⁴	1.5 x10 ⁻⁴	1.55 x10 ⁻⁴	2.2 x10 ⁻⁴
Resistance (Ω)	19.7	10.5	8.9	3.5	3.4	1.2	1.17	2.3
Inductance (mH)	41	8.9	13.5	5.8	6.4	4.2	3.9	9.6
Mechanical time-constant (Ms)	2.0	0.85	1.52	1.66	1.88	3.5	3.33	4.2
Weight(Kg)	0.6	0.8	0.72	1.06	1.2	2.05	2.15	2.75
Motor Length (mm)	68.5	86.5	72	90	110	96	111	116
Brake Motor Length(mm)	101.5	119.5	102	120	140	133	133	155.5
Encoder line number(PPR)	17-bit incremental/17-bit absolute; 23-bit incremental/23-bit absolute encoder							
Insulation class	CLASS F							
Safety class	IP65							



Shenzhen Xinlichuan Electric Co., Ltd.
Address: F/10, Building S8, Tian'an Digital Park, Yantian, Fenggang Town, Dongguan

LC30E driver

AC Servo Motor Kit

Support PP/PV/PT/HM/CSP/CSV/CST mode Built-in 35 reset modes
Support 17bit/23-bit servo motor Adapt to 110/130 series servo motor.



110/130 Series AC Servo Motor

	110 Series					130 Series										
Motor model	LCMT-12L □□-110 M04030	LCMT-15L □□-110 M05030	LCMT-18L □□-110 M06030	LCMT-10L □□-130 M04025	LCMT-13L □□-130 M05025	LCMT-15L □□-130 M06025	LCMT-20L □□-130 M07725	LCMT-15M □□-130 M10015	LCMT-26M □□-130 M10025	LCMT-23M □□-130 M15015	LCMT-38M □□-130 M15025					
Rated power(KW)	1.2	1.5	1.8	1.0	1.3	1.5	2.0	1.5	2.6	2.3	3.8					
Rated voltage(V)	220	220	220	220	220	220	220	220	220	220	220					
Rated current(A)	5.0	6.0	6.0	4.0	5.0	6.0	7.5	6.0	10	9.5	13.5					
Rated speed(rpm)	3000	3000	3000	2500	2500	2500	2500	1500	2500	1500	2500					
Holding torque (N.m)	4.0	5.0	6.0	4.0	5.0	6.0	7.7	10	10	15	15					
Peak torque (N.m)	12	15	18	12	16	18	22	25	25	30	30					
Voltage constant (V/1000r/min)	54	62	60	72	68	65	68	103	70	114	67					
Torque coefficient (N.m/A)	0.8	0.83	1.0	1.0	1.0	1.0	1.03	1.67	1.0	1.58	1.1					
Rotor inertia (Kg.m²)	0.54x10 ⁻³	0.63x10 ⁻³	0.76x10 ⁻³	0.85x10 ⁻³	1.06x10 ⁻³	1.26x10 ⁻³	1.53x10 ⁻³	1.94x10 ⁻³	1.94x10 ⁻³	2.77x10 ⁻³	2.77x10 ⁻³					
Resistance (Ω)	1.09	1.03	0.81	2.76	1.84	1.21	1.01	1.29	0.73	0.64	0.49					
Inductance (mH)	3.3	3.43	2.59	6.42	4.9	3.87	2.94	5.07	2.45	4.45	1.68					
Mechanical time-constant (Ms)	3.0	3.33	3.2	2.32	2.66	3.26	3.80	3.93	3.36	4.05	3.43					
Weight(Kg)	5.5	6.1	6.7	7.7	8.2	8.9	10	11.5	11.5	14.4	14.4					
Motor Length(mm)	189	204	219	166	171	179	192	213	209	241	231					
Brake Motor Length(mm)	263	278	293	223	228	236	249	294	290	322	312					
Encoder linenumber (PPR)	17-bit incremental/17-bit absolute; 23-bit incremental/23-bit absolute encoder															
Insulation class	CLASS B(130°C)															
Safety class	IP65															
Use Environment	Ambient temperature: -20°C~ 50°C; Ambient humidity: Relative humidity <90% (without conditions)															
Motor winding socket	Winding lead	U			V				W				PE			
	Outlet number	2			3				4				1			
Encoder socket	Winding lead	5V	0V	A+	B+	Z+	A-	B-	Z-	U+	V+	W+	U-	V-	W-	PE
	Outlet number	2	3	4	5	6	7	8	9	10	11	12	13	14	5	1



Shenzhen Xinlichuan Electric Co., Ltd.

Address: F/10, Building S8, Tian'an Digital Park, Yantian, Fenggang Town, Dongguan

A6 driver

AC Servo Motor Kit

The product greatly improves the positioning accuracy of the motor, and can make the motor run more smoothly at low speed, with smaller speed errors, suitable for 40~130 series servo motors.

Pulse



40/60/80/90 Series 4 Pole AC Servo Motor

	40 Series		60 Series			80 Series			90 Series			
Motor model	LCMT-005L □-40M 00130	LCMT-01L □-40M 00330	LCMT-02L □-60M 00630	LCMT-04L □-60M 01330	LCMT-06L □-60M 01930	LCMT-04L □-80M 01330	LCMT-07L □-80M 02430	LCMT-07M □-80M 03520	LCMT-10L □-80M 04025	LCMT-07L □-90M 02430	LCMT-07M □-90M 03520	LCMT-10L □-90M 04025
Rated power(KW)	0.05	0.1	0.2	0.4	0.6	0.4	0.75	0.75	1.0	0.75	0.75	1.0
Rated voltage(V)	220	220	220	220	220	220	220	220	220	220	220	220
Rated current(A)	0.4	0.6	1.5	2.8	3.5	2.0	3.0	3.0	4.4	3.0	3.0	4.0
Rated speed(rpm)	3000	3000	3000	3000	3000	3000	3000	2000	3000	3000	2000	2500
Holding torque (N.m)	0.16	0.32	0.637	1.27	1.91	1.27	2.39	3.5	4.0	2.4	3.5	4.0
Peak torque (N.m)	0.32	0.64	1.911	3.8	5.73	3.8	7.1	10.5	12	7.1	10.5	12
Voltage constant (V/1000r/min)	36.8	32.8	28	28	28	6.0	9.0	9.0	13.2	51	67	60
Torque coefficient (N.m/A)	0.4	0.53	0.42	0.5	0.55	40	48	71	56	0.8	1.2	1.0
Rotor inertia (Kg.m ²)	0.025 x10 ⁻⁴	0.051 x10 ⁻⁴	0.17 x10 ⁻⁴	0.302 x10 ⁻⁴	0.438 x10 ⁻⁴	1.05 x10 ⁻⁴	1.82 x10 ⁻⁴	2.63 x10 ⁻⁴	2.97 x10 ⁻⁴	2.45 x10 ⁻⁴	3.4 x10 ⁻⁴	3.7 x10 ⁻⁴
Resistance (Ω)	108	34	11.6	5.83	3.49	4.44	2.88	3.65	1.83	3.2	4.06	2.69
Inductance (mH)	108	40	22	12.23	8.47	7.93	6.4	8.8	4.72	7.0	9.7	6.21
Mechanical time-constant (Ms)	1.0	1.18	1.9	2.1	2.4	1.66	2.22	2.4	2.58	2.2	2.39	2.3
Weight(Kg)	0.32	0.47	1.11	1.33	1.78	1.78	2.86	3.7	3.8	3.4	3.8	4.13
Motor Length (mm)	84	99	115	140	169	123	150	178	190	149	171	181
Brake Motor Length(mm)	None	None	164	189	217	164	191	219	231	198	220	230
Encoder line number(PPR)	2500/17-bit incremental/17-bit absolute encoder											
Insulation class	CLASS B(130°C)											
Safety class	IP65											



Shenzhen Xinlichuan Electric Co., Ltd.

Address: F/10, Building S8, Tian'an Digital Park, Yantian, Fenggang Town, Dongguan

40/60/80 Series 5 Pole AC Servo Motor

	110 Series						130 Series										
Motor model	LCMT-06L□□-110M02030	LCMT-08L□□□-110M04020	LCMT-12L□□□-110M04030	LCMT-15L□□□-110M05030	LCMT-12L□□□-110M06020	LCMT-18L□□□-110M06030	LCMT-10L□□□-130M04025	LCMT-13L□□□-130M05025	LCMT-15L□□□-130M06025	LCMT-20L□□□-130M07725	LCMT-10L□□□-130M10010	LCMT-15L□□□-130M10015	LCMT-26L□□□-130M10025	LCMT-23L□□□-130M15015	LCMT-30L□□□-130M15020	LCMT-38L□□□-130M15025	
Rated power(KW)	0.6	0.8	1.2	1.5	1.2	1.8	1.0	1.3	1.5	2.0	1.0	1.5	2.6	2.3	3.0	3.8	
Rated voltage(V)	220	220	220	220	220	220	220	220	220	220	220	220	220	220	220	220	
Rated current(A)	2.5	3.5	5.0	6.0	4.5	6.0	4.0	5.0	6.0	7.5	4.5	6.0	10	9.5	12	13.5	
Rated speed(rpm)	3000	2000	3000	3000	2000	3000	2500	2500	2500	2500	1000	1500	2500	1500	2000	2500	
Holding torque (N.m)	2.0	4.0	4.0	5.0	6.0	6.0	4.0	5.0	6.0	7.7	10	10	10	15	15	15	
Peak torque (N.m)	6.0	12	12	15	12	18	12	16	18	22	20	25	25	30	30	30	
Voltage constant (V/1000r/min)	56	79	54	62	83	60	72	68	65	68	140	103	70	114	80	67	
Torque coefficient (N.m/A)	0.8	1.14	0.8	0.83	1.3	1.0	1.0	1.0	1.0	1.03	2.2	1.67	1.0	1.58	1.25	1.1	
Rotor inertia (Kg.m ²)	0.31x10 ⁻³	0.54x10 ⁻³	0.54x10 ⁻³	0.63x10 ⁻³	0.76x10 ⁻³	0.76x10 ⁻³	0.85x10 ⁻³	1.06x10 ⁻³	1.26x10 ⁻³	1.53x10 ⁻³	1.94x10 ⁻³	1.94x10 ⁻³	1.94x10 ⁻³	2.77x10 ⁻³	2.77x10 ⁻³	2.77x10 ⁻³	
Resistance (Ω)	3.6	2.41	1.09	1.03	1.46	0.81	2.76	1.84	1.21	1.01	2.7	1.29	0.73	0.64	0.64	0.49	
Inductance (mH)	8.32	7.3	3.3	3.43	4.7	2.59	6.42	4.9	3.87	2.94	8.8	5.07	2.45	4.45	4.45	1.68	
Mechanical time-constant (Ms)	2.3	3.0	3.0	3.33	3.2	3.2	2.32	2.66	3.26	3.80	3.26	3.93	3.36	4.05	4.05	3.43	
Weight(Kg)	4.5	5.2	5.5	6.1	6.7	6.7	7.7	8.2	8.9	10	11.5	11.5	11.5	14.4	14.4	14.4	
Motor Length(mm)	159	189	189	204	219	219	166	171	179	192	213	213	209	241	231	231	
Brake Motor Length(mm)	223	263	263	278	293	293	223	228	236	249	294	294	290	322	312	312	
Encoder linewidth (PPR)	2500/17-bit incremental/17-bit absolute encoder																
Insulation class	CLASS B(130℃)																
Safety class	IP65																
Use Environment	Ambient temperature: -20℃~ 50℃; Ambient humidity: Relative humidity <90% (without conditions)																
Motor winding socket	Winding lead	U				V				W				PE			
	Outlet number	2				3				4				1			
Encoder socket	Winding lead	5V	0V	A+	B+	Z+	A-	B-	Z-	U+	V+	W+	U-	V-	W-	PE	
	Outlet number	2	3	4	5	6	7	8	9	10	11	12	13	14	5	1	

	40 Series		60 Series			80 Series		
Motor model	LCMT-005 SLC17□□ -40M00130B	LCMT-01 SLC17□□ -40M00330B	LCMT-02 SLC17□□ -60M00630B	LCMT-04 SLC17□□ -60M01330B	LCMT-06 SLC17□□ -60M01930B	LCMT-07 SLC17□□ -80M02430B	LCMT-10 SLC17□□ -80M03230B	LCMT-10 SLC17□□ -80M04025B
Rated power(KW)	0.05	0.1	0.2	0.4	0.6	0.75	1.0	1.0
Rated voltage(V)	220	220	220	220	220	220	220	220
Rated current(A)	0.8	1.1	1.6	2.5	3.3	4.5	5.8	4.6
Rated speed(rpm)	3000	3000	3000	3000	3000	3000	3000	2500
Holding torque (N.m)	0.16	0.32	0.637	1.27	1.91	2.39	3.2	4.0
Peak torque (N.m)	0.48	0.95	1.91	3.81	5.71	7.17	7.96	11.46
Voltage constant (V/1000r/min)	19	20	29.3	31.2	34.5	32.8	32.5	50.8
Torque coefficient (N.m/A)	0.2	0.29	0.4	0.5	0.75	0.53	0.55	0.83
Rotor inertia (Kg.m²)	0.053 x10 ⁻⁴	0.06 x10 ⁻⁴	0.3 x10 ⁻⁴	0.52 x10 ⁻⁴	0.58 x10 ⁻⁴	1.5 x10 ⁻⁴	1.55 x10 ⁻⁴	2.2 x10 ⁻⁴
Resistance (Ω)	19.7	10.5	8.9	3.5	3.4	1.2	1.17	2.3
Inductance (mH)	41	8.9	13.5	5.8	6.4	4.2	3.9	9.6
Mechanical time-constant(Ms)	2.0	0.85	1.52	1.66	1.88	3.5	3.33	4.2
Weight(Kg)	0.6	0.8	0.72	1.06	1.2	2.05	2.15	2.75
Motor Length (mm)	68.5	86.5	72	90	110	96	111	116
Brake Motor Length(mm)	101.5	119.5	102	120	140	133	133	155.5
Encoder line number(PPR)	17-bit incremental/17-bit absolute; 23-bit incremental/23-bit absolute encoder							
Insulation class	CLASS F							
Safety class	IP65							

LCDA630P driver

380V Large Power Servo Kit

Support MODBUS, customizable CANopen & EtherCAT communication protocol, which can achieve multi-sero drive networking operation with the uppercomputer;Adapt to 130/180/200/250 series servo motor.



130/180/200/250 Series 380V Servo Motor

Series	Model	Motor encoder type	Rated power (KW)	Rated Speed (RPM)	rated current (A)	Torque (N.M)	Drive Model [Pulse]
130	LCMT-08MCC23NB-130M05015B	23-bit optical encoder; incremental/absolute	0.85	1500	3.5	5.4	LCDA-0805C23-M1534P
	LCMT-10MCC23NB-130M05020B		1.0	2000	3.2	4.77	LCDA-1003C23-M2034P
	LCMT-13MCC23NB-130M08015B		1.3	1500	6.5	8.3	LCDA-1308C23-M1534P
	LCMT-15MCC23NB-130M07020B		1.5	2000	5.8	7.16	LCDA-1508C23-M2034P
	LCMT-18MCC23NB-130M11015B		1.8	1500	6.3	11.4	LCDA-1808C23-M1534P
	LCMT-20MCC23NB-130M10020B		2.0	2000	8.2	10	LCDA-3008C23-M2034P
	LCMT-30MCC23NB-130M15020B		3.0	2000	8.2	15	LCDA-1308C23-M1534P
180	LCMT-30MCC23NB-180M19015B	23-bit optical encoder; incremental/absolute	3.0	1500	7.5	19	LCDA-3008C23-M1534P
	LCMT-45MCC23NB-180M21020B		4.5	2000	10	21.5	LCDA-4512C23-M2034P
	LCMT-45MCC23NB-180M28015B		4.5	1500	10	28.6	LCDA-4512C23-M1534P
	LCMT-55MCC23NB-180M35015B		5.5	1500	12	35	LCDA-5517C23-M1534P
	LCMT-75MCC23NB-180M48015B		7.5	1500	17.5	48	LCDA-7521C23-M1534P
200	LCMT-100MCC23NB-200M65015B	23-bit optical encoder; incremental/absolute	10.2	1500	19.1	65	LCDA-1026C23-M1534P
	LCMT-130MCC23NB-200M84015B		13.2	1500	24.6	84	LCDA-1332C23-M1534P
	LCMT-170MCC23NB-200M108015B		17	1500	31.8	108	LCDA-1737C23-M1534P
	LCMT-200MCC23NB-200M130015B		20.4	1500	39.2	130	LCDA-2045C23-M1534P
	LCMT-240MCC23NB-200M156015B		24.5	1500	44.7	156	LCDA-2460C23-M1534P
	LCMT-280MCC23NB-200M180015B		28.3	1500	52	180	LCDA-2860C23-M1534P
	LCMT-320MCC23NB-200M205015B		32.2	1500	61.8	205	LCDA-3275C23-M1534P
	LCMT-360MCC23NB-200M230015B		36	1500	73	230	LCDA-3675C23-M1534P
250	LCMT-390MCC23NB-250M250015B	23-bit optical encoder; incremental/absolute	39.2	1500	73.3	250	LCDA-3975C23-M1534P
	LCMT-460MCC23NB-250M292015B		45.9	1500	87	292	LCDA-4690C23-M1534P
	LCMT-530MCC23NB-250M340015B		53.4	1500	100	340	LCDA-53112C23-M1534P
	LCMT-580MCC23NB-250M370015B		58.1	1500	110	370	LCDA-58112C23-M1534P
	LCMT-630MCC23NB-250M405015B		63.6	1500	115	405	LCDA-63112C23-M1534P
	LCMT-670MCC23NB-250M429015B		67.4	1500	126	429	LCDA-67140C23-M1534P
	LCMT-770MCC23NB-250M492015B		77.3	1500	146	492	LCDA-77170C23-M1534P
	LCMT-850MCC23NB-250M545015B		85.6	1500	166	545	LCDA-85170C23-M1534P



Shenzhen Xinlichuan Electric Co., Ltd.

Address: F/10, Building S8, Tian'an Digital Park, Yantian, Fenggang Town, Dongguan

DS2-P/R driver

Low-voltage DC Servo Kit

DS2 series DC servo driver supports low-voltage servo motors from 100W to 1500W, supports 17bit/23bit incremental and absolute encoder. It can be connected to an external braking resistor.

Pulse
RS485



40/60/80/110/130 Series DC Servo Motor

	40 Series		60 Series				80 Series		110 Series	130 Series	
Motor model	LC01SC 17N-40M 00330DC□□		LC02SC 17N-60M 00630DC□□		LC04SC 17N-60M 01330DC□□		LC06SC 17N-60M 01930DC48	LC07SC 17N-80M 02430DC48	LC10SC 17N-80M 03230DC48	LC15C 17N-110M 06025DC48	LC15C 17N-130M 06025DC48
Rated power(KW)	0.1		0.2		0.4		0.6	0.75	1.0	1.5	1.5
Rated voltage(V)	24	48	24	48	24	48	48	48	48	48	48
Rated current(A)	6.5	3.7	12	6.0	20	10	15	19	25	45	45
Rated speed(rpm)	3000	3000	3000	3000	3000	3000	3000	3000	3000	2500	2500
Holding torque (N.m)	0.32	0.32	0.637	0.637	1.27	1.27	1.91	2.4	3.2	6.0	6.0
Peak torque (N.m)	0.64	0.64	1.91	1.91	3.81	3.81	5.73	4.8	6.4	12	12
Voltage constant (V/1000r/min)	3.2	5.5	3.85	7.7	4.2	8.4	8.6	8.0	8.0	9.5	9.5
Torque coefficient (N.m/A)	0.05	0.09	0.053	0.106	0.053	0.127	0.127	0.13	0.13	0.83	0.13
Rotor inertia (Kg.m ²)	0.053 x10 ⁻⁴	0.053 x10 ⁻⁴	0.29 x10 ⁻⁴	0.29 x10 ⁻⁴	0.053 x10 ⁻⁴	0.053 x10 ⁻⁴	0.68 x10 ⁻⁴	1.62 x10 ⁻⁴	2.1 x10 ⁻⁴	7.4 x10 ⁻⁴	12.9 x10 ⁻⁴
Resistance (Ω)	0.4	1.22	0.17	0.63	0.1	0.36	0.25	0.08	0.05	0.03	0.2
Inductance (mH)	0.38	1.15	0.27	1.12	0.17	0.65	0.43	0.27	0.17	0.17	0.3
Mechanical time-constant (Ms)	0.95	0.95	1.58	1.77	1.7	1.8	1.7	3.4	3.4	5.7	1.5
Weight(Kg)	0.65	0.65	1.0	1.0	1.4	1.4	1.8	2.5	3.2	6.5	6.5
Motor Length (mm)	79.5	79.5	77.2	77.2	93.7	93.7	125.3	105	119	219	179
Brake Motor Length(mm)	112.5	112.5	109.2	109.2	125.7	125.7	138	142	156	293	237
Encoder line number(PPR)	17-bit incremental/17-bit absolute; 23-bit incremental/23-bit absolute encoder										
Insulation class	CLASSF										
Safety class	IP65										



Shenzhen Xinlichuan Electric Co., Ltd.

Address: F/10, Building S8, Tian'an Digital Park, Yantian, Fenggang Town, Dongguan

DS2-C driver

Low-voltage DC Servo Kit

DS2 series DC servo driver supports low-voltage servo motors from 100W to 1500W, supports 17bit/23bit incremental and absolute encoder. It can be connected to an external braking resistor.



40/60/80/110/130 Series DC Servo Motor

	40 Series		60 Series				80 Series		110 Series	130 Series	
Motor model	LC01SC 17N-40M 00330DC□□		LC02SC 17N-60M 00630DC□□		LC04SC 17N-60M 01330DC□□		LC06SC 17N-60M 01930DC48	LC07SC 17N-80M 02430DC48	LC10SC 17N-80M 03230DC48	LC15C 17N-110M 06025DC48	LC15C 17N-130M 06025DC48
Rated power(KW)	0.1		0.2		0.4		0.6	0.75	1.0	1.5	1.5
Rated voltage(V)	24	48	24	48	24	48	48	48	48	48	48
Rated current(A)	6.5	3.7	12	6.0	20	10	15	19	25	45	45
Rated speed(rpm)	3000	3000	3000	3000	3000	3000	3000	3000	3000	2500	2500
Holding torque (N.m)	0.32	0.32	0.637	0.637	1.27	1.27	1.91	2.4	3.2	6.0	6.0
Peak torque (N.m)	0.64	0.64	1.91	1.91	3.81	3.81	5.73	4.8	6.4	12	12
Voltage constant (V/1000r/min)	3.2	5.5	3.85	7.7	4.2	8.4	8.6	8.0	8.0	9.5	9.5
Torque coefficient (N.m/A)	0.05	0.09	0.053	0.106	0.053	0.127	0.127	0.13	0.13	0.83	0.13
Rotor inertia (Kg.m ²)	0.053 x10 ⁻⁴	0.053 x10 ⁻⁴	0.29 x10 ⁻⁴	0.29 x10 ⁻⁴	0.053 x10 ⁻⁴	0.053 x10 ⁻⁴	0.68 x10 ⁻⁴	1.62 x10 ⁻⁴	2.1 x10 ⁻⁴	7.4 x10 ⁻⁴	12.9 x10 ⁻⁴
Resistance (Ω)	0.4	1.22	0.17	0.63	0.1	0.36	0.25	0.08	0.05	0.03	0.2
Inductance (mH)	0.38	1.15	0.27	1.12	0.17	0.65	0.43	0.27	0.17	0.17	0.3
Mechanical time-constant (Ms)	0.95	0.95	1.58	1.77	1.7	1.8	1.7	3.4	3.4	5.7	1.5
Weight(Kg)	0.65	0.65	1.0	1.0	1.4	1.4	1.8	2.5	3.2	6.5	6.5
Motor Length (mm)	79.5	79.5	77.2	77.2	93.7	93.7	125.3	105	119	219	179
Brake Motor Length(mm)	112.5	112.5	109.2	109.2	125.7	125.7	138	142	156	293	237
Encoder line number(PPR)	17-bit incremental/17-bit absolute; 23-bit incremental/23-bit absolute encoder										
Insulation class	CLASSF										
Safety class	IP65										



Shenzhen Xinlichuan Electric Co., Ltd.

Address: F/10, Building S8, Tian'an Digital Park, Yantian, Fenggang Town, Dongguan

DS2-E driver

Low-voltage DC Servo Kit

DS2 series DC servo driver supports low-voltage servo motors from 100W to 1500W, supports 17bit/23bit incremental and absolute encoder. It can be connected to an external braking resistor.

EtherCAT
bus



40/60/80/110/130 Series DC Servo Motor

	40 Series		60 Series					80 Series		110 Series	130 Series
Motor model	LC01SC 17N-40M 00330DC□□		LC02SC 17N-60M 00630DC□□		LC04SC 17N-60M 01330DC□□		LC06SC 17N-60M 01930DC48	LC07SC 17N-80M 02430DC48	LC10SC 17N-80M 03230DC48	LC15C 17N-110M 06025DC48	LC15C 17N-130M 06025DC48
Rated power(KW)	0.1		0.2		0.4		0.6	0.75	1.0	1.5	1.5
Rated voltage(V)	24	48	24	48	24	48	48	48	48	48	48
Rated current(A)	6.5	3.7	12	6.0	20	10	15	19	25	45	45
Rated speed(rpm)	3000	3000	3000	3000	3000	3000	3000	3000	3000	2500	2500
Holding torque (N.m)	0.32	0.32	0.637	0.637	1.27	1.27	1.91	2.4	3.2	6.0	6.0
Peak torque (N.m)	0.64	0.64	1.91	1.91	3.81	3.81	5.73	4.8	6.4	12	12
Voltage constant (V/1000r/min)	3.2	5.5	3.85	7.7	4.2	8.4	8.6	8.0	8.0	9.5	9.5
Torque coefficient (N.m/A)	0.05	0.09	0.053	0.106	0.053	0.127	0.127	0.13	0.13	0.83	0.13
Rotor inertia (Kg.m ²)	0.053 x10 ⁻⁴	0.053 x10 ⁻⁴	0.29 x10 ⁻⁴	0.29 x10 ⁻⁴	0.053 x10 ⁻⁴	0.053 x10 ⁻⁴	0.68 x10 ⁻⁴	1.62 x10 ⁻⁴	2.1 x10 ⁻⁴	7.4 x10 ⁻⁴	12.9 x10 ⁻⁴
Resistance (Ω)	0.4	1.22	0.17	0.63	0.1	0.36	0.25	0.08	0.05	0.03	0.2
Inductance (mH)	0.38	1.15	0.27	1.12	0.17	0.65	0.43	0.27	0.17	0.17	0.3
Mechanical time-constant (Ms)	0.95	0.95	1.58	1.77	1.7	1.8	1.7	3.4	3.4	5.7	1.5
Weight(Kg)	0.65	0.65	1.0	1.0	1.4	1.4	1.8	2.5	3.2	6.5	6.5
Motor Length (mm)	79.5	79.5	77.2	77.2	93.7	93.7	125.3	105	119	219	179
Brake Motor Length(mm)	112.5	112.5	109.2	109.2	125.7	125.7	138	142	156	293	237
Encoder line number(PPR)	17-bit incremental/17-bit absolute; 23-bit incremental/23-bit absolute encoder										
Insulation class	CLASSF										
Safety class	IP65										



Shenzhen Xinlichuan Electric Co., Ltd.

Address: F/10, Building S8, Tian'an Digital Park, Yantian, Fenggang Town, Dongguan