Sun Fast 3300 “Sun Dragon” (USA 33070) – Rig Sketch

Schematic, not to rigging-drawing accuracy. Heights above the ORR sheer datum. Built from the 2026 ORR certificate (US43110) plus three photos.



Dimensions

Item	Value	Basis
Masthead height (spin halyard, ISPA)	44.32 ft	**Certificate**
Forestay / hounds height, I	41.04 ft (TL above = 3.28 ft)	**Certificate**
J (mast to forestay base) / P / E / boom height	13.71 / 39.33 / 14.53 / 4.84 ft	**Certificate**
Mast section (my reading of MDL/MDT)	≈6.1 × 3.6 in lower, ≈5.2 × 3.6 in upper; carbon, 184 lb, CG 15.66 ft	**Certificate**
Mast rake	5° aft (≈3.9 ft at masthead, ≈3.6 ft at hounds)	**Provided**
Forestay length	≈44.4 ft (≈23° from vertical)	Calculated from I, J and rake

Spreader heights (lower / upper)	≈13.7 / ≈27.4 ft (about ⅓ and ⅔ of mast)	**Photo estimate**
Spreader length (lower / upper)	≈4.6 / ≈3.3 ft, swept ≈33° / ≈41° aft (tips ≈2.5 / 2.2 ft aft of the mast)	**Photo estimate, ±0.5 ft**
Shared chainplate (cap + intermediate + lower) half-width	≈4.7 ft (beam max 11.45 ft)	**Estimate**
Chainplate fore-aft position	≈2.5 ft aft of mast base	**Photo estimate, ±0.8 ft**
Cap / intermediate / lower shroud lengths	≈41.3 / ≈28.0 / ≈14.2 ft (one lower per side, same chainplate as the cap)	**Calculated from estimates**
Backstay (split to transom corners)	≈47 ft each leg, ≈21° from vertical (≈26° off the raked mast); transom ≈20.5 ft aft of mast base	**Calculated from estimates**

Not shown or unverified: exact wire/rod count and whether the shrouds are continuous or discontinuous, tang heights, and exact chainplate and spreader positions (both are photo estimates). Confirm with the Jeanneau/mast-builder rigging drawing or a rigger before ordering or tuning anything.