

```

No.      Time      Source      Destination      Protocol Length Info
    11 2.371072    192.168.0.106    128.119.245.12    HTTP      453      GET /wireshark-labs/HTTP-
wireshark-file4.html HTTP/1.1
Frame 11: 453 bytes on wire (3624 bits), 453 bytes captured (3624 bits) on interface \Device\NPF_{BF23FEA1-
E9C4-4F8F-BB65-52FAE1FF74B2}, id 0
Ethernet II, Src: WistronI_6f:b9:19 (f8:0f:41:6f:b9:19), Dst: Tp-LinkT_66:03:90 (a0:f3:c1:66:03:90)
Internet Protocol Version 4, Src: 192.168.0.106, Dst: 128.119.245.12
Transmission Control Protocol, Src Port: 61039, Dst Port: 80, Seq: 1, Ack: 1, Len: 399
Hypertext Transfer Protocol

No.      Time      Source      Destination      Protocol Length Info
    16 2.512767    128.119.245.12    192.168.0.106    HTTP      1127     HTTP/1.1 200 OK (text/htr
Frame 16: 1127 bytes on wire (9016 bits), 1127 bytes captured (9016 bits) on interface \Device\NPF_{BF23FEA1-
E9C4-4F8F-BB65-52FAE1FF74B2}, id 0
Ethernet II, Src: Tp-LinkT_66:03:90 (a0:f3:c1:66:03:90), Dst: WistronI_6f:b9:19 (f8:0f:41:6f:b9:19)
Internet Protocol Version 4, Src: 128.119.245.12, Dst: 192.168.0.106
Transmission Control Protocol, Src Port: 80, Dst Port: 61039, Seq: 1, Ack: 400, Len: 1073
Hypertext Transfer Protocol
Line-based text data: text/html (17 lines)

No.      Time      Source      Destination      Protocol Length Info
    18 2.592187    192.168.0.106    128.119.245.12    HTTP      410      GET /pearson.png HTTP/1.1
Frame 18: 410 bytes on wire (3280 bits), 410 bytes captured (3280 bits) on interface \Device\NPF_{BF23FEA1-
E9C4-4F8F-BB65-52FAE1FF74B2}, id 0
Ethernet II, Src: WistronI_6f:b9:19 (f8:0f:41:6f:b9:19), Dst: Tp-LinkT_66:03:90 (a0:f3:c1:66:03:90)
Internet Protocol Version 4, Src: 192.168.0.106, Dst: 128.119.245.12
Transmission Control Protocol, Src Port: 61040, Dst Port: 80, Seq: 1, Ack: 1, Len: 356
Hypertext Transfer Protocol

No.      Time      Source      Destination      Protocol Length Info
    27 2.718902    128.119.245.12    192.168.0.106    HTTP      746      HTTP/1.1 200 OK (PNG)
Frame 27: 746 bytes on wire (5968 bits), 746 bytes captured (5968 bits) on interface \Device\NPF_{BF23FEA1-
E9C4-4F8F-BB65-52FAE1FF74B2}, id 0
Ethernet II, Src: Tp-LinkT_66:03:90 (a0:f3:c1:66:03:90), Dst: WistronI_6f:b9:19 (f8:0f:41:6f:b9:19)
Internet Protocol Version 4, Src: 128.119.245.12, Dst: 192.168.0.106
Transmission Control Protocol, Src Port: 80, Dst Port: 61040, Seq: 2921, Ack: 357, Len: 692
[3 Reassembled TCP Segments (3612 bytes): #25(1460), #26(1460), #27(692)]
Hypertext Transfer Protocol
Portable Network Graphics

No.      Time      Source      Destination      Protocol Length Info
    31 2.723473    192.168.0.106    128.119.245.12    HTTP      424      GET /~kurose/
cover_5th_ed.jpg HTTP/1.1
Frame 31: 424 bytes on wire (3392 bits), 424 bytes captured (3392 bits) on interface \Device\NPF_{BF23FEA1-
E9C4-4F8F-BB65-52FAE1FF74B2}, id 0
Ethernet II, Src: WistronI_6f:b9:19 (f8:0f:41:6f:b9:19), Dst: Tp-LinkT_66:03:90 (a0:f3:c1:66:03:90)
Internet Protocol Version 4, Src: 192.168.0.106, Dst: 128.119.245.12
Transmission Control Protocol, Src Port: 61041, Dst Port: 80, Seq: 1, Ack: 1, Len: 370
Hypertext Transfer Protocol

No.      Time      Source      Destination      Protocol Length Info
   132 3.113288    128.119.245.12    192.168.0.106    HTTP      632      HTTP/1.1 200 OK (JPEG JF1
image)
Frame 132: 632 bytes on wire (5056 bits), 632 bytes captured (5056 bits) on interface \Device\NPF_{BF23FEA1-
E9C4-4F8F-BB65-52FAE1FF74B2}, id 0
Ethernet II, Src: Tp-LinkT_66:03:90 (a0:f3:c1:66:03:90), Dst: WistronI_6f:b9:19 (f8:0f:41:6f:b9:19)
Internet Protocol Version 4, Src: 128.119.245.12, Dst: 192.168.0.106
Transmission Control Protocol, Src Port: 80, Dst Port: 61041, Seq: 100741, Ack: 371, Len: 578
[70 Reassembled TCP Segments (101318 bytes): #34(1460), #35(1460), #36(1460), #38(1460), #40(1460), #41(1460),
#43(1460), #44(1460), #46(1460), #47(1460), #50(1460), #51(1460), #52(1460), #53(1460), #54(1460), #55(1460),
#56(1460), #57(1460)]
Hypertext Transfer Protocol
JPEG File Interchange Format

```