```
No.     Time           Source               Destination          Protocol Length Info
     29 3.236949       192.168.0.106        66.6.101.171         HTTP     502    GET /dyn/str_strip/
000000000/00000000/0000000/000000/70000/7000/300/77356/77356.strip.sunday.gif HTTP/1.1
Frame 29: 502 bytes on wire (4016 bits), 502 bytes captured (4016 bits) on interface \Device\NPF_{BF23FEA1-
E9C4-4F8F-BB65-52FAE1FF74B2}, id 0
Ethernet II, Src: WistronI_6f:b9:19 (f8:0f:41:6f:b9:19), Dst: Tp-LinkT_66:03:90 (a0:f3:c1:66:03:90)
Internet Protocol Version 4, Src: 192.168.0.106, Dst: 66.6.101.171
Transmission Control Protocol, Src Port: 60757, Dst Port: 80, Seq: 1, Ack: 1, Len: 448
Hypertext Transfer Protocol
No.     Time           Source               Destination          Protocol Length Info
     33 3.407087       66.6.101.171         192.168.0.106        HTTP     274    HTTP/1.1 301 Moved Permane
Frame 33: 274 bytes on wire (2192 bits), 274 bytes captured (2192 bits) on interface \Device\NPF_{BF23FEA1-
E9C4-4F8F-BB65-52FAE1FF74B2}, id 0
Ethernet II, Src: Tp-LinkT_66:03:90 (a0:f3:c1:66:03:90), Dst: WistronI_6f:b9:19 (f8:0f:41:6f:b9:19)
Internet Protocol Version 4, Src: 66.6.101.171, Dst: 192.168.0.106
Transmission Control Protocol, Src Port: 80, Dst Port: 60757, Seq: 1, Ack: 449, Len: 220
Hypertext Transfer Protocol
No.     Time           Source               Destination          Protocol Length Info
     59 3.853152       192.168.0.106        192.124.249.24       OCSP     447    Request
Frame 59: 447 bytes on wire (3576 bits), 447 bytes captured (3576 bits) on interface \Device\NPF_{BF23FEA1-
E9C4-4F8F-BB65-52FAE1FF74B2}, id 0
Ethernet II, Src: WistronI_6f:b9:19 (f8:0f:41:6f:b9:19), Dst: Tp-LinkT_66:03:90 (a0:f3:c1:66:03:90)
Internet Protocol Version 4, Src: 192.168.0.106, Dst: 192.124.249.24
Transmission Control Protocol, Src Port: 60760, Dst Port: 80, Seq: 1, Ack: 1, Len: 393
Hypertext Transfer Protocol
Online Certificate Status Protocol
No.     Time           Source               Destination          Protocol Length Info
     67 3.914202       192.124.249.24       192.168.0.106        OCSP     880    Response
Frame 67: 880 bytes on wire (7040 bits), 880 bytes captured (7040 bits) on interface \Device\NPF_{BF23FEA1-
E9C4-4F8F-BB65-52FAE1FF74B2}, id 0
Ethernet II, Src: Tp-LinkT_66:03:90 (a0:f3:c1:66:03:90), Dst: WistronI_6f:b9:19 (f8:0f:41:6f:b9:19)
Internet Protocol Version 4, Src: 192.124.249.24, Dst: 192.168.0.106
Transmission Control Protocol, Src Port: 80, Dst Port: 60760, Seq: 1461, Ack: 394, Len: 826
[2 Reassembled TCP Segments (2286 bytes): #66(1460), #67(826)]
Hypertext Transfer Protocol
Online Certificate Status Protocol
```