

# Ungraded Lab: Model Analysis with TFX Evaluator

Now that you've used TFMA as a standalone library in the previous lab, you will now see how it is used by TFX with its [Evaluator](#) component. This component comes after your `Trainer` run and it checks if your trained model meets the minimum required metrics and also compares it with previously generated models.

You will go through a TFX pipeline that prepares and trains the same model architecture you used in the previous lab. As a reminder, this is a binary classifier to be trained on the [Census Income dataset](#). Since you're already familiar with the earlier TFX components, we will just go over them quickly but we've placed notes on where you can modify code if you want to practice or produce a better result.

Let's begin!

*Credits: Some of the code and discussions are based on the TensorFlow team's [official tutorial](#).*

## Setup

### Install TFX

```
In [ ]: !pip install tfx==1.2
```

*Note: In Google Colab, you need to restart the runtime at this point to finalize updating the packages you just installed. You can do so by clicking the `Restart Runtime` at the end of the output cell above (after installation), or by selecting `Runtime > Restart Runtime` in the Menu bar. **Please do not proceed to the next section without restarting.** You can also ignore the errors about version incompatibility of some of the bundled packages because we won't be using those in this notebook.*

### Imports

```
In [1]: import os
import pprint

from tfx.components import CsvExampleGen
from tfx.components import ExampleValidator
from tfx.components import SchemaGen
from tfx.components import StatisticsGen
from tfx.components import Transform
from tfx.components import Tuner
from tfx.components import Trainer
from tfx.components import Evaluator

import tensorflow as tf
import tensorflow_model_analysis as tfma

from tfx.orchestration.experimental.interactive.interactive_context import

tf.get_logger().propagate = False
tf.get_logger().setLevel('ERROR')
pp = pprint.PrettyPrinter()
```

## Set up pipeline paths

```
In [2]: # Location of the pipeline metadata store
_pipeline_root = './pipeline/'

# Directory of the raw data files
_data_root = './data/census'

_data_filepath = os.path.join(_data_root, "data.csv")
```

```
In [3]: # Create the TFX pipeline files directory
!mkdir {_pipeline_root}

# Create the dataset directory
!mkdir -p {_data_root}
```

mkdir: cannot create directory './pipeline/': File exists

## Download and prepare the dataset

Here, you will download the training split of the [Census Income Dataset](#). This is twice as large as the test dataset you used in the previous lab.

```
In [4]: # Define filename and URL
TAR_NAME = 'lab_2_data.tar.gz'
DATA_PATH = f'https://github.com/https-deeplearning-ai/MLEP-public/raw/main/

# Download dataset
!wget -nc {DATA_PATH}

# Extract archive
!tar xvzf {TAR_NAME}

# Delete archive
!rm {TAR_NAME}
```

```
--2021-09-03 08:51:13-- https://github.com/https-deeplearning-ai/MLEP-public/
raw/main/course3/week4-ungraded-lab/lab_2_data.tar.gz
Resolving github.com (github.com)... 140.82.121.4
Connecting to github.com (github.com)|140.82.121.4|:443... connected.
HTTP request sent, awaiting response... 301 Moved Permanently
```

```

Location: https://github.com/https-deeplearning-ai/machine-learning-engineering-for-production-public/raw/main/course3/week4-ungraded-lab/lab_2_data.tar.gz [following]
--2021-09-03 08:51:13-- https://github.com/https-deeplearning-ai/machine-learning-engineering-for-production-public/raw/main/course3/week4-ungraded-lab/lab_2_data.tar.gz
Reusing existing connection to github.com:443.
HTTP request sent, awaiting response... 302 Found
Location: https://raw.githubusercontent.com/https-deeplearning-ai/machine-learning-engineering-for-production-public/main/course3/week4-ungraded-lab/lab_2_data.tar.gz [following]
--2021-09-03 08:51:13-- https://raw.githubusercontent.com/https-deeplearning-ai/machine-learning-engineering-for-production-public/main/course3/week4-ungraded-lab/lab_2_data.tar.gz
Resolving raw.githubusercontent.com (raw.githubusercontent.com)... 185.199.111.133, 185.199.108.133, 185.199.110.133, ...
Connecting to raw.githubusercontent.com (raw.githubusercontent.com)|185.199.111.133|:443... connected.
HTTP request sent, awaiting response... 200 OK
Length: 418898 (409K) [application/octet-stream]
Saving to: 'lab_2_data.tar.gz'

lab_2_data.tar.gz  100%[=====>] 409.08K  --.-KB/s    in 0.01s

2021-09-03 08:51:13 (31.2 MB/s) - 'lab_2_data.tar.gz' saved [418898/418898]

/data/census/data.csv

```

Take a quick look at the first few rows.

In [5]:

```

# Preview dataset
!head {_data_filepath}

```

```

age,workclass,fnlwgt,education,education-num,marital-status,occupation,relationship,race,sex,capital-gain,capital-loss,hours-per-week,native-country,
label
39,State-gov,77516,Bachelors,13,Never-married,Adm-clerical,Not-in-family,White,Male,2174,0,40,United-States,0
50,Self-emp-not-inc,83311,Bachelors,13,Married-civ-spouse,Exec-managerial,Husband,White,Male,0,0,13,United-States,0
38,Private,215646,HS-grad,9,Divorced,Handlers-cleaners,Not-in-family,White,Male,0,0,40,United-States,0
53,Private,234721,11th,7,Married-civ-spouse,Handlers-cleaners,Husband,Black,Male,0,0,40,United-States,0
28,Private,338409,Bachelors,13,Married-civ-spouse,Prof-specialty,Wife,Black,Female,0,0,40,Cuba,0
37,Private,284582,Masters,14,Married-civ-spouse,Exec-managerial,Wife,White,Female,0,0,40,United-States,0
49,Private,160187,9th,5,Married-spouse-absent,Other-service,Not-in-family,Black,Female,0,0,16,Jamaica,0
52,Self-emp-not-inc,209642,HS-grad,9,Married-civ-spouse,Exec-managerial,Husband,White,Male,0,0,45,United-States,1
31,Private,45781,Masters,14,Never-married,Prof-specialty,Not-in-family,White,Female,14084,0,50,United-States,1

```

## TFX Pipeline

### Create the InteractiveContext

As usual, you will initialize the pipeline and use a local SQLite file for the metadata store.

In [6]:

```

# Initialize InteractiveContext
context = InteractiveContext(pipeline_root=_pipeline_root)

```

```

WARNING:absl:InteractiveContext metadata_connection_config not provided: using SQLite ML Metadata database at ./pipeline/metadata.sqlite.

```

### ExampleGen

You will start by ingesting the data through `CsvExampleGen`. The code below uses the default 2:1 train-eval split (i.e. 33% of the data goes to eval) but feel free to modify if you want. You can review splitting techniques [here](#).

```
In [7]: # Run CsvExampleGen
example_gen = CsvExampleGen(input_base=_data_root)
context.run(example_gen)
```

WARNING:apache\_beam.runners.interactive.interactive\_environment:Dependencies required for Interactive Beam PCollection visualization are not available, please use: `pip install apache-beam[interactive]` to install necessary dependencies to enable all data visualization features.

WARNING:root:Make sure that locally built Python SDK docker image has Python 3.7 interpreter.  
WARNING:apache\_beam.io.tfrecordio:Couldn't find python-snappy so the implementation of \_TFRecordUtil.\_masked\_crc32c is not as fast as it could be.

```
Out [7]: ▼ExecutionResult at 0x7f0b4a161310

      .execution_id  13

      .component    ▶CsvExampleGen at 0x7f0ac9d8da50

      .component.inputs  {}

      .component.outputs  ['examples'] ▶Channel of type 'Examples' (1
                           artifact) at 0x7f0acd962fd0
```

```
In [8]: # Print split names and URI
artifact = example_gen.outputs['examples'].get()[0]
print(artifact.split_names, artifact.uri)

["train", "eval"] ./pipeline/CsvExampleGen/examples/13
```

## StatisticsGen

You will then compute the statistics so it can be used by the next components.

```
In [9]: # Run StatisticsGen
statistics_gen = StatisticsGen(
    examples=example_gen.outputs['examples'])
context.run(statistics_gen)
```

WARNING:root:Make sure that locally built Python SDK docker image has Python 3.7 interpreter.


```
Out [9]: ▼ExecutionResult at 0x7f0ac7cc6110

      .execution_id  14

      .component    ▶StatisticsGen at 0x7f0ac7cc6dd0

      .component.inputs  ['examples'] ▶Channel of type 'Examples' (1
                           artifact) at 0x7f0acd962fd0
```

.component.outputs

['statistics']  Channel of type 'ExampleStatistics'  
(1 artifact) at 0x7f0ac7cc6f10

You can look at the visualizations below if you want to explore the data some more.

In [43]:

```
# Visualize statistics
context.show(statistics_gen.outputs['statistics'])
```

Artifact at [./pipeline/StatisticsGen/statistics/14](#)

'train' split:

Sort by

Feature order

☐ Reverse order

Feature search (regex enabled)

Features: ☒ int(7) ☒ string(8)

Numeric Features (7)

	count	missing	mean	std dev	zeros	min	median
age	21.8k	0%	38.61	13.62	0%	17	37
capital-gain	21.8k	0%	1,114.65	7,616.76	91.63%	0	0
capital-loss	21.8k	0%	89.15	406.88	95.22%	0	0
education-num	21.8k	0%	10.08	2.58	0%	1	10

'eval' split:

Sort by

Feature order

☐ Reverse order

Feature search (regex enabled)

Features: ☒ int(7) ☒ string(8)

Numeric Features (7)							
	count	missing	mean	std dev	zeros	min	median
age	10.8k	0%	38.53	13.68	0%	17	37

## SchemaGen

You can then infer the dataset schema with [SchemaGen](#). This will be used to validate incoming data to ensure that it is formatted correctly.

```
In [11]: # Run SchemaGen
schema_gen = SchemaGen(
    statistics=statistics_gen.outputs['statistics'])
context.run(schema_gen)
```

```
Out[11]: ▼ExecutionResult at 0x7f0ac85bc810

      .execution_id  15

      .component    ▶SchemaGen at 0x7f0ac85c4d90

      .component.inputs
                    ['statistics'] ▶Channel of type 'ExampleStatistics'
                                   (1 artifact) at 0x7f0ac7cc6f10

      .component.outputs
                    ['schema'] ▶Channel of type 'Schema' (1 artifact) at
                               0x7f0ac85a2f50
```

For simplicity, you will just accept the inferred schema but feel free to modify with the [TFDV API](#) if you want.

```
In [12]: # Visualize the inferred Schema
context.show(schema_gen.outputs['schema'])
```

### Artifact at ./pipeline/SchemaGen/schema/15

	Type	Presence	Valency	Domain
Feature name				
'education'	STRING	required		'education'
'marital-status'	STRING	required		'marital-status'
'native-country'	STRING	required		'native-country'

	Type	Presence	Valency	Domain
Feature name				
'occupation'	STRING	required		'occupation'
'race'	STRING	required		'race'
'relationship'	STRING	required		'relationship'
'sex'	STRING	required		'sex'
'workclass'	STRING	required		'workclass'
'age'	INT	required		-
'capital-gain'	INT	required		-
'capital-loss'	INT	required		-
'education-num'	INT	required		-
'fnlwgt'	INT	required		-

```

/usr/local/lib/python3.7/dist-packages/tensorflow_data_validation/utils/dis
play_util.py:180: FutureWarning: Passing a negative integer is deprecated i
n version 1.0 and will not be supported in future version. Instead, use Non
e to not limit the column width.
  pd.set_option('max_colwidth', -1)

```

	Values
Domain	
'education'	'10th', '11th', '12th', '1st-4th', '5th-6th', '7th-8th', '9th', 'Assoc-acdm', 'Assoc-voc', 'Bachelors', 'Doctorate', 'HS-grad', 'Masters', 'Preschool', 'Prof-school', 'Some-college'
'marital-status'	'Divorced', 'Married-AF-spouse', 'Married-civ-spouse', 'Married-spouse-absent', 'Never-married', 'Separated', 'Widowed'
'native-country'	'?', 'Cambodia', 'Canada', 'China', 'Columbia', 'Cuba', 'Dominican-Republic', 'Ecuador', 'El-Salvador', 'England', 'France', 'Germany', 'Greece', 'Guatemala', 'Haiti', 'Holand-Netherlands', 'Honduras', 'Hong', 'Hungary', 'India', 'Iran', 'Ireland', 'Italy', 'Jamaica', 'Japan', 'Laos', 'Mexico', 'Nicaragua', 'Outlying-US(Guam-USVI-etc)', 'Peru', 'Philippines', 'Poland', 'Portugal', 'Puerto-Rico', 'Scotland', 'South', 'Taiwan', 'Thailand', 'Trinidad&Tobago', 'United-States', 'Vietnam', 'Yugoslavia'
'occupation'	'?', 'Adm-clerical', 'Armed-Forces', 'Craft-repair', 'Exec-managerial', 'Farming-fishing', 'Handlers-cleaners', 'Machine-op-inspct', 'Other-service', 'Priv-house-serv', 'Prof-specialty', 'Protective-serv', 'Sales', 'Tech-support', 'Transport-moving'
'race'	'Amer-Indian-Eskimo', 'Asian-Pac-Islander', 'Black', 'Other', 'White'
'relationship'	'Husband', 'Not-in-family', 'Other-relative', 'Own-child', 'Unmarried', 'Wife'
'sex'	'Female', 'Male'
'workclass'	'?', 'Federal-gov', 'Local-gov', 'Never-worked', 'Private', 'Self-emp-inc', 'Self-emp-not-inc', 'State-gov', 'Without-pay'

### ExampleValidator

Next, run `ExampleValidator` to check if there are anomalies in the data.

```

In [13]: # Run ExampleValidator
example_validator = ExampleValidator(
    statistics=statistics_gen.outputs['statistics'],
    schema=schema_gen.outputs['schema'])
context.run(example_validator)

```


Out [13]:


▼ **ExecutionResult** at 0x7f0ac85abf50

**.execution\_id** 16


**.component**  **ExampleValidator** at 0x7f0ac85bc610

**.component.inputs**

**['statistics']**  **Channel** of type **'ExampleStatistics'**  
(1 artifact) at 0x7f0ac7cc6f10

**['schema']**  **Channel** of type **'Schema'** (1 artifact)  
at 0x7f0ac85a2f50

**.component.outputs**

**['anomalies']**  **Channel** of type  
**'ExampleAnomalies'** (1 artifact) at  
0x7f0ac85bc990

If you just used the inferred schema, then there should not be any anomalies detected. If you modified the schema, then there might be some results here and you can again use TFDV to modify or relax constraints as needed.

In actual deployments, this component will also help you understand how your data evolves over time and identify data errors. For example, the first batches of data that you get from your users might conform to the schema but it might not be the case after several months. This component will detect that and let you know that your model might need to be updated.

In [14]:

```
# Check results
context.show(example_validator.outputs['anomalies'])
```

**Artifact at ./pipeline/ExampleValidator/anomalies/16**

**'train' split:**

```
/usr/local/lib/python3.7/dist-packages/tensorflow_data_validation/utils/dis
play_util.py:217: FutureWarning: Passing a negative integer is deprecated i
n version 1.0 and will not be supported in future version. Instead, use Non
e to not limit the column width.
  pd.set_option('max_colwidth', -1)
```

**No anomalies found.**

**'eval' split:**

**No anomalies found.**

## Transform

Now you will perform feature engineering on the training data. As shown when you previewed the CSV earlier, the data is still in raw format and cannot be consumed by the model just yet. The transform code in the following cells will take care of scaling your numeric features and one-hot encoding your categorical variables.



*Note: If you're running this exercise for the first time, we advise that you leave the transformation code as is. After you've gone through the entire notebook, then you can modify these for practice and see what results you get. Just make sure that your model builder code in the **Trainer** component will also reflect those changes if needed. For example, removing a feature here should also remove an input layer for that feature in the model.*

```
In [15]: # Set the constants module filename
         _census_constants_module_file = 'census_constants.py'
```

```
In [16]: %%writefile {_census_constants_module_file}

         # Features with string data types that will be converted to indices
         VOCAB_FEATURE_DICT = {
             'education': 16, 'marital-status': 7, 'occupation': 15, 'race': 5,
             'relationship': 6, 'workclass': 9, 'sex': 2, 'native-country': 42
         }

         # Numerical features that are marked as continuous
         NUMERIC_FEATURE_KEYS = ['fnlwgt', 'education-num', 'capital-gain', 'capital

         # Feature that can be grouped into buckets
         BUCKET_FEATURE_DICT = {'age': 4}

         # Number of out-of-vocabulary buckets
         NUM_OOV_BUCKETS = 5

         # Feature that the model will predict
         LABEL_KEY = 'label'

         # Utility function for renaming the feature
         def transformed_name(key):
             return key + '_xf'
```

Overwriting census\_constants.py

```
In [17]: # Set the transform module filename
         _census_transform_module_file = 'census_transform.py'
```

```
In [18]: %%writefile {_census_transform_module_file}

import tensorflow as tf
import tensorflow_transform as tft

# import constants from cells above
import census_constants

# Unpack the contents of the constants module
_NUMERIC_FEATURE_KEYS = census_constants.NUMERIC_FEATURE_KEYS
_VOCAB_FEATURE_DICT = census_constants.VOCAB_FEATURE_DICT
_BUCKET_FEATURE_DICT = census_constants.BUCKET_FEATURE_DICT
_NUM_OOV_BUCKETS = census_constants.NUM_OOV_BUCKETS
_LABEL_KEY = census_constants.LABEL_KEY
_transformed_name = census_constants.transformed_name

# Define the transformations
def preprocessing_fn(inputs):
    """tf.transform's callback function for preprocessing inputs.
    Args:
        inputs: map from feature keys to raw not-yet-transformed features.
    Returns:
        Map from string feature key to transformed feature operations.
    """

    # Initialize outputs dictionary
    outputs = {}

    # Scale these features to the range [0,1]
    for key in _NUMERIC_FEATURE_KEYS:
        scaled = tft.scale_to_0_1(inputs[key])
        outputs[_transformed_name(key)] = tf.reshape(scaled, [-1])

    # Convert strings to indices and convert to one-hot vectors
    for key, vocab_size in _VOCAB_FEATURE_DICT.items():
        indices = tft.compute_and_apply_vocabulary(inputs[key], num_oov_buckets=_NUM_OOV_BUCKETS)
        one_hot = tf.one_hot(indices, vocab_size + _NUM_OOV_BUCKETS)
        outputs[_transformed_name(key)] = tf.reshape(one_hot, [-1, vocab_size + _NUM_OOV_BUCKETS])

    # Bucketize this feature and convert to one-hot vectors
    for key, num_buckets in _BUCKET_FEATURE_DICT.items():
        indices = tft.bucketize(inputs[key], num_buckets)
        one_hot = tf.one_hot(indices, num_buckets)
        outputs[_transformed_name(key)] = tf.reshape(one_hot, [-1, num_buckets])

    # Cast label to float
    outputs[_transformed_name(_LABEL_KEY)] = tf.cast(inputs[_LABEL_KEY], tf.float32)

    return outputs
```

Overwriting census\_transform.py

Now, we pass in this feature engineering code to the **Transform** component and run it to transform your data.

```
In [19]: # Run the Transform component
transform = Transform(
    examples=example_gen.outputs['examples'],
    schema=schema_gen.outputs['schema'],
    module_file=os.path.abspath(_census_transform_module_file))
context.run(transform, enable_cache=False)
```

WARNING:root:This output type hint will be ignored and not used for type-checking purposes. Typically, output type hints for a PTransform are single (or nested) types wrapped by a PCollection, PDone, or None. Got: Tuple[Dict

[illegible]

```
text using `tf.init_scope`: compute_and_apply_vocabulary_6/apply_vocab/text_file_init/InitializeTableFromTextFileV2
WARNING:absl:Tables initialized inside a tf.function will be re-initialized on every invocation of the function. This re-initialization can have significant impact on performance. Consider lifting them out of the graph context using `tf.init_scope`: compute_and_apply_vocabulary_7/apply_vocab/text_file_init/InitializeTableFromTextFileV2
WARNING:root:This output type hint will be ignored and not used for type-checking purposes. Typically, output type hints for a PTransform are single (or nested) types wrapped by a PCollection, PDone, or None. Got: Tuple[Dict[str, Union[NoneType, _Dataset]], Union[Dict[str, Dict[str, PCollection]], NoneType]] instead.
WARNING:root:Make sure that locally built Python SDK docker image has Python
```


Out[19]:


▼ **ExecutionResult** at 0x7f0ac8690d10

**.execution\_id** 17


**.component**  **Transform** at 0x7f0ac8615150


**.component.inputs**

**['examples']**  **Channel** of type '**Examples**' (1 artifact) at 0x7f0acd962fd0


**['schema']**  **Channel** of type '**Schema**' (1 artifact) at 0x7f0ac85a2f50

**.component.outputs**


**['transform\_graph']**  **Channel** of type '**TransformGraph**' (1 artifact) at 0x7f0ac86151d0


**['transformed\_examples']**  **Channel** of type '**Examples**' (1 artifact) at 0x7f0ac8615510

**['updated\_analyzer\_cache']**  **Channel** of type '**TransformCache**' (1 artifact) at 0x7f0ac8615250


**['pre\_transform\_schema']**  **Channel** of type '**Schema**' (1 artifact) at 0x7f0ac8615310

**['pre\_transform\_stats']**  **Channel** of type '**ExampleStatistics**' (1 artifact) at 0x7f0ac8615dd0

**['post\_transform\_schema']**  **Channel** of type '**Schema**' (1 artifact) at 0x7f0ac8615790

**['post\_transform\_stats']**  **Channel** of type '**ExampleStatistics**' (1 artifact) at 0x7f0ac8615f10

['post\_transform\_anomalies']

 Channel of type  
'ExampleAnomalies'  
(1 artifact) at  
0x7f0ac8615390

You can see a sample result for one row with the code below. Notice that the numeric features are indeed scaled and the categorical features are now one-hot encoded.

In [20]:

```
# Get the URI of the output artifact representing the transformed examples
train_uri = os.path.join(transform.outputs['transformed_examples'].get()[0])

# Get the list of files in this directory (all compressed TFRecord files)
tfrecord_filenames = [os.path.join(train_uri, name)
                       for name in os.listdir(train_uri)]

# Create a `TFRecordDataset` to read these files
dataset = tf.data.TFRecordDataset(tfrecord_filenames, compression_type="GZIP")

# Decode the first record and print output
for tfrecord in dataset.take(1):
    serialized_example = tfrecord.numpy()
    example = tf.train.Example()
    example.ParseFromString(serialized_example)
    pp.pprint(example)
```

```
features {
  feature {
    key: "age_xf"
    value {
      float_list {
        value: 0.0
        value: 0.0
        value: 1.0
        value: 0.0
      }
    }
  }
  feature {
    key: "capital-gain_xf"
    value {
      float_list {
        value: 0.02174021676182747
      }
    }
  }
  feature {
    key: "capital-loss_xf"
    value {
      float_list {
        value: 0.0
      }
    }
  }
  feature {
    key: "education-num_xf"
    value {
      float_list {
        value: 0.800000011920929
      }
    }
  }
  feature {
    key: "education_xf"
    value {
      float_list {
        value: 0.0
        value: 0.0
        value: 1.0
        value: 0.0
      }
    }
  }
}
```

```

        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
    }
}
feature {
    key: "fnlwgt_xf"
    value {
        float_list {
            value: 0.044301897287368774
        }
    }
}
feature {
    key: "hours-per-week_xf"
    value {
        float_list {
            value: 0.3979591727256775
        }
    }
}
feature {
    key: "label_xf"
    value {
        float_list {
            value: 0.0
        }
    }
}
feature {
    key: "marital-status_xf"
    value {
        float_list {
            value: 0.0
            value: 1.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
        }
    }
}
feature {
    key: "native-country_xf"
    value {
        float_list {
            value: 1.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0

```

```

        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
    }
}
feature {
    key: "occupation_xf"
    value {
        float_list {
            value: 0.0
            value: 0.0
            value: 0.0
            value: 1.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
            value: 0.0
        }
    }
}
feature {
    key: "race_xf"
    value {
        float_list {
            value: 1.0
            value: 0.0

```

```

        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
        value: 0.0
    }
}
}
feature {
  key: "relationship_xf"
  value {
    float_list {
      value: 0.0
      value: 1.0
      value: 0.0
      value: 0.0
      value: 0.0
      value: 0.0
      value: 0.0
      value: 0.0
      value: 0.0
      value: 0.0
      value: 0.0
    }
  }
}
feature {
  key: "sex_xf"
  value {
    float_list {
      value: 1.0
      value: 0.0
      value: 0.0
      value: 0.0
      value: 0.0
      value: 0.0
      value: 0.0
    }
  }
}
feature {
  key: "workclass_xf"
  value {
    float_list {
      value: 0.0
      value: 0.0
      value: 0.0
      value: 0.0
      value: 1.0
      value: 0.0
      value: 0.0
      value: 0.0
      value: 0.0
      value: 0.0
      value: 0.0
      value: 0.0
      value: 0.0
      value: 0.0
      value: 0.0
    }
  }
}
}

```

As you already know, the `Transform` component not only outputs the transformed examples but also the transformation graph. This should be used on all inputs when your model is deployed to ensure that it is transformed the same way as your training data. Else, it can produce training-serving skew which leads to noisy predictions.

The `Transform` component stores related files in its `transform_graph` output and it would be good to quickly review its contents before we move on to the next component. As



shown below, the URI of this output points to a directory containing three subdirectories.

```
In [21]: # Get URI and list subdirectories
graph_uri = transform.outputs['transform_graph'].get()[0].uri
os.listdir(graph_uri)
```

```
Out[21]: ['metadata', 'transformed_metadata', 'transform_fn']
```

- The `transformed_metadata` subdirectory contains the schema of the preprocessed data.
- The `transform_fn` subdirectory contains the actual preprocessing graph.
- The `metadata` subdirectory contains the schema of the original data.

## Trainer

Next, you will now build the model to make your predictions. As mentioned earlier, this is a binary classifier where the label is 1 if a person earns more than 50k USD and 0 if less than or equal. The model used here uses the [wide and deep model](#) as reference but feel free to modify after you've completed the exercise. Also for simplicity, the hyperparameters (e.g. number of hidden units) have been hardcoded but feel free to use a `Tuner` component as you did in Week 1 if you want to get some practice.

As a reminder, it is best to start from `run_fn()` when you're reviewing the module file below. The `Trainer` component looks for that function first. All other functions defined in the module are just utility functions for `run_fn()`.

Another thing you will notice below is the `_get_serve_tf_examples_fn()` function. This is tied to the `serving_default` [signature](#) which makes it possible for you to just pass in raw features when the model is served for inference. You have seen this in action in the previous lab. This is done by decorating the enclosing function, `serve_tf_examples_fn()`, with [tf.function](#). This indicates that the computation will be done by first tracing a [Tensorflow graph](#). You will notice that this function uses `model.tft_layer` which comes from `transform_graph` output. Now when you call the `.get_concrete_function()` method on this `tf.function` in `run_fn()`, you are creating the graph that will be used in later computations. This graph is used whenever you pass in an `examples` argument pointing to a Tensor with `tf.string` dtype. That matches the format of the serialized batches of data you used in the previous lab.

```
In [22]: # Declare trainer module file
_census_trainer_module_file = 'census_trainer.py'
```

In [23]:

```
%%writefile {_census_trainer_module_file}

from typing import List, Text

import tensorflow as tf
import tensorflow_transform as tft
from tensorflow_transform.tf_metadata import schema_utils

from tfx.components.trainer.fn_args_utils import DataAccessor, FnArgs
from tfx_bsl.public.tfxio import TensorFlowDatasetOptions

# import same constants from transform module
import census_constants

# Unpack the contents of the constants module
_NUMERIC_FEATURE_KEYS = census_constants.NUMERIC_FEATURE_KEYS
_VOCAB_FEATURE_DICT = census_constants.VOCAB_FEATURE_DICT
_BUCKET_FEATURE_DICT = census_constants.BUCKET_FEATURE_DICT
_NUM_OOV_BUCKETS = census_constants.NUM_OOV_BUCKETS
_LABEL_KEY = census_constants.LABEL_KEY
_transformed_name = census_constants.transformed_name

def _gzip_reader_fn(filenamees):
    '''Load compressed dataset

    Args:
        filenamees - filenamees of TFRecords to load

    Returns:
        TFRecordDataset loaded from the filenamees
    '''

    # Load the dataset. Specify the compression type since it is saved as `.gz`
    return tf.data.TFRecordDataset(filenamees, compression_type='GZIP')

def _input_fn(file_pattern,
              tf_transform_output,
              num_epochs=None,
              batch_size=32) -> tf.data.Dataset:
    '''Create batches of features and labels from TF Records

    Args:
        file_pattern - List of files or patterns of file paths containing Example
        tf_transform_output - transform output graph
        num_epochs - Integer specifying the number of times to read through the dataset.
                      If None, cycles through the dataset forever.
        batch_size - An int representing the number of records to combine in a batch

    Returns:
        A dataset of dict elements, (or a tuple of dict elements and label).
        Each dict maps feature keys to Tensor or SparseTensor objects.
    '''

    # Get post-transform feature spec
    transformed_feature_spec = (
        tf_transform_output.transformed_feature_spec().copy())

    # Create batches of data
    dataset = tf.data.experimental.make_batched_features_dataset(
        file_pattern=file_pattern,
        batch_size=batch_size,
        features=transformed_feature_spec,
        reader=_gzip_reader_fn,
        num_epochs=num_epochs,
        label_key=transformed_name(LABEL_KEY))
```

```

return dataset

def _get_serve_tf_examples_fn(model, tf_transform_output):
    """Returns a function that parses a serialized tf.Example and applies TFT

    # Get transformation graph
    model.tft_layer = tf_transform_output.transform_features_layer()

    @tf.function
    def serve_tf_examples_fn(serialized_tf_examples):
        """Returns the output to be used in the serving signature."""
        # Get pre-transform feature spec
        feature_spec = tf_transform_output.raw_feature_spec()

        # Pop label since serving inputs do not include the label
        feature_spec.pop(_LABEL_KEY)

        # Parse raw examples into a dictionary of tensors matching the feature
        parsed_features = tf.io.parse_example(serialized_tf_examples, feature_s

        # Transform the raw examples using the transform graph
        transformed_features = model.tft_layer(parsed_features)

        # Get predictions using the transformed features
        return model(transformed_features)

    return serve_tf_examples_fn

def _build_keras_model(hidden_units: List[int] = None) -> tf.keras.Model:
    """Creates a DNN Keras model for classifying income data.

    Args:
        hidden_units: [int], the layer sizes of the DNN (input layer first).

    Returns:
        A keras Model.
    """

    # Use helper function to create the model
    model = _wide_and_deep_classifier(
        dnn_hidden_units=hidden_units or [100, 70, 50, 25])

    return model

def _wide_and_deep_classifier(dnn_hidden_units):
    """Build a simple keras wide and deep model using the Functional API.

    Args:
        wide_columns: Feature columns wrapped in indicator_column for wide (lin
            part of the model.
        deep_columns: Feature columns for deep part of the model.
        dnn_hidden_units: [int], the layer sizes of the hidden DNN.

    Returns:
        A Wide and Deep Keras model
    """

    # Define input layers for numeric keys
    input_numeric = [
        tf.keras.layers.Input(name=_transformed_name(colname), shape=(1,), dt
        for colname in _NUMERIC_FEATURE_KEYS
    ]

```

```

# Define input layers for bucket key
input_categorical += [
    tf.keras.layers.Input(name=_transformed_name(colname), shape=(num_buc
        for colname, num_buckets in _BUCKET_FEATURE_DICT.items()
    ])

# Concatenate numeric inputs
deep = tf.keras.layers.concatenate(input_numeric)

# Create deep dense network for numeric inputs
for numnodes in dnn_hidden_units:
    deep = tf.keras.layers.Dense(numnodes)(deep)

# Concatenate categorical inputs
wide = tf.keras.layers.concatenate(input_categorical)

# Create shallow dense network for categorical inputs
wide = tf.keras.layers.Dense(128, activation='relu')(wide)

# Combine wide and deep networks
combined = tf.keras.layers.concatenate([deep, wide])

# Define output of binary classifier
output = tf.keras.layers.Dense(
    1, activation='sigmoid')(combined)

# Setup combined input
input_layers = input_numeric + input_categorical

# Create the Keras model
model = tf.keras.Model(input_layers, output)

# Define training parameters
model.compile(
    loss='binary_crossentropy',
    optimizer=tf.keras.optimizers.Adam(lr=0.001),
    metrics='binary_accuracy')

# Print model summary
model.summary()

return model

# TFX Trainer will call this function.
def run_fn(fn_args: FnArgs):
    """Defines and trains the model.

    Args:
        fn_args: Holds args as name/value pairs. Refer here for the complete at
            https://www.tensorflow.org/tfx/api_docs/python/tfx/components/trainer/f
    """

    # Number of nodes in the first layer of the DNN
    first_dnn_layer_size = 100
    num_dnn_layers = 4
    dnn_decay_factor = 0.7

    # Get transform output (i.e. transform graph) wrapper
    tf_transform_output = tft.TFTransformOutput(fn_args.transform_output)

    # Create batches of train and eval sets

```

```

        max(2, int((1 + 1 - dnn_layer_size * dnn_decay_factor) / 2))
        for i in range(num_dnn_layers)
    ])

    # Callback for TensorBoard
    tensorboard_callback = tf.keras.callbacks.TensorBoard(
        log_dir=fn_args.model_run_dir, update_freq='batch')

    # Train the model
    model.fit(
        train_dataset,
        steps_per_epoch=fn_args.train_steps,
        validation_data=eval_dataset,
        validation_steps=fn_args.eval_steps,
        callbacks=[tensorboard_callback])

    # Define default serving signature
    signatures = {
        'serving_default':
            _get_serve_tf_examples_fn(model,
                                       tf_transform_output).get_concrete_function(
                                           tf.TensorSpec(
                                               shape=[None],
                                               dtype=tf.string,
                                               name='examples')),
    }

    # Save model with signature
    model.save(fn_args.serving_model_dir, save_format='tf', signatures=signatures)

```

Overwriting census\_trainer.py

Now, we pass in this model code to the **Trainer** component and run it to train the model.

*Note: You can ignore the **Exception ignored in: <function CapturableResource.\_\_del\_\_>** prompt which generates a long traceback. This might be an issue with the underlying TFMA version used and has been flagged to the TFX team so it can be suppressed. This might pop up here and in the Evaluator component.*

In [24]:

```

from tfx.proto import trainer_pb2

trainer = Trainer(
    module_file=os.path.abspath(_census_trainer_module_file),
    examples=transform.outputs['transformed_examples'],
    transform_graph=transform.outputs['transform_graph'],
    schema=schema_gen.outputs['schema'],
    train_args=trainer_pb2.TrainArgs(num_steps=50),
    eval_args=trainer_pb2.EvalArgs(num_steps=50))
context.run(trainer, enable_cache=False)

```

```

WARNING:absl:Examples artifact does not have payload_format custom property. Falling back to FORMAT_TF_EXAMPLE
WARNING:absl:Examples artifact does not have payload_format custom property. Falling back to FORMAT_TF_EXAMPLE
WARNING:absl:Examples artifact does not have payload_format custom property. Falling back to FORMAT_TF_EXAMPLE

```

```
/usr/local/lib/python3.7/dist-packages/tensorflow/python/keras/optimizer_v2/optimizer_v2.py:375: UserWarning: The `lr` argument is deprecated, use `learning_rate` instead.
```

```
"The `lr` argument is deprecated, use `learning_rate` instead.")
```

```
Model: "model"
```


Layer (type) to	Output Shape	Param #	Connected
=====	=====	=====	=====
fnlwgt_xf (InputLayer)	[(None, 1)]	0	
education-num_xf (InputLayer)	[(None, 1)]	0	
capital-gain_xf (InputLayer)	[(None, 1)]	0	
capital-loss_xf (InputLayer)	[(None, 1)]	0	
hours-per-week_xf (InputLayer)	[(None, 1)]	0	
concatenate (Concatenate) [0][0]	(None, 5)	0	fnlwgt_xf education-num_xf[0][0] capital-ga capital-lo hours-per-
dense (Dense) e[0][0]	(None, 100)	600	concatenat
dense_1 (Dense) [0][0]	(None, 70)	7070	dense
education_xf (InputLayer)	[(None, 21)]	0	
marital-status_xf (InputLayer)	[(None, 12)]	0	
occupation_xf (InputLayer)	[(None, 20)]	0	
race_xf (InputLayer)	[(None, 10)]	0	
relationship_xf (InputLayer)	[(None, 11)]	0	
workclass_xf (InputLayer)	[(None, 14)]	0	
sex_xf (InputLayer)	[(None, 7)]	0	
native-country_xf (InputLayer)	[(None, 47)]	0	
age_xf (InputLayer)	[(None, 4)]	0	
dense_2 (Dense) [0][0]	(None, 48)	3408	dense_1

concatenate_1 (Concatenate) xf[0][0]	(None, 146)	0	education_ marital-st atus_xf[0][0] occupation _xf[0][0] race_xf [0][0] relationsh ip_xf[0][0] workclass_ xf[0][0] sex_xf [0][0] native-cou ntry_xf[0][0] age_xf [0][0]
dense_3 (Dense) [0][0]	(None, 34)	1666	dense_2
dense_4 (Dense) e_1[0][0]	(None, 128)	18816	concatenat
concatenate_2 (Concatenate) [0][0]	(None, 162)	0	dense_3 dense_4
dense_5 (Dense) e_2[0][0]	(None, 1)	163	concatenat
=====			
Total params: 31,723			
Trainable params: 31,723			
Non-trainable params: 0			
=====			
50/50 [=====] - 2s 15ms/step - loss: 0.5082 - bina			
ry accuracy: 0.7625 - val_loss: 0.4058 - val_binary accuracy: 0.8075			


Out[24]:


▼ **ExecutionResult** at 0x7f0ac845d150


**.execution\_id** 18

**.component**  **Trainer** at 0x7f0ac7731f50


**.component.inputs**


['examples']  **Channel** of type 'Examples' (1 artifact) at 0x7f0ac8615510

['transform\_graph']  **Channel** of type 'TransformGraph' (1 artifact) at 0x7f0ac86151d0

['schema']  **Channel** of type 'Schema' (1 artifact) at 0x7f0ac85a2f50

**.component.outputs**

['model']  **Channel** of type 'Model' (1 artifact) at 0x7f0ac7731a90

**['model\_run']**  **Channel** of type **'ModelRun'** (1 artifact) at 0x7f0ac7731510

Let's review the outputs of this component. The `model` output points to the model output itself.

```
In [25]: # Get `model` output of the component
model_artifact_dir = trainer.outputs['model'].get()[0].uri

# List top-level directory
pp.pprint(os.listdir(model_artifact_dir))

# Get model directory
model_dir = os.path.join(model_artifact_dir, 'Format-Serving')

# List subdirectories
pp.pprint(os.listdir(model_dir))

['Format-Serving']
['keras_metadata.pb', 'saved_model.pb', 'assets', 'variables']
```

The `model_run` output acts as the working directory and can be used to output non-model related output (e.g., TensorBoard logs).

```
In [26]: # Get `model_run` output URI
model_run_artifact_dir = trainer.outputs['model_run'].get()[0].uri

# Load results to Tensorboard
%load_ext tensorboard
%tensorboard --logdir {model_run_artifact_dir}
```

## Evaluator

The `Evaluator` component computes model performance metrics over the evaluation set using the [TensorFlow Model Analysis](#) library. The `Evaluator` can also optionally validate that a newly trained model is better than the previous model. This is useful in a production pipeline setting where you may automatically train and validate a model every day.

There's a few steps needed to setup this component and you will do it in the next cells.

### Define EvalConfig

First, you will define the `EvalConfig` message as you did in the previous lab. You can also set thresholds so you can compare subsequent models to it. The module below should look familiar. One minor difference is you don't have to define the candidate and baseline model names in the `model_specs`. That is automatically detected.



In [27]:

```
import tensorflow_model_analysis as tfma
from google.protobuf import text_format

eval_config = text_format.Parse("""
## Model information
model_specs {
  # This assumes a serving model with signature 'serving_default'.
  label_key: "label"
}

## Post training metric information
metrics_specs {
  metrics { class_name: "ExampleCount" }
  metrics {
    class_name: "BinaryAccuracy"
    threshold {
      # Ensure that metric is always > 0.5
      value_threshold {
        lower_bound { value: 0.5 }
      }
      # Ensure that metric does not drop by more than a small epsilon
      # e.g. (candidate - baseline) > -1e-10 or candidate > baseline - 1e-10
      change_threshold {
        direction: HIGHER_IS_BETTER
        absolute { value: -1e-10 }
      }
    }
  }
  metrics { class_name: "BinaryCrossentropy" }
  metrics { class_name: "AUC" }
  metrics { class_name: "AUCPrecisionRecall" }
  metrics { class_name: "Precision" }
  metrics { class_name: "Recall" }
  metrics { class_name: "MeanLabel" }
  metrics { class_name: "MeanPrediction" }
  metrics { class_name: "Calibration" }
  metrics { class_name: "CalibrationPlot" }
  metrics { class_name: "ConfusionMatrixPlot" }
  # ... add additional metrics and plots ...
}

## Slicing information
slicing_specs {} # overall slice
slicing_specs {
  feature_keys: ["race"]
}
slicing_specs {
  feature_keys: ["sex"]
}
""", tfma.EvalConfig())
```

## Resolve latest blessed model

If you remember in the last lab, you were able to validate a candidate model against a baseline by modifying the `EvalConfig` and `EvalSharedModel` definitions. That is also possible using the `Evaluator` component and you will see how it is done in this section.

First thing to note is that the `Evaluator` marks a model as `BLESSED` if it meets the metrics thresholds you set in the eval config module. You can load the latest blessed model by using the `LatestBlessedModelStrategy` with the `Resolver` component. This component takes care of finding the latest blessed model for you so you don't have to remember it manually. The syntax is shown below.

```
In [28]: from tfx.dsl.components.common.resolver import Resolver
from tfx.dsl.input_resolution.strategies.latest_blessed_model_strategy import LatestBlessedModelStrategy
from tfx.types import Channel
from tfx.types.standard_artifacts import Model, ModelBlessing

# Setup the Resolver node to find the latest blessed model
model_resolver = Resolver(
    strategy_class=LatestBlessedModelStrategy,
    model=Channel(type=Model),
    model_blessing=Channel(
        type=ModelBlessing)).with_id(
        'latest_blessed_model_resolver')

# Run the Resolver node
context.run(model_resolver)
```

```
Out[28]: ▼ExecutionResult at 0x7f0ac86e80d0

      .execution_id  19

      .component  <tfx.dsl.components.common.resolver.Resolver object at
                  0x7f0ac811b550>

      .component.inputs
          ['model']  ▶Channel of type 'Model' (0
                    artifacts) at 0x7f0ac814fad0
          ['model_blessing']  ▶Channel of type
                              'ModelBlessing' (0 artifacts) at
                              0x7f0ac817fc90

      .component.outputs
          ['model']  ▶Channel of type 'Model' (0
                    artifacts) at 0x7f0ac40b2a50
          ['model_blessing']  ▶Channel of type
                              'ModelBlessing' (0 artifacts) at
                              0x7f0ac075bf50
```

As expected, the search yielded 0 artifacts because you haven't evaluated any models yet. You will run this component again in later parts of this notebook and you will see a different result.

```
In [29]: # Load Resolver outputs
model_resolver.outputs['model']
```

```
Out[29]: ▼Channel of type 'Model' (0 artifacts) at 0x7f0ac40b2a50

      .type_name  Model

      .artifacts  []
```

Run the Evaluator component

With the `EvalConfig` defined and code to load the latest blessed model available, you can proceed to run the `Evaluator` component.

You will notice that two models are passed into the component. The `Trainer` output will serve as the candidate model while the output of the `Resolver` will be the baseline model. While you can indeed run the `Evaluator` without comparing two models, it would likely be required in production environments so it's best to include it. Since the `Resolver` doesn't have any results yet, the `Evaluator` will just mark the candidate model as `BLESSED` in this run.

Aside from the eval config and models (i.e. Trainer and Resolver output), you will also pass in the *raw* examples from `ExampleGen`. By default, the component will look for the `eval` split of these examples and since you've defined the serving signature, these will be transformed internally before feeding to the model inputs.

*Note: You can ignore the `Exception ignored in: <function CapturableResource.__del__>` prompt which generates a long traceback. This might be an issue with the underlying TFMA version used and has been flagged to the TFX team so it can be suppressed*

In [30]:

```
# Setup and run the Evaluator component
evaluator = Evaluator(
    examples=example_gen.outputs['examples'],
    model=trainer.outputs['model'],
    baseline_model=model_resolver.outputs['model'],
    eval_config=eval_config)
context.run(evaluator, enable_cache=False)
```

```
ERROR:absl:There are change thresholds, but the baseline is missing. This is
allowed only when rubber stamping (first run).
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef
0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t
racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/
func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef
0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t
racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
```

```

function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/
func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef
0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t
racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/
func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef
0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t
racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/
func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 672, in wrapped_fn

```

```

    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t
racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/
func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t
racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/
func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t
racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3444, in _maybe_define_function

```

```

graph_function = self._create_graph_function(args, kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/function.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef0>

Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t_racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/function.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/function.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/function.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef0>

Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t_racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/function.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/function.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/function.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef0>

Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t_racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_function.py", line 889, in __call__

```



```

    result = self._call(*args, **kwargs)
    File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
    File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3022, in _call_
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
    File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
    File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
    File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/
func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
    File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef
0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t
racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3022, in _call_
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/
func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef
0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t
racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3022, in _call_
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/
func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)

```

```
AttributeError: 'NoneType' object has no attribute '__wrapped__'  
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef0>
```

```
Traceback (most recent call last):
```

```
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t  
racking/tracking.py", line 277, in __del__  
    self._destroy_resource()  
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_  
function.py", line 889, in __call__  
    result = self._call(*args, **kwargs)  
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_  
function.py", line 924, in _call  
    results = self._stateful_fn(*args, **kwargs)  
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func_  
tion.py", line 3022, in __call__  
    filtered_flat_args) = self._maybe_define_function(args, kwargs)  
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func_  
tion.py", line 3444, in _maybe_define_function  
    graph_function = self._create_graph_function(args, kwargs)  
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func_  
tion.py", line 3289, in _create_graph_function  
    capture_by_value=self._capture_by_value),  
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/  
func_graph.py", line 999, in func_graph_from_py_func  
    func_outputs = python_func(*func_args, **func_kwargs)  
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_  
function.py", line 672, in wrapped_fn  
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
```

```
AttributeError: 'NoneType' object has no attribute '__wrapped__'  
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef0>
```

```
Traceback (most recent call last):
```

```
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t  
racking/tracking.py", line 277, in __del__  
    self._destroy_resource()  
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_  
function.py", line 889, in __call__  
    result = self._call(*args, **kwargs)  
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_  
function.py", line 924, in _call  
    results = self._stateful_fn(*args, **kwargs)  
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func_  
tion.py", line 3022, in __call__  
    filtered_flat_args) = self._maybe_define_function(args, kwargs)  
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func_  
tion.py", line 3444, in _maybe_define_function  
    graph_function = self._create_graph_function(args, kwargs)  
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func_  
tion.py", line 3289, in _create_graph_function  
    capture_by_value=self._capture_by_value),  
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/  
func_graph.py", line 999, in func_graph_from_py_func  
    func_outputs = python_func(*func_args, **func_kwargs)  
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_  
function.py", line 672, in wrapped_fn  
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
```

```
AttributeError: 'NoneType' object has no attribute '__wrapped__'  
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef0>
```

```
Traceback (most recent call last):
```

```
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t  
racking/tracking.py", line 277, in __del__  
    self._destroy_resource()  
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_  
function.py", line 889, in __call__  
    result = self._call(*args, **kwargs)  
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_  
function.py", line 924, in _call  
    results = self._stateful_fn(*args, **kwargs)  
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func_  
tion.py", line 3022, in __call__  
    filtered_flat_args) = self._maybe_define_function(args, kwargs)  
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func_  
tion.py", line 3444, in _maybe_define_function  
    graph_function = self._create_graph_function(args, kwargs)
```



```

File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/function.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef0>
Traceback (most recent call last):
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/racking/tracking.py", line 277, in __del__
    self._destroy_resource()
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/function.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/function.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/function.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'

```


Out[30]:


▼ **ExecutionResult** at 0x7f0ac85d5e50

**.execution\_id** 20

**.component**  **Evaluator** at 0x7f0ac02117d0


**.component.inputs**


**['examples']**  **Channel** of type '**Examples**' (1 artifact) at 0x7f0acd962fd0

**['model']**  **Channel** of type '**Model**' (1 artifact) at 0x7f0ac7731a90

**['baseline\_model']**  **Channel** of type '**Model**' (0 artifacts) at 0x7f0ac40b2a50

**.component.outputs**

**['evaluation']**  **Channel** of type '**ModelEvaluation**' (1 artifact) at 0x7f0ac0211d90

**['blessing']**  **Channel** of type '**ModelBlessing**' (1 artifact) at 0x7f0ac0211f50

Now let's examine the output artifacts of **Evaluator**.

```
In [31]: # Print component output keys
evaluator.outputs.keys()
```

```
Out[31]: dict_keys(['evaluation', 'blessing'])
```

The **blessing** output simply states if the candidate model was blessed. The artifact URI will have a **BLESSED** or **NOT\_BLESSED** file depending on the result. As mentioned earlier, this first run will pass the evaluation because there is no baseline model yet.

```
In [32]: # Get `Evaluator` blessing output URI
blessing_uri = evaluator.outputs['blessing'].get()[0].uri

# List files under URI
os.listdir(blessing_uri)
```

```
Out[32]: ['BLESSED']
```

The **evaluation** output, on the other hand, contains the evaluation logs and can be used to visualize the global metrics on the entire evaluation set.

```
In [33]: # Visualize the evaluation results
context.show(evaluator.outputs['evaluation'])
```

### Artifact at `./pipeline/Evaluator/evaluation/20`

To see the individual slices, you will need to import TFMA and use the commands you learned in the previous lab.

```
In [34]: import tensorflow_model_analysis as tfma

# Get the TFMA output result path and load the result.
PATH_TO_RESULT = evaluator.outputs['evaluation'].get()[0].uri
tfma_result = tfma.load_eval_result(PATH_TO_RESULT)

# Show data sliced along feature column trip_start_hour.
tfma.view.render_slicing_metrics(
    tfma_result, slicing_column='sex')
```

You can also use TFMA to load the validation results as before by specifying the output URI of the evaluation output. This would be more useful if your model was not blessed because you can see the metric failure prompts. Try to simulate this later by training with fewer epochs (or raising the threshold) and see the results you get here.

```
In [35]: # Get `evaluation` output URI
PATH_TO_RESULT = evaluator.outputs['evaluation'].get()[0].uri

# Print validation result
print(tfma.load_validation_result(PATH_TO_RESULT))

validation_ok: true
validation_details {
  slicing_details {
    slicing_spec {
    }
    num_matching_slices: 8
  }
}
```

Now that your `Evaluator` has finished running, the `Resolver` component should be able to detect the latest blessed model. Let's run the component again.

```
In [36]: # Re-run the Resolver component  
context.run(model_resolver)
```

```
Out[36]: ▼ExecutionResult at 0x7f0abfc93850  
  
      .execution_id  21  
  
      .component    <tfx.dsl.components.common.resolver.Resolver object at  
                   0x7f0ac811b550>  
  
      .component.inputs  
          ['model']  ▶Channel of type 'Model' (0  
                   artifacts) at 0x7f0ac814fad0  
          ['model_blessing'] ▶Channel of type  
                   'ModelBlessing' (0 artifacts) at  
                   0x7f0ac817fc90  
  
      .component.outputs  
          ['model']  ▶Channel of type 'Model' (1  
                   artifact) at 0x7f0ab9bb1f50  
          ['model_blessing'] ▶Channel of type  
                   'ModelBlessing' (1 artifact) at  
                   0x7f0ab9bb14d0
```

You should now see an artifact in the component outputs. You can also get it programmatically as shown below.

```
In [37]: # Get path to latest blessed model  
model_resolver.outputs['model'].get()[0].uri
```

```
Out[37]: './pipeline/Trainer/model/18'
```

## Comparing two models

Now let's see how `Evaluator` compares two models. You will train the same model with more epochs and this should hopefully result in higher accuracy and overall metrics.

In [38]:

```
from tfx.proto import trainer_pb2

# Setup trainer to train with more epochs
trainer = Trainer(
    module_file=os.path.abspath(_census_trainer_module_file),
    examples=transform.outputs['transformed_examples'],
    transform_graph=transform.outputs['transform_graph'],
    schema=schema_gen.outputs['schema'],
    train_args=trainer_pb2.TrainArgs(num_steps=500),
    eval_args=trainer_pb2.EvalArgs(num_steps=200))

# Run trainer
context.run(trainer, enable_cache=False)
```

```
WARNING:absl:Examples artifact does not have payload_format custom property. Falling back to FORMAT_TF_EXAMPLE
WARNING:absl:Examples artifact does not have payload_format custom property. Falling back to FORMAT_TF_EXAMPLE
WARNING:absl:Examples artifact does not have payload_format custom property. Falling back to FORMAT_TF_EXAMPLE
/usr/local/lib/python3.7/dist-packages/tensorflow/python/keras/optimizer_v2/optimizer_v2.py:375: UserWarning: The `lr` argument is deprecated, use `learning_rate` instead.
  "The `lr` argument is deprecated, use `learning_rate` instead.")
Model: "model_1"
```

Layer (type)	Output Shape	Param #	Connected to
fnlwgt_xf (InputLayer)	[(None, 1)]	0	
education-num_xf (InputLayer)	[(None, 1)]	0	
capital-gain_xf (InputLayer)	[(None, 1)]	0	
capital-loss_xf (InputLayer)	[(None, 1)]	0	
hours-per-week_xf (InputLayer)	[(None, 1)]	0	
concatenate_3 (Concatenate)	(None, 5)	0	fnlwgt_xf education-num_xf[0][0] capital-gain_xf[0][0] capital-loss_xf[0][0] hours-per-week_xf[0][0]
dense_6 (Dense)	(None, 100)	600	concatenate_3[0][0]
dense_7 (Dense)	(None, 70)	7070	dense_6[0][0]
education_xf (InputLayer)	[(None, 21)]	0	
marital-status_xf (InputLayer)	[(None, 12)]	0	

occupation_xf (InputLayer)	[(None, 20)]	0	
race_xf (InputLayer)	[(None, 10)]	0	
relationship_xf (InputLayer)	[(None, 11)]	0	
workclass_xf (InputLayer)	[(None, 14)]	0	
sex_xf (InputLayer)	[(None, 7)]	0	
native-country_xf (InputLayer)	[(None, 47)]	0	
age_xf (InputLayer)	[(None, 4)]	0	
dense_8 (Dense) [0][0]	(None, 48)	3408	dense_7
concatenate_4 (Concatenate) xf[0][0]	(None, 146)	0	education_ marital-st occupation race_xf relationsh workclass_ sex_xf native-cou age_xf
atus_xf[0][0] _xf[0][0] [0][0] ip_xf[0][0] xf[0][0] [0][0] ntry_xf[0][0] [0][0]			
dense_9 (Dense) [0][0]	(None, 34)	1666	dense_8
dense_10 (Dense) e_4[0][0]	(None, 128)	18816	concatenat
concatenate_5 (Concatenate) [0][0] [0][0]	(None, 162)	0	dense_9 dense_10
dense_11 (Dense) e_5[0][0]	(None, 1)	163	concatenat

=====  
Total params: 31,723  
Trainable params: 31,723  
Non-trainable params: 0

500/500 [=====] - 4s 6ms/step - loss: 0.3535 - bin


Out[38]: ▼ExecutionResult at 0x7f0abaacfd90


.execution\_id 22

**.component**  **Trainer** at 0x7f0ac860c910


**.component.inputs**


**['examples']**  **Channel** of type **'Examples'**  
(1 artifact) at 0x7f0ac8615510

**['transform\_graph']**  **Channel** of type  
**'TransformGraph'** (1 artifact) at  
0x7f0ac86151d0

**['schema']**  **Channel** of type **'Schema'** (1  
artifact) at 0x7f0ac85a2f50

**.component.outputs**

**['model']**  **Channel** of type **'Model'** (1 artifact)  
at 0x7f0ac860ced0

**['model\_run']**  **Channel** of type **'ModelRun'** (1  
artifact) at 0x7f0ac851d550

You will re-run the evaluator but you will specify the latest trainer output as the candidate model. The baseline is automatically found with the Resolver node.

In [39]:

```
# Re-run the evaluator
evaluator = Evaluator(
    examples=example_gen.outputs['examples'],
    model=trainer.outputs['model'],
    baseline_model=model_resolver.outputs['model'],
    eval_config=eval_config)

context.run(evaluator, enable_cache=False)
```

```
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t
racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/
func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef0>
Traceback (most recent call last):
```

```

File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t
racking/tracking.py", line 277, in __del__
    self._destroy_resource()
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/
func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef
0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t
racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/
func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef
0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t
racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/

```

```

func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef
0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t
racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/
func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef
0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t
racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/
func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef
0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t
racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func

```



```

tion.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/function.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/function.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t_racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/function.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/function.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/function.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t_racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/function.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/function.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/function.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t

```

```

racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func_
tion.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func_
tion.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func_
tion.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/
func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef
0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t
racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func_
tion.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func_
tion.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func_
tion.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/
func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef
0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t
racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func_
tion.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func_
tion.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func_
tion.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/
func_graph.py", line 999, in func_graph_from_py_func

```

```

    func_outputs = python_func(*func_args, **func_kwargs)
    File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 672, in wrapped_fn
        out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef
0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t
racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/
func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef
0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t
racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3022, in __call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/
func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef
0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t
racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def_
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3022, in __call__

```

```

        filtered_flat_args) = self._maybe_define_function(args, kwargs)
    File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3444, in _maybe_define_function
        graph_function = self._create_graph_function(args, kwargs)
    File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3289, in _create_graph_function
        capture_by_value=self._capture_by_value),
    File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/
func_graph.py", line 999, in func_graph_from_py_func
        func_outputs = python_func(*func_args, **func_kwargs)
    File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 672, in wrapped_fn
        out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
Exception ignored in: <function CapturableResource.__del__ at 0x7f0af1d10ef
0>
Traceback (most recent call last):
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/training/t
racking/tracking.py", line 277, in __del__
    self._destroy_resource()
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 889, in __call__
    result = self._call(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 924, in _call
    results = self._stateful_fn(*args, **kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3022, in _call__
    filtered_flat_args) = self._maybe_define_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3444, in _maybe_define_function
    graph_function = self._create_graph_function(args, kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/func
tion.py", line 3289, in _create_graph_function
    capture_by_value=self._capture_by_value),
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/framework/
func_graph.py", line 999, in func_graph_from_py_func
    func_outputs = python_func(*func_args, **func_kwargs)
  File "/usr/local/lib/python3.7/dist-packages/tensorflow/python/eager/def
function.py", line 672, in wrapped_fn
    out = weak_wrapped_fn().__wrapped__(*args, **kwargs)
AttributeError: 'NoneType' object has no attribute '__wrapped__'
WARNING:root:Make sure that locally built Python SDK docker image has Pytho

```


Out[39]:


▼ **ExecutionResult** at 0x7f0ab9b32090

**.execution\_id** 23

**.component**  **Evaluator** at 0x7f0ab9b3c3d0


**.component.inputs**


**['examples']**  **Channel** of type '**Examples**' (1 artifact) at 0x7f0acd962fd0

**['model']**  **Channel** of type '**Model**' (1 artifact) at 0x7f0ac860ced0

**['baseline\_model']**  **Channel** of type '**Model**' (1 artifact) at 0x7f0ab9bb1f50

**.component.outputs**

**['evaluation']**  **Channel** of type '**ModelEvaluation**' (1 artifact) at 0x7f0ab9b3c410

**['blessing']**  **Channel** of type '**ModelBlessing**' (1 artifact) at 0x7f0ab9b3c550

Depending on the result, the Resolver should reflect the latest blessed model. Since you trained with more epochs, it is most likely that your candidate model will pass the thresholds you set in the eval config. If so, the artifact URI should be different here compared to your earlier runs.

```
In [40]: # Re-run the resolver
context.run(model_resolver, enable_cache=False)
```

```
Out[40]: ▼ExecutionResult at 0x7f0ab9b36910

      .execution_id  24

      .component    <tfx.dsl.components.common.resolver.Resolver object at
                    0x7f0ac811b550>

      .component.inputs
                    ['model']  ▶Channel of type 'Model' (0
                               artifacts) at 0x7f0ac814fad0

                               ['model_blessing'] ▶Channel of type
                               'ModelBlessing' (0 artifacts) at
                               0x7f0ac817fc90

      .component.outputs
                    ['model']  ▶Channel of type 'Model' (1
                               artifact) at 0x7f0ac2155a10

                               ['model_blessing'] ▶Channel of type
                               'ModelBlessing' (1 artifact) at
                               0x7f0ac20d3bd0
```

```
In [41]: # Get path to latest blessed model
model_resolver.outputs['model'].get()[0].uri
```

```
Out[41]: './pipeline/Trainer/model/22'
```

Finally, the **evaluation** output of the **Evaluator** component will now be able to produce the **diff** results you saw in the previous lab. This will signify if the metrics from the candidate model has indeed improved compared to the baseline. Unlike when using TFMA as a standalone library, visualizing this will just show the results for the candidate (i.e. only one row instead of two in the tabular output in the graph below).

*Note: You can ignore the warning about failing to find plots.*

```
In [42]: context.show(evaluator.outputs['evaluation'])
```

**Artifact at ./pipeline/Evaluator/evaluation/23**

```
WARNING:absl:Fail to find plots for model name: None . Available model name
s are [candidate, baseline]
WARNING:absl:Fail to find plots for model name: None . Available model name
s are [candidate, baseline]
WARNING:absl:Fail to find plots for model name: None . Available model name
```

```
s are [candidate, baseline]
WARNING:absl:Fail to find plots for model name: None . Available model name
s are [candidate, baseline]
WARNING:absl:Fail to find plots for model name: None . Available model name
s are [candidate, baseline]
WARNING:absl:Fail to find plots for model name: None . Available model name
s are [candidate, baseline]
WARNING:absl:Fail to find plots for model name: None . Available model name
s are [candidate, baseline]
WARNING:absl:Fail to find plots for model name: None . Available model name
s are [candidate, baseline]
```

**Congratulations! You can now successfully evaluate your models in a TFX pipeline! This is a critical part of production ML because you want to make sure that subsequent deployments are indeed improving your results. Moreover, you can extract the evaluation results from your pipeline directory for further investigation with TFMA. In the next sections, you will continue to study techniques related to model evaluation and ensuring fairness.**