Branching algorithms

Serge Gaspers

UNSW

Outline

- Branching algorithms
- 2 Running time analysis
- Feedback Vertex Set
- 4 Maximum Leaf Spanning Tree
- Further Reading

Outline

- Branching algorithms
- 2 Running time analysis
- Feedback Vertex Set
- Maximum Leaf Spanning Tree
- 5 Further Reading

Branching Algorithm

Branching Algorithm

- Selection: Select a local configuration of the problem instance
- Recursion: Recursively solve subinstances
- Combination: Compute a solution of the instance based on the solutions of the subinstances
- Halting rule: 0 recursive calls
- Simplification rule: 1 recursive call
- Branching rule: ≥ 2 recursive calls

```
Algorithm \operatorname{vcl}(G,k);

1 if E=\emptyset then  // all edges are covered

2 \lfloor return Yes

3 else if k \leq 0 then  // we cannot select any vertex

4 \lfloor return No

5 else

6 \rfloor Select an edge uv \in E;

7 return \operatorname{vcl}(G-u,k-1) \vee \operatorname{vcl}(G-v,k-1)
```


Outline

- Branching algorithms
- 2 Running time analysis
- Feedback Vertex Set
- Maximum Leaf Spanning Tree
- Further Reading

Search trees

Recall: A search tree models the recursive calls of an algorithm.

For a b-way branching where the parameter k decreases by a at each recursive call, the number of nodes is at most $b^{k/a} \cdot (k/a+1)$.



If k/a and b are upper bounded by a function of k, and the time spent at each node is FPT (typically, polynomial), then we get an FPT running time.

Outline

- Branching algorithms
- 2 Running time analysis
- Feedback Vertex Set
- Maximum Leaf Spanning Tree
- Further Reading

Feedback Vertex Set


A feedback vertex set of a multigraph G=(V,E) is a set of vertices $S\subseteq V$ such that G-S is acyclic.

FEEDBACK VERTEX SET

Input: Multigraph G = (V, E), integer k

Parameter: k

Question: Does G have a feedback vertex set of size at most k?



We apply the first applicable simplification/halting rule.

(Finished)

If G is acyclic and $k \geq 0$, then return YES.

(Budget-exceeded)

If k < 0, then return No.

10 / 29

¹A rule is applicable if it modifies the instance.

We apply the first applicable simplification/halting rule.

(Finished)

If G is acyclic and $k \ge 0$, then return YES.

(Budget-exceeded)

If k < 0, then return No.

(Loop)

If G has a loop $vv \in E$, then set $G \leftarrow G - v$ and $k \leftarrow k - 1$.

¹A rule is applicable if it modifies the instance.

We apply the first applicable simplification/halting rule.

(Finished)

If G is acyclic and $k \ge 0$, then return YES.

(Budget-exceeded)

If k < 0, then return No.

(Loop)

If G has a loop $vv \in E$, then set $G \leftarrow G - v$ and $k \leftarrow k - 1$.

(Multiedge)

If E contains an edge uv more than twice, remove all but two copies of uv.

S. Gaspers (UNSW) Branching 10 / 29

¹A rule is applicable if it modifies the instance.

(Degree-1)

If $\exists v \in V$ with $d_G(v) \leq 1$, then set $G \leftarrow G - v$.

(Degree-2)

If $\exists v \in V$ with $d_G(v) = 2$, then denote vu, vw its two incident edges and set $G \leftarrow G' = (V \setminus \{v\}, (E \setminus \{vu, vw\}) \cup \{uw\}).$

(Degree-2)

If $\exists v \in V$ with $d_G(v) = 2$, then denote vu, vw its two incident edges and set $G \leftarrow G' = (V \setminus \{v\}, (E \setminus \{vu, vw\}) \cup \{uw\}).$

Lemma 1

(Degree-2) is sound.

Proof.

Suppose S is a feedback vertex set of G of size at most k. Let

$$S' = \begin{cases} S & \text{if } v \notin S \\ (S \setminus \{v\}) \cup \{u\} & \text{if } v \in S. \end{cases}$$

Now, $|S'| \le k$ and S' is a feedback vertex set of G' since every cycle in G' corresponds to a cycle in G, with, possibly, the edge uw replaced by the walk (u, v, w).

Suppose S' is a feedback vertex set of G' of size at most k. Then, S' is also a feedback vertex set of G.

Remaining issues

- A select–discard branching decreases *k* in only one branch
- ullet One could branch on all the vertices of a cycle, but the length of a shortest cycle might not be bounded by any function of k

Remaining issues

- ullet A select-discard branching decreases k in only one branch
- ullet One could branch on all the vertices of a cycle, but the length of a shortest cycle might not be bounded by any function of k

Idea:

- ullet An acyclic graph has average degree <2
- ullet After applying simplification rules, G has average degree ≥ 3
- The selected feeback vertex set needs to be incident to many edges
- ullet Does a feedback vertex set of size at most k contain at least one vertex among the f(k) vertices of highest degree?

The fvs needs to be incident to many edges

Lemma 2

If S is a feedback vertex set of G=(V,E), then

$$\sum_{v \in S} (d_G(v) - 1) \ge |E| - |V| + 1$$

The fvs needs to be incident to many edges

Lemma 2

If S is a feedback vertex set of G = (V, E), then

$$\sum_{v \in S} (d_G(v) - 1) \ge |E| - |V| + 1$$

Proof.

Since F = G - S is acyclic, $|E(F)| \le |V| - |S| - 1$.

Since every edge in $E \setminus E(F)$ is incident with a vertex of S, we have

$$|E| = |E| - |E(F)| + |E(F)|$$

$$\leq \left(\sum_{v \in S} d_G(v)\right) + (|V| - |S| - 1)$$

$$= \left(\sum_{v \in S} (d_G(v) - 1)\right) + |V| - 1.$$

The fvs needs to contain a high-degree vertex

Lemma 3

Let G be a graph with minimum degree at least 3 and let H denote a set of 3k vertices of highest degree in G.

Every feedback vertex set of G of size at most k contains at least one vertex of H.

The fvs needs to contain a high-degree vertex

Lemma 3

Let G be a graph with minimum degree at least 3 and let H denote a set of 3k vertices of highest degree in G.

Every feedback vertex set of G of size at most k contains at least one vertex of H.

Proof.

Suppose not. Let S be a feedback vertex set with $|S| \leq k$ and $S \cap H = \emptyset$. Then,

$$\begin{aligned} 2|E| - |V| &= \sum_{v \in V} (d_G(v) - 1) \\ &= \sum_{v \in H} (d_G(v) - 1) + \sum_{v \in V \setminus H} (d_G(v) - 1) \\ &\geq 3 \cdot (\sum_{v \in S} (d_G(v) - 1)) + \sum_{v \in S} (d_G(v) - 1) \\ &\geq 4 \cdot (|E| - |V| + 1) \\ \Leftrightarrow \quad 3|V| \geq 2|E| + 4. \end{aligned}$$

But this contradicts the fact that every vertex of G has degree at least 3.

Algorithm for Feedback Vertex Set

Theorem 4

FEEDBACK VERTEX SET can be solved in $O^*((3k)^k)$ time.

Proof (sketch).

- Exhaustively apply the simplification rules.
- The branching rule computes H of size 3k, and branches into subproblems (G-v,k-1) for each $v\in H$.

Outline

- Branching algorithms
- 2 Running time analysis
- Feedback Vertex Set
- Maximum Leaf Spanning Tree
- Further Reading

Maximum Leaf Spanning Tree

A leaf of a tree is a vertex with degree 1. A spanning tree in a graph G=(V,E) is a subgraph of G that is a tree and has |V| vertices.

MAXIMUM LEAF SPANNING TREE

Input: connected graph G, integer k

Parameter: k

Question: Does G have a spanning tree with at least k leaves?

Property

A k-leaf tree in G is a subgraph of G that is a tree with at least k leaves. A k-leaf spanning tree in G is a spanning tree in G with at least k leaves.

Lemma 5

Let G = (V, E) be a connected graph.

G has a k-leaf tree $\Leftrightarrow G$ has a k-leaf spanning tree.

Proof.

(⇐): trivial

 (\Rightarrow) : Let T be a k-leaf tree in G. By induction on x:=|V|-|V(T)|, we will show that T can be extended to a k-leaf spanning tree in G.

Base case: x = 0 \checkmark .

Induction: x>0, and assume the claim is true for all x'< x. Choose $uv\in E$ such that $u\in V(T)$ and $v\notin V(T)$. Since $T':=(V(T)\cup\{v\},E(T)\cup\{uv\})$ has $\geq k$ leaves and < x external vertices, it can be extended to a k-leaf spanning tree in G by the induction hypothesis. \square

Strategy

- ullet The branching algorithm will check whether G has a k-leaf tree.
- A tree with ≥ 3 vertices has at least one internal (= non-leaf) vertex.
- "Guess" an internal vertex r, i.e., do a |V|-way branching fixing an initial internal vertex r.

Strategy

- ullet The branching algorithm will check whether G has a k-leaf tree.
- A tree with ≥ 3 vertices has at least one internal (= non-leaf) vertex.
- "Guess" an internal vertex r, i.e., do a |V|-way branching fixing an initial internal vertex r.
- In any branch, the algorithm has computed
 - \bullet T a tree in G
 - I the internal vertices of T, with $r \in I$
 - ullet B a subset of the leaves of T where T may be extended: the boundary set
 - ullet L the remaining leaves of T
 - ullet X the external vertices $V\setminus V(T)$

Strategy

- The branching algorithm will check whether G has a k-leaf tree.
- A tree with ≥ 3 vertices has at least one internal (= non-leaf) vertex.
- "Guess" an internal vertex r, i.e., do a |V|-way branching fixing an initial internal vertex r.
- In any branch, the algorithm has computed
 - \bullet T a tree in G
 - I the internal vertices of T, with $r \in I$
 - ullet B a subset of the leaves of T where T may be extended: the boundary set
 - \bullet L the remaining leaves of T
 - ullet X the external vertices $V\setminus V(T)$
- ullet The question is whether T can be extended to a k-leaf tree where all the vertices in L are leaves.

Apply the first applicable simplification rule:

(Halt-Yes)

If $|L| + |B| \ge k$, then return YES.

(Halt-No)

If |B| = 0, then return No.

(Non-extendable)

If $\exists v \in B$ with $N_G(v) \cap X = \emptyset$, then move v to L.

Branching Lemma

Lemma 6 (Branching Lemma)

Suppose $u \in B$ and there exists a k-leaf tree T' extending T where u is an internal vertex.

Then, there exists a k-leaf tree T'' extending

 $(V(T) \cup N_G(u), E(T) \cup \{uv : v \in N_G(u) \cap X\}).$

Branching Lemma

Lemma 6 (Branching Lemma)

Suppose $u \in B$ and there exists a k-leaf tree T' extending T where u is an internal vertex.

Then, there exists a k-leaf tree T'' extending $(V(T) \cup N_G(u), E(T) \cup \{uv : v \in N_G(u) \cap X\}).$

Proof.

Start from $T'' \leftarrow T'$ and perform the following operation for each $v \in N_G(u) \cap X$. If $v \notin V(T')$, then add he vertex v and the edge uv.

Otherwise, add the edge uv, creating a cycle C in T and remove the other edge of C incident to v. This does not decrease the number of leaves, since it only increases the number of edges incident to u, and u was already internal. \Box

Follow Path Lemma

Lemma 7 (Follow Path Lemma)

Suppose $u \in B$ and $|N_G(u) \cap X| = 1$. Let $N_G(u) \cap X = \{v\}$. If there exists a k-leaf tree extending T where u is internal, but no k-leaf tree extending T where u is a leaf, then there exists a k-leaf tree extending T where both u and v are internal

Follow Path Lemma

Lemma 7 (Follow Path Lemma)

Suppose $u \in B$ and $|N_G(u) \cap X| = 1$. Let $N_G(u) \cap X = \{v\}$. If there exists a k-leaf tree extending T where u is internal, but no k-leaf tree extending T where u is a leaf, then there exists a k-leaf tree extending T where both u and v are internal.

Proof.

Suppose not, and let T' be a k-leaf tree extending T where u is internal and v is a leaf. But then, T-v is a k-leaf tree as well. \qed

Algorithm

- Apply halting & simplification rules
- Select $u \in B$. Branch into
 - $u \in L$
 - $u \in I$. In this case, add $X \cap N_G(u)$ to B (Branching Lemma).
 - In the special case where $|X \cap N_G(u)| = 1$, denote $\{v\} = X \cap N_G(u)$, make v internal, and add $N_G(v) \cap X$ to B, continuing the same way until reaching a vertex with at least 2 neighbors in X (Follow Path Lemma).
 - In the special case where $|X \cap N_G(u)| = 0$, return No.

Algorithm

- Apply halting & simplification rules
- Select $u \in B$. Branch into
 - $u \in L$
 - $u \in I$. In this case, add $X \cap N_G(u)$ to B (Branching Lemma).
 - In the special case where $|X \cap N_G(u)| = 1$, denote $\{v\} = X \cap N_G(u)$, make v internal, and add $N_G(v) \cap X$ to B, continuing the same way until reaching a vertex with at least 2 neighbors in X (Follow Path Lemma).
 - In the special case where $|X \cap N_G(u)| = 0$, return No.
- In one branch, a vertex moves from B to L; in the other branch, |B| increases by at least 1.

Running time analysis

- ullet Consider the "measure" $\mu:=2k-2|L|-|B|$
- We have that $0 \le \mu \le 2k$
- Branch where $u \in L$:
 - ullet |B| decreases by 1, |L| increases by 1
 - ullet μ decreases by 1
- Branch where $u \in I$.
 - ullet u moves from B to I
 - $\bullet \geq 2$ vertices move from X to B
 - ullet μ decreases by at least 1
- \bullet Binary search tree of height $\leq \mu \leq 2k$

Result for Maximum Leaf Spanning Tree

Theorem 8 ((Kneis, Langer, and Rossmanith, 2011))

MAXIMUM LEAF SPANNING TREE can be solved in $O^*(4^k)$ time.

Outline

- Branching algorithms
- 2 Running time analysis
- Feedback Vertex Set
- Maximum Leaf Spanning Tree
- 5 Further Reading

Further Reading

- Chapter 3, Bounded Search Trees in (Cygan et al., 2015)
- Chapter 3, Bounded Search Trees in (Downey and Fellows, 2013)
- Chapter 8, Depth-Bounded Search Trees in (Niedermeier, 2006)

References I

- Marek Cygan, Fedor V. Fomin, Łukasz Kowalik, Daniel Lokshtanov, Dániel Marx, Marcin Pilipczuk, Michał Pilipczuk, and Saket Saurabh (2015). *Parameterized Algorithms*. Springer. DOI: 10.1007/978–3–319–21275–3.
- Rodney G. Downey and Michael R. Fellows (2013). *Fundamentals of Parameterized Complexity*. Springer. DOI: 10.1007/978-1-4471-5559-1.
- Joachim Kneis, Alexander Langer, and Peter Rossmanith (2011). "A New Algorithm for Finding Trees with Many Leaves". In: Algorithmica 61.4, pp. 882–897.
- Rolf Niedermeier (2006). *Invitation to Fixed Parameter Algorithms*. Oxford University Press. DOI: 10.1093/ACPROF:0S0/9780198566076.001.0001.