Get Shipping Labels

Version	Created by	Department
1.0	Héctor Furió	Client Integrations

Introduction

The Get Shipping Labels API allows users to retrieve shipping labels for items in their shipments. Each label is provided individually per item and can be returned in various formats: PDF, EPL, or ZPL. This document outlines the operations enabled by this API, including details about the available endpoints, parameters, and response formats.

Base URL

- Test: https://api-test.cttexpress.com/integrations
- Production: https://api.cttexpress.com/integrations

For a complete definition of each endpoint, you can refer to the Postman collection.

Endpoint Details

Description: Returns shipping labels for the items in a shipment. The data contains one label for each item, and the labels can be returned in PDF, EPL, or ZPL formats.

Available Query Parameters:

- label_type_code (optional): Specifies the type of label format. Default is PDF.
    - Values:
        - PDF: PDF document
        - PDF2: PDF document (2nd option, visual changes)
        - ZPL: ZPL script
        - EPL: EPL script
- model_type_code (optional): Specifies the type of page format. Default is MULTI4.
    - Values:
        - MULTI4: 4 labels per page
        - MULTI3: 3 labels per page in a MULTI4 page format
        - MULTI1: 1 label per page in a MULTI4 page format
        - SINGLE: 1 label per page, full page size
- label_offset (optional): Offset for printing the first label in MULTIX formats. Default is 1.

Example Request:

```
GET /trf/labelling/v1.0/shippings/0082800045229800000017/shipping-
labels?label_type_code=PDF&model_type_code=MULTI4&label_offset=1
```

Multiple Shipping Labels

The API also provides a feature to retrieve multiple labels at once for a set of shipment codes.

Endpoint: `POST {{baseUrl}}/trf/labelling/v1.0/shippings/rpc-multiple-shipping-labels`

Request Body:

```
{
  "shipping_codes": [
    "0007210082809800002175",
    "0007210082809800002173",
    "0007210082809800002171",
    "0007210082809800002170"
  ],
  "model_type_code": "MULTI1",
  "label_type_code": "PDF",
  "label_offset": 0
}
```

Success Response:

```
{
  "data": [
    {
      "shipping_code": "string",
      "label_type_code": "string",
      "model_type_code": "string",
      "label": "string",
      "thermal_label": ["string"]
    }
  ]
}
```

Field Descriptions

- shipping_code: The requested shipping code.
- label_type_code: The requested label type code.

- model_type_code: The requested model type code.
- label: In the case of PDF, this field contains a Base64 string representing the generated PDF document.
- thermal_label: In the case of ZPL or EPL, this field contains the print scripts for each shipping item.

Response Codes

- 200 OK: Success.

Error Responses

- 400 BadRequest: Incorrect query parameters.
- 401 Unauthorized: Authentication or authorization failed.
- 403 Forbidden: The action is forbidden.
- 404 NotFound: Shipping code not found.
- 405 NotAllowed: HTTP method not allowed.
- 500 InternalServerError: Service error; retry later.
- 502 BadGateway: Bad gateway.
- 504 GatewayTimeout: Gateway timeout.