Containerisation API

Version	Created by	Department
1.0	Héctor Furió	Client Integrations

Introduction

This document provides an overview of the Containerisation API v1.0, detailing the available operations, field descriptions, and examples for interacting with the API. The API allows registering shipping containers in batches. You can access the complete API definition through the Postman collection files.

Base URLs:

- Test: https://api-test.cttexpress.com/integrations
- Production: https://api.cttexpress.com/integrations

Endpoint:

POST {{baseUrl}}/trf/client-containers

The endpoint allows registering one or multiple containers in batch, each one with its associated packages.

Headers:

- Authorization: Bearer {token}

Request Body Example:

```
{
    "masterClientCode": "XXXXX",
    "containers": [
        {
            "containerId": "CN6456645456",
            "packages": [
                {
                    "packageId": "00000200828095113388360 01"
                },
                {
                    "packageId": "00000200828095113388540 01"
```

```
                }
            ]
        },
        {
            "containerId": "CN65456454688",
            "packages": [
                {
                    "packageId": "0000020082809511338836001"
                },
                {
                    "packageId": "0000020082809511338854001"
                }
            ]
        }
    ]
}
```


Success Response:

- **HTTP Status:** 204 No Content

Error Responses:

- 400 Bad Request: Wrong arguments.
- 401 Unauthorized: Not authenticated or authorized.
- 403 Forbidden: Action forbidden.
- 404 Not Found: Related data not found.
- 405 Method Not Allowed: Method not allowed.
- 409 Conflict: Conflict with an existing shipping.
- 500 Internal Server Error: Retry the request.

Error Responses root cause overview:

- 400 Bad Request: Incorrect request parameters.
- 401 Unauthorized: Authentication failure.
- 403 Forbidden: Action is not allowed.
- 404 Not Found: Related data is missing.

- 405 Method Not Allowed: HTTP method not allowed.
- 409 Conflict: Data conflict, often related to existing shipping information.
- 500 Internal Server Error: Service error, try again.
- 502 Bad Gateway, 504 Gateway Timeout: Network-related issues.

API Fields

Field	Mandatory	Data Type	Description
masterClientCode	Yes	String	Client Master Code (provided by CTT)
containerId	Yes	String	Unique identifier for the container
packages	Yes	Array	Array of package information
packageId	Yes	String	Unique identifier for each package