Configuration PUDO Services

by CttExpress

Nov 2023

INDEX

1. Service description 3
2. Service limitations 3
3. Get CTT Pickup points list 3
3.1. CSV File 3
3.2. API Rest 4
4. Manifesting PUDO Delivery 7
4.1. Soap OnPremise (SGC) 8
4.1.1 Additional Services information 8
4.1.2 Destination information 8
4.2. Soap Cloud 9
4.2.1 Additional Services information 9
4.2.2 Destination information 9
4.3. API Rest Cloud 10
4.3.1 Additional Services information 10
4.3.2 Destination information 10
5. Manifesting PUDO Drop Off 11
5.1 API Rest Cloud 11
5.1.1 Additional Services information 11
5.2 Soap Cloud 13
5.2.1 Additional Services information 13
5.3 Soap OnPremise (SGC) 15
5.3.1 Additional Services information 15
5.4 Notification creation for PUDO Drop off 16

1. Service description

The Direct Delivery Point (EDP) service offers the possibility of delivering shipments to a selected CTT point so the recipient can pick them up there.

2. Service limitations

PUDO Deliveries can be used in all services except those which have a compromised time of delivery (10h y 14h) and Collect in Agency (REA)

The shipment must accomplish the following characteristics:

- 1 parcel per shipment.
- Maximum weight 20 Kg.
- Height + Width + Length should be 160cm maximum.
- No return service.
- No refund service.
- No shipping due.
- Without management service at destination.
- Without customer delivery note scanning service.
- Without recipient ID verification service.
- Mandatory recipient mobile phone
- Mandatory recipient email.

3. Get CTT Pickup points list

The complete CTT points available for PUDO Direct Deliveries can be downloaded using the following integration methods:

3.1. CSV File

The complete list of the available PUDO Points in CSV can be downloaded using the following link:

http://transfer.cttexpress.com/IT/export/integra/PUNTOSCTT.csv

The file is a CSV and its structure is the following:

Field	Description
Organic Point Code	PUDO CTT Internal code
Point Name	PUDO Name
Phone Number	PUDO Phone number
Address	PUDO Address
Town	PUDO Town
Postal Code	PUDO Zip code
Country Code	PUDO Country Code
GPS Latitude	PUDO Latitude
GPS Longitude	PUDO Longitude
Scheduled	Opening Hours
Services	Services available separated by comma: - PUDO (Delivery in a PUDO) - REVERSE_LOGISTICS (PUDO Drop off)

3.2. API Rest

Using your credentials, the complete list can be downloaded as follows:

End Point:

https://api.cttexpress.com/integrations/delivery/v1.0/distribution-points/search?page_limit=50&page_offsets=3

Headers:

Key	Value
user_name	user1
password	passw0rd$.
Authorization	Bearer eyJraWQiOiJ

Body:

```
{
    "type": "OFFLINE"
}
```

Result:

```
{
  "address": {
    "address": "Agente Payshop - Rua Adário Gonçalves Moreira, nº 1523",
    "town": "Vilar do Pinheiro",
    "country_code": "PT",
    "gps_latitude": 41.2677549,
    "gps_longitude": -8.667106892,
    "postal_code": "4485-826"
  },
  "custom_group_name": "PARC",
  "id": "6458b88c28b0cd94d5883a8c",
  "opening_hours_array": [
    {
      "day_of_week": 1,
      "hours": [
        {
          "from": "07:00",
          "to": "20:00"
        }
      ]
    },
    {
      "day_of_week": 2,
      "hours": [
        {
          "from": "07:00",
          "to": "20:00"
        }
      ]
    },..
  ],
  "organic_point_code": "3000177",
  "phone_number": "229285959",
```

"point_code": "3000177",
"point_name": "Payshop Papelaria Aguarella"
}

4. Manifesting PUDO Delivery

In this paragraph, we will describe how to send a shipment using the different Manifest methods available

It will be necessary to fill in the **Additional Services** section with the correct information to use this service.

It also necessary that the **Destination Information** should be filled using the following considerations:

- Destination Name: Real contact name of the destination (Buyer)
- Destination Contact Name: Pudo's Name + Real contact name of the destination (Buyer)
- Destination Address: PUDO Address
- Destination Zipcode: PUDO zipcode
- Destination Country: PUDO Country
- Destination Email: Buyer Email (Used for notifications)
- Destination Phone: Buyer Prone (Used for notifications)

Detailed below, the additional Service and destination information depending the Integration method.

4.1. Soap OnPremise (SGC)

Endpoint: http://ws.tourlineexpress.com:8200/Service1.svc

4.1.1 Additional Services information

Additional services to be filled for PUDO Deliveries:

```
<tour:AdditionalServices>
<tour1:AdditionalService>
<tour1:Flag>true</tour1:Flag>                          //Fixed field "true" for PUDO Deliveries
<tour1:ServiceCode>PER</tour1:ServiceCode>             //Fixed field "PER" for PUDO Deliveries
<tour1:ServiceText>5XXXXXX</tour1:ServiceText>         //"organic_point_code" field from the PUDO List
<tour1:Value>0</tour1:Value>                           //Fixed field "0" (Zero) for PUDO Deliveries
</tour1:AdditionalService>
</tour:AdditionalServices>
```

4.1.2 Destination information

```
<tour:ContactName>PUDO NAME + BUYER NAME</tour:ContactName>
<tour:RecipientAddress>PUDO ADDRESS</tour:RecipientAddress>
<tour:RecipientCountry>PUDO COUNTRY CODE</tour:RecipientCountry>
<tour:RecipientEmail>BUYER EMAIL<tour:RecipientEmail/>
<tour:RecipientMobile>BUYER PHONE<tour:RecipientMobile/>
<tour:RecipientName> BUYER NAME</tour:RecipientName>
<tour:RecipientPhone>BUYER PHONE</tour:RecipientPhone>
<tour:RecipientPostalCode>PUDO ZIPCODE</tour:RecipientPostalCode>
<tour:RecipientTown>PUDO TOWN</tour:RecipientTown>
```

4.2. Soap Cloud

Endpoint: https://api.cttexpress.com/integrations-legacy/Service1/Service1Soap12

4.2.1 Additional Services information

Additional services to be filled for PUDO Deliveries:

```
<tour:AdditionalServices>
<tour1:AdditionalService>
<tour1:Flag>true</tour1:Flag>                          //Fixed field "true" for PUDO Deliveries
<tour1:ServiceCode>PER</tour1:ServiceCode>             //Fixed field "PER" for PUDO Deliveries
<tour1:ServiceText>5XXXXXX</tour1:ServiceText>         //"organic_point_code" field from the PUDO List
<tour1:Value>0</tour1:Value>                           //Fixed field "0" (Zero) for PUDO Deliveries
<tour1:ServiceSubCode>EDP</tour1:ServiceSubCode>       //Fixed field "EDP" for PUDO Deliveries
</tour1:AdditionalService>
</tour:AdditionalServices>
```

4.2.2 Destination information

```
<tour:ContactName>PUDO NAME + BUYER NAME</tour:ContactName>
<tour:RecipientAddress>PUDO ADDRESS</tour:RecipientAddress>
<tour:RecipientCountry>PUDO COUNTRY CODE</tour:RecipientCountry>
<tour:RecipientEmail>BUYER EMAIL<tour:RecipientEmail/>
<tour:RecipientMobile>BUYER PHONE<tour:RecipientMobile/>
<tour:RecipientName> BUYER NAME</tour:RecipientName>
<tour:RecipientPhone>BUYER PHONE</tour:RecipientPhone>
<tour:RecipientPostalCode>PUDO ZIPCODE</tour:RecipientPostalCode>
<tour:RecipientTown>PUDO TOWN</tour:RecipientTown>
```

4.3. API Rest Cloud

Endpoint: https://api.cttexpress.com/integrations/manifest/v1.0/shippings

4.3.1 Additional Services information

Additional services to be filled for PUDO Deliveries:

```
{
"additional_code":"PER",            //Fixed field "PER" for PUDO Deliveries
"additional_value":0,               //Fixed field "0" (Zero) for PUDO Deliveries
"additional_flag":true,             //Fixed field "true" for PUDO Deliveries
"additional_text":"5500001,         //"organic_point_code" field from the PUDO List
"additional_sub_code":"EDP"         //Fixed field "EDP" for PUDO Deliveries
}
```

4.3.2 Destination information

```
"recipient_name": "BUYER NAME",
"recipient_country_code": "PUDO COUNTRY CODE",
"recipient_postal_code": "PUDO ZIPCODE",
"recipient_address": "PUDO ADDRESS",
"recipient_town": "PUDO TOWN",
"recipient_email_notify_address": "BUYER EMAIL",
"recipient_phones": ["BUYER PHONE1","BUYER PHONE2" ,...],
-----
"delivery": {
"contact_name": "PUDO NAME + BUYER NAME",
------
```

5. Manifesting PUDO Drop Off

In this paragraph, we will describe how to send a shipment using the different Manifest methods available

It will be necessary to fill in the **Additional Services** section with the correct information to use this service.

It is also necessary that the **Sender Information** should be filled in using the following considerations:

- Sender Name: Real contact name of the Sender (Buyer)
- Sender Contact Name: Sender name (Buyer)
- Sender Address: Sender Address
- Sender Zipcode: Sender zipcode
- Sender Country: Sender Country
- Sender Email: Buyer Email (Used for notifications)
- Sender Phone: Buyer Phone (Used for notifications)

Detailed below, are the additional Service and destination information for the Standar File Integration method.

5.1 API Rest Cloud

5.1.1 Additional Services information

Additional services to be filled for PUDO Drop Off in **Spain**:

Field	Vale	Comment
additional_code	ERE	Code for reverse logistics
additional_value	0	Fixed value
additional_flag	true	Fixed value
additional_text		Empty field
additional_sub_code	RDP	Subcode for reverse logistics

Here's an example in an additionals array:

```
{
        "additional_code": "ERE",
        "additional_value": 0,
        "additional_flag": true,
        "additional_text": "",
        "additional_sub_code": "RDP"
}
```

Additional services to be filled for PUDO Drop Off in **Portugal**:

Field	Vale	Comment
additional_code	ERV	Code for reverse logistics
additional_value	0	Fixed value
additional_flag	true	Fixed value
additional_text		Empty field
additional_sub_code		Empty field

Here's an example in an additionals array:

```
{
        "additional_code": "ERV",
        "additional_value": 0,
        "additional_flag": true,
        "additional_text": "",
        "additional_sub_code": ""
}
```

5.2 Soap Cloud

Endpoint: https://api.cttexpress.com/integrations-legacy/Service1/Service1Soap12

5.2.1 Additional Services information

Additional services to be filled for PUDO Drop Off in **Spain**:

Field	Vale	Comment
Flag	true	Fixed value
ServiceCode	ERE	Code for reverse logistics
ServiceText		empty value
Value	0	Fixed field
ServiceSubCode	RDP	Subcode for reverse logistics

Here's an example in an additionals array:

```
<tour:AdditionalServices>
  <tour1:AdditionalService>
    <tour1:Flag>true</tour1:Flag>
    <tour1:ServiceCode>ERE</tour1:ServiceCode>
    <tour1:ServiceText></tour1:ServiceText>
    <tour1:Value>0</tour1:Value>
    <tour1:ServiceSubCode>RDP</tour1:ServiceSubCode>
  </tour1:AdditionalService>
</tour:AdditionalServices>
```

Additional services to be filled for PUDO Drop Off in **Portugal**:

Field	Vale	Comment
Flag	true	Fixed value
ServiceCode	ERV	Code for reverse logistics
ServiceText		empty value
Value	0	Fixed field
ServiceSubCode		empty value

Here’s an example in an additionals array:

```
<tour:AdditionalServices>
  <tour1:AdditionalService>
    <tour1:Flag>true</tour1:Flag>
    <tour1:ServiceCode>ERV</tour1:ServiceCode>
    <tour1:ServiceText></tour1:ServiceText>
    <tour1:Value>0</tour1:Value>
    <tour1:ServiceSubCode> </tour1:ServiceSubCode>
  </tour1:AdditionalService>
</tour:AdditionalServices>
```

5.3 Soap OnPremise (SGC)

Endpoint: http://ws.tourlineexpress.com:8200/Service1.svc

5.3.1 Additional Services information

Additional services to be filled for PUDO Drop Off in **Spain**:

Field	Vale	Comment
Flag	true	Fixed value
ServiceCode	ERE	Code for reverse logistics
ServiceText		empty value
Value	930	Fixed field

Here's an example in an additionals array:

```
<tour:AdditionalServices>
  <tour1:AdditionalService>
    <tour1:Flag>true</tour1:Flag>
    <tour1:ServiceCode>ERE</tour1:ServiceCode>
    <tour1:ServiceText></tour1:ServiceText>
    <tour1:Value>930</tour1:Value>
  </tour1:AdditionalService>
</tour:AdditionalServices>
```

Additional services to be filled for PUDO Drop Off in **Portugal**:

Field	Vale	Comment
Flag	true	Fixed value
ServiceCode	ERV	Code for reverse logistics
ServiceText		empty value
Value	0	Fixed field

Here's an example in an additionals array:

```
<tour:AdditionalServices>
  <tour1:AdditionalService>
    <tour1:Flag>true</tour1:Flag>
    <tour1:ServiceCode>ERV</tour1:ServiceCode>
    <tour1:ServiceText></tour1:ServiceText>
    <tour1:Value>0</tour1:Value>
  </tour1:AdditionalService>
</tour:AdditionalServices>
```

5.4 Notification creation for PUDO Drop off

Usually, CTT will send a notification to the customer with the necessary information to drop off the parcel in a PUDO. In the case, you want to create the notification on your side you should follow the following specifications depending on the country of the PUDO:

Spain notification

The field shipping_code (This code can be returned in the response or calculated by the customer based on the Spanish range asigned by CTT Integration team) returned in the response of the manifest creation should be sent to the customer in a notification in QR, Code-128, and text format. For example:

0082800046388742100078

Portugal notification

The field item_external_code code (This code can be returned in the responses or calculated by the customer based on the Portugal range asigned by CTT Integration team) returned in the response of the manifest creation should be sent to the customer in a notification in QR, Code-128, and text format. For example:

DE020640039PT