

Enhancing Wireless Networks Performance through Learning-based Dynamic Spectrum Access


Sergio Barrachina (sergio.barrachina@upf.edu)

Supervised by Boris Bellalta, Wireless Networking group (WN). Universitat Pompeu Fabra. *Barcelona (Spain)*

The chaos of Wireless Networks


The number of devices accessing the Internet through Wireless Local Area Networks (WLANs) is increasing drastically.

- WLANs are managed by different operators, leading to chaotic wireless spectrum occupancy.
- By means of transmitting in wider channels through dynamic spectrum access (DSA), higher short-term throughputs are achieved.
- However, the contention among nodes leads to undesirable low performance, which is critical in high-density scenarios like football stadiums and apartment buildings.
- What we propose is a **learning-based channel selection policy for optimizing WLANs throughput**.



Applying learning-based policies

- DSA policy:** selects the optimal transmission channel range.
- Input:** sensed channel power and history of actions + reward.
- Reward:** greedy, collaborative, short/long-term throughput, etc.



Channel allocation characterization

Continuous Time Markov Networks (CTMNs) allow to **analytically** capture the operation of idealized wireless networks [2].

- States: channels being used by each node.
- Transitions: DSA policies determine the transition rates.
- Throughput closed form of WLAN i :


$$\Gamma_i = \frac{L}{\sum_{s \in S} \mu_{i,s}(c) \pi_s} \quad \text{Probability of being in state } s$$

Packet length

Departure rate when using c channels


- CTMN model limitations:

- Several assumptions must be considered such as overlapping nodes, continuous backoff, idealized channel, etc.
- Komondor** simulator built in COST [3] is being developed to capture real world wireless phenomena.




On-going work

- Characterize channel selection effects on throughput and fairness.
 - Identify general topologies and phenomena in dense deployments.
 - Standard protocols effect on throughput (e.g., IEEE 802.11).
- Design learning-based DSA policies for enhancing WLANs performance.
 - Identify suitable machine learning techniques [4].
 - Centralized / Decentralized: full / local knowledge available.
- Incorporate transmit power control (TPC) in the learning-based policies.




Open questions

- Feasibility of identifying optimal policies.
- Knowledge extraction: control vs. overhead.
- Greedy vs. collaborative throughput.
- Non-stationarity effects on DSA policies.
- Suitability of combinatorial multi-armed bandits (MABs).



Preliminary analysis

- Selecting the widest channel available may decrease the long-term throughput.
- Optimal transition rates (i.e., DSA policies) depend thoroughly on the scenario.
- The effect of hidden nodes may be critical and hard to prevent.



References

- Gartner, "Gartner Says 6.4 Billion Connected Things Will Be in Use in 2016, Up 30 Percent From 2015", <http://www.gartner.com/newsroom/id/3165317>, Nov. 2015. Accessed: 27 Feb. 2017.
- B. Bellalta, A. Checco, A. Zocca and J. Barcelo, "On the Interactions Between Multiple Overlapping WLANs Using Channel Bonding", in *IEEE Transactions on Vehicular Technology*, vol. 65, no. 2, pp. 796-812, Feb. 2016.
- G. Chen and B. K. Szymanski, "Reusing Simulation Components: COST: A Component-oriented Discrete Event Simulator", in *Proceedings of the 34th Conference on Winter Simulation: Exploring New Frontiers*, ser. WSC '02. Winter Simulation Conference, pp. 776-782, 2012.
- C. Jiang, H. Zhang, Y. Ren, Z. Han, K. C. Chen and L. Hanzo, "Machine Learning Paradigms for Next-Generation Wireless Networks", in *IEEE Wireless Communications*, 2016.

