

Kona N sound capture: shot list

Cabin-only (CAB + optional FWL footwell) · 48 kHz / 24-bit WAV · file name: <take>_r<rep>_<channel>.wav · say the take ID out loud, clap, then record · Tier A first, then B; C optional

Date: _____ Location: _____ Recorder(s): _____ Car / VIN: _____

Before every block

☐ Normal drive mode	☐ ESG OFF (check menu)	☐ Manual / paddles, 4th on dyno
☐ A/C, fan, radio off	☐ Windows up, no rattles	☐ Warm engine
☐ OBD logging	☐ Gains locked after LIMIT	☐ Clap at start + end of block

Dyno session

Done	Take	Tier	Target rpm	Load	Gear	Hold	Actual rpm	Keep	Notes
0 Setup Engine off, fans on. Clap.									
☐	NOISE-DYNO	A	0	engine off	-	30 s			Dyno fans running, engine off: noise profile
1 Idle 30 s each.									
☐ ☐	IDLE	A	800	none	N/P	30 s			Warm engine; the 800 point for both ON and OFF layers
2 Level check Set gains to about -6 dBFS peaks, then LOCK them.									
☐	LIMIT	A	limiter	full (WOT)	4	3 s			Hold on limiter max 3 s
3 Reference ramps Slow sweep 1000 → limiter.									
☐ ☐ ☐	RAMP-ON	A	1000→limiter	full (WOT)	4				Slow sweep (~150-300 rpm/s if dyno has sweep mode); A/B reference for the finished bank
4 ON, tier A, low Stabilise, then 8 s hold. Cool down 2-3 min after. Hold on dyno load control; start the 8 s after rpm is stable									
☐ ☐	SS-ON-1000	A	1000	full (WOT)	4	8 s			
☐ ☐	SS-ON-1300	A	1300	full (WOT)	4	8 s			
☐ ☐	SS-ON-1700	A	1700	full (WOT)	4	8 s			
☐ ☐	SS-ON-2150	A	2150	full (WOT)	4	8 s			
☐ ☐	SS-ON-2700	A	2700	full (WOT)	4	8 s			
5 ON, tier A, high Cool down 2-3 min after.									
☐ ☐	SS-ON-3400	A	3400	full (WOT)	4	8 s			Hold on dyno load control; start the 8 s after rpm is stable
☐ ☐	SS-ON-4250	A	4250	full (WOT)	4	8 s			
☐ ☐	SS-ON-5300	A	5300	full (WOT)	4	8 s			
☐ ☐	SS-ON-6500	A	6500	full (WOT)	4	8 s			
☐ ☐	LIMIT	A	limiter	full (WOT)	4	3 s			Hold on limiter max 3 s

6 OFF layer CD-OFF if the dyno can't motor the car. SS-OFF-* only on a motoring dyno.

☐ ☐ ☐ ☐	CD-OFF	A	6500→800	overrun (0%)	5			Coast-down, slowest decel possible; OFF-layer source when dyno can't motor
☐	SS-OFF-1000	A	1000	overrun (0%)	4	8 s		Only if the dyno can MOTOR the car; otherwise use CD-OFF
☐	SS-OFF-1300	A	1300	overrun (0%)	4	8 s		
☐	SS-OFF-1700	A	1700	overrun (0%)	4	8 s		
☐	SS-OFF-2150	A	2150	overrun (0%)	4	8 s		
☐	SS-OFF-2700	A	2700	overrun (0%)	4	8 s		
☐	SS-OFF-3400	A	3400	overrun (0%)	4	8 s		
☐	SS-OFF-4250	A	4250	overrun (0%)	4	8 s		
☐	SS-OFF-5300	A	5300	overrun (0%)	4	8 s		
☐	SS-OFF-6500	A	6500	overrun (0%)	4	8 s		
☐	SS-OFF-900	B	900	overrun (0%)	4	8 s		
☐	SS-OFF-1150	B	1150	overrun (0%)	4	8 s		
☐	SS-OFF-1500	B	1500	overrun (0%)	4	8 s		
☐	SS-OFF-1900	B	1900	overrun (0%)	4	8 s		
☐	SS-OFF-2400	B	2400	overrun (0%)	4	8 s		
☐	SS-OFF-3000	B	3000	overrun (0%)	4	8 s		
☐	SS-OFF-3800	B	3800	overrun (0%)	4	8 s		
☐	SS-OFF-4750	B	4750	overrun (0%)	4	8 s		
☐	SS-OFF-5900	B	5900	overrun (0%)	4	8 s		

7a ON, tier B, low Cool down 2-3 min after. Hold on dyno load control; start the 8 s after rpm is stable

☐ ☐	SS-ON-900	B	900	full (WOT)	4	8 s		
☐ ☐	SS-ON-1150	B	1150	full (WOT)	4	8 s		
☐ ☐	SS-ON-1500	B	1500	full (WOT)	4	8 s		
☐ ☐	SS-ON-1900	B	1900	full (WOT)	4	8 s		
☐ ☐	SS-ON-2400	B	2400	full (WOT)	4	8 s		

7b ON, tier B, high Hold on dyno load control; start the 8 s after rpm is stable

☐ ☐	SS-ON-3000	B	3000	full (WOT)	4	8 s		
☐ ☐	SS-ON-3800	B	3800	full (WOT)	4	8 s		
☐ ☐	SS-ON-4750	B	4750	full (WOT)	4	8 s		
☐ ☐	SS-ON-5900	B	5900	full (WOT)	4	8 s		

8 Optional mid load Part throttle, 6 s holds, one rep. Optional mid-load layer

☐	SS-MID-900	C	900	part (~30-40%)	4	6 s			
☐	SS-MID-1000	C	1000	part (~30-40%)	4	6 s			
☐	SS-MID-1150	C	1150	part (~30-40%)	4	6 s			
☐	SS-MID-1300	C	1300	part (~30-40%)	4	6 s			
☐	SS-MID-1500	C	1500	part (~30-40%)	4	6 s			
☐	SS-MID-1700	C	1700	part (~30-40%)	4	6 s			
☐	SS-MID-1900	C	1900	part (~30-40%)	4	6 s			
☐	SS-MID-2150	C	2150	part (~30-40%)	4	6 s			
☐	SS-MID-2400	C	2400	part (~30-40%)	4	6 s			
☐	SS-MID-2700	C	2700	part (~30-40%)	4	6 s			
☐	SS-MID-3000	C	3000	part (~30-40%)	4	6 s			
☐	SS-MID-3400	C	3400	part (~30-40%)	4	6 s			
☐	SS-MID-3800	C	3800	part (~30-40%)	4	6 s			
☐	SS-MID-4250	C	4250	part (~30-40%)	4	6 s			
☐	SS-MID-4750	C	4750	part (~30-40%)	4	6 s			
☐	SS-MID-5300	C	5300	part (~30-40%)	4	6 s			
☐	SS-MID-5900	C	5900	part (~30-40%)	4	6 s			
☐	SS-MID-6500	C	6500	part (~30-40%)	4	6 s			

Road session

Done	Take	Tier	Target rpm	Load	Gear	Hold	Actual rpm	Keep	Notes
Noise									
☐	NOISE-ROAD	A	0	engine off	-	30 s			Ambient/cabin noise profile, parked
Shifts Reps are per shift.									
☐ ☐ ☐ ☐ ☐	UP-WOT	A	~6000	full (WOT)	1→2				Paddle upshift at WOT
☐ ☐ ☐ ☐ ☐	UP-WOT	A	~6000	full (WOT)	2→3				
☐ ☐ ☐ ☐ ☐	UP-WOT	A	~6000	full (WOT)	3→4				
☐ ☐ ☐ ☐ ☐	UP-PART	B	~3500	part	2→3 3→4				Soft upshift
☐ ☐ ☐ ☐ ☐	DOWN	A	~3000	overrun	4→3				Rev-match blip, if Normal mode does one
☐ ☐ ☐ ☐ ☐	DOWN	A	~3000	overrun	3→2				

Lift-offs POP-N only if you want pops (N mode, ESG still off).									
☐ ☐ ☐ ☐ ☐ ☐	LIFT	A	4000+ then lift	full→0	3			Sharp lift from WOT: diverter-valve whoosh plus any pops	
☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐	POP-N	B	5000+ then lift	full→0	3			Optional: only if you want pops; Normal mode gives few or none	
Whine									
☐ ☐	CRUISE-WHINE	B	~2000-2500	light	6-8	15 s			Steady cruise, then coast; gearbox whine