

Kona N sound capture: shot list

One phone in the cabin (RecForge II) · 48 kHz WAV · Pass A: Normal + ESG off · Pass B: N + ESG ON · file name: <take>_r<rep>.wav · say the take ID out loud, clap, then record · Private road, same direction every run

Date: _____ Location: _____ Recorder(s): _____ Wind / direction: _____

Before every block

☐ Mode + ESG for the pass, checked in menu	☐ Pass name said into recorder	☐ Manual / paddle mode
☐ A/C, fan, radio off	☐ Windows + sunroof closed, no rattles	☐ Warm engine
☐ Dash video on (optional)	☐ Gain locked since gain check	☐ Say take ID + gear, clap, go

Before the passes

Done	Take	Tier	Target rpm	Load	Gear	Hold	Start/end rpm	Keep	Notes
0 Noise Engine off parked; then steady ~80 km/h in top gear, barely on throttle.									
☐	NOISE-PARK	A	0	engine off	-	30 s			Parked, engine off: background noise profile
☐ ☐	NOISE-CRUISE	B	low	lightest	8 (top)	10 s			Steady ~80 km/h in top gear, barely on throttle: wind/tyre noise profile
1 Gain check: N mode + ESG ON Loudest case. Set gain to about -6 dBFS peaks, then LOCK it for the whole day.									
☐	GAIN-CHECK	A	limiter	full (WOT)	2	2 s			Loudest case: set gain to about -6 dBFS peaks, then lock it for both passes
PASS A Normal mode, ESG OFF. Say "pass A" into the recorder.									
Done	Take	Tier	Target rpm	Load	Gear	Hold	Start/end rpm	Keep	Notes
A1 Idle Stationary, gearbox in Neutral/P. Settled idle rpm: _____ (Normal)									
☐ ☐	IDLE	A	idle	none	Neutral/P	30 s			Stationary, warm engine
A2 Limiter Brief hold in 2nd.									
☐ ☐ ☐	LIMIT	A	limiter	full (WOT)	2	2 s			Brief hold, only if manual mode holds the gear
A3 Full-load pulls Gears from the test run: PULL-LO in _____ PULL-HI in _____ (same in both passes). Full pedal, no changes mid-pull.									
☐ ☐ ☐ ☐	PULL-LO	A	1000→4000	full (WOT)	highest that fits				WOT from ~1000 rpm; at least 6 s to reach 4000
☐ ☐ ☐ ☐	PULL-HI	A	3000→limiter	full (WOT)	3 or 4				WOT from ~3000 rpm to the limiter; at least 7-8 s
A4 Coast-downs Lift fully, stay in gear, no brakes until the take ends.									
☐ ☐ ☐ ☐	COAST-HI	A	limiter→1500	overrun (0%)	3 or 4				Lift fully from near the limiter, stay in gear, no brakes
☐ ☐ ☐	COAST-LO	A	3000→1000	overrun (0%)	5 or 6				Lift from ~3000 in a high gear

A5a Part-load holds, tier A 8 s steady. Use 1st/2nd for the high-rpm points. Constant speed so rpm holds steady									
☐ ☐	SS-PART-1000	A	1000	light	low	8 s			
☐ ☐	SS-PART-1300	A	1300	light	low	8 s			
☐ ☐	SS-PART-1700	A	1700	light	low	8 s			
☐ ☐	SS-PART-2150	A	2150	light	low	8 s			
☐ ☐	SS-PART-2700	A	2700	light	low	8 s			
☐ ☐	SS-PART-3400	A	3400	light	low	8 s			
☐ ☐	SS-PART-4250	A	4250	light	low	8 s			
☐ ☐	SS-PART-5300	A	5300	light	low	8 s			
☐ ☐	SS-PART-6500	A	6500	light	low	8 s			
A5b Part-load holds, tier B Constant speed so rpm holds steady									
☐ ☐	SS-PART-900	B	900	light	low	8 s			
☐ ☐	SS-PART-1150	B	1150	light	low	8 s			
☐ ☐	SS-PART-1500	B	1500	light	low	8 s			
☐ ☐	SS-PART-1900	B	1900	light	low	8 s			
☐ ☐	SS-PART-2400	B	2400	light	low	8 s			
☐ ☐	SS-PART-3000	B	3000	light	low	8 s			
☐ ☐	SS-PART-3800	B	3800	light	low	8 s			
☐ ☐	SS-PART-4750	B	4750	light	low	8 s			
☐ ☐	SS-PART-5900	B	5900	light	low	8 s			
A6 Reference									
☐ ☐	PULL-REF	B	1500→limiter	full (WOT)	2				Normal-speed pull; A/B reference for the finished bank
A7 Shifts, lift-offs, whine Shift reps are per shift.									
☐ ☐ ☐ ☐ ☐	UP-WOT	A	~6000	full (WOT)	1→2				Paddle upshift at WOT
☐ ☐ ☐ ☐ ☐	UP-WOT	A	~6000	full (WOT)	2→3				
☐ ☐ ☐ ☐ ☐	UP-WOT	A	~6000	full (WOT)	3→4				
☐ ☐ ☐ ☐ ☐	UP-PART	B	~3500	part	2→3 3→4				Soft upshift
☐ ☐ ☐ ☐ ☐	DOWN	A	~3000	overrun	4→3				Rev-match blip, if Normal mode does one
☐ ☐ ☐ ☐ ☐	DOWN	A	~3000	overrun	3→2				
☐ ☐ ☐ ☐ ☐ ☐	LIFT	A	4000+ then lift	full→0	3				Sharp lift from WOT: diverter-valve whoosh
☐ ☐	CRUISE-WHINE	B	~2000-2500	light	6-8 15 s				Steady cruise, then coast; gearbox whine

PASS B Switch to N mode, ESG ON. Same gears as pass A. Say "pass B" into the recorder.

Done	Take	Tier	Target rpm	Load	Gear	Hold	Start/end rpm	Keep	Notes
B1 Idle Stationary, gearbox in Neutral/P. Settled idle rpm: ____ (N mode)									
☐ ☐	IDLE-N	A	idle	none	Neutral/P	30 s			Stationary, warm engine; N mode idles higher
B2 Limiter Brief hold in 2nd.									
☐ ☐ ☐	LIMIT-N	A	limiter	full (WOT)	2	2 s			Brief hold, only if manual mode holds the gear
B3 Full-load pulls Gears from the test run: PULL-LO in ____ PULL-HI in ____ (same in both passes). Full pedal, no changes mid-pull.									
☐ ☐ ☐ ☐	PULL-LO-N	A	1000→4000	full (WOT)	highest that fits				WOT from ~1000 rpm; at least 6 s to reach 4000
☐ ☐ ☐ ☐	PULL-HI-N	A	3000→limiter	full (WOT)	3 or 4				WOT from ~3000 rpm to the limiter; at least 7-8 s
B4 Coast-downs Lift fully, stay in gear, no brakes until the take ends.									
☐ ☐ ☐ ☐	COAST-HI-N	A	limiter→1500	overrun (0%)	3 or 4				Lift fully from near the limiter, stay in gear, no brakes
☐ ☐ ☐	COAST-LO-N	A	3000→1000	overrun (0%)	5 or 6				Lift from ~3000 in a high gear
B5a Part-load holds, tier A 8 s steady. Use 1st/2nd for the high-rpm points. Constant speed so rpm holds steady									
☐ ☐	SS-PART-1000-N	A	1000	light	low	8 s			
☐ ☐	SS-PART-1300-N	A	1300	light	low	8 s			
☐ ☐	SS-PART-1700-N	A	1700	light	low	8 s			
☐ ☐	SS-PART-2150-N	A	2150	light	low	8 s			
☐ ☐	SS-PART-2700-N	A	2700	light	low	8 s			
☐ ☐	SS-PART-3400-N	A	3400	light	low	8 s			
☐ ☐	SS-PART-4250-N	A	4250	light	low	8 s			
☐ ☐	SS-PART-5300-N	A	5300	light	low	8 s			
☐ ☐	SS-PART-6500-N	A	6500	light	low	8 s			

B5b Part-load holds, tier B Constant speed so rpm holds steady									
☐ ☐	SS-PART-900-N	B	900	light	low	8 s			
☐ ☐	SS-PART-1150-N	B	1150	light	low	8 s			
☐ ☐	SS-PART-1500-N	B	1500	light	low	8 s			
☐ ☐	SS-PART-1900-N	B	1900	light	low	8 s			
☐ ☐	SS-PART-2400-N	B	2400	light	low	8 s			
☐ ☐	SS-PART-3000-N	B	3000	light	low	8 s			
☐ ☐	SS-PART-3800-N	B	3800	light	low	8 s			
☐ ☐	SS-PART-4750-N	B	4750	light	low	8 s			
☐ ☐	SS-PART-5900-N	B	5900	light	low	8 s			
B6 Reference									
☐ ☐	PULL-REF-N	B	1500→limiter	full (WOT)	2				Normal-speed pull; A/B reference for the finished bank
B7 Shifts and lift-offs Shift reps are per shift. LIFT-N: stay off the throttle 3 s after lifting, for pops.									
☐ ☐ ☐ ☐ ☐	UP-WOT-N	A	~6000	full (WOT)	1→2				Paddle upshift at WOT: spark-cut crack
☐ ☐ ☐ ☐ ☐	UP-WOT-N	A	~6000	full (WOT)	2→3				
☐ ☐ ☐ ☐ ☐	UP-WOT-N	A	~6000	full (WOT)	3→4				
☐ ☐ ☐ ☐ ☐	DOWN-N	A	~3000	overrun	4→3				Rev-match blip
☐ ☐ ☐ ☐ ☐	DOWN-N	A	~3000	overrun	3→2				
☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐	LIFT-N	A	5000+ then lift	full→0	3				Sharp lift from WOT, stay off 3 s: pops and crackles