

Kona N sound capture: shot list

Cabin-only (CAB + optional FWL footwell) · 48 kHz / 24-bit WAV · file name: <take>_r<rep>_<channel>.wav · say the take ID out loud, clap, then record · Private road, same direction every run

Date: _____ Location: _____ Recorder(s): _____ Wind / direction: _____

Before every block

☐ Normal drive mode	☐ ESG OFF (check menu)	☐ Manual / paddle mode
☐ A/C, fan, radio off	☐ Windows + sunroof closed, no rattles	☐ Warm engine
☐ OBD logging	☐ Gains locked after LIMIT	☐ Say take ID, clap, blip, go

Run order

Done	Take	Tier	Target rpm	Load	Gear	Hold	Start/end rpm	Keep	Notes
0 Noise Engine off parked; then rolling in neutral at ~80 km/h, only if safe.									
☐	NOISE-PARK	A	0	engine off	-	30 s			Parked, engine off: background noise profile
☐ ☐	NOISE-ROLL	B	0 (idle)	none	N while rolling	10 s			Coast in neutral at ~80 km/h, engine idling: wind/tyre noise profile for cleanup
1 Idle 30 s each, stationary.									
☐ ☐	IDLE	A	800	none	N/P	30 s			Stationary, warm engine; the 800 point for every layer
2 Level check First take sets gains to about -6 dBFS peaks, then LOCK them.									
☐ ☐ ☐	LIMIT	A	limiter	full (WOT)	2	2 s			Brief hold on the limiter, only if manual mode holds the gear. First take sets gains
3 Full-load pulls Gears from the test run: PULL-LO in __ PULL-HI in __. Full pedal, no changes mid-pull, <= 500 rpm/s.									
☐ ☐ ☐ ☐	PULL-LO	A	1000→4000	full (WOT)	highest that fits				WOT from ~1000 rpm in the highest gear the road allows; aim for <= 500 rpm/s
☐ ☐ ☐ ☐	PULL-HI	A	3000→limiter	full (WOT)	3 or 4				WOT from ~3000 rpm to the limiter in the highest gear that reaches it in your road length
4 Coast-downs Lift fully, stay in gear, no brakes until the take ends.									
☐ ☐ ☐ ☐	COAST-HI	A	limiter→1500	overrun (0%)	3 or 4				Lift fully from near the limiter, stay in gear, no brakes
☐ ☐ ☐	COAST-LO	A	3000→1000	overrun (0%)	5 or 6				Lift from ~3000 in a high gear; slow decel covers the low rpm points

5a Part-load holds, tier A 8 s steady. Use 1st/2nd for the high-rpm points. Constant speed so rpm holds steady									
☐ ☐	SS-PART-1000	A	1000	light	low	8 s			
☐ ☐	SS-PART-1300	A	1300	light	low	8 s			
☐ ☐	SS-PART-1700	A	1700	light	low	8 s			
☐ ☐	SS-PART-2150	A	2150	light	low	8 s			
☐ ☐	SS-PART-2700	A	2700	light	low	8 s			
☐ ☐	SS-PART-3400	A	3400	light	low	8 s			
☐ ☐	SS-PART-4250	A	4250	light	low	8 s			
☐ ☐	SS-PART-5300	A	5300	light	low	8 s			
☐ ☐	SS-PART-6500	A	6500	light	low	8 s			
5b Part-load holds, tier B Constant speed so rpm holds steady									
☐ ☐	SS-PART-900	B	900	light	low	8 s			
☐ ☐	SS-PART-1150	B	1150	light	low	8 s			
☐ ☐	SS-PART-1500	B	1500	light	low	8 s			
☐ ☐	SS-PART-1900	B	1900	light	low	8 s			
☐ ☐	SS-PART-2400	B	2400	light	low	8 s			
☐ ☐	SS-PART-3000	B	3000	light	low	8 s			
☐ ☐	SS-PART-3800	B	3800	light	low	8 s			
☐ ☐	SS-PART-4750	B	4750	light	low	8 s			
☐ ☐	SS-PART-5900	B	5900	light	low	8 s			
6 Reference									
☐ ☐	PULL-REF	B	1500→limiter	full (WOT)	2				Normal-speed pull; A/B reference for the finished bank
7 Shifts Reps are per shift.									
☐ ☐ ☐ ☐ ☐	UP-WOT	A	~6000	full (WOT)	1→2				Paddle upshift at WOT
☐ ☐ ☐ ☐ ☐	UP-WOT	A	~6000	full (WOT)	2→3				
☐ ☐ ☐ ☐ ☐	UP-WOT	A	~6000	full (WOT)	3→4				
☐ ☐ ☐ ☐ ☐	UP-PART	B	~3500	part	2→3 3→4				Soft upshift
☐ ☐ ☐ ☐ ☐	DOWN	A	~3000	overrun	4→3				Rev-match blip, if Normal mode does one
☐ ☐ ☐ ☐ ☐	DOWN	A	~3000	overrun	3→2				

8 Lift-offs POP-N only if you want pops (N mode, ESG still off).

☐ ☐ ☐ ☐ ☐ ☐	LIFT	A	4000+ then lift	full→0	3			Sharp lift from WOT: diverter-valve whoosh plus any pops
☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐	POP-N	B	5000+ then lift	full→0	3			Optional: only if you want pops; Normal mode gives few or none

9 Whine

☐ ☐	CRUISE-WHINE	B	~2000-2500	light	6-8	15 s		Steady cruise, then coast; gearbox whine
---	---------------------	---	------------	-------	-----	------	--	--