

## **EloPOS™ Pack**

Windows Compute Engine for Point-of-Sale Applications





**Connectivity-Rich** 



**Compact Form-Factor** 



## **Product Overview**

The EloPOS Pack delivers a powerful enterprise-ready compute platform in a sleek, compact form factor. Backed by the security and infrastructure of a Windows-based system and the speed of the Intel Q370 Chipset, the EloPOS Pack provides the power you need to run your business. With versatile connectivity options, plug in anything from Elo's latest monitor via single cable USB-C to a legacy printer requiring a 12V powered-USB. The system provides flexibility to make upgrades as your business requirements change.

Whether you want Windows 10 or a no-OS model to run Linux, the enterprise-ready EloPOS Pack provides the freedom to adapt to your infrastructure. To get you up and running quicker, the no-OS models have been pretested with Linux SuSE, Ubuntu and Red Hat operating systems.

i3 & i5 Models Offer: TPM 2.0, Intel AMT, Intel Standard Manageability & Intel vPro

Well suited for Self-Service, Point-of-Sale and Industrial Automation applications

Secure Mounting - Easily secure the EloPOS Pack to any counter in a snap. For added security, you can use the Kensington locks.

## **EloPOS Pack**

|                             |  |  | Intel Core i5-9500TE (9M Smart  | Intel Core i7-9700TE (12M Smart   |  |  |
|-----------------------------|--|--|---|---|--|--|
| Processor                   | Intel® Celeron® G4900T (2M<br>Cache, up to 2.9 GHz)  | Intel Core i3-9100TE (6M Cache,<br>up to 3.20 GHz) | Cache, up to 3.60 GHz by Intel<br>Turbo Boost Technology 2.0) Intel<br>vPro Support | Cache, up to 3.80 GHz by Intel®<br>Turbo Boost Technology 2.0) Inte<br>vPro Support |  |  |
| Chipset                     | Intel Q370 Express   |  |   |   |  |  |
| Video                       | Intel UHD Graphics 610   | Intel UHD Graphics 610 Intel UHD Graphics 630      |   |   |  |  |
| BIOS                        | AMI  |  |   |   |  |  |
| Storage                     | 128GB M.2 SATA SSD, 72 TBW (GB equals one billion bytes when referring to storage capacity. Accessible capacity may be less.)  |  |   |   |  |  |
| Memory                      | 4GB 2133MHz DDR4 SO-DIMM on 1 of 4 slots (Expandable to 64GB maximum on 4 slots)  8GB 2133MHz DDR4 SO-DIMM on 1 of 4 slots (Expandable to 64GB maximum on 4 slots)   |  |   |   |  |  |
|                             | Maximum memory using 4 slots. Expandable up to 64GB maximum, SO-DIMM DDR4-2133. Check brand of the memory included in your unit before purchasing the memory kit.  |  |   |   |  |  |
| Operating Systems Supported | No Operating System Microsoft Windows 10 IoT Enterprise LTSC 64-bit  |  |   |   |  |  |
| Languages                   | Windows 10 - 36 Language groups  |  |   |   |  |  |
| Control Buttons             | Power  |  |   |   |  |  |
| I/O Ports                   | 1 x HDMI port, 1 x LAN RJ45 (Gigabit), 1 x 24V and 5 x 12V powered USB, 1 x RJ50, 12V/24V Cash Drawer Port on I/O (EPSON Pinout, 24V default; selectable by internal swtich), 1 x Full-function USB-C (Power up to 27W, USB 3.0, Display Port), 1 x 3.5 mm headset jack  |  |   |   |  |  |
| Wireless                    | 802.11 a/b/g/n/ac 2.4GHz and 5GHz  |  |   |   |  |  |
| Antenna                     | 2T2R design with External SMA connector  |  |   |   |  |  |
| Bluetooth                   | Bluetooth 5.0  |  |   |   |  |  |
| TPM                         | TPM 2.0  |  |   |   |  |  |
| AMT                         | Active Management Technology (Intel AMT 11.0) Support.   |  |   |   |  |  |
| Real Time Clock             | Replaceable CR2032 lithium metal battery for clock   |  |   |   |  |  |
| Power Supply                | External 24VDC universal-type power supply brick, AC input voltage: 100-240 VAC, Input frequency: 50-60 Hz, Maximum output power: 180W   |  |   |   |  |  |
| Power Consumption           | 32.415W  | 48.87W   | 55.34W  | 65W   |  |  |
| Mounting Options            | Bracket mounts to table with screws, System slides forward to engage hooks on bracket  |  |   |   |  |  |
| Other Features              | Serviceable internal components. Kensington Mano Security Slot. Kensington lock slot (Standard Size).  |  |   |   |  |  |
| Upgrade Options             | 256GB M.2 SATA SSD - Elo P/N: E206556, E762128, E503575; 512GB M.2 SATA SSD - Elo P/N: E865041; 4GB DDR4 SO-DIMM - Elo P/N: E275416, E951667, E952623, E952056; 8GB DDR4 SO-DIMM - Elo P/N: E275635, E951857, E952813, E952252; 16GB DDR4 SO-DIMM - Elo P/N: E953014, E952437  |  |   |   |  |  |
| Dimensions                  | 10.9" x 1.4" x 9.4" / 276 mm x 37 mm x 237.5 mm  |  |   |   |  |  |
| Shipping Box Dimensions     | 16.3" x 6.7" x 13.6" / 414 mm x 169 mm x 346 mm  |  |   |   |  |  |
| Weight                      | Unpackaged: 5.76 lbs / 2.6 kg; Packaged: 11.02 lbs / 5.0 kg  |  |   |   |  |  |
| Temperature                 | Operating: 0°C to 40°C (32°F to 104°F); Storage: -20°C to 60°C (-4°F to 140°F)   |  |   |   |  |  |
| Humidity (non-condensing)   | Operating: 10% to 90%; Storage: 0% to 95% (38.7°C max wet bulb temperature)  |  |   |   |  |  |
| Agency Approvals            | UL/cUL, FCC, TUV, CE, CB, Mexico NOM, C-Tick/RCM, VCCI, Argentina S-Mark, CCC, UKCA  |  |   |   |  |  |
| Compliance                  | Energy Star 8.0 for i3 and i5 models   |  |   |   |  |  |
| Warranty                    | 3 years  |  |   |   |  |  |
| Extended Warranty           | 4 year coverage - Elo P/N: E819598 ; 5 year coverage - Elo P/N: E819795 3 year coverage + AUR - Elo P/N: E820186; 4 year coverage + AUR - Elo P/N: E820388; 5 year coverage + AUR - Elo P/N: E820582   |  |   |   |  |  |
| MTBF                        | 50,000 hours demonstrated  |  |   |   |  |  |
| What's in the box           | EloPOS Pack, North America Power Cord (1800+/-50mm), (6 ft +/- 1 inch), EU Power Cord (1800+/-50mm), Power Adapter – 180W, Cable RJ-50 to DB-9 (900+/-30mm), (3 ft +/- 1 inch), USB Type-C cable (1800+/-50mm), (6 ft +/- 1 inch), HDMI cable (1800+/-50mm), (6 ft +/- 1 inch), USB cable (1800+/-50mm), (6 ft +/- 1 inch), 2x SMA Antenna, Quick Installation Guide (QIG) |  |   |   |  |  |

## **Ordering Information**

| Part Numbers | OS         | Processor | Storage   | Memory (RAM) |
|--------------|------------|-----------|-----------|--------------|
| E943670      | Windows 10 | G4900T    | 128GB SSD | 4GB RAM      |
| E923382      | Windows 10 | G4900T    | 128GB SSD | 8GB RAM      |
| E944068      | Windows 10 | i3-9100TE | 128GB SSD | 8GB RAM      |
| E945053      | Windows 10 | i5-9500TE | 128GB SSD | 8GB RAM      |
| E102709      | Windows 10 | i5-9500TE | 256GB SSD | 8GB RAM      |
| E981371      | Windows 10 | i5-9500TE | 256GB SSD | 16GB RAM     |
| E496697      | Windows 10 | i5-9500TE | 256GB SSD | 32GB RAM     |
| E943471      | No OS      | G4900T    | 128GB SSD | 4GB RAM      |
| E930351      | No OS      | G4900T    | 128GB SSD | 8GB RAM      |
| E943864      | No OS      | i3-9100TE | 128GB SSD | 8GB RAM      |
| E948191      | No OS      | i3-9100TE | 128GB SSD | 16GB RAM     |
| E944853      | No OS      | i5-9500TE | 128GB SSD | 8GB RAM      |
| E945259      | No OS      | i5-9500TE | 512GB SSD | 8GB RAM      |
| E948397      | No OS      | i5-9500TE | 128GB SSD | 16GB RAM     |
| E511521      | No OS      | i5-9500TE | 256GB SSD | 32GB RAM     |
| E511713      | No OS      | i5-9700TE | 256GB SSD | 32GB RAM     |

Learn more about Elo at **EloTouch.com**.

 Americas
 Europe (EMEA)
 Asia Pacific

 Tel +1 408 597 8000
 Tel +32 16 930 136
 Tel +86 (21) 3329 1385

 elosales.na@elotouch.com
 EMEA.Sales@elotouch.com
 www.elotouch.com.cn

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and EloPOS are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners.

© 2022 Elo Touch Solutions, Inc. All rights reserved. 22052AES00133

