

### Material Specifications:

**Body/Shells:** 304/L Stainless Steel  
**Flange:** 304/L Stainless Steel or Epoxy Coated Carbon Steel  
**Gaskets:** ANSI/NSF/CAN 61 Approved NBR  
**Test Port:** ¾ Inch NPT Welded Type 304/L Stainless Steel Test Port with ¾ Inch Lead Free Red Brass Per ASTM B584 Pipe Plug Installed.

**Bolts:**

Oval Neck Track head per ANSI/ASME B18.10  
5/8-11 UNC Rolled Thread  
Type 304/L Stainless Steel per ASTM A-193 Grade B8  
Finish: Double Fluoropolymer coating. Bolts installable in either direction

**Nuts:**

Heavy Hex Nut 5/8-11 UNC Rolled Thread per ASME B18.2.2  
Type 304/L Stainless Steel per ASTM A-194 Grade 8  
Finish: Double Fluoropolymer coated to prevent galling & retain torque

**Washers:**

Heavy Duty 5/8 Inch Washer  
Material 18-8 Type 304 Stainless Steel  
Double Fluoropolymer coated to prevent galling & retain torque

**Notes:**

316/L Stainless options available upon request.  
316 Bolts to have a bare electropolish finish.  
316 Nuts and Washers to be fluoropolymer coated


**NOTE: PRODUCT CAN BE PROVIDED TO BE AIS COMPLIANT (DOMESTIC MATERIAL). PLEASE CONTACT TPS CUSTOMER SERVICE FOR PART NUMBERS, PRICING, AND LEAD TIME**

THE INFORMATION DISCLOSED IN THIS DOCUMENT, INCLUDING ALL DESIGNS AND RELATED MATERIALS, IS THE VALUABLE PROPERTY OF DRESSER WATER, LLC (DW). DW RESERVES ALL PATENT, COPYRIGHT, AND PROPRIETARY RIGHTS TO THE INFORMATION SET FORTH IN THIS DOCUMENT INCLUDING ALL DESIGN, MANUFACTURING, REPRODUCTION, USE AND SALES RIGHTS THERETO, EXCEPT TO THE EXTENT SAID RIGHTS ARE EXPRESSLY GRANTED TO OTHERS. REPRODUCTION, TRANSMISSION, OR DISCLOSURE, WITHOUT DW'S EXPRESS PRIOR WRITTEN CONSENT, OF THIS DOCUMENT OR THE INFORMATION SET FORTH IN THIS DOCUMENT TO ANY THIRD PARTY IS PROHIBITED.

Triple Tap Tapping Sleeve for 4-12" Nominal Pipe Sizes				
OUTLET SIZE	WIDTH	FLANGE HEIGHT	BOLT QTY	BOLT SIZE
3 or 4	15	5.25	8	5/8"-11
6	15	5.25	8	5/8"-11
8	20	5.25	10	5/8"-11
10	25	5.25	14	5/8"-11
12	25	5.375	14	5/8"-11
Triple Tap Tapping Sleeve for 14-16" Nominal Pipe Sizes				
OUTLET SIZE	WIDTH	FLANGE HEIGHT	BOLT QTY	BOLT SIZE
3 or 4	15	5.25	10	5/8"-11
6	15	5.25	10	5/8"-11
8	20	5.25	14	5/8"-11
10	25	5.25	18	5/8"-11
12	25	5.375	18	5/8"-11
14 or 16	32	5.375	22	5/8"-11
Triple Tap Tapping Sleeve for 18"-30" Nominal Pipe Sizes				
OUTLET SIZE	WIDTH	FLANGE HEIGHT	BOLT QTY	BOLT SIZE
3 or 4	25	5.25	18	5/8"-11
6	25	5.25	18	5/8"-11
8	25	5.25	18	5/8"-11
10	25	5.25	18	5/8"-11
12	25	5.375	18	5/8"-11
14 or 16	32	5.375	22	5/8"-11

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN INCHES.  
TOLERANCES ARE:  
FRACTIONS:  $\pm 1/16"$       ANGLE:  $\pm 1^\circ$   
DECIMALS: .XX  $\pm .02$   
              .XXX  $\pm .005$   
DO NOT SCALE DRAWING

### THIRD ANGLE PROJECTION



CONTRACT NO.
--------------

APPROVALS	DATE
DRAWN: RJF	06/12/18
CHECKED: G	

APPD

**DRESSER WATER, LLC**  
P.O. BOX 586, OLEAN, N.Y. 14760

TITLE	<b>Triple Tap Tapping Sleeve Submittal</b>
-------	--

SIZE <b>C</b>	CAGE CODE	DWG NO <b>60516</b>	REV <b>D3</b>
SCALE 1:8	WEIGHT	SHEET 1 OF 1	