

Programming assignment 4.

Due date: Sunday, November 1 2020 at 11:59pm

.....

Implement a function to find the K elements of a given array that are closest to the median. (**Hint**: You could use Quick_Select to find the answer!)

1. Request the user to enter a positive integer, and call it n .
2. Generate n random integers between -100 to 100 and save them in a .
3. Print the generated array.
4. Request the user to enter a number between 1 to n , and call it K .
5. Find the median of the array. (**Hint**: The time complexity in this step is $O(n)$.)
6. Save the differences from the median ($a[i]$ -median) in a new array and call it **diff**. (**Question**: What is the time complexity in this stage?)
7. Use **diff** to find the K closest numbers.

(**Hint Important**:

✚ The K closet elements have the K smallest absolute difference from the median.

✚ Could you modify in your **if/while statements** of your partitioning step in your QuickSelect? Maybe using absolute values? What is the time complexity in this step?)

8. Shift the found K numbers back to their original value (+median). (**Question**: What is the time complexity in this step?)
9. Print the answer 😊
10. Calculate the total time complexity of your algorithm and present your answer when demoing.

Example 1: Input: $a = [10, 4, 2, 15, 18]$, $K = 2$

Output: 4, 15

Example 2: Input: $a = [25, 3, 1, 8, 7, 2, 32]$, $K = 4$

Output: 1, 2, 3, 8