My title

My name

October 28, 2026

1 Introduction

In this study we will investigate how to use R packages such as mice and miclust to apply statistical tools for missing data. Our goal is to generate clusters to analyze and visualize our dataset. This dataset is a subset of the variables studied in the original paper by Basagaña et al.CITA AQUI

2 Analysis

2.1 Description of missingness

```
n_participants <- nrow(copd)
n_variables <- ncol(copd)
missing_per_variable <- colMeans(is.na(copd)) * 100

min_missing <- sprintf("%.1f", min(missing_per_variable))
max_missing <- sprintf("%.1f", max(missing_per_variable))

pct_variables_lt5 <- sprintf("%.1f", mean(missing_per_variable < 5) * 100) # mean
# calcula la proporció de true
# equivalent: AA <- sprintf("%.1f", sum((missing_per_variable < 5))/n_variables * 100)
# true=1, false=0

pct_complete_cases <- sprintf("%.1f", mean(complete.cases(copd)) * 100)
pct_missing_total <- sprintf("%.1f", mean(is.na(as.matrix(copd))) * 100)

total_cells <- prettyNum(n_participants * n_variables, big.mark=",") # n_participants
                                                    # * n_variables = total_cells
```

The subset used here included 342 participants and 45 variables. The range of missing data in the different variables went from 0.0% to 31.6%, with 68.9% of the variables having less than 5% of the data missing. Only 33.3% of the participants had complete data on all 45 variables. Overall, 5.4% of the information was missing; that is, 5.4% of the total of 15,390 cells (45 x 342 = 15,390) had missing data.

2.2 Multiple imputation

Apply multiple imputation to copd data using 100 imputations. Explain in a reasoned manner how you decided to set the values of the arguments method and predictorMatrix when using the mice() function. Show your code

```
ini <- mice(copd, maxit = 0)

meth <- ini$method
pred <- ini$predictorMatrix

meth["id"] <- "" # do not impute "id"
pred["id", ] <- 0 # we don't want "id" to be imputed
```

```r
pred[, "id"] <- 0 # we don't want "id" to be predictor

# Fem les 100 imputacions:
imp <- mice(copd, method = meth, predictorMatrix = pred, m = 100,
            printFlag = FALSE, seed = 123)
```

We've kept using the same methodology and the prediction matrix, with the exception of id as it isn't relevant for this process. The variable 'm' encodes de number of imputations, 'printFlag' is used to show the current imputation although it's not important for the results, and the 'seed' is set up for replicability.

2.3 Integration of multiple imputation in cluster analysis

Reproduce the original analysis in the paper using the miclust package to integrate multiple imputation in the cluster analysis. Apply the proposed framework using the same setting than in the original analysis.

To do that, follow these steps:

1. Read the help of the getdata() function in the miclust package. Then, accordingly, create a list of data.frames and pass it to the getdata() function. Give a detailed explanation of the data processing you did to get that list. Show your code.

```r
resultat_mice <- complete(imp, action = "all", include = TRUE)
# action = "all" ja em posa les dades incials com a primer element

categoriques <- c(
  "sin11_v1", "iam_chv1", "sin15_v1", "sin7_v1", "sin8_v1",
  "cccs1_v0", "vtit_catv1", "urg_ambv0", "sin5_v1",
  "sin6_v1", "graudisn_v1"
)

resultat_mice <- lapply(resultat_mice, function(d) {
  d$id <- NULL
  d[categoriques] <- lapply(d[categoriques], function(x)
    as.numeric(as.character(x)))
  d
})

miclustdata <- getdata(resultat_mice) # adapta les dades al format de miclust
```

As 'getdata()' necessitates a list of dataframes, where the first element has the initial data and the imputations are stored in the subsequent elements, we call the 'complete' function that returns the needed information when using "action=all" and "include=TRUE". Furthermore, we must adapt the categorical variables to numerical values. Thus we define a function that transforms the values stored in text into numbers and using the 'lapply()' function, we reach our goal: the list of dataframes that 'getdata()' needs.

2. Use the miclust() function to perform the integration of missing data in cluster analysis using the same settings as in the original analysis. Show your code and explain how and why you set all arguments in the miclust() function.

```r
# Segon apartat:
copd_miclustdata <- miclust(data = miclustdata,search = "backward",
                            ks = 2:3,
                            distance = "manhattan",
                            centpos = "means",
                            initcl = "hc",
                            verbose = TRUE,
                            seed = 123)

## . . . . imp   5 . . . . imp  10 . . . . imp  15 . . . . imp  20
```

```
## . . . . imp  25 . . . . imp  30 . . . . imp  35 . . . . imp  40
## . . . . imp  45 . . . . imp  50 . . . . imp  55 . . . . imp  60
## . . . . imp  65 . . . . imp  70 . . . . imp  75 . . . . imp  80
## . . . . imp  85 . . . . imp  90 . . . . imp  95 . . . . imp 100
##
##  Analysis done.
```

The chosen elements have been: 'backward', because we were instructed to during class; 'ks = 2:3', as the paper itself led us to believe that a high number of clusters would lead to inaccurate results; 'manhattan', the default option; 'means', as we are using the k-means algorithm; 'hc', we decided on a jerarquical inicialitzation over a random one for better results; 'verbose = TRUE', so show the progress of this long process; 'seed=123' for replicability.

3 Results

Using plot() and summary() methods in the miclust package, provide plots1 and tables for the results similar than those shown in the original paper. Also, show a barplot for the percentage of times each variable is selected among the imputed data sets, in decreasing order2. Explain how you set all arguments in all functions and methods you use. Show your code.

```
plot(copd_miclustdata, metric="nclfreq", col.nclfreq = "blue")
```




Figure 1: Number of clusters frequency

```
plot(copd_miclustdata, metric="critcf", col.critcf = "orange")
```




Figure 2: CritCF value versus number of clusters

```
plot(copd_miclustdata, metric="nvarfreq", col.nvarfreq = "forestgreen")
```




Figure 3: Frequency of the number of times each variable being selected furing multiple imputation

```
plot(copd_miclustdata, metric="varsel", col.varsel = "gray")
```




Figure 4: Frequency of each variable being selected during multiple imputation

We only needed to define the colors to show the plots.

```r
res2 <- summary(copd_miclustdata, k = 2, quantilevars = 0.5)
res3 <- summary(copd_miclustdata, k = 3, quantilevars = 0.5)

resum_prob <- rbind(res2$allocationprobabilities, res3$allocationprobabilities)

rownames(resum_prob) <- c("k = 2, Cluster 1",
                          "k = 2, Cluster 2",
                          "k = 3, Cluster 1",
                          "k = 3, Cluster 2",
                          "k = 3, Cluster 3")

modtable <- xtable(resum_prob,
                   digits = c(0, 3, 3, 3, 3, 3),
                   caption = "Distribution of the Frequencies of Assignment
                   (Proportions) for Each Cluster (for k = 2 and k = 3)",
                   label = "tab:frequency")
# cosmetics for table head (LaTeX slash (\) must be doubled inside a R chunk):
colnames(modtable) <- c("\\multicolumn{1}{c}{\\bf Minimum}",
                        "\\multicolumn{1}{c}{\\bf First Quartile}",
                        "\\multicolumn{1}{c}{\\bf Median}",
                        "\\multicolumn{1}{c}{\\bf Third Quartile}",
                        "\\multicolumn{1}{c}{\\bf Maximum}")

# format and print the table:
print(modtable,
      table.placement = "ht",
      size = "footnotesize",
      include.rownames = TRUE,
      include.colnames = TRUE,
      floating = TRUE,                  # whether \begin{table}
      # should be created (TRUE) or not (FALSE)
      # important to treat content
      # of columns as latex function
      sanitize.text.function = force)
```

	Minimum	First Quartile	Median	Third Quartile	Maximum
k = 2, Cluster 1	0.520	1.000	1.000	1.000	1.000
k = 2, Cluster 2	0.540	1.000	1.000	1.000	1.000
k = 3, Cluster 1	0.600	1.000	1.000	1.000	1.000
k = 3, Cluster 2	0.500	1.000	1.000	1.000	1.000
k = 3, Cluster 3	0.540	1.000	1.000	1.000	1.000

Table 1: Distribution of the Frequencies of Assignment (Proportions) for Each Cluster (for k = 2 and k = 3)

Answer: To create the first table we use the 'summary()' function for the differnet k-values, and using a template provided by the professor, we show the desired results.

```r
descr <- as.data.frame(res2$summarybycluster)

taula3 <- data.frame(Variable = gsub("_", "\\_", rownames(descr)),
                     Missing = as.numeric(descr[["%miss."]]),
                     Cluster1 = as.numeric(descr[["mean (cl.1)"]]),
                     Cluster2 = as.numeric(descr[["mean (cl.2)"]]),
                     check.names = FALSE
)

n <- res2$clusterssize[, "50%"] # Valor del nombre medià dels clusters
```

```r
modtable <- xtable(taula3,
                   digits = c(0, 0, 2, 2, 2),
                   caption = "Description of the Variables (Mean Values) by Cluster",
                   label = "tab:descr")
# cosmetics for table head (LaTeX slash (\) must be doubled inside a R chunk):
colnames(modtable) <- c("\\multicolumn{1}{c}{\\bf Variable}",
                        "\\multicolumn{1}{c}{\\bf \\% of Subjects With Missing Values}",
                        paste0("\\multicolumn{1}{c}{\\bf Cluster 1 (n = ", n[1], ")}"),
                        #paste0 per a ajuntar strings
                        paste0("\\multicolumn{1}{c}{\\bf Cluster 2 (n = ", n[2], ")}"))

# format and print the table:
print(modtable,
      table.placement = "ht",
      size = "footnotesize",
      include.rownames = FALSE,
      include.colnames = TRUE,
      # whether \begin{table} should be created (TRUE) or not (FALSE)
      floating = TRUE,
      # important to treat content of columns as latex function
      sanitize.text.function = force)
```

Variable	% of Subjects With Missing Values	Cluster 1 (n = 186)	Cluster 2 (n = 156)
activityv1	1.17	35.80	60.79
fevp_postv1	0.00	62.74	39.12
fvcp_postv1	0.00	79.93	63.65
iam_chv1	0.88	0.12	0.08
ic_prepv1	5.56	72.84	52.43
quo_calcpostv1	0.00	58.83	45.89
rv_prepv1	7.89	138.51	184.77
rv_tlcv1	7.89	50.89	63.19
sin15_v1	1.17	0.09	0.09
vas2_v1	1.17	4.18	6.49
vc_prepv1	5.56	77.48	60.45
impactsv1	1.17	18.61	35.81
po2_v1	3.22	77.39	69.67
graudisn_v1	1.17	1.91	3.27
vas1_v1	1.17	2.00	3.98
cccs1_v0	1.46	0.15	0.18
index_barthel2v1	2.63	100.00	98.15

Table 2: Description of the Variables (Mean Values) by Cluster

We haven't included the 'F values' in the second table, nor used the unprocessed data for the average-value analisys, but we have decided to show other results from the 'summary()' function, those we considered relevant to the imputated data. To do this, an auxiliary dataframa of the 'summary' was needed. Furthermore, we obtained the mean valur of the clusters just like the original paper did.

4 Report

5 Use of artificial intelligence