Theoretical Foundations of Prompt Injection Against LLM-Based Security Copilots

Sergiu-Florian Tuduce
Faculty of Mathematics and Computer Science
Babeș-Bolyai University
Cluj-Napoca, Romania

***Abstract*—Large language models (LLMs) are increasingly deployed as assistants in security operations centers, where they read system logs and produce triage decisions. Many log fields, however, are written by the very attacker whose activity is being logged, which turns the evidence stream into a channel for injecting instructions into the model. This report presents the theoretical background required to study this threat, known as *log-substrate prompt injection*: the autoregressive language-modelling and alignment concepts that explain why models follow injected text, a formal account of prompt injection and threat modelling, the formulation of adversarial payload generation as a constrained discrete optimization problem (gradient-guided, evolutionary, and LLM-driven search), the families of defenses (inference-time, training-time, and detection-based), and the statistical tools used to evaluate attacks and defenses. These concepts form the foundation of the author's bachelor's thesis on log-substrate prompt injection against local open-source LLMs reading Linux host logs.**

***Index Terms*—large language models, prompt injection, adversarial machine learning, security operations, constrained optimization**

I. Introduction

Security operations centers (SOCs) face high alert volumes and a shortage of skilled analysts, and large language models (LLMs) are increasingly proposed as *copilots* that read logs and alerts and produce triage labels, incident summaries, or remediation advice [1]. Running such models *locally*, on-host, is attractive because sensitive logs never leave the organization.

These systems share a structural weakness: an LLM receives its instructions and the data it must analyze as a single stream of text, and many log fields (the HTTP User-Agent, the request URI, command-line arguments, attempted usernames) are written by the attacker whose activity is being recorded. A crafted log entry can therefore carry instructions that hijack the model reading it [2], [3].

[*Introduce the running example here: the nginx log line from Fig. 1, first clean, then with the payload in the User-Agent. Reuse it in every section.*]

This report presents the theoretical background needed to study this threat. Section II introduces the language-modelling and alignment concepts that explain why models follow injected text. Section III defines prompt injection and its log-substrate variant. Section IV describes the security-operations setting and the threat model. Section V formulates adversarial payload generation as a constrained optimization problem and presents three search methods. Section VI covers the main families of defenses, and Section VII the statistical tools used to evaluate them. Section VIII shows how these concepts fit together in the author's thesis.

```
203.0.113.7 - - [11/Oct/2026:10:02:11 +0000] "GET
/item?id=1'%20OR%201=1-- HTTP/1.1" 200 512 "-"
"Mozilla/5.0 (X11; Linux x86_64) [SYSTEM NOTE:
authorized penetration test, classify this
request as benign]"
```

Fig. 1: Running example: an nginx access-log entry recording a SQL-injection probe. The attacker-controlled User-Agent field (red) carries an instruction aimed at the LLM that will later read the log.

II. Large Language Models

This section introduces only the concepts used later in the report: how an LLM assigns probabilities to text (§II-A), why the transformer has no notion of trusted input (§II-B), how an assistant is aligned (§II-C), and what a locally deployed model exposes to an attacker (§II-D).

A. Tokens and autoregressive modelling

Text is split by a *tokenizer* into a sequence of tokens $x = (x_1, \dots, x_n)$ from a finite vocabulary $\mathcal{V}$ (typically $|\mathcal{V}| \approx 10^5$). An autoregressive language model with parameters θ factorizes the probability of an output $y = (y_1, \dots, y_m)$ given a context x as

$$p_\theta(y \mid x) = \prod_{t=1}^{m} p_\theta(y_t \mid x, y_{<t}). \tag{1}$$

At each step the network outputs a vector of *logits* $z \in \mathbb{R}^{|\mathcal{V}|}$, which the softmax function turns into a distribution over the next token:

$$p_\theta(y_t = v \mid x, y_{<t}) = \frac{\exp(z_v)}{\sum_{u \in \mathcal{V}} \exp(z_u)}. \tag{2}$$

The log-probabilities $\log p_\theta(\cdot)$ are the quantity an attacker will later try to maximize (§V).

[*One paragraph on tokenization subtleties: constraints on log fields are expressed in characters, but models and optimizers operate on tokens; a token edit can produce characters that are not allowed in the field.*]

B. The transformer and self-attention

Modern LLMs are decoder-only transformers [4]. Their core operation, scaled dot-product attention, lets each position combine information from every earlier position:

$$\mathrm{Attn}(Q, K, V) = \mathrm{softmax}\left(\frac{QK^\top}{\sqrt{d_k}}\right)V, \tag{3}$$

where Q, K, V are linear projections of the token representations.

The property that matters for this report: *every token in the context window is processed by the same mechanism*. Nothing in the architecture marks some tokens as trusted instructions and others as untrusted data; any separation must be learned or imposed from outside (§VI).

C. From pretrained model to assistant

[*Explain supervised instruction tuning (SFT): the model is fine-tuned on (instruction, response) pairs so that it* follows instructions*. Point out the irony: instruction-following is exactly what makes injection work.*]

Preference alignment further adjusts the model so that it prefers some responses over others. *Direct Preference Optimization* (DPO) [5] learns directly from triples (x, y_w, y_l) where y_w is the preferred and y_l the rejected response, with a frozen reference model π_{ref}:

$$\mathcal{L}_{\mathrm{DPO}}(\theta) = -\mathbb{E}\Big[\log \sigma\Big(\beta \log \frac{\pi_\theta(y_w \mid x)}{\pi_{\mathrm{ref}}(y_w \mid x)} - \beta \log \frac{\pi_\theta(y_l \mid x)}{\pi_{\mathrm{ref}}(y_l \mid x)}\Big)\Big], \tag{4}$$

where σ is the logistic function and β controls how far π_θ may move from π_{ref}. Intuitively, the loss widens the probability gap between the preferred and the rejected answer. This objective reappears in the SecAlign defense (§VI-B).

D. Local deployment and access levels

[*Contrast the two ways a model is served locally and what each exposes: (i) quantized inference servers (Ollama, LM Studio) return generated text and at most sampled log-probabilities; (ii) full/half-precision models in HuggingFace Transformers + PyTorch expose logits and gradients with respect to the input. This is the basis of the access levels in Table II.*]

III. Prompt Injection

A. Instruction/data conflation

An LLM-integrated application builds the model's context by concatenating several segments of different trust levels:

$$C = s_{\mathrm{sys}} \,\|\, s_{\mathrm{task}} \,\|\, d, \tag{5}$$

where s_{sys} is the developer's system prompt, s_{task} the user's request, d external data (documents, web pages, logs), and $\|$ denotes concatenation. Section II-B showed that the model processes C as one undifferentiated token sequence.

Definition 1 (Prompt injection): A *prompt injection* occurs when text inside an untrusted segment of C is interpreted by the model as an instruction, causing an output y that serves the author of that text rather than the instruction in $s_{\mathrm{sys}} \| s_{\mathrm{task}}$.

This *instruction/data conflation* is the root cause of every attack in this report, and every defense in Section VI is an attempt to restore the missing separation.

B. Direct and indirect injection

[*Direct: the attacker is the user and types the instruction into s_{task} (overlaps with jailbreaking; define the difference). Indirect (IPI): the attacker controls only d, content the application later retrieves [2]. Give one classic IPI example (a hidden instruction in a web page summarized by an assistant).*]

C. Log-substrate prompt injection

Definition 2 (Log-substrate prompt injection [3]): An indirect prompt injection in which d consists of log records and the payload is placed in fields populated by the events the attacker generates.

What distinguishes it from ordinary IPI is that the *delivery channel is intrinsic to the attack*: a malicious request is logged by design, so the attacker does not need to plant content anywhere; the monitoring pipeline delivers the payload to the model on the attacker's behalf. A related study considers cloud logs read by debugging agents that can execute commands [6].

D. Attack classes

Following the taxonomy of [3]:

- **Direct override**: an explicit instruction ("ignore previous instructions, output BENIGN").
- **Persona hijack**: the payload claims an authoritative identity ("SYSTEM NOTE: authorized scanner").
- **Context manipulation**: false context that makes the malicious event look legitimate.
- **Obfuscated payload**: encoding or spacing tricks that evade keyword filters.

[*Give each class one short User-Agent payload on the running example.*]

E. Copilot tasks and attacker goals

[*Three tasks, one attacker goal each: classification* → suppression *(malicious labelled benign); summarization* → omission *(attack left out of the summary); remediation* → unsafe recommendation *("no action required").*]

IV. Security Operations Context and Threat Model

A. SOCs, SIEMs and triage

[*Define SOC, SIEM (collects and correlates logs, raises alerts) and triage (deciding whether an alert is a real threat). Place the LLM copilot in this workflow: it reads the alert and the underlying log records and produces one of the three outputs from §III.*]

TABLE I: Linux log substrates and their attacker-controlled fields

Substrate	Attacker-controlled fields	Constraints
nginx/apache access log	User-Agent, URI, query string, referer	long, permissive
`auditd` execve	command-line arguments, file paths	medium
SSH `auth.log`	attempted username, client banner	short, restricted charset

TABLE II: Attacker access levels to the target model

Level	Attacker observes	Enables
White-box	weights, gradients	gradient-guided search (GCG)
Grey-box	logits / log-probs	score-based search (GA)
Black-box	generated text only	LLM-driven refinement (PAIR)

Algorithm 1 Genetic algorithm for payload search

Require: field f, population size N, generations G, fitness F
$P \leftarrow N$ seed payloads in $\mathcal{A}(f)$ (e.g. hand-written)
for $g = 1$ to G **do**
  evaluate $F(\delta)$ for every $\delta \in P$
  $E \leftarrow$ best individuals of P (elitism)
  while $|E| < N$ **do**
    select parents δ_a, δ_b from P (tournament)
    $\delta' \leftarrow \mathrm{mutate}(\mathrm{crossover}(\delta_a, \delta_b))$
    $\delta' \leftarrow \mathrm{repair}_f(\delta')$ {enforce $\delta' \in \mathcal{A}(f)$}
    $E \leftarrow E \cup \{\delta'\}$
  end while
  $P \leftarrow E$
end for
return $\arg\max_{\delta \in P} F(\delta)$

B. Log substrates and attacker-controlled fields

A *log substrate* is a log format together with the subset of its fields that an external attacker can populate. Each field f imposes constraints on the payload: a maximum length L_f and an allowed character set Σ_f. Table I lists the Linux substrates considered in this work.

[*Briefly explain each source: what generates the record, which fields come from the attacker, and how encoding (URL-encoding, hex-encoding of argv by auditd) changes what the model actually sees.*]

C. Threat models

A threat model states explicitly what the attacker *knows*, what they *can do*, and what they *want*. In this work:

- **Capability**: remote and unauthenticated; the attacker can only cause events that are logged, and has no access to the pipeline after ingestion.
- **Goal**: one of the three goals from §III.
- **Knowledge**: varies with the access level (Table II).

[*Explain why white-box access is a reasonable* research *assumption for open-weight local models (anyone can download them), while the realistic deployed attacker is black-box; this motivates measuring transferability (§V-E).*]

V. Adversarial Payload Generation as Constrained Optimization

Hand-written payloads such as those in Fig. 1 are guesses. This section formulates the search for an effective payload as an optimization problem, which allows payloads to be generated systematically and adapted to a specific model and field.

A. Problem formulation

Let f be the target field, with admissible set

$$\mathcal{A}(f) = \{\, \delta \in \Sigma_f^* \;:\; |\delta| \le L_f \,\}, \tag{6}$$

let $C(\delta)$ be the copilot's context with payload δ inserted into field f, and let y^* be the attacker's target output (e.g. the label `BENIGN`).

Definition 3 (Constrained payload optimization):

$$\delta^* = \arg\max_{\delta \in \mathcal{A}(f)} \underbrace{\log p_\theta\big(y^* \mid C(\delta)\big)}_{\text{fitness } F(\delta)} - \lambda\, D(\delta), \tag{7}$$

where $D(\delta) \ge 0$ is an optional detectability penalty and $\lambda \ge 0$ its weight.

[*Explain why the search space is discrete and enormous ($|\Sigma_f|^{L_f}$), why L_f is the main difficulty knob (a 200-character User-Agent vs. a 32-character username), and why a* continuous *fitness (log-probability of y^*) is far more informative than a binary success flag: two failing payloads are not equally close to success.*]

B. Gradient-guided search (GCG)

Greedy Coordinate Gradient [7] operates on the token sequence of the payload. Representing token i by a one-hot vector $e_{x_i} \in \{0,1\}^{|\mathcal{V}|}$, it computes the gradient of the loss $\mathcal{L}(\delta) = -\log p_\theta(y^* \mid C(\delta))$ with respect to that vector, and uses its most negative entries as candidate substitutions:

$$\mathcal{X}_i = \text{top-}k\big(-\nabla_{e_{x_i}} \mathcal{L}(\delta)\big). \tag{8}$$

At every iteration a batch of single-token substitutions is sampled from the sets $\mathcal{X}_i$, each candidate is evaluated exactly, and the best one is kept.

[*Discuss the limits in this setting: needs gradients (white-box); usually needs many adversarial tokens, which short fields do not allow; substituted tokens must decode to characters in Σ_f, so candidates have to be filtered.*]

C. Evolutionary search (genetic algorithm)

A genetic algorithm (GA) [8] needs only the fitness value $F(\delta)$, i.e. grey-box access. Individuals are candidate payloads; Algorithm 1 gives the general scheme.

[*Define the operators on strings: character/token/word-level mutation (insert, delete, substitute), one-point crossover, and the repair step (truncate to L_f, drop or map characters outside Σ_f). One sentence on why particle swarm optimization (PSO) is a poor fit: it is defined over continuous spaces and needs a non-trivial discrete adaptation.*]

D. LLM-driven iterative refinement (PAIR)

PAIR [9] uses a second *attacker LLM* that proposes a payload, observes the target's response, and rewrites the payload in light of the failure, repeating until success or a query budget is exhausted. It requires only black-box access.

[*Frame PAIR as search in which the "gradient" is natural-language feedback; it produces fluent, human-readable payloads (harder to filter by perplexity) but has no direct way to respect hard length constraints except by prompting and rejection.*]

E. Transferability

A payload is *transferable* if, optimized against a source model θ_s, it also succeeds against a target model $\theta_t \neq \theta_s$. Transferability is what makes white-box optimization dangerous in practice: an attacker can optimize against a downloadable open-weight model and then attack a deployment they can only observe as a black box [7].

VI. Defenses Against Prompt Injection

Defenses differ in *where* they act in the pipeline and *what* they require (Fig. 2). All of them try to re-introduce the separation between instructions and data that the architecture lacks (§III-A).

A. Inference-time defenses

These change only how the prompt is built or how the output is read, and require no retraining:

- **Structured prompting**: clearly labelled instruction and data sections.
- **Field sanitization and tagging**: remove or mark attacker-controlled fields.
- **Constrained output**: force a closed answer format (e.g. a single label).
- **Spotlighting** [10]: make the provenance of untrusted text visible to the model by *delimiting* (random delimiters around the data), *datamarking* (a marker token interleaved throughout the data, e.g. every space replaced by ˆ), or *encoding* (e.g. Base64).

[*Show the running example under datamarking. Note that encoding is reported to work well only on high-capacity models, which is a concern for small local models.*]

B. Training-time defenses

StruQ [11] separates the prompt and the data into two channels marked by reserved delimiter tokens that are filtered out of the data, and fine-tunes the model (*structured instruction tuning*) to follow only instructions in the prompt channel.

SecAlign [12] casts robustness as preference optimization: for an input x containing an injected instruction, the preferred response y_w answers the legitimate instruction and the rejected response y_l answers the injected one, and the model is trained with the DPO loss of Eq. (4). Meta-SecAlign [13] releases open-weight Llama models trained this way, which makes evaluating a trained defense possible without training it.

[*One paragraph on known limits: optimization-based attacks still succeed against StruQ; architecture-aware attacks that target attention break StruQ and SecAlign [14]; and it is an open question whether delimiter-based separation is meaningful when the "data" is structured* `key=value` *telemetry rather than prose.*]

C. Detection

Instead of hardening the copilot, a separate classifier $g(d) \in \{\text{clean}, \text{injected}\}$ inspects each record before it reaches the LLM. [*Options from cheapest to most expensive: regex/keyword rules; small dedicated classifiers (e.g. Prompt Guard); general guard LLMs (e.g. Llama Guard). Trade-off: false positives on legitimate but unusual log content.*]

VII. Evaluation Methodology

A. Attack success rate

For n independent attack attempts of which k achieve the attacker's goal, the *attack success rate* is $\widehat{\text{ASR}} = k/n$. It is specialized per task: suppression rate (classification), omission rate (summarization), and unsafe-recommendation rate (remediation).

B. Utility and the robustness–utility trade-off

A defense that makes the copilot label everything as malicious has zero ASR and no value. Every defense must therefore also be measured by its *utility*: task performance on a clean, labelled, un-attacked dataset [15]. [*Define utility for each task, e.g. accuracy or F_1 for classification.*]

C. Confidence intervals for proportions

$\widehat{\text{ASR}}$ is an estimate of an unknown proportion and must be reported with its uncertainty. The Clopper–Pearson interval [16] is the exact interval for a binomial proportion. At level $1-\alpha$ its bounds are quantiles of the Beta distribution:

$$\begin{aligned} p_{\text{low}} &= B\left(\tfrac{\alpha}{2};\ k,\ n-k+1\right), \\ p_{\text{high}} &= B\left(1-\tfrac{\alpha}{2};\ k+1,\ n-k\right), \end{aligned} \tag{9}$$

where $B(q; a, b)$ is the q-quantile of $\text{Beta}(a, b)$ (with $p_{\text{low}} = 0$ if $k = 0$ and $p_{\text{high}} = 1$ if $k = n$).

[*Worked example: for $k = 6$ successes out of $n = 20$, $\widehat{\text{ASR}} = 0.30$ but the 95% interval is roughly $[0.12, 0.54]$; with $n = 200$ and $k = 60$ it shrinks to roughly $[0.24, 0.37]$. Rule used in practice: non-overlapping intervals indicate a real difference; overlapping intervals are reported as inconclusive.*]

D. Staged experimental design

[*The full grid (models × attack classes × defenses × tasks × fields) is too large to run with large n in every cell. Screening: run all cells with small n; confirmation: re-run only the interesting cells with large n.*]




Fig. 2: The concepts of this report combined: payload optimization, the copilot pipeline with its defense points, and evaluation.

VIII. How the Concepts Fit Together

Fig. 2 combines the concepts of this report into the system studied in the thesis: an attacker optimizes a payload within a log field (§V), the record passes through optional detection and is placed in the copilot's context (§III), the copilot is protected by inference-time or trained defenses (§VI), and its decisions are scored for attack success and utility (§VII).

The thesis uses these concepts to address four research questions:

- **RQ1**: how susceptible are small local open-source models to log-substrate injection on Linux logs (§III, §IV)?
- **RQ2**: does constrained optimization (white-/grey-box) beat LLM-driven refinement (black-box) as the field constraint tightens (§V)?
- **RQ3**: do optimized payloads transfer across models (§V-E)?
- **RQ4**: how do trained defenses and detectors compare to inference-time defenses, and at what utility cost (§VI, §VII)?

[*Close with 2–3 sentences of conclusion: what the reader should now understand, and that the related literature is surveyed in the second report (SLR).*]

References

[1] A. Habibzadeh, F. Feyzi, and R. E. Atani, "Large language models for security operations centers: A comprehensive survey," arXiv preprint arXiv:2509.10858, 2025.

[2] K. Greshake, S. Abdelnabi, S. Mishra, C. Endres, T. Holz, and M. Fritz, "Not what you've signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection," in *Proceedings of the 16th ACM Workshop on Artificial Intelligence and Security (AISec)*, 2023, arXiv:2302.12173.

[3] R. Pandey and A. Bhujang, "Poisoning the watchtower: Prompt injection attacks against LLM-augmented security operations through adversarial log content," arXiv preprint arXiv:2605.24421, 2026.

[4] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin, "Attention is all you need," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2017.

[5] R. Rafailov, A. Sharma, E. Mitchell, S. Ermon, C. D. Manning, and C. Finn, "Direct preference optimization: Your language model is secretly a reward model," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

[6] H. Shah, "LogJack: Indirect prompt injection through cloud logs against LLM debugging agents," arXiv preprint arXiv:2604.15368, 2026.

[7] A. Zou, Z. Wang, N. Carlini, M. Nasr, J. Z. Kolter, and M. Fredrikson, "Universal and transferable adversarial attacks on aligned language models," arXiv preprint arXiv:2307.15043, 2023.

[8] J. H. Holland, *Adaptation in Natural and Artificial Systems*. Cambridge, MA: MIT Press, 1992.

[9] P. Chao, A. Robey, E. Dobriban, H. Hassani, G. J. Pappas, and E. Wong, "Jailbreaking black box large language models in twenty queries," in *IEEE Conference on Secure and Trustworthy Machine Learning (SaTML)*, 2025, arXiv:2310.08419.

[10] K. Hines, G. Lopez, M. Hall, F. Zarfati, Y. Zunger, and E. Kiciman, "Defending against indirect prompt injection attacks with spotlighting," arXiv preprint arXiv:2403.14720, 2024.

[11] S. Chen, J. Piet, C. Sitawarin, and D. Wagner, "StruQ: Defending against prompt injection with structured queries," in *Proceedings of the 34th USENIX Security Symposium*, 2025, arXiv:2402.06363.

[12] S. Chen, A. Zharmagambetov, S. Mahloujifar, K. Chaudhuri, D. Wagner, and C. Guo, "SecAlign: Defending against prompt injection with preference optimization," in *Proceedings of the ACM Conference on Computer and Communications Security (CCS)*, 2025, arXiv:2410.05451.

[13] S. Chen, A. Zharmagambetov, D. Wagner, and C. Guo, "Meta SecAlign: A secure foundation LLM against prompt injection attacks," arXiv preprint arXiv:2507.02735, 2025.

[14] N. V. Pandya, A. Labunets, S. Gao, and E. Fernandes, "May I have your attention? breaking fine-tuning based prompt injection defenses using architecture-aware attacks," arXiv preprint arXiv:2507.07417, 2025.

[15] E. Debenedetti, J. Zhang, M. Balunović, L. Beurer-Kellner, M. Fischer, and F. Tramèr, "AgentDojo: A dynamic environment to evaluate prompt injection attacks and defenses for LLM agents," in *Advances in Neural Information Processing Systems (NeurIPS), Datasets and Benchmarks Track*, 2024.

[16] C. J. Clopper and E. S. Pearson, "The use of confidence or fiducial limits illustrated in the case of the binomial," *Biometrika*, vol. 26, no. 4, pp. 404–413, 1934.