

# Getting to Know your Oracle DB

WEEK 03

# Some Tools to Work with your New Oracle DB

---

Tool	OS Platform	Free?
PL/SQL Developer <a href="https://www.allroundautomations.com/plsqldev.html">https://www.allroundautomations.com/plsqldev.html</a>	Windows	No (\$216 per user)
Oracle Toad <a href="https://www.quest.com/products/toad-for-oracle/">https://www.quest.com/products/toad-for-oracle/</a>	Windows	No (€1128 per user)
Oracle SQL Developer <a href="http://www.oracle.com/technetwork/developer-tools/sql-developer/overview/index.html">http://www.oracle.com/technetwork/developer-tools/sql-developer/overview/index.html</a>	Cross platform	Yes
Sqlplus (is part of any Oracle DB Server setup)	Cross platform	Yes

# Oracle DB Viewed from Outside

JUST A BUNCH OF  
FILES AND SOME  
“STRANGE”  
PROCESSES...

# The First Challenge of the Week

---

1

List the database files (hint: /u01/app/oracle/oradata). Can you figure out the size of the database?

2

Look at the "oracle" processes which are currently running and guess the ones belonging to Oracle system


# Oracle DB Viewed from Inside

WELL, WE HAVE TO  
CONNECT FIRST...

# The Client-server Architecture

Source:

[https://www.ibm.com/support/knowledgecenter/en/SSLTBW\\_2.3.0/com.ibm.zos.v2r3.ieak500/ieak5cli.gif](https://www.ibm.com/support/knowledgecenter/en/SSLTBW_2.3.0/com.ibm.zos.v2r3.ieak500/ieak5cli.gif)



# What is Needed to Get to the Database (basic scenario)

---

1

The client  
application


2

Network  
connectivity


3

A valid username  
and password

# Network Communication



The big picture



Detailed picture



It's a separate component

It can be configured via a configuration file called "listener.ora", typically located in \$ORACLE\_HOME/network/admin

It can be managed using a special tool called "lsnrctl".

## The Oracle Listener

# Basic Authentication

---

A valid username and password are needed.

On the database installation you are asked to provide the password for two admin users:

The user's credentials are checked by the database layer, not by the listener.


SYS: the most powerful one (it's like the "root" user in linux)

SYSTEM: a less powerful user but still having administrative rights and recommended to be used on daily administration tasks

# Basic Info Required to Connect to an Oracle DB

Before trying to connect to an Oracle database, ensure that you have:

- A valid username and password
- The IP address where the listener is running
- The port where the listener is listening
- The database/service name




# Oracle DB Viewed from Inside

DB Objects

Tables containing  
business data:

EMPLOYEES  
DEPARTMENTS  
LOCATIONS  
JOB\_HISTORY  
...



Data dictionary  
views:

DICTIONARY  
USER\_OBJECTS  
USER\_TABLES  
USER\_TAB\_COLUMNS  
...

# The Database Dictionary

---

Did You Know  
that?

## DB Dictionary...

It is owned by SYS user

It's a metadata repository  
about the data within the  
database

You must NEVER alter  
directly the dictionary data  
(only if Oracle Support  
advises so)

It is the most common place  
DBAs are looking for to  
accomplish various tasks:  
adding more space,  
troubleshooting, tuning etc.

# Common Dictionary Queries

What tables are in my  
own schema?

What columns have a  
table?

How many indexes are  
defined?

What Oracle users are  
created in the  
database?

How many  
connections/sessions do  
currently exist for every  
user?

In which PL/SQL objects  
(procedures, triggers,  
packages etc) a  
particular table is being  
referenced?

# The Oracle Instance Architecture



# Do You Remember the Previous Challenge?

---

1

List the database files (hint: /u01/app/oracle/oradata). Can you figure out the size of the database?

**This is the Oracle DATABASE**


2

Look at the "oracle" processes which are currently running and guess the ones belonging to Oracle system

**This is the Oracle INSTANCE**

Do You Remember  
This Slide?


---



# What is the Oracle Instance

A COLLECTION OF OS  
PROCESSES AND  
MEMORY  
STRUCTURES.

# The Just-enough Diagram



# Processes Types

---

**BACKGROUND PROCESSES:** takes care of the good health of the database and maintains it in an optimized operational mode: DBWR, LOGWR, SMON, PMON etc.

Process	Description	Mandatory
PMON	Ensure everything is fine after an instance process had died unexpectedly	YES
SMON	Performs instance recovery	YES
DBWn	Writes dirty buffers from buffer cache to the datafiles	YES
LGWR	Writes from log buffer to the online redolog files	YES
ARCn	Copy online redolog files to the archiving location	NO

**FOREGROUND PROCESSES:** in the Oracle dedicated server architecture, to every user connection a new server process is allocated which does the database work on behalf of the client requests

# Memory Structures

---

**SGA (System Global Area):** a big chunk of shared memory. It contains sub-caches:


- Shared pool:
  - Library cache: pl/sql code, shared SQL area
  - Dictionary cache: dictionary metadata
  - Server results cache
- DB Buffer cache
- Log Buffer
- Large Pool: used by parallel processes, RMAN and others
- Java Pool: used by java code
- Streams Pool: used by streams

**PGA (Program Global Area):** private memory allocated to the process only


# The Detailed Diagram

## Oracle Database 12c: INTERACTIVE QUICK REFERENCE

Source: <https://goo.gl/RMo6C8>



# Relationship between an Instance and a Database





# Startup the Instance

---

1

Only SYS (or a SYSDBA user) can start an Oracle instance.

2


In sqlplus, it's just a matter of executing the "startup" command.

3

The startup can be phased (see the next slide).

# Phased Instance Startup

---





OMG! SPFILE,  
Control file? I  
feel lost!

DON'T WORRY! WE'LL COVER  
THESE SHORTLY!

# Shutdown the Instance

---

1

Only SYS user can shutdown the instance

2


In “sqlplus” it’s just a matter of executing the “shutdown” command

3

How gracefully or not the shutdown is intended to be can be controlled with some parameters given to the “shutdown” command

# Shutdown Phases

---



# Shutdown Modes

	ABORT	IMMEDIATE	TRANSACTIONAL	NORMAL
New user connections are permitted	NO	NO	NO	NO
Waits until current sessions end	NO	NO	NO	YES
Waits until current transactions end	NO	NO	YES	YES
The data-files are closed cleanly	NO	YES	YES	YES

# Play around with Startup & Shutdown

## Practical session:

- Login to your dedicated server using the “oracle” user
- Check if there is any oracle instance running
- Assuming that no instance is running, start up the Oracle instance
- Using “sqlplus”, connect using the FB user (password “fb”)
- Insert a new record into the “ACCOUNTS” table (look at the table structure and figure out how to write the INSERT statement). Leave this sqlplus window/terminal opened.
- Open a new terminal, connect as SYS using sqlplus and execute “shutdown transactional”
- Explain what happens

# Configure the Oracle Instance

---

Initialization  
parameters

PFILE vs SPFILE

SPFILE location

STATIC parameters  
vs DYNAMIC  
parameters

How to alter  
initialization  
parameters

Parameters  
documentation  
reference





Settings which tailor the Oracle instance configuration.



Oracle is a very configurable system therefore there are a lot of initialization parameters.



Some settings can be changed on the fly, others need an instance restart to be taken into consideration.



These parameters are stored in a special file called PFILE or SPFILE.



They can be set on the instance level or on the session level.


# What are Initialization Parameters?

# PFILE vs SPFILE

PFILE	SPFILE
A text based configuration file.	A binary configuration file.
Can be edited with a text editor.	Editing directly this file is not supported.
Obsolete, but needed sometimes.	The recommended format.
It is not automatically updated by the Oracle instance.	It is automatically maintained by the Oracle instance.

# When is the [S]PFILE being read?

---



# Static vs Dynamic Parameters

---

1

A dynamic parameter can be changed on the fly without restarting the database:

2

A change of a static parameter value cannot be effective without restarting the database.

# Changing Instance Settings

The "ALTER SYSTEM SET param\_name = param\_value" command is your friend. It changes a setting on the instance level.

Use "ALTER SESSION SET . . ." If you want to change a setting on the session level.

You can use the SCOPE parameter of the "ALTER SYSTEM SET command":

- Change the setting just in the SPFILE: ALTER SYSTEM SET ... SCOPE=SPFILE;
- Change the setting just in memory: ALTER SYSTEM SET ... SCOPE=MEMORY;
- Change the settings for both: ALTER SYSTEM SET ... SCOPE=BOTH;

## 1.186 MEMORY\_TARGET

`MEMORY_TARGET` specifies the Oracle systemwide usable memory. The database tunes memory to the `MEMORY_TARGET` value, reducing or enlarging the SGA and PGA as needed.

Property	Description
Parameter type	Big integer
Syntax	<code>MEMORY_TARGET = integer [K   M   G]</code>
Default value	0 (SGA autotuning is disabled for <code>DEFERRED</code> mode autotuning requests, but allowed for <code>IMMEDIATE</code> mode autotuning requests)
Modifiable	<code>ALTER SYSTEM</code>
Modifiable in a PDB	No
Range of values	152 MB to <code>MEMORY_MAX_TARGET</code>
Basic	No

`MEMORY_TARGET` should be set higher than or equal to the sum of the current sizes of the SGA and PGA.


In a text-based initialization parameter file, if you omit `MEMORY_MAX_TARGET` and include a value for `MEMORY_TARGET`, then the database automatically sets `MEMORY_MAX_TARGET` to the value of `MEMORY_TARGET`. If you omit the line for `MEMORY_TARGET` and include a value for `MEMORY_MAX_TARGET`, the `MEMORY_TARGET` parameter defaults to zero. After startup, you can then dynamically change `MEMORY_TARGET` to a nonzero value, provided that it does not exceed the value of `MEMORY_MAX_TARGET`.



# Parameters Doc Reference

<https://docs.oracle.com/en/database/oracle/oracle-database/12.2/refrn/index.html>

# Mounting the Instance



# What is the controlfile?

---

A critical file: without the controlfile the database can't be opened

It is relatively small in size

It stores data files locations

It stores checkpoint/synchronization data

It stores various database properties (e.g. the DB character-set)

It stores backups metadata


It can be multiplexed (more than one control files)



# Challenge

---


Find out where the controlfile(s) of your database is/are located.



Check the size of your controlfiles.

# Open the Database

startup



SHUTDOWN

NOMOUNT

MOUNT

OPEN

Database files are  
opened by the  
instance

Location?



```
sqlplus / as sysdba  
alter database open;
```

# That's all for today!

THANKS AND SEE YOU NEXT WEEK!