

Computer Vision

Fall 2017

Problem Set #6

Sergiy Palguyev
sergiy.palguyev@gatech.edu

1a: Average face



ps6-1-a-1.png

1b: Eigenvectors

eigenface_0



eigenface_1



eigenface_2



eigenface_3



eigenface_4



eigenface_5



eigenface_6



eigenface_7



eigenface_8



eigenface_9



ps6-1-b-1.png

1c: Analysis

The predictions perform better than randomly selecting a label provided a good data set is given.


Lowering k value significantly decreases accuracy.

Increasing k value slight increases accuracy.

Lowering or Increasing p value to extremes will decrease accuracy in both cases.

1c: Analysis

Example used for analysis:




```
C:\> Command Prompt

Good predictions = 54 Bad predictions = 29
65.06% accuracy p= 0.5 k= 5
Good predictions = 56 Bad predictions = 93
37.58% accuracy p= 0.1 k= 5
Good predictions = 9 Bad predictions = 8
52.94% accuracy p= 0.9 k= 5
Good predictions = 12 Bad predictions = 71
14.46% accuracy p= 0.5 k= 1
Good predictions = 62 Bad predictions = 21
74.70% accuracy p= 0.5 k= 25
```

2a: Average accuracy

Approximately 88% for training and 82% for testing:



```
Command Prompt
(Random) Training accuracy: 51.33%
(Weak) Training accuracy 88.26%
(Boosting) Training accuracy 88.26%
(Random) Testing accuracy: 46.88%
(Weak) Testing accuracy 82.50%
(Boosting) Testing accuracy 82.50%
```

2a: Analysis

Between Random, Weak, and Boosting, it appears there is not much difference between Weak and Boosting methods.

Slightly lowering p value, increases testing accuracy and slightly the training accuracy.

Dropping p value lower, increases training accuracy and slightly the testing accuracy.

Decreasing number of iterations slightly lowers accuracy for all.


Increasing number of iterations slightly increases accuracy for all.

2a: Analysis

Example used for analysis:


```
(Random) Training accuracy: 48.20%
(Weak) Training accuracy 87.79%
(Boosting) Training accuracy 88.42%
(Random) Testing accuracy: 46.88%
(Weak) Testing accuracy 83.75%
(Boosting) Testing accuracy 83.12%
p= 0.8 num_iter= 5
(Random) Training accuracy: 50.13%
(Weak) Training accuracy 88.22%
(Boosting) Training accuracy 88.22%
(Random) Testing accuracy: 54.00%
(Weak) Testing accuracy 87.75%
(Boosting) Testing accuracy 87.75%
p= 0.5 num_iter= 5
(Random) Training accuracy: 52.20%
(Weak) Training accuracy 91.82%
(Boosting) Training accuracy 91.82%
(Random) Testing accuracy: 50.00%
(Weak) Testing accuracy 85.62%
(Boosting) Testing accuracy 85.62%
p= 0.2 num_iter= 5
(Random) Training accuracy: 47.89%
(Weak) Training accuracy 87.95%
(Boosting) Training accuracy 87.95%
(Random) Testing accuracy: 47.50%
(Weak) Testing accuracy 83.12%
(Boosting) Testing accuracy 83.12%
p= 0.8 num_iter= 1
(Random) Training accuracy: 46.48%
(Weak) Training accuracy 88.26%
(Boosting) Training accuracy 88.26%
(Random) Testing accuracy: 53.12%
(Weak) Testing accuracy 85.62%
(Boosting) Testing accuracy 85.62%
p= 0.8 num_iter= 25
```


3a: Haar Features




ps6-3-a-1.png

3a: Haar Features




ps6-3-a-2.png

3a: Haar Features




ps6-3-a-3.png

3a: Haar Features



ps6-3-a-4.png

3a: Haar Features



ps6-3-a-5.png

3c: Analysis

Using integral imaging helps by allowing estimations to be made in almost constant time irrelevant of image size, whereas a `np.sum` function would require quadratic compute time with the growth of image size.

4b: Viola Jones Features



ps6-4-b-1.png

4b: Viola Jones Features



ps6-4-b-2.png

4b: Analysis

Add more slides if needed.

4c: Viola Jones Face Recognition



ps6-4-c-1.png