

Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

SECTION 1: IDENTIFICATION

Product name : Contact OL Oxidising Solvent

Product code : 0893 60

Manufacturer or supplier's details

Company : Wurth Australia Pty. Ltd.

Address : Building 5, 43 - 63 Princes Highway

Dandenong South, VIC 3175

Telephone : +61 3 8788 1111

Emergency telephone number : 1300 657 765. Advisory office in case of poisoning - National

Poisons Centre: 131 126

E-mail address : product@wurth.com.au

Recommended use of the chemical and restrictions on use

Recommended use :

Corrosion inhibitor

Detergent

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Aerosols : Category 1

Skin corrosion/irritation : Category 2

Serious eye damage/eye irri-

tation

Category 2A

Specific target organ toxicity - :

single exposure

Category 3

Aspiration hazard : Category 1

GHS label elements



Contact OL Oxidising Solvent

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.11.2024

 9.0
 20.01.2025
 10686705-00015
 Date of first issue: 08.10.2010

Hazard pictograms :







Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Precautionary statements

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention

P337 + P313 If eye irritation persists: Get medical advice/ attention

P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.



Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

П

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Propan-2-ol	67-63-0	>= 20 -< 30
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	>= 10 -< 20
Butan-2-ol	78-92-2	>= 10 -< 20
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	64742-49-0	>= 1 -< 10
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	92128-66-0	>= 1 -< 10
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	>= 1 -< 10
Hydrocarbons, C6, isoalkanes, <5% n-hexane	64742-49-0	>= 1 -< 10
Carbon dioxide	124-38-9	< 10
n-Hexane	110-54-3	< 3

Alternative CAS Numbers for some regions

Chemical name	Alternative CAS Number(s)		
Hydrocarbons, C6-C7, n-alkanes, isoalkanes,	64742-49-0		
cyclics, <5% n-hexane			

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.



Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

If swallowed : If swallowed, DO NOT induce vomiting.

If vomiting occurs have person lean forward.

Call a physician or poison control centre immediately.

Rinse mouth thoroughly with water.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation. May cause drowsiness or dizziness.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire-

fighting

Flash back possible over considerable distance.

Vapours may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Hazardous combustion prod-

ucts

Carbon oxides

Specific extinguishing meth-

. ods Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Hazchem Code : 2YE



Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Remove all sources of ignition.

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Non-sparking tools should be used.

Soak up with inert absorbent material.

Suppress (knock down) gases/vapours/mists with a water spray jet.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventila-

tion.

Advice on safe handling : Do not get on skin or clothing.

Avoid breathing spray.

Do not swallow. Do not get in eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-



Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

sessment

Keep container tightly closed.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the

environment.

Do not spray on an open flame or other ignition source.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working

place

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

Conditions for safe storage : Store locked up.

Keep tightly closed.

Keep in a cool, well-ventilated place.

Store in accordance with the particular national regulations.

Do not pierce or burn, even after use. Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:

Self-reactive substances and mixtures

Organic peroxides Oxidizing agents Flammable liquids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Explosives

Recommended storage tem: :

perature

< 40 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Propan-2-ol	67-63-0	STEL	500 ppm 1,230 mg/m3	AU OEL
		TWA	400 ppm 983 mg/m3	AU OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	TWA (Mist)	5 mg/m3	AU OEL



Contact OL Oxidising Solvent

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.11.2024

 9.0
 20.01.2025
 10686705-00015
 Date of first issue: 08.10.2010

		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
Butan-2-ol	78-92-2	TWA	100 ppm 303 mg/m3	AU OEL
		TWA	100 ppm	ACGIH
Hydrocarbons, C6-C7, isoal-kanes, cyclics, <5% n-hexane	64742-49-0	TWA	900 mg/m3	AU OEL
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	92128-66-0	TWA (Mist)	5 mg/m3	AU OEL
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	STEL	500 ppm 2,050 mg/m3	AU OEL
		TWA	400 ppm 1,640 mg/m3	AU OEL
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
Hydrocarbons, C6, isoalkanes, <5% n-hexane	64742-49-0	TWA	500 ppm 1,760 mg/m3	AU OEL
		STEL	1,000 ppm 3,500 mg/m3	AU OEL
		TWA	200 ppm	ACGIH
Carbon dioxide	124-38-9	TWA	5,000 ppm 9,000 mg/m3	AU OEL
		STEL	30,000 ppm 54,000 mg/m3	AU OEL
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
n-Hexane	110-54-3	TWA	20 ppm 72 mg/m3	AU OEL
		TWA	50 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentration	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work- week	40 mg/l	ACGIH BEI
n-Hexane	110-54-3	2,5- Hexanedi- one	Urine	End of shift	0.5 mg/l	ACGIH BEI

Engineering measures

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.



Contact OL Oxidising Solvent

Version 9.0

Revision Date: 20.01.2025

SDS Number: 10686705-00015

Date of last issue: 25.11.2024 Date of first issue: 08.10.2010

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : butyl-rubber
Break through time : 240 min
Glove thickness : 0.7 mm

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:

Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Wear the following personal protective equipment:

If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic

protective clothing.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Propellant : Carbon dioxide

Colour : red

Odour : alcohol-like

Odour Threshold : No data available



Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

pH : Solvent mixture; pH value determination not possible, no

aqueous solution

Melting point/freezing point : No data available

Initial boiling point and boiling

range

Not applicable

Flash point : < 0 °C

(1,013 hPa)

Method: closed cup

Flash point is only valid for liquid portion in the aerosol can.

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

12.0 %(V)

Lower explosion limit / Lower

flammability limit

0.6 %(V)

Vapour pressure : ca. 6,000 - 6,500 hPa (20 °C)

Relative vapour density : Not applicable

Density : 0.762 - 0.782 g/cm³ (20 °C)

Solubility(ies)

Water solubility : partly soluble

Partition coefficient: n-

octanol/water

Not applicable

Auto-ignition temperature : > 200 °C

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics

Particle size : Not applicable



Contact OL Oxidising Solvent

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.11.2024

 9.0
 20.01.2025
 10686705-00015
 Date of first issue: 08.10.2010

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Extremely flammable aerosol.

Vapours may form explosive mixture with air.

If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Exposure routes : Inhalation

Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

Propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25 mg/l

Exposure time: 6 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 4,951 mg/m3

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials



Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Butan-2-ol:

Acute oral toxicity : LD50 (Rat): 2,054 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 3,350 mg/kg

Remarks: Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25.2 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Acute oral toxicity : LD50 (Rat): > 5,840 mg/kg

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 23.3 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,800 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials



Contact OL Oxidising Solvent

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.11.2024

 9.0
 20.01.2025
 10686705-00015
 Date of first issue: 08.10.2010

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25.2 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Carbon dioxide:

Acute inhalation toxicity : LC50 (Rat): 40000 - 50000 ppm

Exposure time: 30 min Test atmosphere: vapour

n-Hexane:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 31.86 mg/l

Exposure time: 4 h Test atmosphere: vapour

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Causes skin irritation.

Components:

Propan-2-ol:

Species : Rabbit

Result : No skin irritation

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rabbit

Result : Mild skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Butan-2-ol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:



Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Assessment : Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Species : Rabbit Result : Skin irritation

Remarks : Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

n-Hexane:

Species : Rabbit Result : Skin irritation

Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Propan-2-ol:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Butan-2-ol:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Method : OECD Test Guideline 405



Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Result : No eye irritation

Remarks : Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Result : No eye irritation

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Species : Rabbit

Result : No eye irritation

Remarks : Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Species : Rabbit

Result : No eye irritation

n-Hexane:

Species : Rabbit

Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Propan-2-ol:

Test Type : Buehler Test Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Remarks : Based on data from similar materials

Butan-2-ol:

Test Type : Maximisation Test



Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact
Species : Mouse
Result : negative

Remarks : Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Remarks : Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

n-Hexane:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact
Species : Mouse
Result : negative

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Components:

Propan-2-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative



Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion

Result: negative

Butan-2-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosomal aberration

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Remarks: Based on data from similar materials

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)



Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay)
Species: Rat

Application Route: inhalation (vapour)

Method: OPPTS 870.5395

Result: negative

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: Based on data from similar materials

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (vapour)

Method: OPPTS 870.5395

Result: negative

n-Hexane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative



Contact OL Oxidising Solvent

Date of last issue: 25.11.2024 Version Revision Date: SDS Number: 20.01.2025 10686705-00015 9.0 Date of first issue: 08.10.2010

Genotoxicity in vivo Test Type: Rodent dominant lethal test (germ cell) (in vivo)

Species: Mouse

Application Route: inhalation (vapour)

Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Propan-2-ol:

Species Rat

Application Route : inhalation (vapour)

Exposure time : 104 weeks

Method : OECD Test Guideline 451

Result : negative

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species

Application Route inhalation (vapour)

Exposure time : 105 weeks : negative Result

Remarks Based on data from similar materials

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Species : Rat

: inhalation (vapour)

Species
Application Route
Exposure time
Result : 2 Years Result negative :

Remarks Based on data from similar materials

Species : Mouse

: inhalation (vapour)

Application Route
Exposure time : 2 Years Result : negative

Remarks Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species Mouse Application Route Skin contact Exposure time 102 weeks Result negative



Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Species : Mouse
Application Route : Skin contact
Exposure time : 102 weeks
Result : negative

n-Hexane:

Species : Mouse

Application Route : inhalation (vapour)

Exposure time : 2 Years

Method : OECD Test Guideline 451

Result : negative

Remarks : Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:

Propan-2-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion

Result: negative

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Remarks: Based on data from similar materials

Butan-2-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on foetal develop: Test Type: Embryo-foetal development



Contact OL Oxidising Solvent

Date of last issue: 25.11.2024 Version Revision Date: SDS Number: 20.01.2025 10686705-00015 9.0 Date of first issue: 08.10.2010

ment Species: Rat

Application Route: Ingestion

Result: negative

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Effects on fertility Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-Test Type: Embryo-foetal development

Species: Rat ment

Application Route: inhalation (vapour)

Result: negative

Remarks: Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Effects on fertility Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Test Type: Embryo-foetal development Effects on foetal develop-

ment Species: Rat

Application Route: inhalation (vapour)

Result: negative

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Effects on fertility Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-Test Type: Fertility/early embryonic development

ment

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Remarks: Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Effects on fertility Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Effects on foetal develop-Test Type: Embryo-foetal development

ment Species: Rat



Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

Application Route: inhalation (vapour)

Result: negative

n-Hexane:

Effects on fertility : Test Type: Fertility/early embryonic development

Application Route: inhalation (vapour)

Result: positive

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Mouse

Application Route: inhalation (vapour)

Result: negative

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on sexual function and

fertility, based on animal experiments.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Propan-2-ol:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

Butan-2-ol:

Assessment : May cause respiratory irritation.

May cause drowsiness or dizziness.

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

n-Hexane:

Assessment : May cause drowsiness or dizziness.



Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

STOT - repeated exposure

Not classified based on available information.

Components:

n-Hexane:

Exposure routes : inhalation (vapour)
Target Organs : Central nervous system

Assessment : May cause damage to organs through prolonged or repeated

exposure.

Repeated dose toxicity

Components:

Propan-2-ol:

Species : Rat NOAEL : 12.5 mg/l

Application Route : inhalation (vapour)

Exposure time : 104 Weeks

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rat

NOAEL : 10,186 mg/m3
Application Route : inhalation (vapour)

Exposure time : 13 Weeks

Butan-2-ol:

Species : Rat

NOAEL : >= 15.11 mg/l
Application Route : inhalation (vapour)
Exposure time : 80 - 90 Days

Remarks : Based on data from similar materials

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Species : Rat, male

NOAEL : 10.504 mg/l

LOAEL : 31.652 mg/l

Application Route : inhalation (vapour)

Exposure time : 13 Weeks

Remarks : Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rat NOAEL : > 20 mg/l

Application Route : inhalation (vapour)

Exposure time : 13 Weeks

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:



Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

Species : Rat
NOAEL : 12.47 mg/l
Application Route : Inhalation
Exposure time : 90 Days

Remarks : Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Species : Rat NOAEL : > 20 mg/l

Application Route : inhalation (vapour)

Exposure time : 13 Weeks

n-Hexane:

Species : Mouse LOAEL : 1.76 mg/l

Application Route : inhalation (vapour)

Exposure time : 13 Weeks

Species : Rat, male
NOAEL : 568 mg/kg
LOAEL : 3,973 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May be fatal if swallowed and enters airways.

Components:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.



Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

n-Hexane:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Experience with human exposure

Components:

n-Hexane:

Inhalation : Target Organs: Central nervous system

Symptoms: Central nervous system depression

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Propan-2-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 24 h

Toxicity to microorganisms : EC50 (Pseudomonas putida): > 1,050 mg/l

Exposure time: 16 h

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 30 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 22 - 46 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): > 1,000

mg/l

Exposure time: 72 h



Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 1

ma/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Butan-2-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

EC10 (Pseudokirchneriella subcapitata (green algae)): > 1

mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 12 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 3 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Toxicity to algae/aquatic

plants

EL50 (Selenastrum capricornutum (green algae)): > 10 - 100

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOELR (Selenastrum capricornutum (green algae)): 0.1 mg/l

Exposure time: 72 h



Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): 8.2 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 4.5 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): 3.1

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 0.5

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOELR (Daphnia magna (Water flea)): 2.6 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 13.4 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 3 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EL50 (Selenastrum capricornutum (green algae)): > 10 - 100

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201



Contact OL Oxidising Solvent

Date of last issue: 25.11.2024 Version Revision Date: SDS Number: 20.01.2025 10686705-00015 Date of first issue: 08.10.2010 9.0

Remarks: Based on data from similar materials

NOELR (Selenastrum capricornutum (green algae)): 0.1 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.17 mg/l

Exposure time: 21 d

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Toxicity to fish LL50 (Pimephales promelas (fathead minnow)): 8.2 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 4.5 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): 3.1

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 0.5

ma/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOELR (Daphnia magna (Water flea)): 2.6 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Carbon dioxide:

Toxicity to fish NOEC (Lepomis macrochirus (Bluegill sunfish)): > 100 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

NOEC (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Remarks: Based on data from similar materials



Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

n-Hexane:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.5 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 3.88 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): 55 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOEL (Pseudokirchneriella subcapitata (green algae)): 30

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Persistence and degradability

Components:

Propan-2-ol:

Biodegradability : Result: rapidly degradable

BOD/COD : BOD: 1,19 (BOD5)

COD: 2,23 BOD/COD: 53 %

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 89 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

Butan-2-ol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 86 % Exposure time: 5 d

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 81 % Exposure time: 28 d



Contact OL Oxidising Solvent

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.11.2024

 9.0
 20.01.2025
 10686705-00015
 Date of first issue: 08.10.2010

Method: OECD Test Guideline 301F

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 77.05 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 77.05 % Exposure time: 28 d

Method: OECD Test Guideline 301F

n-Hexane:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

Bioaccumulative potential

Components:

Propan-2-ol:

Partition coefficient: n-

log Pow: 0.05

octanol/water

Butan-2-ol:

Partition coefficient: n-

log Pow: 0.65

octanol/water

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Partition coefficient: n- : log Pow: > 3 - < 4

octanol/water Remarks: Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Partition coefficient: n- : log Pow: 4

octanol/water Remarks: Based on data from similar materials

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Partition coefficient: n- : log Pow: > 4



Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

octanol/water Remarks: Based on data from similar materials

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Partition coefficient: n- : log Pow: 4

octanol/water Remarks: Based on data from similar materials

Carbon dioxide:

Partition coefficient: n-

octanol/water

log Pow: 0.83

n-Hexane:

Partition coefficient: n-

octanol/water

log Pow: 4

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty

(including propellant)

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1950 Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 Environmentally hazardous : no



Contact OL Oxidising Solvent

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.11.2024

 9.0
 20.01.2025
 10686705-00015
 Date of first issue: 08.10.2010

IATA-DGR

UN/ID No. : UN 1950

Proper shipping name : Aerosols, flammable

Class : 2.1

Packing group : Not assigned by regulation

Labels : Flammable Gas

Packing instruction (cargo : 203

aircraft)

Packing instruction (passen: 203

ger aircraft)

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 Hazchem Code : 2YE Environmentally hazardous : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Therapeutic Goods (Poisons : Schedule 5 (Please use the original publication to check for Standard) Instrument specific uses, specific conditions or threshold limits that might

apply for this chemical)

Prohibition/Licensing Requirements : There is no applicable prohibition,

authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-



Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

tions.

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 690.44 g/l

VOC content excluding water

The components of this product are reported in the following inventories:

AIIC : All ingredients listed or exempt.

SECTION 16: ANY OTHER RELEVANT INFORMATION

Further information

Revision Date : 20.01.2025

Sources of key data used to

compile the Safety Data

Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

AU OEL : Australia. Workplace Exposure Standards for Airborne Con-

taminants.

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

AU OEL / TWA : Exposure standard - time weighted average AU OEL / STEL : Exposure standard - short term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Con-



Contact OL Oxidising Solvent

Version Revision Date: SDS Number: Date of last issue: 25.11.2024 9.0 20.01.2025 10686705-00015 Date of first issue: 08.10.2010

centration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified: Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NOM - Official Mexican Norm: NTP - National Toxicology Program: NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

AU / EN