

DOS Pipe Sealant 250 mL

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2024
8.2	21.11.2024	10638426-00015	Date of first issue: 07.05.2014

SECTION 1: IDENTIFICATION

Product name : DOS Pipe Sealant 250 mL

Product code : 0893 511 250

Manufacturer or supplier's details

Company : Wurth Australia Pty. Ltd.

Address : Building 5, 43 - 63 Princes Highway
Dandenong South, VIC 3175

Telephone : +61 3 8788 1111

Emergency telephone number : 1300 657 765. Advisory office in case of poisoning - National
Poisons Centre: 131 126

E-mail address : product@wurth.com.au

Recommended use of the chemical and restrictions on use

Recommended use : Adhesives

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Not a hazardous substance or mixture.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Titanium dioxide	13463-67-7	≥ 1 - < 10
α,α -dimethylbenzyl hydroperoxide	80-15-9	< 1
2'-Phenylacetohydrazide	114-83-0	< 10

DOS Pipe Sealant 250 mL

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2024
8.2	21.11.2024	10638426-00015	Date of first issue: 07.05.2014

SECTION 4. FIRST AID MEASURES

- | | | |
|---|---|---|
| If inhaled | : | If inhaled, remove to fresh air.
Get medical attention if symptoms occur. |
| In case of skin contact | : | Wash with water and soap as a precaution.
Get medical attention if symptoms occur. |
| In case of eye contact | : | Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists. |
| If swallowed | : | If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water. |
| Most important symptoms and effects, both acute and delayed | : | None known. |
| Protection of first-aiders | : | No special precautions are necessary for first aid responders. |
| Notes to physician | : | Treat symptomatically and supportively. |
-

SECTION 5. FIREFIGHTING MEASURES

- | | | |
|---------------------------------------|---|---|
| Suitable extinguishing media | : | Water spray
Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : | None known. |
| Specific hazards during fire-fighting | : | Exposure to combustion products may be a hazard to health. |
| Hazardous combustion products | : | Carbon oxides
Fluorine compounds
Silicon oxides |
| Specific extinguishing methods | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area. |

DOS Pipe Sealant 250 mL

Version	Revision Date:	SDS Number:	Date of last issue:
8.2	21.11.2024	10638426-00015	07.03.2024
			Date of first issue: 07.05.2014

Special protective equipment : Wear self-contained breathing apparatus for firefighting if necessary.
for firefighters Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.

DOS Pipe Sealant 250 mL

Version	Revision Date:	SDS Number:	Date of last issue:
8.2	21.11.2024	10638426-00015	07.03.2024
			Date of first issue: 07.05.2014

Wash contaminated clothing before re-use.

Conditions for safe storage : Keep in properly labelled containers.
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Titanium dioxide	13463-67-7	TWA	10 mg/m ³	AU OEL
		TWA (Respirable particulate matter)	2.5 mg/m ³ (Titanium dioxide)	ACGIH

This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Titanium dioxide

Engineering measures : Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Particulates type

Hand protection

Material : Latex gloves
Break through time : 480 min
Glove thickness : 1 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.

DOS Pipe Sealant 250 mL

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2024
8.2	21.11.2024	10638426-00015	Date of first issue: 07.05.2014

Wear the following personal protective equipment:
Safety glasses
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.

Skin and body protection : Skin should be washed after contact.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: white
Odour	: characteristic
Odour Threshold	: No data available
pH	: 6 - 7 Concentration: 10 %
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: 457 °C
Flash point	: > 100 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Flammability (liquids)	: Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Density	: 1.1 g/cm ³ (20 °C)
Solubility(ies)	

DOS Pipe Sealant 250 mL

Version	Revision Date:	SDS Number:	Date of last issue:
8.2	21.11.2024	10638426-00015	07.03.2024
			Date of first issue: 07.05.2014

Water solubility	:	practically insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	180,000 - 300,000 mPa.s (20 °C) Method: Brookfield
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics		
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Can react with strong oxidizing agents.
Conditions to avoid	:	None known.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Exposure routes	:	Inhalation Skin contact Ingestion Eye contact
-----------------	---	--

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg
---------------------	---	--

DOS Pipe Sealant 250 mL

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2024
8.2	21.11.2024	10638426-00015	Date of first issue: 07.05.2014

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:**Titanium dioxide:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

 α,α -dimethylbenzyl hydroperoxide:

Acute oral toxicity : LD50 (Rat, male): 382 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Expert judgement
Remarks: Based on national or regional regulation.

Acute dermal toxicity : LD50 (Rabbit, male): 133.6 mg/kg

2'-Phenylacetohydrazide:

Acute oral toxicity : LD50 (Mouse): 270 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 300 - 2,000 mg/kg
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:**Titanium dioxide:**

Species : Rabbit
Result : No skin irritation

 α,α -dimethylbenzyl hydroperoxide:

Species : Rabbit

DOS Pipe Sealant 250 mL

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2024
8.2	21.11.2024	10638426-00015	Date of first issue: 07.05.2014

Result : Corrosive after 4 hours or less of exposure

2'-Phenylacetohydrazide:

Species : Rabbit
Result : Skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Titanium dioxide:**

Species : Rabbit
Result : No eye irritation

 α,α -dimethylbenzyl hydroperoxide:

Species : Rabbit
Result : Irreversible effects on the eye

2'-Phenylacetohydrazide:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Remarks : Based on data from similar materials

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:**Titanium dioxide:**

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Result : negative

Chronic toxicity**Germ cell mutagenicity**

Not classified based on available information.

Components:**Titanium dioxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

DOS Pipe Sealant 250 mL

Version	Revision Date:	SDS Number:	Date of last issue:
8.2	21.11.2024	10638426-00015	07.03.2024
			Date of first issue: 07.05.2014

Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Result: negative

 α,α -dimethylbenzyl hydroperoxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: positive

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: positive

Test Type: Chromosome aberration test in vitro
Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Skin contact
Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

2'-Phenylacetohydrazide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: positive

Carcinogenicity

Not classified based on available information.

Components:**Titanium dioxide:**

Species : Rat
Application Route : inhalation (dust/mist/fume)
Exposure time : 2 Years
Method : OECD Test Guideline 453
Result : positive
Remarks : The mechanism or mode of action may not be relevant in humans.
This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

DOS Pipe Sealant 250 mL

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2024
8.2	21.11.2024	10638426-00015	Date of first issue: 07.05.2014

Reproductive toxicity

Not classified based on available information.

Components:**α,α-dimethylbenzyl hydroperoxide:**

Effects on foetal development	:	Test Type: Embryo-foetal development
	:	Species: Rat
	:	Application Route: Ingestion
	:	Method: OECD Test Guideline 414
	:	Result: negative

STOT - single exposure

Not classified based on available information.

Components:**α,α-dimethylbenzyl hydroperoxide:**

Assessment	:	May cause respiratory irritation.
------------	---	-----------------------------------

STOT - repeated exposure

Not classified based on available information.

Components:**α,α-dimethylbenzyl hydroperoxide:**

Exposure routes	:	Inhalation
Target Organs	:	Lungs
Assessment	:	Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Repeated dose toxicity**Components:****Titanium dioxide:**

Species	:	Rat
NOAEL	:	24,000 mg/kg
Application Route	:	Ingestion
Exposure time	:	28 Days
Species	:	Rat
NOAEL	:	10 mg/m ³
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	2 yr

Aspiration toxicity

Not classified based on available information.

DOS Pipe Sealant 250 mL

Version	Revision Date:	SDS Number:	Date of last issue:
8.2	21.11.2024	10638426-00015	07.03.2024
			Date of first issue: 07.05.2014

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Titanium dioxide:**

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l Exposure time: 72 h
Toxicity to microorganisms	:	EC50: > 1,000 mg/l Exposure time: 3 h Method: OECD Test Guideline 209

 α,α -dimethylbenzyl hydroperoxide:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 3.9 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 18.84 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	ErC50 (Desmodesmus subspicatus (green algae)): 3.1 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 NOEC (Desmodesmus subspicatus (green algae)): 1 mg/l Exposure time: 72 h Method: OECD Test Guideline 201

2'-Phenylacetohydrazide:

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 0.1 - 1 mg/l Exposure time: 96 h Remarks: Based on data from similar materials
------------------	---	--

Persistence and degradability**Components:** **α,α -dimethylbenzyl hydroperoxide:**

Biodegradability	:	Result: Not readily biodegradable. Biodegradation: 3 %
------------------	---	---

DOS Pipe Sealant 250 mL

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2024
8.2	21.11.2024	10638426-00015	Date of first issue: 07.05.2014

Exposure time: 28 d
Method: OECD Test Guideline 301B

2'-Phenylacetohydrazide:

Biodegradability : Result: Readily biodegradable.
Remarks: Based on data from similar materials

Bioaccumulative potential**Components:** **α,α -dimethylbenzyl hydroperoxide:**

Partition coefficient: n- : log Pow: 1.6
octanol/water Method: OECD Test Guideline 117

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Environmentally hazardous : no

IATA-DGR

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable

DOS Pipe Sealant 250 mL

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2024
8.2	21.11.2024	10638426-00015	Date of first issue: 07.05.2014

Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo aircraft) : Not applicable
Packing instruction (passenger aircraft) : Not applicable

IMDG-Code

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
EmS Code : Not applicable
Marine pollutant : Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**ADG**

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Hazchem Code : Not applicable

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Therapeutic Goods (Poisons Standard) Instrument : Schedule 6 (Please use the original publication to check for specific uses, specific conditions or threshold limits that might apply for this chemical)

Prohibition/Licensing Requirements : There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 3.7 g/l

DOS Pipe Sealant 250 mL

Version	Revision Date:	SDS Number:	Date of last issue:
8.2	21.11.2024	10638426-00015	07.03.2024
			Date of first issue: 07.05.2014

The components of this product are reported in the following inventories:

AIIC : All ingredients listed or exempt.

SECTION 16: ANY OTHER RELEVANT INFORMATION**Further information**

Revision Date : 21.11.2024

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.

ACGIH / TWA : 8-hour, time-weighted average
AU OEL / TWA : Exposure standard - time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recom-

DOS Pipe Sealant 250 mL

Version	Revision Date:	SDS Number:	Date of last issue: 07.03.2024
8.2	21.11.2024	10638426-00015	Date of first issue: 07.05.2014

mendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

AU / EN