

Umbilical Choir:

Automated Live Testing for Edge-To-Cloud FaaS Applications

M. Malekabbasi, T. Pfandzelter, D. Bermbach | Scalable Software Systems

The Challenge: Risky Releases in Edge-to-Cloud FaaS

- Users demand high QoS¹; frequent releases (thanks to CI/CD²) increase risk.
 - Amazon: Deploying every 11.6 seconds³.
 - Siemens: Over 4 production deployments per month by GitLab and AWS
- **Edge-to-Cloud Gap:** Standard cloud live testing (A/B, canary) doesn't fit.
 - Lacks **geo-awareness** for distributed edge nodes.
 - FaaS platforms offer limited native live testing features.
- **Result:**
Developers hard-code complex, error-prone solutions, or skip thorough testing.



Elfie, a comedy juggler


1. Quality of Service
2. Continuous Integration / Continuous Delivery
3. DevOps Research and Assessment (DORA) State of DevOps Report

Umbilical Choir (UC): Automated Live Testing for the Edge

➤ A novel framework for **serverless edge-to-cloud live testing**.

➤ Core Idea: Tree-like Hierarchy

- **Release Managers (RMs):**
Plan & delegate strategies across regions.
- **Agents:**
Execute tests on FaaS platforms
(via a Proxy Function for traffic control).



➤ **Key Design:** Scalable, geo-aware by structure,
FaaS platform-agnostic (deploys a Proxy function),
works with edge network limitation (no push/ssh access).

Umbilical Choir: Declarative & Flexible Live Testing

➤ Declarative Strategies (YAML): Define multi-stage releases.

- Supports: A/B, Canary, Dark Launch, Gradual Rollout.
- Metric-based conditions for progression/rollback.

➤ Geo-Aware Rollouts:

- **Global Incremental:** (Good for critical patches).



- **Local Sequential:** (Minimizes risk).



- **Regional Incremental:** Global Incremental applied to a specific region first.

- **Regional Sequential:** Local Sequential applied within a specific region.



- These can be combined for complex scenarios.

A simple "Release Strategy"

```
1 id: 12
2 name: A/BTestF1Function
3 type: patch/major/minor
4 functions:
5   - name: f1
6     base_version:
7       path: fns/f1_v1
8       env: nodejs
9     new_version:
10      path: fns/f1_v2
11      env: nodejs
12 stages:
13   - name: A/B Test f1
14     type: Sequential
15     func_name: f1
16     variants:
17       - name: base_version
18         trafficPercentage: 50
19       - name: new_version
20         trafficPercentage: 50
21     metrics_conditions: # AND condition
22       - name: errorRate
23         threshold: "<0.01"
24       - name: responseTime
25         threshold: "<=200"
26         compareWith: "Median"
27     end_conditions:
28       - name: minDuration
29         threshold: 10s
30       - name: minCalls
31         threshold: "50"
32     end_action:
33       onSuccess: rollout # keyword
34       onFailure: rollback #Or "Canary f1 10"
35 # - name: Canary f1 10
36 # ...
37 rollback:
38   action:
39     function: base_version
```

Evaluation: UC Works in Practice

- **Open-Source Prototype (Go):** Supports major FaaS providers (e.g., GCP Cloud Run) and edge FaaS (e.g., tinyFaaS).
- **Proxy Overhead:** Measurable, but enables crucial features.
- **Complex Scenario Success:** Successfully orchestrated a multi-stage, geo-distributed release (canary -> A/B -> gradual rollout) across edge (RPi) and cloud (GCP).



Conclusion: Enabling Safer Edge-to-Cloud Releases

- Edge-to-cloud FaaS needs robust, geo-aware live testing.
- **Umbilical Choir provides a solution:**
 - Automates complex release strategies.
 - Reduces risk of QoS regressions.
- **Impact:**

Empowers developers to innovate faster and more safely in the evolving edge-to-cloud landscape.
- **Thank You & Questions!**



 Contribution and
Technical Meat



Preprint
To be published at ICFC 2025

