
Fast Lane Group

Worldwide Education & Professional Services

Microsoft Solutions Partner

Microsoft Cloud Training Services



www.flane.de | © 2026 Fast Lane Institute for Knowledge Transfer GmbH

— AGENTIC AI: FROM STRATEGY TO **PRODUCTION.**

Alexander Kastil

Full stack, from enterprise software to agentic AI. Since 1996

AI at Work
Value discovery, KPI mapping and roadmap

Enterprise AI
Governed multi-agent systems on Microsoft Copilot and Foundry

Agentic Software Engineering
Harness architecture for Claude Code and GitHub Copilot

Team Enablement
AI driven content production and delivery

integrations.at
alexander.kastil@integrations.at

github.com/alexander-kastil
linkedin.com/in/alexander-kastil

INTEGRATIONS

AGENTIC AI CONSULTING · VIENNA



Microsoft CERTIFIED — AGENTIC AI BUSINESS SOLUTIONS ARCHITECT — ★★★

Microsoft CERTIFIED — AZURE AI APP AND AGENT DEVELOPER — ASSOCIATE ★★

Microsoft CERTIFIED — DEVOPS ENGINEER — EXPERT ★★★

SCAN TO CONNECT
integrations.at

MODULE 7

Optimize, Secure and Observe the Agentic Harness

Cut the cost, contain untrusted bytes, follow the work



01

Prompt Audit

Remove instructions for retired models

02

Caveman Compression

Fewer tokens, every rule intact

03

Autoresearch Loop

Measured changes to a skill

04

Threat Model

Injection, poisoning and isolation

05

Guardrails and Least Privilege

Hooks that block before a call runs

06

Tracing, Cost and Failure Diagnosis

OpenTelemetry, failure modes and drift

Optimize, secure, observe

Cut the cost, contain untrusted bytes, follow the work


- **Cost**: context loaded on every turn is a recurring bill, multiplied across a team
- **Threats**: prompt injection, tool poisoning and the isolation that stops both
- **Visibility**: tracing, cost attribution and failure diagnosis



Overview

The path through the module

- Start with an audit that removes dated instructions
- Compress **CLAUDE.md** with caveman mode and prove no rule was lost
- Improve a skill with the **autoresearch loop**: one change, measured
- Isolate **untrusted bytes**, then block dangerous actions with hooks
- Finally **trace** the work, attribute cost and diagnose failures



01


Prompt Audit

Remove instructions for retired models

What the prompt audit looks for

Instructions written for models that have been retired


- Current models follow instructions literally, so dated text **over-applies**
- Shouting, step scripts and word caps, plus fixes for retired models
- **Harness integrity**: missing files and scripts, files that contradict
- The **keep list**: author-only context, exact safe sequences, live prohibitions
- Not a length pass: audit first, then compress what survives



Running the prompt audit

Two entry points, one report, confidence decides the diff

- `/doctor prompt-audit` covers the harness; `/checkup` is its alias
- `/claude-api prompt-audit` also reads prompts in application code
- The audit first states its **scope** and the **target model**
- **High** and **medium** findings reach the proposed diff; **low** stays a flag
- Requires Claude Code v2.1.283 or later



Applying the audit and re-auditing

From 25 findings to four changed files

- Demo harness: **25 findings** and a proposed diff over four files
- Facts in every run: missing files, a missing script, Jest against Vitest
- Take the diff **hunk by hunk**; a rewrite that keeps the purpose beats a deletion
- Re-audit until **no finding** reaches the diff
- Re-run the audit at every model release



02


Caveman Compression

Fewer tokens, every rule intact

Caveman compression

Remove the wrapper, keep every rule

- Strip **articles**, copulas, hedges and politeness scaffolding
- Imperatives only: "Do X", not "You should do X"
- Keep every section heading, code fence and file path exactly
- Write `CLAUDE.caveman.md` beside the original; swap only after parity
- Count tokens with **js-tiktoken** (`cl100k_base`) before and after



Caveman compression results

1,725 tokens down to 559, all 35 rules intact

- `CLAUDE.verbose.md`: **1,725** tokens; `CLAUDE.caveman.md`: **559**
- 68% fewer tokens, 75% fewer words, 72% fewer bytes
- Per sprint: 3,450,000 tokens down to 1,118,000
- Rule-by-rule parity check: **35 of 35** rules still enforceable
- The parity verdict is a model judgement: review it before swapping



Measure	Verbose	Caveman	Change
Words	1,465	362	75% fewer
Bytes	9,579	2,707	72% smaller
Tokens per sprint	3,450,000	1,118,000	2,332,000 saved
Rules enforceable	**35**	**35**	**none lost**

03


Autoresearch Loop

Measured changes to a skill

The autoresearch loop

Measure first, change one thing, let the rule decide

- Subject: the **course-status** plugin, modelled on class-dashboard's evaluate step
- Baseline: **claude plugin eval**, three runs with and three without the plugin
- **One variable** per proposal, written down with a prediction
- Re-measure with the same command and the same run count
- Read skill-fired first: an indicator plugin eval never scores



Four metrics, six graders

Plugin eval scores each run on its own

- **Sections present**: three regex graders, a table, a percentage, the gaps
- **Evaluator evidence**: read-log on the trace, quotes-log on the answer
- **Abort rate**: no grader, read the error field of each run
- **Identical output**: no grader, plugin eval never compares runs
- The baseline picks the target: only quotes-log, at 2 of 3, had room

Metric	Grader	Type	Baseline, 3 runs
Sections present	`status-table, completion, gaps`	`regex`	3 of 3 each
Evidence: the step	`read-log`	`tool_used`	3 of 3
Evidence: the answer	`quotes-log` target	`regex`	**2 of 3**
Abort rate	none: read each run's error		0 errors
Identical output	none: runs are never compared		no grader

```
Evaluated 14 modules -> course/dashboard.json
```

the evaluator's own line, the only text quotes-log accepts

The promote or revert rule

Three conditions, all of them, or revert

- The **targeted grader** passed in more runs
- No other scored grader lost more than one run
- The **error count** stayed at zero
- One added sentence moved `quotes-log` from 2 of 3 to **3 of 3**
- Δ 0.93 to 1.00, so PROMOTE; the lesson is the asset



04


Threat Model

Injection, poisoning and isolation

Where attacks enter the loop

Every byte the model did not type is potentially adversarial


- File contents, tool outputs, **MCP responses**, fetched pages, database fixtures
- Inside one context the model cannot tell **content** from **command**
- A **prompt injection** is just instructions hiding in data
- Defense is structural: tag untrusted content, keep instructions in the system prompt
- Reserve writes, network and shell for steps that see only trusted context



Tool poisoning and MCP provenance

An MCP server is external code


- A malicious server can hide instructions inside a normal-looking result
- Control **provenance**: pin each server by source and version
- Prefer first-party or audited servers
- Review `.mcp.json` like a `package.json` dependency tree
- Validate responses with a **PostToolUse** hook that can replace the result



Quarantine untrusted content in a sub-agent

The parent acts on a structured summary, never the raw bytes

- Untrusted content goes to a **sub-agent** whose context never crosses back
- Give it only the tools to read and summarize: `tools: Read, Grep`
- Pin the output contract: `accounts`, `open_questions`, `ignored_instructions`
- The injection comes back **quoted** in a named field, not obeyed
- `/context` shows the parent never held the poisoned bytes



05


Guardrails and Least Privilege

Hooks that block before a call runs

Guardrails and scope

Two layers with two different jobs


- **Guardrails**: hooks, deny lists and allowlists stop specific actions
- **Scope**: per-agent and per-sub-agent tool subsets shrink the surface
- A hook runs in the harness, so an injected instruction cannot argue past it
- An **allow** rule only skips the prompt; it never restricts
- Restriction comes from **deny** rules and a sub-agent's `tools` list



Hooks as hard stops

Match every tool that can reach a shell

- A `PreToolUse` hook rejects the call before it runs
- On Windows, match `PowerShell` as well as `Bash`, or half the guardrail is decorative
- Exit `0` with `permissionDecision: deny` JSON: the model gets the reason
- Exit `2`: stdout is ignored and **stderr** becomes the reason
- The demo blocks six destructive patterns and logs every attempt



06


Tracing, Cost and Failure Diagnosis

OpenTelemetry, failure modes and drift

Tracing tool chains and cost

Follow the work, not the request boundary


- Every tool call, sub-agent spawn and model turn is a **span**
- Tag spans with agent, tool, tokens and cost, attribute up to the task
- Telemetry is configured through **environment variables** in `env`
- Export **OpenTelemetry** to a collector, Datadog or a Postgres table
- `/usage` for the session; Console and Analytics API for the organization



Stuck, runaway and hallucinating agents

Three failure modes and the first move for each


- **Stuck**: hung MCP server or an approval prompt nobody saw
- **Runaway**: a loop of near-identical calls; cap it with maxTurns or a budget
- **Hallucinating**: invented files or APIs; force grounding by reading first
- The loop: pull the trace, find the last successful call, see what followed
- Then decide whether the prompt or the harness changes



Checking that the agent is still right

Stratified sampling catches confidently wrong output

- A format change upstream fails silently: confidence stays high
- Sample **proportionally** by document type, field, confidence band and edge case
- Include the **high-confidence** tier that skips review
- Precision is a trust budget: drop a 65% false-positive category
- Enforce provenance with `source_ids` and a script that counts them



Takeaways

What to carry into your own harness

- Measure before you change: token counts, captured runs, a decision rule
- Audit dated instructions first, then **caveman-compress** what survives
- Change one sentence of a skill per cycle and let the numbers decide
- Treat every byte the model did not type as untrusted; enforce with hooks
- Trace spans and cost, and sample output for drift

