Lab 5: Configuring NAT (Network Address Translation) on a Router

NAME: Senabadhy Sesan R

REGNO: RA2211003050047

Aim:

Configure NAT on a router to enable multiple devices to share a single public IP address.

Objectives:

1. 2. Set up NAT on a router.

Configure internal devices to use private IP addresses.

3. Verify NAT functionality.

Steps:

1. **Open Cisco Packet Tracer:**

○ Start a new project.

2. **Add Devices:**

○ **Add a Router:** Drag a router (e.g., 2911).

○ **Add PCs and a Server:** Connect PCs and a server to the router.

3. **Configure NAT on the Router:**

Access the router CLI and configure NAT :

```
Router> enable
Router# configure terminal
Router(config)# interface gig0/0
```

```
Router(config-if)# ip address 192.168.1.1 255.255.255.0
Router(config-if)# ip nat inside
Router(config-if)# exit
Router(config)# interface gig0/1
Router(config-if)# ip address 203.0.113.1 255.255.255.0
Router(config-if)# ip nat outsideRouter(config-if)# exit
Router(config)# ip nat inside source list 1 interface gig0/1
overload
Router(config)# access-list 1 permit 192.168.1.0 0.0.0.255
```

4. **Configure PCs with Private IP Addresses:**
   ○ Assign private IP addresses to PCs (e.g., 192.168.1.2, 192.168.1.3).

5. **Verify NAT Functionality:**
   ○ On each PC, use the Command Prompt to ping an external IP address (e.g., 8.8.8.8) to verify NAT is working.