```
Fichier Edition Sélection Affichage Atteindre Exécuter Terminal Aide
Ð
       EXPLORATEUR
                                        settings.json
                                                         to json.py
                                                                        🥏 inject new data to redis.py 🗙 🧠 inject new data to mongo.py
                                                                                                                                                                                                                             ▷ ∨ • □ □ □ ···

√ TUTO

                                         src > libs > DAL > 🧽 inject_new_data_to_redis.py > .
                                          1 import ison
       V Des CEC
                 SORTIE TERMINAL PORTS SQL CONSOLE CONSOLE DE DÉBOGAGE
                                                                                                                                                                                                                     1 x at 21:26:46
          ~/Info/Developement/etudes/apres info/BUT/3A/bdd/project nosql/tuto
          docker exec -it dev-mongo-1 mongosh "mongodb://
                                                                           @mongo:27017/admin?authSource=admin&replicaSet=rs0&retryWrites=true&w=majority&readPreference=primary&connectTimeoutMS=5000&socketTimeoutMS=5000"
       Current Mongosh Log ID: 672539985dfd872360fe6910
       Connecting to:
                               mongodb://<credentials>@mongo:27017/admin?authSource=admin&replicaSet=rs0&retryWrites=true&w=majority&readPreference=primary&connectTimeoutMS=5000&socketTimeoutMS=5000&appName=mongosh+2.3.2
       Using MongoDB:
                               8.0.3
       Using Mongosh:
                               2.3.2
       For mongosh info see: https://www.mongodb.com/docs/mongodb-shell/
 S
       To help improve our products, anonymous usage data is collected and sent to MongoDB periodically (https://www.mongodb.com/legal/privacy-policy).
       You can opt-out by running the disableTelemetry() command.
          The server generated these startup warnings when booting
          2024-11-01T19:35:37.130+00:00: Using the XFS filesystem is strongly recommended with the WiredTiger storage engine. See http://dochub.mongodb.org/core/prodnotes-filesystem
 榝
          2024-11-01T19:35:37.867+00:00: For customers running the current memory allocator, we suggest changing the contents of the following sysfsFile
          2024-11-01T19:35:37.867+00:00: For customers running the current memory allocator, we suggest changing the contents of the following sysfsFile
          2024-11-01T19:35:37.867+00:00: We suggest setting the contents of sysfsFile to 0.
          2024-11-01T19:35:37.868+00:00: Your system has glibc support for rseq built in, which is not yet supported by tcmalloc-google and has critical performance implications. Please set the environment variable GLIBC TUNABLES=glibc.
       pthread.rseq=0
          2024-11-01T19:35:37.868+00:00: vm.max map count is too low
          2024-11-01T19:35:37.868+00:00: We suggest setting swappiness to 0 or 1, as swapping can cause performance problems.
       rs0 [primary] admin> show dbs
       BookingSystem 132.00 KiB
       admin
                      140.00 KiB
       config
                      208.00 KiB
       local
                      484.00 KiB
       rs0 [primary] admin> use BookingSystem
       switched to db BookingSystem
       rs0 [primary] BookingSystem> show collections
       clients
       reservations
       rs0 [primary] BookingSystem> db.clients.find()
            id: '1001',
           NomCl: 'Becquerel',
           Adresse: {
             NumRueCl: '24',
             NomRueCl: 'Rue De Fabre',
             CodePosteCl: '13015',
             VilleCl: 'Marseille'
           Email: '',
           Telephone: ''
```