
[Public] Create and Build a Flex Web Project in Moonshine (Desktop Build)

This article expected followings before proceed


- You have Moonshine setup in your local system. If you haven't, you can follow the installation steps by going to the following links: Windows: http://moonshine-ide.com/wp-content/uploads/Moonshine.exe MacOS: http://moonshine-ide.com/wp-content/uploads/Moonshine.dmg
- 2. You have all the other requisite setups (i.e. Apache Flex SDK (http://flex.apache.org/installer.html), SVN (https://sliksvn.com/downlo ad/) optional, ANT (http://ant.apache.org) optional etc.) to proceed to next steps.

Create and Build a Project

- Start Moonshine
- Setup Apache Flex SDK in Settings
 - -- Make sure you have downloaded Apache Flex SDK with AIR SDK at http://flex.apache.org/installer.html
 - -- In Moonshine choose File -> Settings -> MXMLC Compiler Plugin



- -- In opening view click on Change link inside Default Flex SDK section, this will open you a file browser dialogue
- -- Locate the Apache Flex SDK folder (that you've downloaded) in file browser dialogue and choose Select Folder
- -- You should see Default Flex SDK is now pointing to Apache Flex SDK directory you choose
- -- Click Save
- To create a new web based Flex project do either one the following things:
 - -- In Moonshine choose File -> New -> Flex Browser Project (SWF): MXML and ActionScript support
 - -- In Moonshine choose File -> New -> ActionScript Project (SWF, Desktop): Choose this if you want pure ActionScript project
 - -- Choose New ActionScript Project (SWF, Desktop) in Moonshine splash screen
 - -- Choose Flex Browser Project (MacOS, Windows) in Moonshine splash screen
- Choosing any above option will open new project creation dialogue:



In ActionScript Project (SWF, Desktop) options you'll find an extra option to choose between Desktop and Web as output type:



Editable fields are:

- --- Project Name
- --- Project Directory

- --- Select Project Type (ActionScript Project only)
- After necessary in the fields above, click Create to generate a new Flex Web project
- Create option immediately create a new Flex project, open the project in Moonshine workspace (left-hand tree menu) and it's application file in Moonshine editor

```
NewFlexBrowserProject.mxml
                                                                                         Projects
  1| 1
| xml version="1.0" encoding="utf-8"?>
                                                                                          NewFlexBrowserProject
   <s:Application xmlns:fx="http://ns.adobe.com/mxml/2009"</pre>
                                                                                           build
                    xmlns:s="library://ns.adobe.com/flex/spark"
                                                                                              ant-contrib-0.6.jar
                    xmlns:mx="library://ns.adobe.com/flex/mx" minWidth="955" minHe
        <fx:Declarations>
                                                                                            NewFlexBrowserProject.as3proj
        </fx:Declarations>
        <fx:Script>

    NewFlexBrowserProject.mxml

            <![CDATA[
 10
 11
            ]]>
        </fx:Script>
        <s:Label fontSize="24" fontWeight="bold" textAlign="center"
            horizontalCenter="0" verticalCenter="0
 16
            text="Hello World!"/>
 18 </s:Application>
```

- Moonshine generates any project with it's supported types with demo 'Hello World! text, so you can immediately build the project and check it's output; an optional ANT build script fully configured so you build a release SWF immediately as well!
- To run the project choose Project -> Build & Run. You can see command line outputs in Moonshine's console window (at bottom)

```
: Compiling NewFlexBrowserProject
: Sending to mxmlx: mxmlc -load-config+=obj/NewFlexBrowserProjectConfig.xml -optimize=false -debug=true -o bin-debug/NewFlexBrowserProject.swf
: Apache Flex Compiler SHell (fcsh)
: Version 4.14.0 build 20150123
: Copyright 2015 The Apache Software Foundation.
: (fcsh)
: FSCH target: 1
```

If everything goes fine, Moonshine will generate the SWF and runs inside default browser window


Debug a Project

- Open the project in Moonshine that you wants to debug
- To set breakpoint (optional), open the class file in Moonshine editor and click once at far-left numbered bar to set breakpoint to any line line's numbered bar will change color to mark set as breakpoint click again to remove breakpoint:

```
*NewFlexBrowserProject.mxm
  1<?xml version="1.0" encoding="utf-8"?>
  2 <s:Application xmlns:fx="http://ns.adobe.com/mxml/2009</pre>
                   xmlns:s="library://ns.adobe.com/flex/spark"
                   xmlns:mx="library://ns.adobe.com/flex/mx" minWidth="955" minHeight="600"
                   creationComplete="testFunction()">
       <fx:Declarations>
       </fx:Declarations>
 10
       <fx:Script>
 11
            <! [CDATA]
 12
 13
                private function testFunction():void
                    trace("Method called.");
 17
           ]]>
       </fx:Script>
        <s:Label fontSize="24" fontWeight="bold" textAlign="center"
 21
            horizontalCenter="0" verticalCenter="0"
 22
            text="Hello World!"/>
 24 </s:Application>
```

(In above image breakpoint set to line# 14)

To start a debug choose *Debug -> Build & Debug* from top menus. Moonshine will start a debug session, all the debug command line
output can be viewable in bottom Moonshine *console* window, Moonshine will add a new **Debug View** at left panel, too. Debugger will
halt where breakpoint raised and current memory items will be shown in Debug View panel:



- To step over while debugging you can press F6 in keyboard or choose Debug -> Step Over
- To resume while debugging you can press F8 in keyboard or choose Debug -> Resume
- To stop/terminate debug process choose Debug -> Stop

ANT Build

- Starting an ANT build requires ANT installed in your system and setup as environment variable (http://ant.apache.org ensure ANT version meets minimum requirement of 1.9.2)
- Moonshine supplies all the requisite files for ANT build process and configured. You can immediately start an ANT build process if you already setup ANT in your system; to start an ANT build process we need to locate the ANT build script file (build.xml) prior to run the process. Moonshine supplies ANT build script file in it's project's build folder. To locate the build script file choose ANT -> Configure from top menu, in opening file browser dialogue navigate to your Flex project's folder and select build/build.xml file; click Open in browser dialogue
- To run the ANT build process choose ANT -> Build. ANT build should produce .SWF and it's HTML wrapper file set
- · Upon successful completion of the process, installer files can be located at DEPLOY folder inside build folder