



# Security Assessment

## **cBridge v2**

Nov 17th, 2021

# Table of Contents

## Summary

### Overview

[Project Summary](#)

[Audit Summary](#)

[Vulnerability Summary](#)

[Audit Scope](#)

### Findings

[GLOBAL-01 : Centralization Risk](#)

[GLOBAL-02 : Validators should have the ability to stop receiving delegations and evict delegators](#)

[BCK-01 : Unnecessary fallback function](#)

[BCK-02 : Lack of input validation](#)

[BCK-03 : Usage of `transfer\(\)` for sending Ether](#)

[BCK-04 : Uninitialized state variable](#)

[FRC-01 : Privileged Function Allows Owner to Withdraw Tokens](#)

[GCK-01 : Lack of input validation](#)

[PBC-01 : Inconsistent Solidity Version and potentially unsafe math operations](#)

[PCK-01 : Inconsistent Solidity Version and potentially unsafe math operations](#)

[PCK-02 : Lack of input validation](#)

[PCK-03 : Lack of input validation](#)

[PFC-01 : Inconsistent Solidity Version and potentially unsafe math operations](#)

[PPC-01 : Inconsistent Solidity Version and potentially unsafe math operations](#)

[PSC-01 : Inconsistent Solidity Version and potentially unsafe math operations](#)

[PSK-01 : Inconsistent Solidity Version and potentially unsafe math operations](#)

[SCK-01 : By default whitelist not enabled and hackers can block other validators from be initialized](#)

[SCK-02 : Malicious validator can block other validators from being initialized and updating signer](#)

[SCK-03 : Privileged Function Allows Owner to Withdraw Tokens](#)

[SCK-04 : Wrong variable used](#)

[SCK-05 : Wrong variable used](#)

[SCK-06 : Incorrect placement of the decentralization check](#)

[SCK-07 : Problematic condition check](#)

[SCK-08 : Validator status should not be `Null`](#)

[SCK-09 : `jailPeriod` should also apply when validator status is `Unbonding`](#)

[SCK-10 : Lack of input validation](#)

[SGN-01 : Privileged Function Allows Owner to Withdraw Tokens](#)

[SRC-01 : Privileged Function Allows Owner to Withdraw Tokens](#)

[VCK-01 : Incorrect ForLoop initial value](#)

[Appendix](#)

[Disclaimer](#)

[About](#)

# Summary

This report has been prepared for **Celer** to discover issues and vulnerabilities in the source code of the cBridge v2 project as well as any contract dependencies that were not part of an officially recognized library. A comprehensive examination has been performed, utilizing Manual Review and Static Analysis techniques.

The auditing process pays special attention to the following considerations:

- Testing the smart contracts against both common and uncommon attack vectors.
- Assessing the codebase to ensure compliance with current best practices and industry standards.
- Ensuring contract logic meets the specifications and intentions of the client.
- Cross referencing contract structure and implementation against similar smart contracts produced by industry leaders.
- Thorough line-by-line manual review of the entire codebase by industry experts.

The security assessment resulted in findings that ranged from critical to informational. We recommend addressing these findings to ensure a high level of security standards and industry practices. We suggest recommendations that could better serve the project from the security perspective:

- Enhance general coding practices for better structures of source codes;
- Add enough unit tests to cover the possible use cases;
- Provide more comments per each function for readability, especially contracts that are verified in public;
- Provide more transparency on privileged activities once the protocol is live.

# Overview

## Project Summary

Project Name	cBridge v2
Description	State Guardian Network from <b>Celer</b> Network
Platform	CosmosSDK, <b>Celer</b> Network
Language	Solidity
Codebase	<a href="https://github.com/celer-network/sgn-v2-contracts/tree/803e5377cfe6142c049a6f5067825272a7e73b6f">https://github.com/celer-network/sgn-v2-contracts/tree/803e5377cfe6142c049a6f5067825272a7e73b6f</a>
Commit	803e5377cfe6142c049a6f5067825272a7e73b6f bad4774b43c5e8abee81b9399fb3fca75d22e61e eaae4e2d705cbb5025c9e7b1ec9040b126122a6 a436e2e1d88d320c4bcfe831d23ac325a214e003 5e9cf3159f86c4d2a8695742e5051374cf10bf58 c5766f5d10594661198491d3235ea22c6dffc327

## Audit Summary

Delivery Date	Nov 17, 2021
Audit Methodology	Manual Review, Static Analysis
Key Components	

## Vulnerability Summary

Vulnerability Level	Total	⚠ Pending	⊗ Declined	ℹ Acknowledged	🔄 Partially Resolved	✓ Resolved
● Critical	0	0	0	0	0	0
● Major	7	0	0	7	0	0
● Medium	9	0	0	4	0	5
● Minor	13	0	0	2	0	11
● Informational	0	0	0	0	0	0
● Discussion	0	0	0	0	0	0

## Audit Scope

ID	File	SHA256 Checksum
ISV	interfaces/ISigsVerifier.sol	c305e9f3f4b1179005494f7ee4262e8ac5532fd0d70c17c5b0e7926d017ea1e8
REA	libraries/proto/README.md	9b872eddde04db2b1cc671530beadcc7c2e465756efe4b4df621df66f6292aed
BRI	libraries/proto/bridge.proto	848501ecd3a2331bea320906162c6d3f5d7ffeb1a889e95ed62ec6e2d23652a0
FAR	libraries/proto/farming.proto	ff30bf43bfaaaea9aba23e97c423e2178fb0329c3af1b19d96b8cd73d3578e7a
POO	libraries/proto/pool.proto	0188e88bbf2a89c0ace97cf73472b2716b50a8b1c5739ce965f27407f4e25b25
SGN	libraries/proto/sgn.proto	4af43f06f23a5756a8f7983d7aa0882be46e23166962a7794ab1934c61a21fa3
STA	libraries/proto/staking.proto	3f91795ee52894f10dcdb0f9e49c832e2723f48da5738369454a0d29e0d14510
DTC	libraries/DataTypes.sol	c3d63e448008855a9eaff5c48eea02dd39e1c9a924dc5397cdfb233ae742791e
PCK	libraries/Pb.sol	7d86a7759dfaf99794b7cd50202151688e4d25682bf99a8ecc04fc5a18ffd59b
PBC	libraries/PbBridge.sol	723d3762e267019ebe8d4402ce207b8fcc3ad578f9f96eaaab7729802d3ded814
PFC	libraries/PbFarming.sol	a3b326e9990f2db0101b3724b12560ccb7cd364294ca6580f1eaba7dfba8c646
PPC	libraries/PbPool.sol	6b9303c804816ebf253fbb1d1a65e7b09268e29c2c8b0c42613b62425642da1c
PSC	libraries/PbSgn.sol	eb157a132d45300aef958a6501f9d8891c0218dcf9f6a3e13f373a2ee05f6b1e
PSK	libraries/PbStaking.sol	fe04d84b66e908fc2346cf3df633f010569a0fbe5e19da2b328a06e1ecce1011
FCK	test-helpers/Faucet.sol	c197173ef37726d24f544d43ef51e3913c85eac1920703faa44d485d74a67ef8
MER	test-helpers/MintableERC20.sol	1d4ceef52513a5843cfb30a9d07b29ebc5a9d905faeb4b2e6dbb24d3d86c98dd
TER	test-helpers/TestERC20.sol	dfe34d8aee4afb0a6428af281bbd4068ae78ae9c968f77290e65919022fe10b6
BCK	Bridge.sol	3c80d0f61157666347beff31a32e0dbd8682657fb7862b537edd17f0ec035372
FRC	FarmingRewards.sol	44f67695143b5fcd7557c48c6d8fd90c9a21eacbe46734a756fd6cee3b006d2
GCK	Govern.sol	99a3813586e868b1f9669b1d6ef759831c4d16aeaf1fe668d271d1a9bbbbcf02
PCP	Pool.sol	ac1ff669e9e04cdfc6cfdbf71a7ce1a7cb93d67b119769ce039b824c55f8b00d
SGC	SGN.sol	dfb1b697ce57be1706d87e12928d3fc69540e3c7460aea4518f978323f888eb3

ID	File	SHA256 Checksum
SCK	Signers.sol	9f769048bb6a734859cac0913d0c4da6703e32eb9813a51863c9076eeec2b6ee
SCP	Staking.sol	1630e7d92d29db87873bcee964ece01d078e72588e636b7b6ec36cb8500a2511
SRC	StakingReward.sol	d7bb33ba9a86fdd9c283de1a94e57df648797ecfcfdb7b666f635adc81f37f89
VCK	Viewer.sol	f8b7fba41466a45e76d537516e098d29f50bc6b50216c9f23f3fe9051db6a6aa
WCK	Whitelist.sol	e38844661760e2d247e7e0179f789d1b76216c5801aa601b72e5ca1c0888f9d0



# Findings



Critical	0 (0.00%)
Major	7 (24.14%)
Medium	9 (31.03%)
Minor	13 (44.83%)
Informational	0 (0.00%)
Discussion	0 (0.00%)

ID	Title	Category	Severity	Status
GLOBAL-01	Centralization Risk	Centralization / Privilege	Major	ⓘ Acknowledged
GLOBAL-02	Validators should have the ability to stop receiving delegations and evict delegators	Logical Issue	Medium	ⓘ Acknowledged
BCK-01	Unnecessary fallback function	Language Specific	Minor	✓ Resolved
BCK-02	Lack of input validation	Logical Issue	Minor	ⓘ Acknowledged
BCK-03	Usage of <code>transfer()</code> for sending Ether	Volatile Code	Minor	✓ Resolved
BCK-04	Uninitialized state variable	Volatile Code	Medium	ⓘ Acknowledged
FRC-01	Privileged Function Allows Owner to Withdraw Tokens	Centralization / Privilege	Major	ⓘ Acknowledged
GCK-01	Lack of input validation	Logical Issue	Minor	✓ Resolved
PBC-01	Inconsistent Solidity Version and potentially unsafe math operations	Mathematical Operations, Inconsistency	Minor	✓ Resolved
PCK-01	Inconsistent Solidity Version and potentially unsafe math operations	Mathematical Operations, Inconsistency	Minor	✓ Resolved
PCK-02	Lack of input validation	Logical Issue	Medium	ⓘ Acknowledged
PCK-03	Lack of input validation	Logical Issue	Medium	ⓘ Acknowledged

ID	Title	Category	Severity	Status
PFC-01	Inconsistent Solidity Version and potentially unsafe math operations	Mathematical Operations, Inconsistency	Minor	Resolved
PPC-01	Inconsistent Solidity Version and potentially unsafe math operations	Mathematical Operations, Inconsistency	Minor	Resolved
PSC-01	Inconsistent Solidity Version and potentially unsafe math operations	Mathematical Operations, Inconsistency	Minor	Resolved
PSK-01	Inconsistent Solidity Version and potentially unsafe math operations	Mathematical Operations, Inconsistency	Minor	Resolved
SCK-01	By default whitelist not enabled and hackers can block other validators from be initialized	Logical Issue	Major	Acknowledged
SCK-02	Malicious validator can block other validators from being initialized and updating signer	Logical Issue	Major	Acknowledged
<b>SCK-03</b>	Privileged Function Allows Owner to Withdraw Tokens	<b>Centralization / Privilege</b>	<b>Major</b>	Acknowledged
SCK-04	Wrong variable used	Logical Issue	Medium	Resolved
SCK-05	Wrong variable used	Logical Issue	Medium	Resolved
SCK-06	Incorrect placement of the decentralization check	Logical Issue	Medium	Resolved
SCK-07	Problematic condition check	Logical Issue	Minor	Resolved
SCK-08	Validator status should not be <code>Null</code>	Logical Issue	Minor	Resolved
SCK-09	<code>jailPeriod</code> should also apply when validator status is <code>Unbonding</code>	Logical Issue	Medium	Resolved
SCK-10	Lack of input validation	Logical Issue	Minor	Acknowledged
<b>SGN-01</b>	Privileged Function Allows Owner to Withdraw Tokens	<b>Centralization / Privilege</b>	<b>Major</b>	Acknowledged

ID	Title	Category	Severity	Status
SRC-01	Privileged Function Allows Owner to Withdraw Tokens	Centralization / Privilege	● Major	ⓘ Acknowledged
VCK-01	Incorrect ForLoop initial value	Logical Issue	● Medium	☑ Resolved

## GLOBAL-01 | Centralization Risk

Category	Severity	Location	Status
Centralization / Privilege	● Major	Global	ⓘ Acknowledged

### Description

In the contract `[Signers.sol]`, the role `[owner]` has the authority over the following function:

- `[resetSigners()]`
- `[notifyResetSigners()]`
- `[increaseNoticePeriod()]`

In the contract `[Bridge.sol]`, the role `[owner]` has the authority over the following function:

- `[setMinSend()]`
- `[setMinSlippage()]`
- `[setWrap()]`

Any compromise to the `[owner]` account may allow the hacker to take advantage of this and make the contract malfunction, change signers at will, make the contract invoke malicious code.

### Recommendation

We advise the client to carefully manage the `[owner]` account's private key to avoid any potential risks of being hacked. In general, we strongly recommend centralized privileges or roles in the protocol to be improved via a decentralized mechanism or smart-contract-based accounts with enhanced security practices, e.g., Multisignature wallets.

Indicatively, here is some feasible suggestions that would also mitigate the potential risk at the different level in term of short-term and long-term:

- Time-lock with reasonable latency, e.g., 48 hours, for awareness on privileged operations;
- Assignment of privileged roles to multi-signature wallets to prevent a single point of failure due to the private key;
- Introduction of a DAO/governance/voting module to increase transparency and user involvement.

### Alleviation

**[Celer team]:** "We plan to start with a guarded launch mode, for which we have a hardware wallet owner account to handle emergencies if there are any. The owner role will be revoked or transferred to a

governance contract when the mainnet is proven secure and stable."

## GLOBAL-02 | Validators should have the ability to stop receiving delegations and evict delegators

Category	Severity	Location	Status
Logical Issue	● Medium	Global	ⓘ Acknowledged

### Description

To prevent decentralization check failure, validators should have the ability to stop receiving delegations and evict delegators. Otherwise, malicious delegators can intentionally delegate a large number of tokens such that victim validators can not become bonded.

### Recommendation

We advise the client to add functionality to `Staking.sol` to allow validators to stop receiving delegations and to evict delegators.

### Alleviation

**[Celer team]:** "This “attack” requires the malicious delegators to delegate a very large amount of tokens to an unbonded validator, just for the purpose to block a validator candidate from becoming bonded. Such an attack costs the attacker lots of liquidity, while not introducing any risk to the availability of sgn chain or fund security of any party. Therefore we believe it is less of a concern and decide to keep the code as it is."

## BCK-01 | Unnecessary fallback function

Category	Severity	Location	Status
Language Specific	● Minor	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/contracts/Bridge.sol (aad51fc): 131	🟢 Resolved

### Description

The fallback function in the `Bridge.sol` contract is unnecessary since there is already `receive()` function to receive ethers. And fallback function will make calling non-existing functions of the contract always succeed which may not be desired behavior.

### Recommendation

Consider removing the fallback function in the `Bridge.sol` contract.

### Alleviation

Fixed in commit `bad4774b43c5e8abee81b9399fb3fca75d22e61e`.

## BCK-02 | Lack of input validation

Category	Severity	Location	Status
Logical Issue	Minor	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/c ontracts/Bridge.sol (aad51fc): 54	ⓘ Acknowledged

### Description

Based on bridge functionality, destination chain ID should not be current chain ID.

### Recommendation

We advise the client to add a check to make sure destination chain ID is not current chain ID.

### Alleviation

**[Celer team]:** "This is checked in the tendermint based SGN chan. If chain IDs are different, transfers will be refunded. We keep the code as it is to make the hardhat unitests easier."



## BCK-03 | Usage of `transfer()` for sending Ether

Category	Severity	Location	Status
Volatile Code	Minor	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/contracts/Bridge.sol (aad51fc): 97	✓ Resolved

### Description

After [EIP-1884](#) was included in the Istanbul hard fork, it is not recommended to use `.transfer()` or `.send()` for transferring ether as these functions have a hard-coded value for gas costs making them obsolete as they are forwarding a fixed amount of gas, specifically `2300`. This can cause issues in case the linked statements are meant to be able to transfer funds to other contracts instead of EOAs.

### Recommendation

We advise the client to use the `sendValue()` function in Openzeppelin `Address` library.  
(<https://github.com/OpenZeppelin/openzeppelin-contracts/blob/v4.3.2/contracts/utils/Address.sol>)

### Alleviation

Fixed in commit `bad4774b43c5e8abee81b9399fb3fca75d22e61e`.

## BCK-04 | Uninitialized state variable

Category	Severity	Location	Status
Volatile Code	● Medium	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/contracts/Bridge.sol (aad51fc): 94	ⓘ Acknowledged

### Description

After the contract `Bridge` is deployed, by default `nativeWrap` is not initialized. It may cause malfunction of function `relay()`: sending erc20 tokens instead of chain native tokens.

### Recommendation

We advise the client to add a constructor to initialize `nativeWrap`.

### Alleviation

**[Celer team]:** "All parameters should be set correctly before the contract starts to be used (i.e., hold assets). This could be verified by anyone who wants to use the contract."

## FRC-01 | Privileged Function Allows Owner to Withdraw Tokens

Category	Severity	Location	Status
Centralization / Privilege	● Major	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/contracts/FarmingRewards.sol (aad51fc): 94, 84, 76	① Acknowledged

### Description

In the contract `[FarmingRewards]`, the role `[owner]` has the authority over the following function:

- `[pause()]`
- `[unpause()]`
- `[drainToken()]`

Any compromise to the `[owner]` account may allow the hacker to take advantage of this and make the contract malfunction, steal funds from the contract.

### Recommendation

We advise the client to carefully manage the `[owner]` account's private key to avoid any potential risks of being hacked. In general, we strongly recommend centralized privileges or roles in the protocol to be improved via a decentralized mechanism or smart-contract-based accounts with enhanced security practices, e.g., Multisignature wallets.

Indicatively, here is some feasible suggestions that would also mitigate the potential risk at the different level in term of short-term and long-term:

- Time-lock with reasonable latency, e.g., 48 hours, for awareness on privileged operations;
- Assignment of privileged roles to multi-signature wallets to prevent a single point of failure due to the private key;
- Introduction of a DAO/governance/voting module to increase transparency and user involvement.

### Alleviation

**[Celer team]:** "We plan to start with a guarded launch mode, for which we have a hardware wallet owner account to handle emergencies if there are any. The owner role will be revoked or transferred to a governance contract when the mainnet is proven secure and stable."

## GCK-01 | Lack of input validation

Category	Severity	Location	Status
Logical Issue	● Minor	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/contracts/Govern.sol (aad51fc): 107	🟢 Resolved

### Description

The function parameter `_vote` should not be `Null`.

### Recommendation

We advise the client to add a check to make sure `_vote` is not `VoteOption.Null`.

### Alleviation

Fixed in commit `bad4774b43c5e8abee81b9399fb3fca75d22e61e`.

## PBC-01 | Inconsistent Solidity Version and potentially unsafe math operations

Category	Severity	Location	Status
Mathematical Operations, Inconsistency	● Minor	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/contracts/libraries/PbBridge.sol (aad51fc): 5	🟢 Resolved

### Description

The solidity versions in Pb.sol, PbBridge.sol, PbFarming.sol, PbPool.sol, PbSgn.sol, PbStaking.sol are `>=0.5.0`, while other contracts are using `0.8.9`. If the solidity version is below `0.8.0`, native math operations are not safe because overflow/underflow is not checked.

### Recommendation

It is okay to try different compiler versions during the development stage. However, we recommend locking the solidity version when it reaches the production stage, and in this case, 0.8.9 should be used.

### Alleviation

Fixed in commit `bad4774b43c5e8abee81b9399fb3fca75d22e61e`.

## PCK-01 | Inconsistent Solidity Version and potentially unsafe math operations

Category	Severity	Location	Status
Mathematical Operations, Inconsistency	Minor	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/contracts/libraries/Pb.sol (aad51fc): 3	Resolved

### Description

The solidity versions in Pb.sol, PbBridge.sol, PbFarming.sol, PbPool.sol, PbSgn.sol, PbStaking.sol are `>=0.5.0`, while other contracts are using `0.8.9`. If the solidity version is below `0.8.0`, native math operations are not safe because overflow/underflow is not checked.

### Recommendation

It is okay to try different compiler versions during the development stage. However, we recommend locking the solidity version when it reaches the production stage, and in this case, 0.8.9 should be used.

### Alleviation

Fixed in commit `bad4774b43c5e8abee81b9399fb3fca75d22e61e`.

## PCK-02 | Lack of input validation

Category	Severity	Location	Status
Logical Issue	● Medium	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6 f/contracts/libraries/Pb.sol (aad51fc): 71~72	① Acknowledged

### Description

The function `decVarint()` does not check if `buf.idx` plus length of decoded data is bigger than `buf.b.length`. If it is true, the input parameter `buf` is malformed.

### Recommendation

We advise the client to add a check to make sure `buf.idx <= buf.b.length` before return.

### Alleviation

**[Celer team]:** "This does not have real risk because: 1) malformed msg won't be signed 2) overflow is checked at the beginning of each decode."

## PCK-03 | Lack of input validation

Category	Severity	Location	Status
Logical Issue	● Medium	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/contracts/libraries/Pb.sol (aad51fc): 108~111	① Acknowledged

### Description

After decoding data, `buf.idx` should be equal to `end`. Otherwise, the input parameter `buf` is malformed.

### Recommendation

We advise the client to add a check to make sure `buf.idx == end` after decoding data.

### Alleviation

**[Celer team]:** "This does not have real risk because: 1) malformed msg won't be signed 2) overflow is checked at the beginning of each decode."



## PFC-01 | Inconsistent Solidity Version and potentially unsafe math operations

Category	Severity	Location	Status
Mathematical Operations, Inconsistency	● Minor	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/contracts/libraries/PbFarming.sol (aad51fc): 5	🟢 Resolved

### Description

The solidity versions in Pb.sol, PbBridge.sol, PbFarming.sol, PbPool.sol, PbSgn.sol, PbStaking.sol are `>=0.5.0`, while other contracts are using `0.8.9`. If the solidity version is below `0.8.0`, native math operations are not safe because overflow/underflow is not checked.

### Recommendation

It is okay to try different compiler versions during the development stage. However, we recommend locking the solidity version when it reaches the production stage, and in this case, 0.8.9 should be used.

### Alleviation

Fixed in commit `bad4774b43c5e8abee81b9399fb3fca75d22e61e`.

## PPC-01 | Inconsistent Solidity Version and potentially unsafe math operations

Category	Severity	Location	Status
Mathematical Operations, Inconsistency	● Minor	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/contracts/libraries/PbPool.sol (aad51fc): 5	🟢 Resolved

### Description

The solidity versions in Pb.sol, PbBridge.sol, PbFarming.sol, PbPool.sol, PbSgn.sol, PbStaking.sol are `>=0.5.0`, while other contracts are using `0.8.9`. If the solidity version is below `0.8.0`, native math operations are not safe because overflow/underflow is not checked.

### Recommendation

It is okay to try different compiler versions during the development stage. However, we recommend locking the solidity version when it reaches the production stage, and in this case, 0.8.9 should be used.

### Alleviation

Fixed in commit `bad4774b43c5e8abee81b9399fb3fca75d22e61e`.

## PSC-01 | Inconsistent Solidity Version and potentially unsafe math operations

Category	Severity	Location	Status
Mathematical Operations, Inconsistency	● Minor	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/contracts/libraries/PbStaking.sol (aad51fc): 5	🟢 Resolved

### Description

The solidity versions in Pb.sol, PbBridge.sol, PbFarming.sol, PbPool.sol, PbSgn.sol, PbStaking.sol are `>=0.5.0`, while other contracts are using `0.8.9`. If the solidity version is below `0.8.0`, native math operations are not safe because overflow/underflow is not checked.

### Recommendation

It is okay to try different compiler versions during the development stage. However, we recommend locking the solidity version when it reaches the production stage, and in this case, 0.8.9 should be used.

### Alleviation

Fixed in commit `bad4774b43c5e8abee81b9399fb3fca75d22e61e`.

## PSK-01 | Inconsistent Solidity Version and potentially unsafe math operations

Category	Severity	Location	Status
Mathematical Operations, Inconsistency	Minor	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/contracts/libraries/PbSgn.sol (aad51fc): 5	Resolved

### Description

The solidity versions in Pb.sol, PbBridge.sol, PbFarming.sol, PbPool.sol, PbSgn.sol, PbStaking.sol are `>=0.5.0`, while other contracts are using `0.8.9`. If the solidity version is below `0.8.0`, native math operations are not safe because overflow/underflow is not checked.

### Recommendation

It is okay to try different compiler versions during the development stage. However, we recommend locking the solidity version when it reaches the production stage, and in this case, 0.8.9 should be used.

### Alleviation

Fixed in commit `bad4774b43c5e8abee81b9399fb3fca75d22e61e`.

## SCK-01 | By default whitelist not enabled and hackers can block other validators from be initialized

Category	Severity	Location	Status
Logical Issue	● Major	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/c ontracts/Staking.sol (aad51fc): 102, 110~111, 105	ⓘ Acknowledged

### Description

After the `Staking` contract is deployed, by default whitelist is not enabled. Anyone can call the `initializeValidator()` function and become a validator. Hackers can specify a victim validator address or the signer address of a victim validator as the `_signer` parameter. Then it will fail when the victim validator calls the function.

### Recommendation

We advise the client to enable whitelist by default, require crypto signature from signer to prove the relationship between validator and signer.

### Alleviation

**[Celer team]:** "Whitelist will be enabled right after the contract is deployed. Hackers are not incentivized to hack a contract without any tokens."

## SCK-02 | Malicious validator can block other validators from being initialized and updating signer

Category	Severity	Location	Status
Logical Issue	● Major	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/c ontracts/Staking.sol (aad51fc): 129, 133	ⓘ Acknowledged

### Description

A malicious validator can call function `updateValidatorSigner()` and specify a victim validator address or the signer address of a victim validator as the `_signer` parameter. Then it will fail when the victim validator tries to call function `initializeValidator()` or `updateValidatorSigner()`.

### Recommendation

We advise the client to require crypto signature from signer to prove the relationship between validator and signer.

### Alleviation

**[Celer team]:** "This could prevent some other address to become a signer, but could not pose fund security risks or system availability issues to any party."

## SCK-03 | Privileged Function Allows Owner to Withdraw Tokens

Category	Severity	Location	Status
Centralization / Privilege	● Major	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e7 3b6f/contracts/Staking.sol (aad51fc): 479, 470, 462, 454, 447, 440, 433, 425, 420	① Acknowledged

### Description

In the contract `[Staking.sol]`, the role `[owner]` has the authority over the following function:

- `[pause()]`
- `[unpause()]`
- `[drainToken()]`
- `[setGovContract()]`
- `[setRewardContract()]`
- `[setWhitelistEnabled()]`
- `[addWhitelisted()]`
- `[removeWhitelisted()]`
- `[setMaxSlashFactor()]`

Any compromise to the `[owner]` account may allow the hacker to take advantage of this and make the contract malfunction, steal funds from the contract.

### Recommendation

We advise the client to carefully manage the `[owner]` account's private key to avoid any potential risks of being hacked. In general, we strongly recommend centralized privileges or roles in the protocol to be improved via a decentralized mechanism or smart-contract-based accounts with enhanced security practices, e.g., Multisignature wallets.

Indicatively, here is some feasible suggestions that would also mitigate the potential risk at the different level in term of short-term and long-term:

- Time-lock with reasonable latency, e.g., 48 hours, for awareness on privileged operations;
- Assignment of privileged roles to multi-signature wallets to prevent a single point of failure due to the private key;
- Introduction of a DAO/governance/voting module to increase transparency and user involvement.

### Alleviation

**[Celer team]:** "We plan to start with a guarded launch mode, for which we have a hardware wallet owner account to handle emergencies if there are any. The owner role will be revoked or transferred to a governance contract when the mainnet is proven secure and stable."



## SCK-04 | Wrong variable used

Category	Severity	Location	Status
Logical Issue	● Medium	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/contracts/Staking.sol (aad51fc): 579	🟢 Resolved

### Description

The function `getBondedValidatorsTokens()` is intended to return information about bonded validators, not all validators.

The current implementation in line 579 consist the bug and makes the function allocate excessive array memory for all validators, and many elements in the returned array are empty and wasted.

```
1 function getBondedValidatorsTokens() public view returns (dt.ValidatorTokens[]  
memory) {  
2     dt.ValidatorTokens[] memory infos = new dt.ValidatorTokens[]  
(valAddrs.length);  
3     ...  
4     return infos;  
5 }
```

### Recommendation

We advise the client to use the `bondedValAddrs.length` in line 579.

### Alleviation

Fixed in commit `bad4774b43c5e8abee81b9399fb3fca75d22e61e`.

## SCK-05 | Wrong variable used

Category	Severity	Location	Status
Logical Issue	● Medium	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/contracts/Staking.sol (aad51fc): 623	🟢 Resolved

### Description

In the function `getDelegatorInfo()`, the line 623 is calculating the total of `undelegationShares`, however the current implementation is using the variable `d.undelegations.queue`, which is an outdated value that might lead to incorrect result.

```
621 for (uint256 i = 0; i < len; i++) {  
622     undelegations[i] = d.undelegations.queue[i + d.undelegations.head];  
623     undelegationShares += d.undelegations.queue[i].shares;  
624 }  
625
```

### Recommendation

We advise the client to use `undelegations` instead of `d.undelegations.queue` in line 623.

### Alleviation

Fixed in commit `bad4774b43c5e8abee81b9399fb3fca75d22e61e`.

## SCK-06 | Incorrect placement of the decentralization check

Category	Severity	Location	Status
Logical Issue	● Medium	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/contracts/Staking.sol (aad51fc): 168	🟢 Resolved

### Description

Decentralization check should be done before the function returns because a single bonded validator should not have excessive voting power.

### Recommendation

We advise the client to call `_decentralizationCheck()` before return.

### Alleviation

Fixed in commit `bad4774b43c5e8abee81b9399fb3fca75d22e61e`.

## SCK-07 | Problematic condition check

Category	Severity	Location	Status
Logical Issue	● Minor	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/contracts/Staking.sol (aad51fc): 236	🟢 Resolved

### Description

If a delegator delegates 1.9 shares, then undelegates 1 share. After that he/she can never undelegate the left 0.9 share.

### Recommendation

We advise the client to modify the check to accommodate the situation describe above.

### Alleviation

Fixed in commit hash `eaae4e2d705cbbe5025c9e7b1ec9040b126122a6`.

## SCK-08 | Validator status should not be `Null`

Category	Severity	Location	Status
Logical Issue	● Minor	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/contracts/Staking.sol (aad51fc): 354	✓ Resolved

### Description

Based on the context, the validator status should not be `Unbonded` or `Null`.

### Recommendation

We advise the client to add a check to make sure validator status is not `Null`.

### Alleviation

Fixed in commit `bad4774b43c5e8abee81b9399fb3fca75d22e61e`.

## SCK-09 | `jailPeriod` should also apply when validator status is `Unbonding`

Category	Severity	Location	Status
Logical Issue	● Medium	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/contracts/Staking.sol (aad51fc): 363~365	✓ Resolved

### Description

`jailPeriod` should also apply when validator status is `Unbonding`. Otherwise, the slashed validator can become bonded immediately.

### Recommendation

We advise the client to update `validator.bondBlock` when validator status is `Unbonding`.

### Alleviation

Fixed in commit hash `bad4774b43c5e8abee81b9399fb3fca75d22e61e`.

## SCK-10 | Lack of input validation

Category	Severity	Location	Status
Logical Issue	Minor	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/c ontracts/Staking.sol (aad51fc): 74	ⓘ Acknowledged

### Description

According to the comment line, the max slashing value `_maxSlashFactor` is `dt.SLASH_FACTOR_DECIMAL`, however there is no require check for ensuring the `_maxSlashFactor` range.

```
62 * @param _maxSlashFactor maximal slashing factor (1e6 = 100%)
```

### Recommendation

We advise the client to ensure the variable `_maxSlashFactor <= dt.SLASH_FACTOR_DECIMAL`.

### Alleviation

**[Celer team]:** "With current logic, `maxSlashFactor > SLASH_FACTOR_DECIMAL` is equivalent to `maxSlashFactor = 100%`"

## SGN-01 | Privileged Function Allows Owner to Withdraw Tokens

Category	Severity	Location	Status
Centralization / Privilege	● Major	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/contracts/SGN.sol (aad51fc): 101, 93, 110	① Acknowledged

### Description

In the contract `[SGN.sol]`, the role `[owner]` has the authority over the following function:

- `[pause()]`
- `[unpause()]`
- `[drainToken()]`

Any compromise to the `[owner]` account may allow the hacker to take advantage of this and make the contract malfunction, steal funds from the contract.

### Recommendation

We advise the client to carefully manage the `[owner]` account's private key to avoid any potential risks of being hacked. In general, we strongly recommend centralized privileges or roles in the protocol to be improved via a decentralized mechanism or smart-contract-based accounts with enhanced security practices, e.g., Multisignature wallets.

Indicatively, here is some feasible suggestions that would also mitigate the potential risk at the different level in term of short-term and long-term:

- Time-lock with reasonable latency, e.g., 48 hours, for awareness on privileged operations;
- Assignment of privileged roles to multi-signature wallets to prevent a single point of failure due to the private key;
- Introduction of a DAO/governance/voting module to increase transparency and user involvement.

### Alleviation

**[Celer team]:** "We plan to start with a guarded launch mode, for which we have a hardware wallet owner account to handle emergencies if there are any. The owner role will be revoked or transferred to a governance contract when the mainnet is proven secure and stable."



## SRC-01 | Privileged Function Allows Owner to Withdraw Tokens

Category	Severity	Location	Status
Centralization / Privilege	● Major	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/contracts/StakingReward.sol (aad51fc): 68, 60, 77	① Acknowledged

### Description

In the contract `[StakingReward.sol]`, the role `[owner]` has the authority over the following function:

- `[pause()]`
- `[unpause()]`
- `[drainToken()]`

Any compromise to the `[owner]` account may allow the hacker to take advantage of this and make the contract malfunction, stealing funds from the contract.

### Recommendation

We advise the client to carefully manage the `[owner]` account's private key to avoid any potential risks of being hacked. In general, we strongly recommend centralized privileges or roles in the protocol to be improved via a decentralized mechanism or smart-contract-based accounts with enhanced security practices, e.g., Multisignature wallets.

Indicatively, here is some feasible suggestions that would also mitigate the potential risk at the different level in term of short-term and long-term:

- Time-lock with reasonable latency, e.g., 48 hours, for awareness on privileged operations;
- Assignment of privileged roles to multi-signature wallets to prevent a single point of failure due to the private key;
- Introduction of a DAO/governance/voting module to increase transparency and user involvement.

### Alleviation

**[Celer team]:** "We plan to start with a guarded launch mode, for which we have a hardware wallet owner account to handle emergencies if there are any. The owner role will be revoked or transferred to a governance contract when the mainnet is proven secure and stable."

## VCK-01 | Incorrect ForLoop initial value

Category	Severity	Location	Status
Logical Issue	● Medium	projects/sgn-v2-contracts-803e5377cfe6142c049a6f5067825272a7e73b6f/contracts/Viewer.sol (aad51fc): 106	🟢 Resolved

### Description

If `i` starts from 1, the `tokens` value from bonded validator 0 is not checked. Then the calculation of return value may be wrong.

### Recommendation

We advise the client to use 0 as the initial value of `i`.

### Alleviation

Fixed in commit `bad4774b43c5e8abee81b9399fb3fca75d22e61e`.

# Appendix

## Finding Categories

### Centralization / Privilege

Centralization / Privilege findings refer to either feature logic or implementation of components that act against the nature of decentralization, such as explicit ownership or specialized access roles in combination with a mechanism to relocate funds.

### Mathematical Operations

Mathematical Operation findings relate to mishandling of math formulas, such as overflows, incorrect operations etc.

### Logical Issue

Logical Issue findings detail a fault in the logic of the linked code, such as an incorrect notion on how `block.timestamp` works.

### Volatile Code

Volatile Code findings refer to segments of code that behave unexpectedly on certain edge cases that may result in a vulnerability.

### Language Specific

Language Specific findings are issues that would only arise within Solidity, i.e. incorrect usage of `private` or `delete`.

### Inconsistency

Inconsistency findings refer to functions that should seemingly behave similarly yet contain different code, such as a constructor assignment imposing different require statements on the input variables than a setter function.

## Checksum Calculation Method

The "Checksum" field in the "Audit Scope" section is calculated as the SHA-256 (Secure Hash Algorithm 2 with digest size of 256 bits) digest of the content of each file hosted in the listed source repository under the specified commit.

The result is hexadecimal encoded and is the same as the output of the Linux "sha256sum" command against the target file.

# Disclaimer

This report is subject to the terms and conditions (including without limitation, description of services, confidentiality, disclaimer and limitation of liability) set forth in the Services Agreement, or the scope of services, and terms and conditions provided to you (“Customer” or the “Company”) in connection with the Agreement. This report provided in connection with the Services set forth in the Agreement shall be used by the Company only to the extent permitted under the terms and conditions set forth in the Agreement. This report may not be transmitted, disclosed, referred to or relied upon by any person for any purposes, nor may copies be delivered to any other person other than the Company, without CertiK’s prior written consent in each instance.

This report is not, nor should be considered, an “endorsement” or “disapproval” of any particular project or team. This report is not, nor should be considered, an indication of the economics or value of any “product” or “asset” created by any team or project that contracts CertiK to perform a security assessment. This report does not provide any warranty or guarantee regarding the absolute bug-free nature of the technology analyzed, nor do they provide any indication of the technologies proprietors, business, business model or legal compliance.

This report should not be used in any way to make decisions around investment or involvement with any particular project. This report in no way provides investment advice, nor should be leveraged as investment advice of any sort. This report represents an extensive assessing process intending to help our customers increase the quality of their code while reducing the high level of risk presented by cryptographic tokens and blockchain technology.

Blockchain technology and cryptographic assets present a high level of ongoing risk. CertiK’s position is that each company and individual are responsible for their own due diligence and continuous security. CertiK’s goal is to help reduce the attack vectors and the high level of variance associated with utilizing new and consistently changing technologies, and in no way claims any guarantee of security or functionality of the technology we agree to analyze.

The assessment services provided by CertiK is subject to dependencies and under continuing development. You agree that your access and/or use, including but not limited to any services, reports, and materials, will be at your sole risk on an as-is, where-is, and as-available basis. Cryptographic tokens are emergent technologies and carry with them high levels of technical risk and uncertainty. The assessment reports could include false positives, false negatives, and other unpredictable results. The services may access, and depend upon, multiple layers of third-parties.

ALL SERVICES, THE LABELS, THE ASSESSMENT REPORT, WORK PRODUCT, OR OTHER MATERIALS, OR ANY PRODUCTS OR RESULTS OF THE USE THEREOF ARE PROVIDED “AS IS” AND “AS

AVAILABLE” AND WITH ALL FAULTS AND DEFECTS WITHOUT WARRANTY OF ANY KIND. TO THE MAXIMUM EXTENT PERMITTED UNDER APPLICABLE LAW, CERTIK HEREBY DISCLAIMS ALL WARRANTIES, WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE WITH RESPECT TO THE SERVICES, ASSESSMENT REPORT, OR OTHER MATERIALS. WITHOUT LIMITING THE FOREGOING, CERTIK SPECIFICALLY DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE AND NON-INFRINGEMENT, AND ALL WARRANTIES ARISING FROM COURSE OF DEALING, USAGE, OR TRADE PRACTICE. WITHOUT LIMITING THE FOREGOING, CERTIK MAKES NO WARRANTY OF ANY KIND THAT THE SERVICES, THE LABELS, THE ASSESSMENT REPORT, WORK PRODUCT, OR OTHER MATERIALS, OR ANY PRODUCTS OR RESULTS OF THE USE THEREOF, WILL MEET CUSTOMER’S OR ANY OTHER PERSON’S REQUIREMENTS, ACHIEVE ANY INTENDED RESULT, BE COMPATIBLE OR WORK WITH ANY SOFTWARE, SYSTEM, OR OTHER SERVICES, OR BE SECURE, ACCURATE, COMPLETE, FREE OF HARMFUL CODE, OR ERROR-FREE. WITHOUT LIMITATION TO THE FOREGOING, CERTIK PROVIDES NO WARRANTY OR UNDERTAKING, AND MAKES NO REPRESENTATION OF ANY KIND THAT THE SERVICE WILL MEET CUSTOMER’S REQUIREMENTS, ACHIEVE ANY INTENDED RESULTS, BE COMPATIBLE OR WORK WITH ANY OTHER SOFTWARE, APPLICATIONS, SYSTEMS OR SERVICES, OPERATE WITHOUT INTERRUPTION, MEET ANY PERFORMANCE OR RELIABILITY STANDARDS OR BE ERROR FREE OR THAT ANY ERRORS OR DEFECTS CAN OR WILL BE CORRECTED.

WITHOUT LIMITING THE FOREGOING, NEITHER CERTIK NOR ANY OF CERTIK’S AGENTS MAKES ANY REPRESENTATION OR WARRANTY OF ANY KIND, EXPRESS OR IMPLIED AS TO THE ACCURACY, RELIABILITY, OR CURRENCY OF ANY INFORMATION OR CONTENT PROVIDED THROUGH THE SERVICE. CERTIK WILL ASSUME NO LIABILITY OR RESPONSIBILITY FOR (I) ANY ERRORS, MISTAKES, OR INACCURACIES OF CONTENT AND MATERIALS OR FOR ANY LOSS OR DAMAGE OF ANY KIND INCURRED AS A RESULT OF THE USE OF ANY CONTENT, OR (II) ANY PERSONAL INJURY OR PROPERTY DAMAGE, OF ANY NATURE WHATSOEVER, RESULTING FROM CUSTOMER’S ACCESS TO OR USE OF THE SERVICES, ASSESSMENT REPORT, OR OTHER MATERIALS.

ALL THIRD-PARTY MATERIALS ARE PROVIDED “AS IS” AND ANY REPRESENTATION OR WARRANTY OF OR CONCERNING ANY THIRD-PARTY MATERIALS IS STRICTLY BETWEEN CUSTOMER AND THE THIRD-PARTY OWNER OR DISTRIBUTOR OF THE THIRD-PARTY MATERIALS.

THE SERVICES, ASSESSMENT REPORT, AND ANY OTHER MATERIALS HEREUNDER ARE SOLELY PROVIDED TO CUSTOMER AND MAY NOT BE RELIED ON BY ANY OTHER PERSON OR FOR ANY PURPOSE NOT SPECIFICALLY IDENTIFIED IN THIS AGREEMENT, NOR MAY COPIES BE DELIVERED TO, ANY OTHER PERSON WITHOUT CERTIK’S PRIOR WRITTEN CONSENT IN EACH INSTANCE.

NO THIRD PARTY OR ANYONE ACTING ON BEHALF OF ANY THEREOF, SHALL BE A THIRD PARTY OR OTHER BENEFICIARY OF SUCH SERVICES, ASSESSMENT REPORT, AND ANY ACCOMPANYING

MATERIALS AND NO SUCH THIRD PARTY SHALL HAVE ANY RIGHTS OF CONTRIBUTION AGAINST CERTIK WITH RESPECT TO SUCH SERVICES, ASSESSMENT REPORT, AND ANY ACCOMPANYING MATERIALS.

THE REPRESENTATIONS AND WARRANTIES OF CERTIK CONTAINED IN THIS AGREEMENT ARE SOLELY FOR THE BENEFIT OF CUSTOMER. ACCORDINGLY, NO THIRD PARTY OR ANYONE ACTING ON BEHALF OF ANY THEREOF, SHALL BE A THIRD PARTY OR OTHER BENEFICIARY OF SUCH REPRESENTATIONS AND WARRANTIES AND NO SUCH THIRD PARTY SHALL HAVE ANY RIGHTS OF CONTRIBUTION AGAINST CERTIK WITH RESPECT TO SUCH REPRESENTATIONS OR WARRANTIES OR ANY MATTER SUBJECT TO OR RESULTING IN INDEMNIFICATION UNDER THIS AGREEMENT OR OTHERWISE.

FOR AVOIDANCE OF DOUBT, THE SERVICES, INCLUDING ANY ASSOCIATED ASSESSMENT REPORTS OR MATERIALS, SHALL NOT BE CONSIDERED OR RELIED UPON AS ANY FORM OF FINANCIAL, TAX, LEGAL, REGULATORY, OR OTHER ADVICE.

## About

Founded in 2017 by leading academics in the field of Computer Science from both Yale and Columbia University, CertiK is a leading blockchain security company that serves to verify the security and correctness of smart contracts and blockchain-based protocols. Through the utilization of our world-class technical expertise, alongside our proprietary, innovative tech, we're able to support the success of our clients with best-in-class security, all whilst realizing our overarching vision; provable trust for all throughout all facets of blockchain.

