











PAR 56 Q500PAR56WFL 120V

43496

# **Product information**

PAR lamps provide a robust and flexible design solution for a wide range of applications. Choice of PAR36, PAR46, PAR56 or PAR64

- 3000 K or 4200 K colour temperature
- Choice of beam widths
- Excellent colour rendering
- High efficiency combined with low operating costs
- Robust and reliable
- UV control
- Easy retrofit
- Colour consistent throughout life
- Colour blends with halogen and fluorescent

#### **Application areas**



Club and Disco









## **Product data**

Cap/Base	G16d
Bulb Shape	PAR
Bulb Diameter [mm]	177.8
Maximum Overall Length [mm]	127
Net weight per piece [g]	594
Gross weight per piece [g]	742
Brand	General Electric (GE)

## Performance data

Colour Rendering Index (CRI) [Ra]	100
Nominal correlated colour temperature (CCT) [K]	2750
Nominal beam angle [°]	30
Nominal center beam candlepower (CBCP) [cd]	19000
Nominal lumens [lm]	7650
Energy efficiency class (EEC)	D
Rated Life [h]	4000
Weighted energy consumption [kWh/1000h]	55011

### **Electrical data**

Nominal power [W]	500
Nominal lamp voltage [V]	120
Coil type	CC-6
Ballast Required	Yes





## Logistic data

DUN Code	00043168434966
EAN Code	0043168434966
Pack Quantity	6
Layer quantity	1 UK
Layer quantity UK	1
Pallet quantity UK (PC)	288
Outer case size	349 x 300 x 446 (mm)
Product status	Available

#### **Downloads & Links**

Go to the catalog site (HTTP)

**Entertainment Solution Spectrum Catalogue (PDF)** 

**Lighting design tools & calculators (HTTP)** 

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

#### Disclaimer

Special purpose lamp – Stage Studio. Not suitable for household illumination.