

Advanced Statistical Inference Projection

Maurizio Filippone
Maurizio.Filippone@eurecom.fr

Department of Data Science
EURECOM

Introduction

M. Filippone

Introduction

Features

Projections

PCA

ICA

Introduction

M. Filippone

Introduction

Features

Projections

PCA

ICA

Part 1: Feature selection and PCA

Introduction

M. Filippone

Introduction

Features

Projections

PCA

ICA

Introduction

M. Filippone

Introduction

Features


Projections

PCA

ICA

A problem - too many features

- ▶ Aim: To build a classifier that can diagnose leukaemia using Gene expression data.
- ▶ Data: 27 healthy samples, 11 leukaemia samples ($N = 38$). Each sample is the expression (activity) level for 3751 genes. (Also have an independent test set)




- ▶ In general, the number of parameters will increase with the number of **features** – $D = 3751$.
 - ▶ e.g. Logistic regression – \mathbf{w} would have length 3751!
- ▶ Fitting lots of parameters is hard – imagine Metropolis-Hastings in 3751 dimensions rather than 2!

Features

- ▶ For visualisation, most examples we've seen have had only 2 features $\mathbf{x} = [x_1, x_2]^T$.
- ▶ We sometimes **created** more: $\mathbf{x} = [1, x_1, x_1^2, x_1^3, \dots]^T$.
- ▶ Now, we've been given lots (3751) to start with.
- ▶ We need to reduce this number.
- ▶ 2 general schemes:
 - ▶ Use a **subset** of the originals.
 - ▶ Make new ones by **combining** the originals.

Finding a subset – example

- ▶ Take one feature – N values.



- ▶ Some values from objects in class 1, some from class 0.
- ▶ Split them based on class and compute μ and σ^2 for each class.
- ▶ Compute s for each feature:

$$s = \frac{|\mu_1 - \mu_0|}{\sigma_0^2 + \sigma_1^2}$$

- ▶ Keep features with high s .

Introduction

M. Filippone

Introduction


Features

Projections

PCA

ICA

Examples



Features get better (higher s) from left to right...

$$s = \frac{|\mu_1 - \mu_0|}{\sigma_0^2 + \sigma_1^2}$$

- ▶ Each feature has an s -score. The higher the better.
- ▶ Use the S features with the highest scores.
- ▶ How to choose S ?

Introduction

M. Filippone

Introduction

Features

Projections

PCA

ICA

A feature selection scheme (CV)

- ▶ For each candidate S value:
- ▶ Split the data into C folds (just as in CV)
- ▶ For each fold...
 1. Find the feature scores on the **training** data.
 2. Train the classifier (whichever we choose).
 3. Record the performance.
- ▶ Important: Must only compute scores on training data. Otherwise we are implicitly using the test labels for training – biased.

Introduction

M. Filippone

Introduction


Features

Projections

PCA

ICA

Example



Best two features in our leukaemia data (points labeled by class).

Introduction

M. Filippone

Introduction


Features

Projections

PCA

ICA

Example



Performance as S increases.

Introduction
M. Filippone

Introduction
Features
Projections
PCA
ICA


Making new features

- ▶ An alternative to choosing features is making new ones.
- ▶ Cluster:
 - ▶ Cluster the features (turn our clustering problem around)
 - ▶ If we use say K-means, our new features will be the K mean vectors.
- ▶ Projection/combination
 - ▶ Reduce the number of features by projecting into a lower dimensional space.
 - ▶ Do this by making new features that are combinations (linear) of the old ones.

Introduction
M. Filippone

Introduction
Features
Projections
PCA
ICA

Projection



Introduction
M. Filippone

Introduction
Features
Projections
PCA
ICA

Projection


- ▶ We can project data (D dimensions) into a lower number of dimensions (M).
- ▶ $\mathbf{Z} = \mathbf{X}\mathbf{W}$
 - ▶ \mathbf{X} is $N \times D$
 - ▶ \mathbf{W} is $D \times M$
- ▶ \mathbf{Z} is $N \times M$ – an M -dimensional representation of our N objects.
- ▶ \mathbf{W} defines the projection
 - ▶ Changing \mathbf{W} is like changing where the light is coming from for the shadow (or rotating the hand).
 - ▶ (\mathbf{X} is the hand, \mathbf{Z} is the shadow)
- ▶ Once we've chosen \mathbf{W} we can project test data into this new space too: $\mathbf{Z}_{\text{new}} = \mathbf{X}_{\text{new}}\mathbf{W}$

Introduction
M. Filippone

Introduction
Features
Projections
PCA
ICA

Choosing \mathbf{W}

- ▶ Different \mathbf{W} will give us different projections (imagine moving the light).
- ▶ Which should we use?
- ▶ Not all will represent our data well...



Introduction
M. Filippone

Introduction
Features
Projections
PCA
ICA

Principal Components Analysis

- ▶ Principal Components Analysis (PCA) is a method for choosing \mathbf{W} .
- ▶ It finds the columns of \mathbf{W} one at a time (define the m th column as \mathbf{w}_m).
 - ▶ Each $D \times 1$ column defines one new dimension.
- ▶ Consider one of the new dimensions (columns of \mathbf{Z}):

$$\mathbf{z}_m = \mathbf{X}\mathbf{w}_m$$

- ▶ PCA chooses \mathbf{w}_m to maximise the variance of \mathbf{z}_m


$$\frac{1}{N} \sum_{n=1}^N (z_{mn} - \mu_m)^2, \quad \mu_m = \frac{1}{N} \sum_{n=1}^N z_{mn}$$

- ▶ Once the first one has been found, the \mathbf{w}_2 is found that maximises the variance and is **orthogonal** to the first one etc etc.

Introduction
M. Filippone

Introduction
Features
Projections
PCA
ICA

PCA – a visualisation




- ▶ Original data in 2-dimensions.
- ▶ We'd like a 1-dimensional projection.

Introduction
M. Filippone

Introduction
Features
Projections
PCA
ICA

PCA – a visualisation




- ▶ Pick some arbitrary \mathbf{w} .
- ▶ Project the data onto it.
- ▶ Compute the variance (on the line).
- ▶ The position on the line is our 1 dimensional representation.

Introduction
M. Filippone


Introduction
Features
Projections
PCA
ICA

PCA – a visualisation



- ▶ Pick some arbitrary \mathbf{w} .
- ▶ Project the data onto it.
- ▶ Compute the variance (on the line).
- ▶ The position on the line is our 1 dimensional representation.

PCA – a visualisation




- ▶ Pick some arbitrary \mathbf{w} .
- ▶ Project the data onto it.
- ▶ Compute the variance (on the line).
- ▶ The position on the line is our 1 dimensional representation.

PCA – analytic solution


- ▶ Could search for $\mathbf{w}_1, \dots, \mathbf{w}_M$
- ▶ But, analytic solution is available.
- ▶ \mathbf{w} are the **eigenvectors** of the covariance matrix of \mathbf{X} .
 - ▶ You don't need to know this!
- ▶ Matlab: `princomp(x)`

PCA – analytic solution




- ▶ What would be the second component?

PCA – leukaemia data



First two principal components in our leukaemia data (points labeled by class).

PCA – leukaemia data




Test error as more and more components are used.

Summary

- ▶ Sometimes we have too much data (too many dimensions).
- ▶ Need to select features.
- ▶ Features can be dimensions that already exist.
- ▶ Or we can make new ones.
- ▶ We've seen one example of each.
- ▶ To think about during the break: Why might PCA do worse than the scoring method?

Part 2: ICA (the cocktail party problem)

The cocktail party problem



- ▶ Each microphone will record a combination of all speakers.
- ▶ Can we separate them back out again?

Introduction

M. Filippone

Introduction

Features

Projections

PCA

ICA

Demo

- ▶ Online:
 - ▶ http://www.cis.hut.fi/projects/ica/cocktail/cocktail_en.cgi
- ▶ Matlab:
 - ▶ Available on course webpage
 - ▶ To run:
 - ▶ `load ica_demo.mat`
 - ▶ `ica_image`

Introduction

M. Filippone

Introduction

Features

Projections

PCA

ICA

Independent components analysis – how it works...

- ▶ Corrupted data (images/sounds) is a vector of D numbers. i.e. n th image:

$$\mathbf{x}_n$$

- ▶ We have \mathbf{N} images – stack them up into an $N \times D$ matrix:

$$\mathbf{X}$$

- ▶ Assume that this is the result of the following corrupting process:

$$\mathbf{X} = \mathbf{AS} + \mathbf{E}$$

- ▶ \mathbf{A} is mixing matrix. \mathbf{E} is noise. (\mathbf{S} is $N \times D$).

$$e_{nd} \sim \mathcal{N}(0, \sigma^2)$$

Introduction

M. Filippone

Introduction

Features

Projections

PCA

ICA

Inference

- ▶ From Bayes' (look back...)

$$p(\mathbf{S}|\mathbf{X}, \mathbf{A}, \sigma^2) \propto p(\mathbf{X}|\mathbf{S}, \mathbf{A}, \sigma^2)p(\mathbf{S})$$

- ▶ In our demo, we found values of \mathbf{S} , \mathbf{A} and σ^2 that maximised the log posterior.
- ▶ MAP solution...
- ▶ There is some further reading on the webpage if you want to know more...

Introduction

M. Filippone

Introduction

Features

Projections


PCA

ICA

Aside – ICA and the central limit theorem

- ▶ Central limit theorem (paraphrased):
 - ▶ If we keep adding the outcomes of independent random variables together, we eventually get something that looks Gaussian.

- ▶ Example: Roll a die m times and take the average. (Repeat this lots of times to get histogram)



- ▶ From left to right: $m = 1$, $m = 2$, $m = 5$. Looking more Gaussian as m increases.

Introduction

M. Filippone

Introduction

Features

Projections

PCA

ICA

Aside – ICA and the central limit theorem

- ▶ Sometimes ICA is performed by **reversing** this theorem:

$$\mathbf{X} = \mathbf{AS} + \mathbf{E}$$

- ▶ \mathbf{X} is some random variables added together.
- ▶ It will be more 'Gaussian' than \mathbf{S}
- ▶ Find \mathbf{S} that is as non-Gaussian as possible.
- ▶ More resource:
 - ▶ <http://www.cis.hut.fi/projects/ica/icademo/>
 - ▶ <http://www.cis.hut.fi/projects/ica/>

Introduction

M. Filippone

Introduction

Features

Projections

PCA

ICA

Summary

- ▶ PCA and ICA are both examples of projection techniques.
- ▶ Both assume a linear transformation
 - ▶ ICA: $\mathbf{X} = \mathbf{AS} + \mathbf{E}$
 - ▶ PCA: $\mathbf{Z} = \mathbf{XW}$
- ▶ PCA can be used for Data pre-processing or visualisation.
- ▶ ICA can be used to separate sources that have been mixed together.
- ▶ Also looked at PCA as a feature selection method.

Introduction

M. Filippone

Introduction

Features

Projections

PCA

ICA