

# What is a cluster?





**Computer cluster**




**Asteroid cluster**



**Activity clusters**



**Winter cluster**



**Consonant cluster**

A group of entities which are alike. Entities from different clusters are not alike



# Clustering

The task of grouping a set of objects in such a way that objects in the same group (**a cluster**) are more **similar** (in some sense) to each other than to those in other groups (clusters).

Main task of exploratory data mining, and a common technique for statistical data analysis


*Fields of use:* machine learning, pattern recognition, image analysis, information retrieval, bioinformatics, data compression, and computer graphics.

[https://en.wikipedia.org/wiki/Cluster\\_analysis](https://en.wikipedia.org/wiki/Cluster_analysis)

# Examples in healthcare




**Gene expression**  
Shamir et al.  
BMC Bioinformatics 2014



**Population study**  
Lefèvre et al. PlosOne 2014



**Image segmentation**  
Ashburner & Friston Neuroimage 2005







**Shape clusters**  
Bruse et al. IEEE TBME 2017



# Clustering: Key elements

- Similarity criteria
- Number of groups
- Features



Method name	Parameters	Scalability	Usecase	Geometry (metric used)
<b>K-Means</b>	number of clusters	Very large <code>n_samples</code> , medium <code>n_clusters</code> with <a href="#">MiniBatch code</a>	General-purpose, even cluster size, flat geometry, not too many clusters	Distances between points
<b>Affinity propagation</b>	damping, sample preference	Not scalable with <code>n_samples</code>	Many clusters, uneven cluster size, non-flat geometry	Graph distance (e.g. nearest-neighbor graph)
<b>Mean-shift</b>	bandwidth	Not scalable with <code>n_samples</code>	Many clusters, uneven cluster size, non-flat geometry	Distances between points
<b>Spectral clustering</b>	number of clusters	Medium <code>n_samples</code> , small <code>n_clusters</code>	Few clusters, even cluster size, non-flat geometry	Graph distance (e.g. nearest-neighbor graph)
<b>Ward hierarchical clustering</b>	number of clusters	Large <code>n_samples</code> and <code>n_clusters</code>	Many clusters, possibly connectivity constraints	Distances between points
<b>Agglomerative clustering</b>	number of clusters, linkage type, distance	Large <code>n_samples</code> and <code>n_clusters</code>	Many clusters, possibly connectivity constraints, non Euclidean distances	Any pairwise distance
<b>DBSCAN</b>	neighborhood size	Very large <code>n_samples</code> , medium <code>n_clusters</code>	Non-flat geometry, uneven cluster sizes	Distances between nearest points
<b>Gaussian mixtures</b>	many	Not scalable	Flat geometry, good for density estimation	Mahalanobis distances to centers
<b>Birch</b>	branching factor, threshold, optional global clusterer.	Large <code>n_clusters</code> and <code>n_samples</code>	Large dataset, outlier removal, data reduction.	Euclidean distance between points

<https://scikit-learn.org/stable/modules/clustering.html>

# K-means: Formalisation

# K-means: Formalisation

- Dataset:  $\mathcal{D} = \{\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_N\} \in \mathbf{R}^D$



# K-means: Formalisation

- Dataset:  $\mathcal{D} = \{\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_N\} \in \mathbf{R}^D$
- Goal v1.0: Partition the dataset into K clusters

# K-means: Formalisation

- Dataset:  $\mathcal{D} = \{\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_N\} \in \mathbf{R}^D$
- Goal v1.0: Partition the dataset into K clusters
- D-dimensional vector  $\mu_k$ ,  $k = 1, \dots, K$ , a prototype associated to the  $k^{\text{th}}$  cluster.

# K-means: Formalisation

- Dataset:  $\mathcal{D} = \{\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_N\} \in \mathbf{R}^D$
- **Goal v1.0:** Partition the dataset into  $K$  clusters
- $D$ -dimensional vector  $\mu_k$ ,  $k = 1, \dots, K$ , a prototype associated to the  $k^{\text{th}}$  cluster.
- **Goal v2.0:** Find an assignment of points  $\mathbf{x}_1, \dots, \mathbf{x}_N$  to clusters, and a set of vectors  $\{\mu_k\}$ , which minimise the sum of square distances of each point to its closest vector



# K-means: Formalisation

# K-means: Formalisation

- To designate membership of each  $\mathbf{x}_i$ , use a binary indicator variable:

$$r_{ik} \in \{0,1\} \quad \begin{array}{l} k = 1, \dots, K \\ i = 1, \dots, N \end{array}$$

# K-means: Formalisation

- To designate membership of each  $\mathbf{x}_i$ , use a binary indicator variable:

$$r_{ik} \in \{0,1\} \quad \begin{array}{l} k = 1, \dots, K \\ i = 1, \dots, N \end{array}$$

- $r_{ik} = 1$  when the point  $\mathbf{x}_i$  belongs to cluster  $k$ .  $r_{ij} = 0$  for  $j \neq k$




# K-means: Formalisation

- To designate membership of each  $\mathbf{x}_i$ , use a binary indicator variable:

$$r_{ik} \in \{0,1\} \quad \begin{array}{l} k = 1, \dots, K \\ i = 1, \dots, N \end{array}$$

- $r_{ik} = 1$  when the point  $\mathbf{x}_i$  belongs to cluster  $k$ .  $r_{ij} = 0$  for  $j \neq k$

x	k
1	GM
2	WM
3	CSF
4	WM
5	WM



x	r
1	(1,0,0)
2	(0,1,0)
3	(0,0,1)
4	(0,1,0)
5	(0,1,0)

This representation scheme is denoted 1-of-K coding. It is better known as one hot encoding

Clusters = {GM, WM, CSF}


# K-means: Goal v3.0

- Find  $k$  prototype vectors  $\{\mu_k\}$  and a 1-of- $K$  coding scheme, represented by  $r_{ik}$ , that minimises the *distortion measure* given by

$$J = \sum_{i=1}^N \sum_{k=1}^K r_{ik} \|\mathbf{x}_i - \mu_k\|^2$$

# K-means: Goal v3.0

- Find  $k$  prototype vectors  $\{\mu_k\}$  and a 1-of- $K$  coding scheme, represented by  $r_{ik}$ , that minimises the *distortion measure* given by

$$J = \sum_{i=1}^N \sum_{k=1}^K r_{ik} \|\mathbf{x}_i - \mu_k\|^2$$


Sum of the squares of the distances of each data point to vector  $\mu_k$



# Optimisation algorithm

- Iterative procedure involving optimisation of  $r_{ik}, \mu_k$

Initialise  $\mu_k$

Iterate:

Minimise  $J$  w.r.t  $r_{ik}$  keeping fixed  $\mu_k$

Minimise  $J$  w.r.t  $\mu_k$  keeping fixed  $r_{ik}$

repeat until convergence

# Optimisation algorithm: $r_{ik}$

- Minimisation of  $J$  w.r.t  $r_{ik}$

$$J = \sum_{i=1}^N \sum_{k=1}^K r_{ik} \|\mathbf{x}_i - \mu_k\|^2$$

# Optimisation algorithm: $r_{ik}$

- Minimisation of  $J$  w.r.t  $r_{ik}$

$$J = \sum_{i=1}^N \sum_{k=1}^K r_{ik} \underbrace{\|\mathbf{x}_i - \mu_k\|^2}_{\text{Independent for each } i}$$

Only one term is non-zero



# Optimisation algorithm: $r_{ik}$

- Minimisation of  $J$  w.r.t  $r_{ik}$

$$J = \sum_{i=1}^N \sum_{k=1}^K r_{ik} \underbrace{\|\mathbf{x}_i - \mu_k\|^2}_{\text{Independent for each } i}$$

Only one term is non-zero

$$r_{i1}\|\mathbf{x}_i - \mu_1\|^2, r_{i2}\|\mathbf{x}_i - \mu_2\|^2, r_{i3}\|\mathbf{x}_i - \mu_3\|^2, \dots, r_{iK}\|\mathbf{x}_i - \mu_K\|^2$$

# Optimisation algorithm: $r_{ik}$

- Minimisation of  $J$  w.r.t  $r_{ik}$

$$J = \sum_{i=1}^N \sum_{k=1}^K r_{ik} \underbrace{\|\mathbf{x}_i - \mu_k\|^2}_{\text{Independent for each } i}$$

Only one term is non-zero

$$r_{i1}\|\mathbf{x}_i - \mu_1\|^2, r_{i2}\|\mathbf{x}_i - \mu_2\|^2, r_{i3}\|\mathbf{x}_i - \mu_3\|^2, \dots, r_{iK}\|\mathbf{x}_i - \mu_K\|^2$$

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$

# Optimisation algorithm: $\mu_k$

$$J = \sum_{i=1}^N \sum_{k=1}^K r_{ik} \|\mathbf{x}_i - \mu_k\|^2$$

# Optimisation algorithm: $\mu_k$

- Minimisation of J w.r.t  $\mu_k$

$$J = \sum_{i=1}^N \sum_{k=1}^K r_{ik} \|\mathbf{x}_i - \mu_k\|^2$$



# Optimisation algorithm: $\mu_k$

- Minimisation of J w.r.t  $\mu_k$

$$J = \sum_{i=1}^N \sum_{k=1}^K r_{ik} \|\mathbf{x}_i - \mu_k\|^2$$

- Derive J w.r.t  $\mu_k$

$$J = \sum_{k=1}^K \sum_{i=1}^N r_{ik} \|\mathbf{x}_i - \mu_k\|^2$$

# Optimisation algorithm: $\mu_k$


- Minimisation of J w.r.t  $\mu_k$

$$J = \sum_{i=1}^N \sum_{k=1}^K r_{ik} \|\mathbf{x}_i - \mu_k\|^2$$

- Derive J w.r.t  $\mu_k$

$$J = \sum_{k=1}^K \sum_{i=1}^N r_{ik} \|\mathbf{x}_i - \mu_k\|^2$$

**J<sub>k</sub>**



# Optimisation algorithm: $\mu_k$


- Minimisation of J w.r.t  $\mu_k$

$$J = \sum_{i=1}^N \sum_{k=1}^K r_{ik} \|\mathbf{x}_i - \mu_k\|^2$$

- Derive J w.r.t  $\mu_k$

$$J = \sum_{k=1}^K \underbrace{\sum_{i=1}^N r_{ik} \|\mathbf{x}_i - \mu_k\|^2}_{\mathbf{J}_k}$$

$$2 \sum_{i=1}^N r_{ik} (\mathbf{x}_i - \mu_k) = 0$$



$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

# Optimisation algorithm: $\mu_k$


- Minimisation of J w.r.t  $\mu_k$

$$J = \sum_{i=1}^N \sum_{k=1}^K r_{ik} \|\mathbf{x}_i - \mu_k\|^2$$

- Derive J w.r.t  $\mu_k$

$$J = \sum_{k=1}^K \underbrace{\sum_{i=1}^N r_{ik} \|\mathbf{x}_i - \mu_k\|^2}_{\mathbf{J}_k}$$

$$2 \sum_{i=1}^N r_{ik} (\mathbf{x}_i - \mu_k) = 0$$



$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$



# Optimisation algorithm: $\mu_k$


- Minimisation of J w.r.t  $\mu_k$

$$J = \sum_{i=1}^N \sum_{k=1}^K r_{ik} \|\mathbf{x}_i - \mu_k\|^2$$

- Derive J w.r.t  $\mu_k$

$$J = \sum_{k=1}^K \underbrace{\sum_{i=1}^N r_{ik} \|\mathbf{x}_i - \mu_k\|^2}_{\mathbf{J}_k}$$

$$2 \sum_{i=1}^N r_{ik} (\mathbf{x}_i - \mu_k) = 0$$



$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$



**K-means**



# K-means algorithm

Initialise  $\mu_k, k = 1, \dots, K$

Repeat

for each  $\mathbf{x}_i$ :

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$

for each  $\mu_k$ :

$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

until  $\mu_k$  converges

# K-means algorithm

Initialise  $\mu_k, k = 1, \dots, K$

Repeat

for each  $\mathbf{x}_i$ :

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$

**E-step (expectation)**  
1- Find nearest centroid for each point  
2- Assign points to clusters (update)


for each  $\mu_k$ :

$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

**M-step (maximisation)**  
Compute centroid for each cluster

until  $\mu_k$  converges

# K-means algorithm



► Initialise  $\mu_k, k = 1, \dots, K$

Repeat

for each  $\mathbf{x}_i$ :

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$

for each  $\mu_k$ :

$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

until  $\mu_k$  converges

## E-step (expectation)

- 1- Find nearest centroid for each point
- 2- Assign points to clusters (update)

## M-step (maximisation)

Compute centroid for each cluster

Example adapted from Fig 9.1, 9.2 - Bishop

# K-means algorithm

Initialise  $\mu_k, k = 1, \dots, K$

Repeat


for each  $\mathbf{x}_i$ :

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$

for each  $\mu_k$ :

$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

until  $\mu_k$  converges



## E-step (expectation)

- 1- Find nearest centroid for each point
- 2- Assign points to clusters (update)

## M-step (maximisation)

Compute centroid for each cluster

Example adapted from Fig 9.1, 9.2 - Bishop

# K-means algorithm

Initialise  $\mu_k, k = 1, \dots, K$

Repeat


for each  $\mathbf{x}_i$ :

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$

for each  $\mu_k$ :

$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

until  $\mu_k$  converges



## E-step (expectation)

- 1- Find nearest centroid for each point
- 2- Assign points to clusters (update)


## M-step (maximisation)

Compute centroid for each cluster

Example adapted from Fig 9.1, 9.2 - Bishop



# K-means algorithm



Initialise  $\mu_k, k = 1, \dots, K$

Repeat

for each  $\mathbf{x}_i$ :

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$

for each  $\mu_k$ :

$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

until  $\mu_k$  converges

## E-step (expectation)


- 1- Find nearest centroid for each point
- 2- Assign points to clusters (update)

## M-step (maximisation)

Compute centroid for each cluster

Example adapted from Fig 9.1, 9.2 - Bishop

# K-means algorithm



Initialise  $\mu_k, k = 1, \dots, K$

Repeat

for each  $\mathbf{x}_i$ :

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$

for each  $\mu_k$ :

$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

until  $\mu_k$  converges

## E-step (expectation)

- 1- Find nearest centroid for each point
- 2- Assign points to clusters (update)

## M-step (maximisation)

Compute centroid for each cluster

Example adapted from Fig 9.1, 9.2 - Bishop

# K-means algorithm

Initialise  $\mu_k, k = 1, \dots, K$

Repeat


for each  $\mathbf{x}_i$ :

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$

for each  $\mu_k$ :

$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

until  $\mu_k$  converges



## E-step (expectation)

- 1- Find nearest centroid for each point
- 2- Assign points to clusters (update)

## M-step (maximisation)

Compute centroid for each cluster

Example adapted from Fig 9.1, 9.2 - Bishop

# K-means algorithm

Initialise  $\mu_k, k = 1, \dots, K$

Repeat


for each  $\mathbf{x}_i$ :

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$

for each  $\mu_k$ :

$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

until  $\mu_k$  converges



## E-step (expectation)

- 1- Find nearest centroid for each point
- 2- Assign points to clusters (update)


## M-step (maximisation)

Compute centroid for each cluster

Example adapted from Fig 9.1, 9.2 - Bishop



# K-means algorithm



Initialise  $\mu_k, k = 1, \dots, K$

Repeat

for each  $\mathbf{x}_i$ :

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$

for each  $\mu_k$ :

$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

until  $\mu_k$  converges

## E-step (expectation)

- 1- Find nearest centroid for each point
- 2- Assign points to clusters (update)


## M-step (maximisation)

Compute centroid for each cluster

Example adapted from Fig 9.1, 9.2 - Bishop



# K-means algorithm



Initialise  $\mu_k, k = 1, \dots, K$

Repeat

for each  $\mathbf{x}_i$ :

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$

for each  $\mu_k$ :

$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

until  $\mu_k$  converges

## E-step (expectation)


- 1- Find nearest centroid for each point
- 2- Assign points to clusters (update)

## M-step (maximisation)

Compute centroid for each cluster

Example adapted from Fig 9.1, 9.2 - Bishop

# K-means algorithm



Initialise  $\mu_k, k = 1, \dots, K$

Repeat

for each  $\mathbf{x}_i$ :

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$

for each  $\mu_k$ :

$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

until  $\mu_k$  converges

## E-step (expectation)


- 1- Find nearest centroid for each point
- 2- Assign points to clusters (update)

## M-step (maximisation)

Compute centroid for each cluster

Example adapted from Fig 9.1, 9.2 - Bishop

# K-means algorithm



Initialise  $\mu_k, k = 1, \dots, K$

Repeat

for each  $\mathbf{x}_i$ :

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$

for each  $\mu_k$ :

$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

until  $\mu_k$  converges

## E-step (expectation)


- 1- Find nearest centroid for each point
- 2- Assign points to clusters (update)

## M-step (maximisation)

Compute centroid for each cluster

Example adapted from Fig 9.1, 9.2 - Bishop

# K-means algorithm



Initialise  $\mu_k, k = 1, \dots, K$

Repeat

for each  $\mathbf{x}_i$ :

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$

for each  $\mu_k$ :

$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

until  $\mu_k$  converges

## E-step (expectation)

- 1- Find nearest centroid for each point
- 2- Assign points to clusters (update)


## M-step (maximisation)

Compute centroid for each cluster

Example adapted from Fig 9.1, 9.2 - Bishop



# K-means algorithm



Initialise  $\mu_k, k = 1, \dots, K$

Repeat

for each  $\mathbf{x}_i$ :

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$

for each  $\mu_k$ :

$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

until  $\mu_k$  converges

## E-step (expectation)


- 1- Find nearest centroid for each point
- 2- Assign points to clusters (update)

## M-step (maximisation)

Compute centroid for each cluster

Example adapted from Fig 9.1, 9.2 - Bishop

# K-means algorithm



Initialise  $\mu_k, k = 1, \dots, K$

Repeat

for each  $\mathbf{x}_i$ :

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$

for each  $\mu_k$ :

$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

until  $\mu_k$  converges

## E-step (expectation)

- 1- Find nearest centroid for each point
- 2- Assign points to clusters (update)

## M-step (maximisation)

Compute centroid for each cluster

Example adapted from Fig 9.1, 9.2 - Bishop



# K-means algorithm

Initialise  $\mu_k, k = 1, \dots, K$

Repeat


for each  $\mathbf{x}_i$ :

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$

for each  $\mu_k$ :

$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

until  $\mu_k$  converges



## E-step (expectation)

- 1- Find nearest centroid for each point
- 2- Assign points to clusters (update)

## M-step (maximisation)

Compute centroid for each cluster

Example adapted from Fig 9.1, 9.2 - Bishop

# K-means algorithm

Initialise  $\mu_k, k = 1, \dots, K$

Repeat


for each  $\mathbf{x}_i$ :

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$

for each  $\mu_k$ :

$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

until  $\mu_k$  converges



## E-step (expectation)

- 1- Find nearest centroid for each point
- 2- Assign points to clusters (update)

## M-step (maximisation)

Compute centroid for each cluster

Example adapted from Fig 9.1, 9.2 - Bishop

# K-means algorithm

Initialise  $\mu_k, k = 1, \dots, K$

Repeat


for each  $\mathbf{x}_i$ :

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$

for each  $\mu_k$ :

$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

until  $\mu_k$  converges



## E-step (expectation)

- 1- Find nearest centroid for each point
- 2- Assign points to clusters (update)

## M-step (maximisation)

Compute centroid for each cluster

Example adapted from Fig 9.1, 9.2 - Bishop

# K-means algorithm

Initialise  $\mu_k, k = 1, \dots, K$

Repeat



for each  $\mathbf{x}_i$ :

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$

for each  $\mu_k$ :

$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

until  $\mu_k$  converges





# K-means algorithm

Initialise  $\mu_k, k = 1, \dots, K$

Repeat



for each  $\mathbf{x}_i$ :

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$

for each  $\mu_k$ :

$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

► until  $\mu_k$  converges



# K-means algorithm

Initialise  $\mu_k, k = 1, \dots, K$

Repeat


for each  $\mathbf{x}_i$ :

$$r_{ik} = \begin{cases} 1 & \text{if } k = \arg \min_j \|\mathbf{x}_i - \mu_j\|^2 \\ 0 & \text{otherwise} \end{cases}$$


for each  $\mu_k$ :

$$\mu_k = \frac{\sum_i r_{ik} \mathbf{x}_i}{\sum_i r_{ik}}$$

► until  $\mu_k$  converges





Algorithm complexity?







# Real example: Brain segmentation



# Real example




**K= 2**




**K= 3**

# Limitations







Despotovic et al. CMMM 2015







Source: scikit-learn



# Limitations



Slow  
Similarity metric



Despotovic et al. CMMM 2015

Source: scikit-learn

# Further reading

- AK. Jain. Data clustering: 50 years beyond K-means. Pattern Recognition Letters. 2010
- L. Kaufman & P. Rosseuw. Clustering by means of Medoids. Statistical Data Analysis Based on the  $\ell_1$ -Norm and Related Methods. 1987
- J. Newling & F. Fleuret. K-medoids for K-means seeding. NIPS 2017
- S. Sohely-Kahn et al. Generalized k-means-based clustering for temporal data under weighted and kernel time warp. Pattern Recognition Letters. 2016

# This week

- Exercises 9.1, 9.2 Bishop
- Implement own version of K-means (no scikit-learn, no ITK)
  - Apply it to brain image segmentation
  - Experiment with different initialisation strategies
  - Bonus: Computationally efficient implementation

**Next session:** Gaussian mixtures & Expectation maximisation algorithm