

# Machine Learning and Intelligent Systems

## Unsupervised Learning - Setup

---

Maria A. Zuluaga

Jan 26, 2023

EURECOM - Data Science Department

# Table of contents

Recap

Unsupervised Learning

Definition and Setup

Canonical Examples

Wrap-up


## Recap

---

# Supervised Learning: Learn with a teacher

## Regression

Learning a continuous function  
from a set of examples




Examples:

- Forecasting
- Price of a good (stocks, flights, etc).
- Expected salary

## Classification

Learning a rule from examples that can  
separate data from one another



Examples:

- Spam filtering
- Image classification
- Disease diagnosis

# Unsupervised Learning

---

# Unsupervised learning: No teacher

- No target or labels.
- The goal is to discover "interesting structure" in the data, often also referred to as knowledge discovery.
- Since there is no desired output, our task becomes one of **density estimation**.

# Unsupervised learning: No teacher

- No target or labels.
- The goal is to discover "interesting structure" in the data, often also referred to as knowledge discovery.
- Since there is no desired output, our task becomes one of **density estimation**.

**Formulation:** The training set  $\mathcal{D}$  consists of  $N$  observations  $\mathbf{x}_i \in \mathbb{R}^D$  drawn from a probability distribution  $p(X)$ .

- **Supervised learning:**  $p(\mathbf{y}|\mathbf{X})$
- **Unsupervised learning:**  $p(\mathbf{X})$

# Unsupervised learning: No teacher

- No target or labels.
- The goal is to discover "interesting structure" in the data, often also referred to as knowledge discovery.
- Since there is no desired output, our task becomes one of **density estimation**.

**Formulation:** The training set  $\mathcal{D}$  consists of  $N$  observations  $\mathbf{x}_i \in \mathbb{R}^D$  drawn from a probability distribution  $p(X)$ .

- **Supervised learning:**  $p(\mathbf{y}|\mathbf{X})$
- **Unsupervised learning:**  $p(\mathbf{X})$

**Goal:** Directly infer the properties of this probability density function (PDF) without the help of a supervisor providing correct answers.



## Canonical Examples: Discovering Clusters

**Goal:** Attempts to find multiple convex regions of the  $X$ -space that contain modes of  $p(\mathbf{X})$ .

Allows to determine whether or not  $p(\mathbf{X})$  can be represented by a mixture of simpler densities representing distinct types or classes of observations.

# Canonical Examples: Discovering Clusters

**Goal:** Attempts to find multiple convex regions of the  $X$ -space that contain modes of  $p(\mathbf{X})$ .

Allows to determine whether or not  $p(\mathbf{X})$  can be represented by a mixture of simpler densities representing distinct types or classes of observations.

## Tasks:

- In the supervised case, we knew the expected number of clusters. In the unsupervised case, you decide this number (model selection).
- Determine which sample belongs to each cluster.

# Canonical Examples: Discovering Clusters

**Goal:** Attempts to find multiple convex regions of the  $X$ -space that contain modes of  $p(\mathbf{X})$ .

Allows to determine whether or not  $p(\mathbf{X})$  can be represented by a mixture of simpler densities representing distinct types or classes of observations.

## Tasks:

- In the supervised case, we knew the expected number of clusters. In the unsupervised case, you decide this number (model selection).
- Determine which sample belongs to each cluster.

**Real-world applications:** Segmentation (images, groups of people, genes), sub-population of cells (biology), groups of stars (astronomy), novelty and outlier detection.

# Canonical Examples: Discovering Clusters

**Goal:** Attempts to find multiple convex regions of the  $X$ -space that contain modes of  $p(\mathbf{X})$ .

Allows to determine whether or not  $p(\mathbf{X})$  can be represented by a mixture of simpler densities representing distinct types or classes of observations.

## Tasks:

- In the supervised case, we knew the expected number of clusters. In the unsupervised case, you decide this number (model selection).
- Determine which sample belongs to each cluster.

**Real-world applications:** Segmentation (images, groups of people, genes), sub-population of cells (biology), groups of stars (astronomy), novelty and outlier detection.

**Algorithms:** K-means, Hierarchical clustering, DBSCAN

**Note:** Mixture models have similar goals and are sometimes considered as clustering techniques

# Canonical Examples: Dimensionality Reduction

**Goal:** Attempts to identify low-dimensional manifolds within the  $X$ -space that represent high data density.

Provides information about associations among variables and whether or not they can be considered as functions of a smaller set of latent variables.

The motivation behind this technique is that although the data may appear high dimensional, there may only be a small number of degrees of variability, corresponding to latent factors

# Canonical Examples: Dimensionality Reduction

**Goal:** Attempts to identify low-dimensional manifolds within the  $X$ -space that represent high data density.

Provides information about associations among variables and whether or not they can be considered as functions of a smaller set of latent variables.

The motivation behind this technique is that although the data may appear high dimensional, there may only be a small number of degrees of variability, corresponding to latent factors

**Real-world applications:** interpretation of gene microarray data, data visualization, separation of signals into different sources (speech recognition).

# Canonical Examples: Dimensionality Reduction

**Goal:** Attempts to identify low-dimensional manifolds within the  $X$ -space that represent high data density.

Provides information about associations among variables and whether or not they can be considered as functions of a smaller set of latent variables.

The motivation behind this technique is that although the data may appear high dimensional, there may only be a small number of degrees of variability, corresponding to latent factors

**Real-world applications:** interpretation of gene microarray data, data visualization, separation of signals into different sources (speech recognition).

**Algorithms:** Principal component analysis, self-organizing maps, autoencoders, principal curves, multidimensional scaling

# Canonical Examples: Matrix Completion

**Goal:** Allows to complete data that may be missing from the collected data. This is often also called as imputation.

**Real-world applications:** Image inpainting, collaborative filtering, market basket analysis.

**Algorithms:** Non-negative matrix factorization



# Canonical Examples: Matrix Completion

**Goal:** Allows to complete data that may be missing from the collected data. This is often also called as imputation.

**Real-world applications:** Image inpainting, collaborative filtering, market basket analysis.

**Algorithms:** Non-negative matrix factorization

**Note:** Scikit-learn proposes a very good catalog of unsupervised techniques, while using a different taxonomy [\[link\]](#) .

## Wrap-up

---

- We presented the setup for unsupervised learning
- We introduced some of the main techniques used

# Key Concepts

- Probability density function
- Clustering
- Dimensionality reduction

## References

## Further Reading and Useful Material

Source	Notes
The Elements of Statistical Learning	Ch. 14