



Computer Systems & Networks



01: Command Line




Commands · Arguments ·
Options · Variables

02: File Management



Globs · Copy · Move ·
Remove

03: IO Redirection



STDIN · STDOUT · STDERR

Lab



File Management · IO
Redirection · Search &
Filter text

Linux Essentials

Content

Objectives

Key Terms

10.1
10.1.1
10.1.2
10.1.2.1
10.1.2.2
10.1.3
10.2
10.3
10.3.1
10.3.2
10.3.3
10.3.4
10.4
10.4.1
10.5
10.6
10.7
10.8
10.8.1
10.8.2
10.8.3
10.8.4
10.8.5
10.8.6

10.3 Input/Output Redirection

Input/Output (I/O) redirection allows for command line information to be passed to different streams. Before discussing redirection, it is important to understand the standard *streams*.

STDIN

Standard input, or *STDIN*, is information entered normally by the user via the keyboard. When a command prompts the shell for data, the shell provides the user with the ability to type commands that, in turn, are sent to the command as *STDIN*.

STDOUT

Standard output, or *STDOUT*, is the normal output of commands. When a command functions correctly (without errors) the output it produces is called *STDOUT*. By default, *STDOUT* is displayed in the terminal window where the command is executing. *STDOUT* is also known as *stream* or *channel* #1.

STDERR


Standard error, or *STDERR*, is error messages generated by commands. By default, *STDERR* is displayed in the terminal window where the command is executing. *STDERR* is also known as *stream* or *channel* #2.

I/O redirection allows the user to redirect *STDIN* so that data comes from a file and *STDOUT*/*STDERR* so that output goes to a file. Redirection is achieved by using the arrow `<` `>` characters.

◀ Previous

Next ▶

Input/Output Redirection




You might consider using redirection to:

- Redirect a command output to a file, instead of to the monitor
- Redirect a program to instead receive input from a file (where, by default, it receives input from the keyboard)
- Redirect error messages to files, instead of to the screen by default

File Descriptors (FD)



The kernel acts as an **interface between your hardware devices, constantly moving data between i/p and o/p devices**



In Linux, a process is **any active (running) instance of a program.**

a program is any executable file held in storage on your machine.

Anytime you run a program, you have created a process



Processes know where data should be sent to using **file descriptors.**

File Descriptors (FD)

File	FD
STDIN	0
STDOUT	1
STDERR	2

- In Linux/Unix, **everything** is a file
- Every File has an associated number called File Descriptor (**FD**).
- If a program is executed the output is sent to the FD of the screen (FD 1) & you see program output on your monitor (default).
- Similarly, if the output is sent to FD of the printer, the program output would have been printed.

Look at the file descriptors of given processes

- Devices registered when the kernel was instantiated can be seen in the **/dev** directory of your host.

File	FD
STDIN	0
STDOUT	1
STDERR	2


```
compsys@compsys-virtualbox:~$ ls -l /dev/ | less
```

- Can you see their FD's, as expected

```
lrwxrwxrwx 1 root root 15 Sep 2 12:45 stderr -> /proc/self/fd/2
lrwxrwxrwx 1 root root 15 Sep 2 12:45 stdin -> /proc/self/fd/0
lrwxrwxrwx 1 root root 15 Sep 2 12:45 stdout -> /proc/self/fd/1
```


Input Output Redirection

- ...allows for command line information to be passed to different *streams*
- The streams are:
 - STDIN (0) - Standard input (default keyboard)
 - STDOUT (1) - Standard output (data printed by the program, defaults to the screen)
 - STDERR (2) - Standard error (for error messages, also defaults to the screen)



Input/Output Redirection

- 3 files open when you exe any program/command:



File	FD
STDIN	0
STDOUT	1
STDERR	2

- redirection=routing defaults to something other than the default


Redirection Metacharacters

Command redirection is enabled by the following standard shell **metacharacters**:

- Redirection of standard input (<)
- Redirection of standard output (>)
- Redirection of standard error (2>)
- The pipe character (|)

1. Redirection of standard input <

Input redirection on Linux



1. Redirection of standard input <

\$command < filename

or

\$command 0< filename

File	FD
STDIN	0
STDOUT	1
STDERR	2

1. Redirection of standard input <

```
compsys@compsys-virtualbox:~$ cat emp*
300 frank manager sales €5000
400 caroline developer technology €5500
100 mary sysadmin technology €7000
200 rosanne manager marketing €9500
500 eamonn dba technology €6000
600 colm sysadmin technology €4500
```

```
compsys@compsys-virtualbox:~$ sort < emp*
100 mary sysadmin technology €7000
200 rosanne manager marketing €9500
300 frank manager sales €5000
400 caroline developer technology €5500
500 eamonn dba technology €6000
600 colm sysadmin technology €4500
compsys@compsys-virtualbox:~$ cat emp*
300 frank manager sales €5000
400 caroline developer technology €5500
100 mary sysadmin technology €7000
200 rosanne manager marketing €9500
500 eamonn dba technology €6000
600 colm sysadmin technology €4500
```

1. Redirection of standard input <

The commands that normally take their input from the standard input can have their input redirected from a file in this manner.


E.G. to count the number of lines in a file named *stats*, you can execute the command

```
$wc -l < stats
```

File	FD
STDIN	0
STDOUT	1
STDERR	2

2. Redirection of standard output (>)

Output redirection on Linux



2. Redirection of standard output (>)

File	FD
STDIN	0
STDOUT	1
STDERR	2

The standard output STDOUT of the `echo` command is to the

```
SC compsys@compsys-virtualbox:~$ echo "Caroline Cahill"  
Caroline Cahill
```

```
$ echo "Caroline Cahill" > classlist.txt
```

- Redirected the standard output to a file "classlist.txt" instead:

```
$ cat classlist.txt  
Caroline Cahill
```


2. Redirection of standard output (>)

PROBLEM:

Redirecting using > will **overwrite**



```
$ hostname > classlist.txt
```

`cat` the new contents of `classlist.txt`

3. Redirection of standard output (>>)


Preserve the contents of an existing file using the >> characters

- append to a file instead of overwriting it.

```
compsys@compsys-virtualbox:~$ date > classlist.txt
compsys@compsys-virtualbox:~$ cat class*
Fri 02 Sep 2022 12:30:46 IST
compsys@compsys-virtualbox:~$ hostname >> classli*
compsys@compsys-virtualbox:~$ cat class*
Fri 02 Sep 2022 12:30:46 IST
compsys-virtualbox
compsys@compsys-virtualbox:~$ uname -r >> classli*
compsys@compsys-virtualbox:~$ cat class*
Fri 02 Sep 2022 12:30:46 IST
compsys-virtualbox
5.15.0-47-generic
compsys@compsys-virtualbox:~$ echo "Phew, each line was appended to the end" >> classli*
compsys@compsys-virtualbox:~$ cat class*
Fri 02 Sep 2022 12:30:46 IST
compsys-virtualbox
5.15.0-47-generic
Phew, each line was appended to the end
compsys@compsys-virtualbox:~$
```

Redirection of standard error (2>)

Error redirection on Linux



Redirection of standard error (2>)

File	FD
STDIN	0
STDOUT	1
STDERR	2

- STDERR can be redirected similarly to STDOUT.

2>

→ all standard error messages should be sent to the file `error.txt`:

```
compsys@compsys-virtualbox: $ ls /fake
ls: cannot access /fake: No such file or directory
compsys@compsys-virtualbox:~$ ls /fake 2> error.txt
compsys@compsys-virtualbox:~$ cat error.txt
ls: cannot access /fake: No such file or directory
```

Redirecting Multiple Streams

File	FD
STDIN	0
STDOUT	1
STDERR	2

`$command 2>&1 filename`

`$command &> filename`

`2>&1` redirects STDERR to the same location as STDOUT

`$ls /usr/bin > command.txt 2>&1`

`ls /usr/bin`

#is the command to be executed

`> command.txt`

#redirects the STDOUT of the `ls` command to `command.txt`

`2>&1`

#sends the output of the stderr to the same file as stdout ie `command.txt`

Re-written in a *more streamlined* manner:

`$ls /usr/bin &> command.txt`

2>&1

List Contents of 2 Directories "Documents" & "ABC"
Directory "ABC" not found. "Documents" shown



```
compsys@compsys-virtualbox:~$ ls Documents ABC
ls: cannot access 'ABC': No such file or directory
Documents:
```

Redirecting standard output. Error output is still shown



```
compsys@compsys-virtualbox:~$ ls Documents ABC > dirlist
ls: cannot access 'ABC': No such file or directory
```

```
compsys@compsys-virtualbox:~$ ls Documents ABC > dirlist 2>&1
compsys@compsys-virtualbox:~$ cat dirlist
ls: cannot access 'ABC': No such file or directory
Documents:
```



2>&1

Redirecting error output to standard output

Standard output is already being re-directed to file > dirlist

Hence, both error and standard output are written to file

dirlist

Redirecting Multiple Streams

File	FD
STDIN	0
STDOUT	1
STDERR	2

- Both STDOUT and STDERR can be sent to a file by using the **&>** (this means both **1>** and **2>**)

```
compsys@compsys-virtualbox:~$ ls /fake /etc/ppp
ls: cannot access /fake: No such file or directory
/etc/ppp:
ip-down.d  ip-up.d
compsys@compsys-virtualbox :~$ ls /fake /etc/ppp &> all.txt
compsys@compsys-virtualbox :~$ cat all.txt
ls: cannot access /fake: No such file or directory
/etc/ppp:
ip-down.d
ip-up.d
```

- If you want STDOUT and STDERR to both go to different files:

```
compsys@compsys-virtualbox:~$ ls /fake /etc/ppp > example.txt 2> error.txt
```

/dev/null bitbucket

- /dev/null is the null device
- It takes any input you want and throws it away.
- It can be used to suppress any output

```
compsys@compsys-virtualbox:~$ ls /fake
ls: cannot access '/fake': No such file or directory
compsys@compsys-virtualbox:~$
```

- Control error messages by pushing to /dev/null

```
compsys@compsys-virtualbox:~$ ls /fake 2> /dev/null
compsys@compsys-virtualbox:~$
```



Redirection to Devices

- Can redirect standard output, to not just files, but also devices!

```
$ cat music.mp3 > /dev/audio
```


- The cat command reads the file **music.mp3** and sends the output to **/dev/audio** which is the audio device.

SUMMARY: Redirection Metacharacters

Symbol	Description
>	Directs the standard output of a command to a file. If the file exists, it is overwritten.
>>	Directs the output to a file, adding the output to the end of the existing file.
2>	Directs standard error to the file.
2>>	Directs the standard error to a file, adding the output to the end of the existing file.
&>	Directs standard output and standard error to the file.
<	Directs the contents of a file to the command.
<<	Accepts text on the following lines as standard input.
<>	The specified file is used for both standard input and standard output.

Try out
this weeks
Lab

01: Command Line




Commands · Arguments ·
Options · Variables

02: File Management



Globs · Copy · Move ·
Remove

03: IO Redirection



STDIN · STDOUT · STDERR

Lab



```
#!/bin/bash
```

File Management · IO
Redirection · Search &
Filter text

File Manipulation

01. Wildcards

02. Copy Move Remove

03. IO Redirection

Cisco NetAcad

03. IO Redirection

STDIN · STDOUT · STDERR

Redirecting using <

Use the **employee.txt** file as the STDIN for the **sort** command (by default this will sort by the first column)

```
$ sort < employee.txt
```



Redirecting STDOUT using >

Use the **employee.txt** file as the STDIN for the **sort** command, this time sending the STDOUT (i.e. the sorted list) into a new **SortedEmployees.txt** file

```
$ sort < employee.txt > SortedEmployee.txt
```



View your **SortedEmployee.txt** file to check if the output is as expected using the `___` command

REDIRECTION

Redirecting STDOUT using >>

Add the following new record to your **employee.txt** file using `>>`

```
compsys@compsys-virtualbox:~$ echo 600 colm sysadmin technology €4500 >> employee.txt
compsys@compsys-virtualbox:~$ cat employee.txt
100 frank manager sales €5000
200 caroline developer technology €5500
300 mary sysadmin technology €7000
400 rosanne manager marketing €9500
500 eamonn dba technology €6000
600 colm sysadmin technology €4500
```