



Higher Diploma in Computer Science

Computer Systems & Networks



Week 3

00: Module introduction



Linux · Computer Networks

01: Intro and Command Line...




Scripting · Permissions · Navigation

02: File and Text Manipulation



Redirection · grep · Positional Param · Exit Codes

03: Loops, Menus, sed



case · select · loops · sed · awk · 5% HW


03: if, while, for, break & continue; case & select for menus; using sed editor

01: Conditionals and Loops




test · if · for · while · until

02: Loop manipulation




break · continue · case · select

03: sed



Stream editor · find and replace

Lab



Loops · Menus · sed

#!/bin/bash

Lab

Computer Systems & Networks

Current Week

2

Search

Computer Syste...

03: Loops, Men...

Week 3 Class 1...

Lab

Advancing Scripting Skills

01. Conditionals
02. Loops
03. Menu driven scripts
04. sed
05. EXER Add new records
06. Cisco NetAcad

SOLUTIONS FROM WEEK 2:

Arithmetic Operators

- Create a **numEmp** file that returns basic details from **employee.txt**

```
empCount=$(cat ~/employee.txt | wc -l)
echo "Today on `date` there are ${empCount} employees."
```

Some examples for reference i.e. to multiply is included here

Addition

Computes addition of two numbers provided as operands.

```
#!/bin/bash
x=$(( 15 + 8 ))
echo $x
```

Week 2 LAB Recap

REMEMBER: Use Resources Freely Available to you

Share resources via Slack

- Here's *one of many* examples

This is a link but you'll have
to download the class
contents

- *links are not accessible directly
from tutors*

Ryans Tutorials

Bash Scripting Tutorial - 4. Arithmetic of 8

Arithmetic!

It all adds up.



Arithmetic Expansion **`$((...))`** v's older **`expr`**

- use **`$((...))`** to do math calculations

```
~$ echo "$(( 3 + (4+5) ))"
```

Why use **`$((... ))`**

- ✓ Inside **`((...))`**, you don't need to use `$` to reference variables.
- ✓ Supports all integer arithmetic operators, as per next slide.
- ✓ more forgiving about spaces.
- ✓ **`((...))`** is a **built-in Bash feature**, so it's *faster* than external commands like **`expr`**

- What would be a more efficient way of writing the following?

```
compsys@compsys-virtualbox:~$ myvar=100  
compsys@compsys-virtualbox:~$ expr ${myvar}  
300
```

```
$myvar=100;  
$echo $((myvar * 3))
```

Arithmetic Expansion **`$((...))`** v's older **`expr`**

```
#!/bin/bash
```

```
x=10
```

```
y=3
```

```
echo $(( x + y )) # addition
```

```
echo $(( $x + $y )) # also valid
```

```
echo $(( x - y )) # subtraction
```

```
echo $(( $x - $y )) # also valid
```

```
echo $(( x * y )) # multiplication
```

```
echo $(( $x * $y )) # also valid
```

```
echo $(( x / y )) # division
```

```
echo $(( $x / $y )) # also valid
```

```
echo $(( x ** y )) # exponentiation
```

```
echo $(( $x ** $y )) # also valid
```

```
echo $(( x % y )) # modular division
```

```
echo $(( $x % $y )) # also valid
```

```
(( x += 4 )) # increment variable by constant
```

```
echo $x
```

```
(( x -= 4 )) # decrement variable by constant
```

```
echo $x
```

```
(( x *= 4 )) # multiply variable by constant
```


```
echo $x
```

```
(( x /= 4 )) # divide variable by constant
```

```
echo $x
```

```
(( x %= 4 )) # Remainder of Dividing Variable by Constant
```

```
echo $x
```



Pipes

I

Working with Pipelines



- One of the most powerful Linux commands
 - Syntax: `|`
 - takes **output** from one command and **uses it as input** for another
- ✓ Can link/chain multiple pipes

Main purpose: filtering

- The most popular use for pipes involves the commands **sort** and **grep**

DON'T CONFUSE pipe (|) redirection with file redirection (>) and (<).

cmd1 > file

or

cmd1 < file

→ File redirection either sends output to a file

→ instead of STDOUT (screen) **OR**

→ pulls input from file instead of STDIN

→ (keyboard)

pipe and sort

sort file on the basis of 1st three fields:

```
$ sort -t"," -k1,3 employee.txt
```

Where

- t** = option is used to provide the delimiter, assuming it's a comma
- k** = specify the keys on the basis of which the sorting has to be done.
format of '-k' is : '-km,n' (m = the starting key and n = the ending key)
- f** would sort and ignore case
- n** would sort numerically
- C** would sort and remove duplicates

grep pipe and sort

We want to return only the lines that *do not* contain the characters 'Manager', but the result should be in *reverse* order.

```
$ cat employee.txt | grep -vi Manager | sort - r
```

Counting files

- For example, you can list the number of files in the current directory:

\$ls #send output to STDOUT (screen) by default

\$ls -l | less # pipe to less to make output easier to read/scrollable

\$ ls | head -3 | tail -1 #stack(/chain) commands using pipes

\$ls | head -3 | tail -1 > myoutput #combine with redirection

Count lines

\$ wc -l employee.txt #How many lines are in *employee.txt*?

How to pipe the output of **ls** command into **wc**:

- (i) **\$ls ~ | wc -l** #how many files are home
- (ii) Pipe this to `less` to inspect, q to quit
- (iii) \$ _____ #how many lines are in the /etc

Pipe Syntax

|

vertical line

View history of
commands, in
scrollable
format:

\$history | less

Try out

\$history | head -5

Count the number
of lines in the
home directory

\$ls ~ | wc -l

Week 3

space style 1 space

```
if [ condition1 ]  
then  
    statements  
elif [ condition2 ]  
then  
    statements  
else  
    statements  
fi
```

style 2

```
if [ condition1 ]; then  
    statements  
elif [ condition2 ]; then  
    statements  
else  
    statements  
fi
```

Conditional Statements

test



test command – is true/false

```
Caroline@ICTSkills>~$ test 10 -gt 55; echo $?  
1
```

Tests can be combined with logical **AND** and **OR**

```
compsys@compsys-virtualbox:~$ test 56 -gt 55 && echo true || echo false  
true  
compsys@compsys-virtualbox:~$ test 6 -gt 55 && echo true || echo false  
false
```

Re-written using square brackets

```
compsys@compsys-virtualbox:~$ [ 56 -gt 55 ] && echo true || echo false
```

Arithmetic Operators

+ -	Addition, subtraction
++ --	Increment, decrement
* / %	Multiplication, division, remainder
**	Exponentiation

-eq	→	_____
-ge	→	_____
-gt	→	_____
-le	→	_____
-lt	→	_____
-ne	→	_____

If BASH double parenthesis i.e. **(())** are not used
then the **test** command must be used to **compare** integer
variables

Try out this weeks Lab

01: Conditionals and Loops

02: Loop manipulation

03: sed

Lab

03: if, while, for, break & continue; case & select for menus; using sed editor

Advancing Scripting Skills

1. Conditionals

2. Loops

3. Menu driven scripts

4. sed

5. EXER Add new records

6. Cisco NetAcad

Combining Multiple Operators

It can be convenient at the beginning of execution to **check if a particular file exists** and create if not.

Here's the steps:

1. first check if a file **sample.txt** exists in your home directory (try make use of [**-f filename**] instead of the [**-d filename**] used above)

2. if it exists, print a message to STDOUT (**echo "File exists."**).

3. If not, create the file (**touch ~/sample.txt**)

```
compsys@compsys-virtualbox:~$ ls -l samp*
ls: cannot access 'samp*': No such file or directory
compsys@compsys-virtualbox:~$ [ -f ~/sample.txt ] && echo "File exists." || touch ~/sample.txt
compsys@compsys-virtualbox:~$ ls -l samp*
-rw-rw-r-- 1 compsys compsys 0 Sep  8 11:55 sample.txt
compsys@compsys-virtualbox:~$
```

test statement

Often used to testing verifying conditions, including:



if

if statement

= does a string comparison and

-eq does a numerical comparison

if [*test*]

then

commands

fi

```
if [ "$userinput" != "$password" ];  
then  
echo "Oops; Wrong Password Entered!"  
exit 1  
fi
```

How to use exit codes in scripts with an *if*

- Return a message to the user if this file called “employee.txt” ran successfully

What will be the output?

```
#!/bin/bash

cat employee.txt

if [ $? -eq 0 ]
then
    echo "This file $0 ran OK"
    exit 0
else
    echo "File failed"
    exit 1
fi
```

if/then/else

- Sometimes we may have a series of conditions that may lead to different paths.

```
if [ test ]  
then commands  
else commands  
fi
```

```
#!/bin/bash  
if [ -f employee.bak ]  
    then echo employee.bak regular  
file exists!  
    else echo employee.bak not found!  
fi
```

How to use **exit codes** in scripts with an *if/then/else*

\$? = the **exit status** of the last command executed

```
if [ $? -eq 0 ]; then
```

```
    # do something as the last command executed OK
```

```
else
```

```
    # do something else as last command executed with
```

```
error
```

```
fi
```

```
exit
```


if then elif

- You can nest a new **if** inside an **else** with **elif**

```
#!/bin/bash
count=42
if [ $count -eq 42 ]
then
    echo "42 is correct."
elif [ $count -gt 42 ]
then
    echo "Too much."
else
    echo "More!"
fi
```

\$# Shell Variable

- is the number of arguments taken in

\$echo \$# #outputs the number of positional parameters of your script.

```
if [ $# -eq 1 ]
then
    echo $1
else
    echo "invalid argument please pass only one argument, (Y or N): "
fi
exit
```

Try out this weeks Lab

03: if, while, for, break & continue; case & select for menus; using sed editor

01: Conditionals and Loops



LOOPS REPEAT ACTIONS... SO YOU DON'T HAVE TO

test · if · for · while · until

02: Loop manipulation

```
break, break {n}
exit, exit {n}
exit {n}
exit {n}
exit {n}
exit {n}
exit {n}
exit {n}
exit {n}
exit {n}
```

break · continue · case · select

03: sed



Stream editor · find and replace

Lab



Loops · Menus · sed

Advancing Scripting Skills

01. Conditionals

02. Loops

03. Menu driven scripts

04. sed

05. EXER Add new records

06. Cisco NetAcad

if statement

1. Make a backup of **employee.txt** called **employee.bak**

```
cp employee.txt employee.bak
```


2. Write a script **rmOld** which checks if an old temporary file exists called **employee.bak** and if so, then delete this

HINT: **-a filename** or **-e filename** will check if **filename** exists.

```
if [ -a employee.bak ]; then
rm -f employee.bak
fi
```

3. If **/.bashrc** is a regular file (use the **-f** option) and reply to the user "Hello username. You've checked a regular file"

Loop Constructs






for

Recap: Use Resources Freely Available to you

Share resources via Slack, for *(one of many)* example:



File Permissions

- Bash Ownership
- Bash Modify (chmod)
- Bash Ownership (chown)
- Bash Group (chgrp)

Scripting

Bash Syntax

- Bash Script
- Bash Variables
- Bash Data Types
- Bash Operators
- Bash If...Else
- Bash Loops
- Bash Functions
- Bash Arrays
- Bash Schedule (cron)

for

#!/bin/bash

Basic range in loop

for value in {1..5}

do

echo \$value

done

echo All done!

General format:

```
for var in varlist
do
    commands
done
```

The **for** statement executes the commands once for each value in the list

for example 1

```
# prints the numbers from 101 to 105
#
for num in 1 2 3 4 5
do
    expr $num + 100
done
```

Try out this weeks Lab

03: if, while, for, break & continue; case & select for menus; using sed editor


01: Conditionals and Loops



LOOPS REPEAT ACTIONS... SO YOU DON'T HAVE TO

test · if · for · while · until

02: Loop manipulation



break · continue · case · select

03: sed



Stream editor · find and replace

Lab



Loops · Menus · sed

Computer System... > 03: Loops, Men... > Week 3 Class 1... > Lab

02. Loops

for · while

for

Amend the basic **for** loop from the class notes to include a **for**, including an **if** statement and **break**

1. Look through this **for** code below: what is the expected output?

```
for i in {1..5};
do
  for j in {1..3};
  do
    if [[ $j -eq 2 ]]; then
      break
    fi
```




while

- general syntax for using the Bash while loop is

while [condition]

do

//code to execute here

//increment/decrement

done

while

Programming languages have loop constructs to allow a block of code to be executed repeatedly, either a fixed number of times, or while some condition holds.

while instruction general format

```
while [ condition ]  
do  
    commands  
done
```

Example: The following script prints all numbers from 1 to 100

```
# Prints all numbers from 1 to 100  
#  
num=1  
while [ $num -le 100 ]  
do  
    echo $num  
    num=`expr $num + 1`  
done
```

file=filename

while read -r line;
do

echo \$line

done < "\$file"

Infinite loops

CTRL+C

- the **`true`** indicates the while loop will **forever** iterate

If it returns quickly, it's beneficial to insert a small pause between executions to avoid CPU load, eg

```
while true
do
    echo "I will continue to iterate unless you press Ctrl+C"
    echo "let me also rest 1 second between every iteration"
    sleep 1
done
```

\$# Shell Variable

echo \$# outputs the number of positional parameters of your script.

```
if [[ $# -ne 1 ]]; then
    echo "Please use only one
    argument for file name"
    exit 1
fi
```

while loop example:

```
#!/bin/bash
```

```
while [ "$#" -ne 1 ]; do
    #your commands here
done
```



until

until

until **CONDITION;**

do

CONSEQUENT-COMMANDS;

done

```
#!/bin/bash
```

```
counter=0
```

```
until [ $counter -ge 5 ]
```

```
do
```

```
    echo Counter: $counter
```

```
    ((counter++))
```

```
done
```

- Very similar to **while** loop
 - except that the loop executes until the **TEST-COMMAND** executes successfully

Try out this weeks Lab

03: if, while, for, break & continue; case & select for menus; using sed editor

01: Conditionals and Loops



LOOPS REPEAT ACTIONS... SO YOU DON'T HAVE TO

test · if · for · while · until

02: Loop manipulation



break · continue · case · select

03: sed



Stream editor · find and replace

Lab



Loops · Menus · sed

Computer System... > 03: Loops, Men... > Week 3 Class 1... > Lab

EXERCISE

- Write the code, making use of a **for** loop to make a backup copy of each of your **.txt** files i.e. **filename.bak**

HINT consider listing and then redirecting all of your **.txt** files into some **temp** file; then consider copying each of these files as a new file extension)

while

Create a basic script to verify that the user has passed five arguments into it (Make use of class notes)

```
while [ "$#" -ne 5 ]; do
    #your commands here
    echo You must pass exactly five arguments please
    exit 1
done
```