



Higher Diploma in Computer Science

Computer Systems & Networks



Week 2 Class 1 LAB SOLUTIONS

From your **01. Wildcards** lab

- Using **find** to return files that begin with **temp**

```
compsys@compsys-virtualbox:~$ find ~ -name "temp*"
/home/compsys/temp
/home/compsys/snap/firefox/common/.mozilla/firefox/o49vw619.default/storage/temporary
/home/compsys/tempdate
compsys@compsys-virtualbox:~$
```

File Manipulation

01. Wildcards

02. Copy Move Remove

03. IO Redirection

Cisco NetAcad

EXERCISE: Using **find**

Write the command to find and return all files whose name begins with **tmp**

- The **find** command is a file search utility (Search for files in a directory hierarchy).

```
$ find ./Desktop -name "comp*" #command
./Desktop/computer.desktop #output
```

- Sample output:

```
compsys@compsys-virtualbox:~$ find ~ -name "temp*"
/tmp
/snap/firefox/common/.mozilla/firefox/o49vw619.default/datareporting/glean/tmp
compsys@compsys-virtualbox:~$
```

Week 2 Class 1 LAB SOLUTIONS

From your **03. IO Redirection** lab

File Manipulation

01. Wildcards

02. Copy Move Remove

03. IO Redirection

Cisco NetAcad

- **ls /usr/bin** is the command run
- **> command.txt** redirects the output of the **ls** command into the text file
- **2>&1** sends the output of the FD2 (stderr) to the same location as the FD1 (stdout)

This could be re-written more streamlined as

```
$ls /usr/bin ____ command.txt <<fill in the blank>>
```



EXERCISE:

Usign redirection

- allow the user to add (**echo**) a new record to the **employee.txt** file

Ensure this new record is appended to the existing **employee.txt** file, test it

```
compsys@compsys-virtualbox:~$ echo "123 Caroline Manager Sales €1234" >> employee.txt
compsys@compsys-virtualbox:~$ cat emp*
300 frank manager sales €5000
400 caroline developer technology €5500
999 catherine dev tech €4500
100 mary sysadmin technology €7000
200 rosanne manager marketing €9500
500 eamonn dba technology €6000
600 colm sysadmin technology €4500
echo "There are no $ currency, only € in employee.txt"
just another example katherine
666 Katherine dev tech €6000
123 Caroline Manager Sales €1234
```

Sorting Files or Input

↓ Z ↓ A
↓ A ↓ Z

↓ 9 ↓ 1
↓ 1 ↓ 9

Sorting Files for Input

- The **sort** command can be used to rearrange the lines of files or input in either dictionary or numeric order.

\$ sort filename

- **sort** command can rearrange the output based on the contents of one or more fields

\$ sort employee.txt

Delimited Files

- Fields are determined by a *field delimiter* contained on each line
 - **tab** character is the default delimiter
 - REMEMBER a "space" in between each word is actually a *single tab character*

Fields and Sort Options

- the following command can be used to **sort** the `passwd` file (alphabetically by first column by default)

```
compsys@compsys-virtualbox:~$ sort -t: passwd
```

- **-t** option will allow for another field separator to be specified
- You can specify to sort by a specific field (i.e. column 3) in numericcal order:

```
lbox:~$ sort -t: -n -k3 passwd
```

- **-n** option is used to perform a numeric sort.
- **-k** option allowd you specify which field to **sort** by

Viewing File Statistics

109

Lines

1518

Words

72

Sentence

9336

Characters

Viewing File Statistics

- The **wc** command provides the number of lines, words and bytes (1 byte = 1 character in a text file) for a file, and a total line count if more than one file is specified.

```
$ wc employee.txt
```

- It is also possible to view only specific statistics:
 - Use the **-l** option to show just the **number of lines**
 - The **-w** option to show just the **number of words**
 - The **-c** option to show just the **number of bytes**
 - or any combination of these options

Command Line Pipes

The **pipe** | character → used to send the output of one command to another.

E.g. The pipe character allows you to utilise the head and tail commands not only on files, but on the output of other commands.

Multiple pipes can be used consecutively to **link** multiple commands together. Each command only sees input from the previous command.

```
ubuntu@golinux:~$ cat fruits.txt
apple
banana
mango
orange
watermelon
ubuntu@golinux:~$ cut -b 1 fruits.txt
a
b
m
o
w
```

Filtering Files

Cut command in Linux

Filter File Sections

The **cut** command can extract *columns* of text from

- i. a file or
- ii. standard input.



In Linux the cut command is used to **snip a portion from a file or we can say to print a particular section or a particular line. This command first appeared in AT&T System III UNIX in 1982.**

Filter File Sections

- The **cut** command is for working with delimited files

```
albox:~$ cut -d: -f1,5-7 passwd
```

- **-d** option allows a specific alternative *delimiter* (default in **cut** expects input to be separated by the **Tab/space** character)
- **-f** option can specify *which fields to display* (here it displays the first, fifth, sixth and seventh fields from a `passwd` file)

```
albox:~$ cut -d: -f1,5-7 passwd | head -3
```

Filter File Sections

-c option is used to extract columns of text based upon character position

Return only the first three characters of the *employee.txt* file:

```
oX:~$ cut -c1-3 empl*
```

(globally search
for a regular
expression and
print matching
lines)



grep

grep

on every distribution
of Linux

search directories and
files for keywords and
strings

- search input files for a search string, and print the lines that match it

is a pattern searcher

- If the pattern is found, it displays the line containing it.

\$ grep *string filename*

grep

One of the renowned
search tool on Unix-
like systems

can be used to
search for anything

- a file
- or a line
- or multiple lines

\$ grep *string filename*

Different Versions

```
graph TD; A[Different Versions] --- B[grep]; A --- C[grep -E]; A --- D[grep -F];
```

grep

grep

grep -E

grep -F

Syntax

```
compsys@compsys-virtualbox:~$ grep "sysadmin" employee.txt
100 mary sysadmin technology €7000
600 colm sysadmin technology €4500
```

- `-n` parameter to show line numbers

```
3:100 mary sysadmin technology €7000
6:600 colm sysadmin technology €4500
```

- `-v` prints all of the lines that do not match the search string

```
1:300 frank manager sales €5000
2:400 caroline developer technology €5500
4:200 rosanne manager marketing €9500
5:500 eamonn dba technology €6000
```

Syntax

- **-c** option tells grep to suppress the printing of matching lines, and only display the number of lines that match (or **-v** for *do not* match) the query.

```
compsys@compsys-virtualbox:~$ grep -c "sysadmin" employee.txt
2
compsys@compsys-virtualbox:~$ grep -cv "sysadmin" employee.txt
4
```

Meta characters of grep

- + Equivalent to one or more occurrences of previous character.
- ? almost 1 repetition of previous character (**a?** match 'a' or 'aa')
- (Start of alternation expression
-) End of alternation expression
- | Matching either of the expression separated by '|'.
“(a|b)cde” would match either ‘acde’ or ‘bcde’
- { start of range specifier.
“a{2}” matches “aa” in file i.e. the letter ‘a’ 2 times.
- } end of range specifier

Using metacharacters **egrep**

^ → caret metacharacter indicated the beginning of the line

```
compsys@compsys-virtualbox:~$ grep '^4' employ*  
400 caroline developer technology €5500
```

\$ metacharacter indicates the end of the line

```
y €4500  
~$ grep '4$' employ*
```

So then, what will this search for?

```
$ grep '^4$' employ*
```

Using Regular Expressions With **grep**

- → zero or more instances of characters matching the pattern
 - You want to search for all instances of the letters **ar** in employee.txt

```
$ grep 'ar*' employ*
```

- This command reads “match all lines that start with “a” and may or may not have in them extra “r”

```
$ grep 'arr*' employ*
```

grep as a filter

- as a filter with other commands
- “|” pipe the output of the command through grep.

```
~$ ls -l | grep '^d'
```


♥ grep ♥

JULIA EVANS
@b0rk

grep lets you search
files for text

```
$ grep bananas foo.txt
```

Here are some of my
favourite grep command
line arguments!

 **-i** case insensitive

 **-A** Show context for your
search.
 **-B** `$ grep -A 3 foo`
 **-C** will show 3 lines of
context after a match

 **-E**
aka
egrep

Use if you want
regexps like ".+" to
work. otherwise you
need to use ".\+"

 **-v**

invert match: find
all lines that don't
match

 **-l**

only show the
filenames of the files
that matched

 **-F**

don't treat the match
string as a regex
eg `$ grep -F ...`

 **-r**

recursive! Search
all the files in
a directory.




 **-o**

only print the
matching part of
the line (not the
whole line)

 **-a**

search binaries:
treat binary data
like it's text instead
of ignoring it!

grep alternatives

 ack  ag  ripgrep
(better for searching code!)