# 가이드

## scss 파일 구조

common - 공통 scss 파일 / style - 기본 scss 파일

```
scss
common.scss
style.scss

import
base
component
utills
```



## 정의

## 1. 변수

#### base/\_variable.scss

```
// 폰트 파일명 정의
$font: SpoqaHanSansNeo;
$font2: OneShinhan;
```

- \$font, \$font2 변수에 폰트 공통 이름
- \$font-face-custom 에 해당 폰트의 상세 이름
- \$root-px 설정

#### 2. 컴포넌트

#### component/button, form, table ...

button, form, table 등과 같은 공통 컴포넌트 스타일 정의

#### 3. mixin

#### utills/mixin/ ...

믹스인 정의

## 사용

#### 1. 폰트

```
//fontName, fontSize, lineHeight 사용할 경우
@include font('regular', 14px, 20/14);
```

```
//compile
font-family: SpoqaHanSansNeo-Regular;
font-size: 1rem;
line-height: 1.5;

//font-family만 사용할 경우
@include font-family('regular');

//compile
font-family: SpoqaHanSansNeo-Regular;
```

base/\_font-face.scss , utills/mixin/\_mixin\_font.scss

#### 2. rem 변환

```
//rem(값)
height: rem(54px);

//compile
height: 3.85rem;
```

utills/function/\_fn\_unit\_calculator.scss

## 3. mediaQuery

```
//screen(minWidth, maxWidth)
@include screen(360px, 960px){
    @content;
};
//compile
@media screen and (min-width: 360px) and (max-width: 960px){
    @content;
};
//max-screen(maxWidth)
@include max-screen(960px){
    @content;
};
//compile
@media screen and (max-width: 960px){
    @content;
};
```

```
//min-screen(minWidth)
@include min-screen(960px){
    @content;
};
//compile
@media screen and (min-width: 960px){
    @content;
//screen-height(minHeight, maxHeight)
@include screen-height(640px, 1080px){
    @content;
//compile
@media screen and (min-height: 640px) and (max-height: 1080px){
    @content;
};
//max-screen-height(maxHeight)
@include max-screen-height(640px){
    @content;
};
//compile
@media screen and (max-height: 640px){
    @content;
};
//min-screen-height(minHeight)
@include min-screen-height(640px){
    @content;
};
//compile
@media screen and (min-height: 640px){
    @content;
};
```

utills/mixin/\_mixin\_mediaquery.scss

### 4. utills (vendor-prefix)

```
//vendor-prefix(name, prop)
p{ @include vendor-prefix(appearance, none); }
//compile
p {
  -webkit-appearance: none;
  -moz-appearance: none;
  -ms-appearance: none;
  -o-appearance: none;
```

```
appearance: none;
//webkit(name, prop)
p{ @include webkit(appearance, none); }
//compile
p {
  -webkit-appearance: none;
 appearance: none;
}
//moz(name, prop)
p{ @include moz(appearance, none); }
//compile
p {
  -moz-appearance: none;
  appearance: none;
}
//ms(name, prop)
p{ @include ms(appearance, none); }
//compile
p {
  -ms-appearance: none;
  appearance: none;
//o(name, prop)
p{ @include o(appearance, none);}
//compile
p {
  -o-appearance: none;
  appearance: none;
}
```

utills/mixin/\_mixin\_utills.scss