

# Copyright Notice

These slides are distributed under the Creative Commons License.

[DeepLearning.AI](#) makes these slides available for educational purposes. You may not use or distribute these slides for commercial purposes. You may make copies of these slides and use or distribute them for educational purposes as long as you cite [DeepLearning.AI](#) as the source of the slides.

For the rest of the details of the license, see <https://creativecommons.org/licenses/by-sa/2.0/legalcode>



deeplearning.ai

# Hyperparameter tuning

---

## Tuning process

# Hyperparameters

→  $\alpha$

$\beta$  0.9

$\beta_1, \beta_2, \epsilon$   
0.9 0.999  $10^{-8}$



# layers

# hidden units


learning rate decay

mini-batch size

# Try random values: Don't use a grid



# Coarse to fine





deeplearning.ai


# Hyperparameter tuning

---

Using an appropriate  
scale to pick  
hyperparameters

# Picking hyperparameters at random

→  $n^{\text{test}} = 50, \dots, 100$





→ #layers     L :     2 - 4

2 , 3 , 4

# Appropriate scale for hyperparameters

$$\alpha = 0.0001, \dots, 1$$



$$10^a$$

$$a = \log_{10} 0.0001$$

$$= -4$$

$$r = -4 * \text{np.random.rand}()$$

$$\alpha = 10^r$$

$$r \in [-4, 0]$$

$$10^{-4} \dots 10^0$$

$$\frac{10^a \dots 10^b}{}$$

$$\frac{r \in [a, b]}{[-4, 0]}$$

$$\underline{\alpha = 10^r}$$

$$10^b$$

$$\frac{b = \log_{10} 1}{= 0}$$



# Hyperparameters for exponentially weighted averages

$$\beta = 0.9 \quad \dots \quad 0.999$$

$\downarrow$   
10

$\downarrow$   
1000

$$1 - \beta = 0.1 \quad \dots \quad 0.001$$


---


$$\beta: 0.999 \rightarrow 0.9995 \quad \} \sim 10$$

$$\beta: 0.999 \rightarrow 0.9995$$

$\sim 1000$

$\sim 2000$

$$\frac{1}{1 - \beta_K}$$



$$r \in [-3, -1]$$

$$1 - \beta = 10^r$$

$$\beta = 1 - 10^r$$




deeplearning.ai

# Hyperparameters tuning

---


Hyperparameters  
tuning in practice:  
Pandas vs. Caviar

# Re-test hyperparameters occasionally




- NLP, Vision, Speech,  
Ads, logistics, ....
- Intuitions do get stale.  
Re-evaluate occasionally.

# Babysitting one model



Panda ←

# Training many models in parallel



Caviar ←




deeplearning.ai

# Batch Normalization

---

Normalizing activations  
in a network

# Normalizing inputs to speed up learning





$$\mu = \frac{1}{n} \sum_i x^{(i)}$$

$$X = X - \mu$$

$$\sigma^2 = \frac{1}{n} \sum_i x^{(i)2} \quad \leftarrow \text{element-wise}$$

$$X = X / \sigma^2$$



Can we normalize  $\frac{a^{[2]}}{w^{[2]}, b^{[2]}}$  so as to train faster

Normalize  $\frac{z^{[2]}}{\uparrow}$

# Implementing Batch Norm

Given some intermediate values in NN

$$\begin{matrix} \downarrow & \downarrow \\ z^{(1)} & \dots, z^{(m)} \end{matrix}$$

$z^{[l]}(i)$

$$\begin{aligned} \mu &= \frac{1}{m} \sum_i z^{(i)} \\ \sigma^2 &= \frac{1}{m} \sum_i (z^{(i)} - \mu)^2 \\ z_{\text{norm}}^{(i)} &= \frac{z^{(i)} - \mu}{\sqrt{\sigma^2 + \epsilon}} \\ \hat{z}^{(i)} &= \gamma z_{\text{norm}}^{(i)} + \beta \end{aligned}$$


If

$$\gamma = \sqrt{\sigma^2 + \epsilon}$$

$$\beta = \mu$$

then  $\hat{z}^{(i)} = z^{(i)}$

learnable parameters of model.



Use  $\hat{z}^{[l]}(i)$  instead of  $z^{[l]}(i)$ .



deeplearning.ai


# Batch Normalization

---

Fitting Batch Norm  
into a neural network



# Adding Batch Norm to a network



$$X \xrightarrow{W^{[1]}, b^{[1]}} \underline{z^{[1]}} \xrightarrow[\text{Batch Norm (BN)}]{\beta^{[1]}, \gamma^{[1]}} \underline{z^{[1]}} \rightarrow a^{[1]} = g(z^{[1]}) \xrightarrow{W^{[2]}, b^{[2]}} \underline{z^{[2]}} \xrightarrow[\text{BN}]{\beta^{[2]}, \gamma^{[2]}} \underline{z^{[2]}} \rightarrow a^{[2]} \rightarrow \dots$$

Parameters:  $\left\{ W^{[1]}, b^{[1]}, W^{[2]}, b^{[2]}, \dots, W^{[L]}, b^{[L]} \right\}$   
 $\rightarrow \underline{\beta^{[1]}}, \underline{\gamma^{[1]}}, \underline{\beta^{[2]}}, \underline{\gamma^{[2]}}, \dots, \underline{\beta^{[L]}}, \underline{\gamma^{[L]}}$   
 $\rightarrow \underline{\beta}$

$$d\beta^{[L]} \quad \beta = \beta - \alpha d\beta^{[L]}$$

tf.nn.batch-normalization ←

# Working with mini-batches

$$\underline{X^{[1]}} \xrightarrow{W^{[1]}, b^{[1]}} \underline{z^{[1]}} \xrightarrow[\text{BN}]{\beta^{[1]}, \gamma^{[1]}} \underline{\tilde{z}^{[1]}} \rightarrow g^{[1]}(\tilde{z}^{[1]}) = a^{[1]} \xrightarrow{W^{[2]}, b^{[2]}} \underline{z^{[2]}} \rightarrow \dots$$

$$\boxed{X^{[2]}} \rightarrow \underline{z^{[2]}} \xrightarrow[\text{BN}]{\beta^{[2]}, \gamma^{[2]}} \underline{\tilde{z}^{[2]}} \rightarrow \dots$$

$$X^{[3]} \rightarrow \dots$$

Parameters:  $W^{[L]}, \cancel{b^{[L]}}, \beta^{[L]}, \gamma^{[L]}$

$\uparrow$   $(n^{[L]}, 1)$      $\uparrow$   $(n^{[L]}, 1)$      $\uparrow$   $(n^{[L]}, 1)$

$\uparrow$   $z^{[L]}_{(n^{[L]}, 1)}$

$$\rightarrow \underline{z^{[L]}} = W^{[L]} a^{[L-1]} + \cancel{b^{[L]}}$$

$\uparrow$

$$z^{[L]} = W^{[L]} a^{[L-1]}$$

$$z^{[L]}_{\text{norm}}$$

$$\rightarrow \underline{\tilde{z}^{[L]}} = \gamma^{[L]} z^{[L]}_{\text{norm}} + \boxed{\beta^{[L]}}$$

# Implementing gradient descent

for  $t = 1 \dots \text{num Mini Batches}$

Compute forward pass on  $X^{\{t\}}$ .

In each hidden layer, use BN to replace  $\underline{z}^{\{t\}}$  with  $\underline{\hat{z}}^{\{t\}}$ .

Use backprop to compute  $\underline{dw}^{\{t\}}$ ,  ~~$\underline{db}^{\{t\}}$~~ ,  $\underline{dp}^{\{t\}}$ ,  $\underline{df}^{\{t\}}$

Update params  $\left. \begin{aligned} w^{\{t\}} &:= w^{\{t-1\}} - \alpha \underline{dw}^{\{t\}} \\ \beta^{\{t\}} &:= \beta^{\{t-1\}} - \alpha \underline{dp}^{\{t\}} \\ \gamma^{\{t\}} &:= \dots \end{aligned} \right\} \leftarrow$

Works w/ momentum, RMSprop, Adam.




deeplearning.ai

# Batch Normalization

---

Why does  
Batch Norm work?

# Learning on shifting input distribution





Cat

Non-Cat

$y = 1$  ✓

$y = 0$



$y = 1$  ✓


$y = 0$



"Covariate shift"

$\underline{x} \rightarrow y$

# Why this is a problem with neural networks?



# Batch Norm as regularization

- Each mini-batch is scaled by the mean/variance computed on just that mini-batch.
- This adds some noise to the values  $z^{[l]}$  within that minibatch. So similar to dropout, it adds some noise to each hidden layer's activations.
- This has a slight regularization effect.

mini-batch : 64  $\longrightarrow$  512

# Batch Norm at test time

$$\begin{aligned} \rightarrow \underline{\mu} &= \frac{1}{m} \sum_i z^{(i)} \\ \rightarrow \underline{\sigma^2} &= \frac{1}{m} \sum_i (z^{(i)} - \underline{\mu})^2 \end{aligned}$$

$$\rightarrow z_{\text{norm}}^{(i)} = \frac{z^{(i)} - \underline{\mu}}{\sqrt{\underline{\sigma^2} + \epsilon}} \leftarrow$$

$$\rightarrow \tilde{z}^{(i)} = \gamma \underline{z_{\text{norm}}}^{(i)} + \beta$$

$\underline{\mu}, \underline{\sigma^2}$ : estimate using exponentially weighted average (across mini-batches).

$$\begin{array}{ccccccc} X^{\{1\}}, X^{\{2\}}, X^{\{3\}}, \dots & & & & & & \\ \downarrow & \searrow & \searrow & & & & \\ \cancel{\underline{\mu}^{\{1\}}} & \underline{\mu}^{\{2\}[1]} & \underline{\mu}^{\{3\}[1]} & \dots & \rightarrow & \underline{\mu} & \\ \cancel{\underline{\sigma^2}^{\{1\}}} & \underline{\sigma^2}^{\{2\}[1]} & \underline{\sigma^2}^{\{3\}[1]} & \dots & & \underline{\sigma^2} & \\ \hline \tilde{z}_{\text{norm}} = \frac{z - \underline{\mu}}{\sqrt{\underline{\sigma^2} + \epsilon}} & & & & \tilde{z} = \gamma \tilde{z}_{\text{norm}} + \beta & & \end{array}$$



# Batch Norm at test time

$$\rightarrow \mu = \frac{1}{m} \sum_i z^{(i)}$$

$$\sigma^2 = \frac{1}{m} \sum_i (z^{(i)} - \mu)^2$$

$$z_{\text{norm}}^{(i)} = \frac{z^{(i)} - \mu}{\sqrt{\sigma^2 + \epsilon}}$$

$$\tilde{z}^{(i)} = \gamma z_{\text{norm}}^{(i)} + \beta$$



deeplearning.ai

# Multi-class classification

---

## Softmax regression

# Recognizing cats, dogs, and baby chicks



3



1



2



0



3




2




0




1









# Softmax layer



# Softmax layer



# Softmax examples





# Understanding softmax

(4,1)

$$z^{[L]} = \begin{bmatrix} 5 \\ 2 \\ -1 \\ 3 \end{bmatrix} \quad t = \begin{bmatrix} e^5 \\ e^2 \\ e^{-1} \\ e^3 \end{bmatrix}$$

$C = 4$

$g^{[L]}(\cdot)$

"soft max"

$$a^{[L]} = g^{[L]}(z^{[L]}) = \begin{bmatrix} e^5 / (e^5 + e^2 + e^{-1} + e^3) \\ e^2 / (e^5 + e^2 + e^{-1} + e^3) \\ e^{-1} / (e^5 + e^2 + e^{-1} + e^3) \\ e^3 / (e^5 + e^2 + e^{-1} + e^3) \end{bmatrix} = \begin{bmatrix} 0.842 \\ 0.042 \\ 0.002 \\ 0.114 \end{bmatrix}$$

"hard max"

$$\begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix}$$

Softmax regression generalizes logistic regression to  $C$  classes.

If  $C=2$ , softmax reduces to logistic regression.  $a^{[L]} = \begin{bmatrix} 0.842 \\ 0.158 \end{bmatrix}$

# Loss function

$(4,1)$   
 $y^{(1)} = \begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix}$  - cat  
 $y_2 = 1$   
 $y_1 = y_3 = y_4 = 0$

$(4,1)$   
 $a^{(1)} = \hat{y}^{(1)} = \begin{bmatrix} 0.3 \\ 0.2 \\ 0.1 \\ 0.4 \end{bmatrix}$

$C=4$

$\underbrace{\mathcal{L}(\hat{y}, y)}_{\text{small}} = - \sum_{j=1}^C y_j \log \hat{y}_j$

$\mathcal{J}(w^{(1)}, b^{(1)}, \dots) = \frac{1}{n} \sum_{i=1}^n \mathcal{L}(\hat{y}^{(i)}, y^{(i)})$

$- y_2 \log \hat{y}_2 = - \log \hat{y}_2$

Make  $\hat{y}_2$  big.

$Y = [y^{(1)} \ y^{(2)} \ \dots \ y^{(n)}]$

$\hat{Y} = [\hat{y}^{(1)} \ \dots \ \hat{y}^{(n)}]$

$= \begin{bmatrix} 0 & 0 & 1 & \dots \\ 1 & 0 & 0 & \dots \\ 0 & 1 & 0 & \dots \\ 0 & 0 & 0 & \dots \end{bmatrix}$   
 $(4, m)$

$= \begin{bmatrix} 0.3 & \dots \\ 0.2 & \dots \\ 0.1 & \dots \\ 0.4 & \dots \end{bmatrix}$   
 $(4, m)$





deeplearning.ai

# Programming Frameworks

---

# Deep Learning frameworks

# Deep learning frameworks

- Caffe/Caffe2
- CNTK
- DL4J
- Keras
- Lasagne
- mxnet
- PaddlePaddle
- TensorFlow
- Theano
- Torch

## Choosing deep learning frameworks

- Ease of programming (development and deployment)
- Running speed
- - Truly open (open source with good governance)



deeplearning.ai

# Programming Frameworks

---

## TensorFlow

# Motivating problem

$$\begin{aligned} J(w) &= \boxed{w^2 - 10w + 25} \\ &\quad \swarrow \\ &\quad (w-5)^2 \\ &\quad w=5 \end{aligned}$$

$$\begin{aligned} J(w, b) \\ \uparrow \quad \uparrow \end{aligned}$$

# Code example

```
import numpy as np
import tensorflow as tf
```

```
coefficients = np.array([[1], [-20], [25]])
```

```
w = tf.Variable([0], dtype=tf.float32)
```

```
x = tf.placeholder(tf.float32, [3, 1])
```

```
cost = x[0][0]*w**2 + x[1][0]*w + x[2][0] # (w-5)**2
```

```
train = tf.train.GradientDescentOptimizer(0.01).minimize(cost)
```

```
init = tf.global_variables_initializer()
```

```
session = tf.Session()
```

```
session.run(init)
```

```
print(session.run(w))
```

```
with tf.Session() as session:
```

```
    session.run(init)
```

```
    print(session.run(w))
```

```
for i in range(1000):
```

```
    session.run(train, feed_dict={x:coefficients})
```

```
print(session.run(w))
```

