
(NN Structure




RGB has 3 Channels ex) 3x64x64


* Padding:

1	-1	1		0	0	٥	Đ	อ
0	I	(\longrightarrow	0	_	7	١	0
0	٥	1		0	0	ſ	(0
		•	•	0	0	0	ı	д
				0	0	0	0	δ

if input data is $R^{5\times5}$, and apply hernel 3×3 , $R^{5\times5} \to R^{3\times3}$ After padding to data, $R^{5\times5} \to R^{7\times7}$, and when we apply 5×5 keynel, $R^{7\times7} \to R^{5\times5}$. It prevents loosing information

* Stride: How far the filter moves in every step along





Stride = 2										
0	0	٥	0	O						
0	. [1.	١.	0						
0	0	-((-	0	L					
0	0	0	1	д						
0	0	0	0	٥						
	,									

$$\left(\frac{5-3}{2}+1\right)\times\left(\frac{5-3}{2}+1\right)=2\times2$$

Why?

*Dimension: $\left(\frac{d_1-k_1}{s}\right)+1 \times \left(\frac{d_2-k_2}{s}\right)+1$

* Convolutional layer: Convolution + (Normalize) + Activortion
Optional

Code example w/ PyTorch:

nn. Conv 2d (input_ channel, output_channel, kevnel_size, stuide, panding, bias = False),),

nn. Botch Norm 2d (out put_size),

nn. Leany ReLU(0.2),