Go course

Petr Shevtsov 2019-05-13

Contents

Preface			
1	Basic Concepts 1.1 What is Go? 1.2 Hello, world! 1.3 The Go CLI 1.4 Value types 1.5 Variables 1.6 Operators 1.7 Constants 1.8 Comments 1.9 Packages and imports Module project	77 77 77 77 77 77 77	
2	Conditionals and Loops 2.1 The if statement 2.2 The else statement 2.3 if/else chains 2.4 The if statement with expression 2.5 The switch statement 2.6 The switch without condition 2.7 The for statement 2.8 The defer statement Module project	9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	
3	3.1 Arrays 3.2 Loops and arrays 3.3 Slices 3.4 Appending items to slices 3.5 Range 3.6 Maps 3.7 Arrays vs maps 3.8 Structs 3.9 Struct literals 3.10 Operations with structs	11 11 11 11 11 11 11 11 11 11	
4	4.1 Function declaration	15 15 15	

4 CONTENTS

	4.4	Error handling	15
	4.5	Variadic functions	15
	4.6	Iteration and recursion	15
	4.7	Anonymous functions	15
	4.8	Panic	15
	4.9	Pointers	15
	4.10	Functions and pointers	15
	Mod	lule project	15
5	Met	chods	17
	5.1	Method declarations	17
	5.2	Methods with a pointer receiver	17
	5.3	Composing types with structs	17
	5.4	Working with struct methods	17
	5.5	Method values	17
	5.6	Method expressions	17
	5.7	Encapsulation	17
6	Into	erfaces	19
U	6.1	Introduction	19
	6.2	Interface types	19
	6.2	Satisfaction	19
	6.4	flag.Value	19
	6.5		19
		Interface values	
	6.6	Sorting with sort.Interface	19
	6.7	The error interface	19
	6.8	Type assertions	19
	6.9	Type switches	19
7	Gor	outines and channels	2 1
	7.1	What is goroutine	21
	7.2	Introduction to concurrency	21
	7.3	Channels	21
	7.4	Types of channels	21
	7.5	Pipelines	21
	7.6	Looping in parallel	21
	7.7	time.Tick	21
	7.8	The select statement	21
	7.9	Cancellation	21
	Mod	lule project	21

Preface

The course is targeted at a beginner level student new to Go but might be familiar with 1-2 other languages (e.g. Python, HTML).

6 CONTENTS

Basic Concepts

- 1.1 What is Go?
- 1.2 Hello, world!
- 1.3 The Go CLI
- 1.4 Value types
- 1.5 Variables
- 1.6 Operators
- 1.7 Constants
- 1.8 Comments
- 1.9 Packages and imports

```
// This is a comment.
// Every Go file must be a part of some package.
// This file is a part of package main.
package main

// We import package "fmt" from the standard Go library.
import "fmt"

// `who` is a constant.
```

```
const who = "world"

// Function main() is the main entry point of any application written in Go.
func main() {
    // We declare `greeting` as a variable of type string and assign the value.
    var greeting string = "Hello"
    // We declare `message` variable using the shorthand syntax. The type of
    // the variable is determined by the assigned value. In our case it is
    // string type.
    message := greeting + ", " + who
    // Let's print the value of the variable `message` using the function from
    // the package "fmt".
    fmt.Println(message)
}
```

Hello, world

Conditionals and Loops

- 2.1 The if statement
- 2.2 The else statement
- 2.3 if/else chains
- 2.4 The if statement with expression
- 2.5 The switch statement
- 2.6 The switch without condition
- 2.7 The for statement
- 2.8 The defer statement

```
package main
import "fmt"

func main() {
   for age := 0; age < 99; age++ {
      switch age {
      case 16:
         fmt.Println("When you're", age, "you can drive a car!")
      case 18:
        fmt.Println("When you're", age, "you can buy a lottery ticket!")
      case 21:</pre>
```

Composite Data Types

- 3.1 Arrays
- 3.2 Loops and arrays
- 3.3 Slices
- 3.4 Appending items to slices
- 3.5 Range
- **3.6** Maps
- 3.7 Arrays vs maps
- 3.8 Structs
- 3.9 Struct literals
- 3.10 Operations with structs

```
package main
import (
    "fmt"
    "strings"
)
```

cruel 1

```
const Shakespeare = `
From fairest creatures we desire increase,
That thereby beauty's rose might never die,
But as the riper should by time decease,
His tender heir might bear his memory:
But thou contracted to thine own bright eyes,
Feed'st thy light's flame with self-substantial fuel,
Making a famine where abundance lies,
Thy self thy foe, to thy sweet self too cruel:
Thou that art now the world's fresh ornament,
And only herald to the gaudy spring,
Within thine own bud buriest thy content,
And tender churl mak'st waste in niggarding:
 Pity the world, or else this glutton be,
 To eat the world's due, by the grave and thee.
func main() {
    wordCount := make(map[string]int)
    for _, word := range strings.Fields(Shakespeare) {
        word = strings.Trim(word, ",:.")
        word = strings.ToLower(word)
        count := wordCount[word]
        count++
        wordCount[word] = count
    }
    for word, count := range wordCount {
        fmt.Println(word, count)
    }
}
## but 2
## waste 1
## in 1
## self-substantial 1
## fuel 1
## die 1
## as 1
## his 2
## bear 1
## thou 2
## feed'st 1
## niggarding 1
## tender 2
## with 1
## spring 1
## or 1
## grave 1
## might 2
## should 1
## bright 1
```

now 1 ## churl 1 ## rose 1 ## eat 1 ## the 6 ## decease 1 ## thine 2 ## art 1 ## content 1 ## memory 1 ## own 2 ## self 2 ## gaudy 1 ## mak'st 1 ## lies 1 ## herald 1 ## too 1 ## never 1 ## time 1 ## to 4 ## thy 5 ## flame 1 ## where 1 ## creatures 1 ## a 1 ## thee 1 ## riper 1 ## world's 2 ## ornament 1 ## only 1 ## world 1 ## this 1 ## bud 1 ## buriest 1 ## desire 1 ## by 2 ## heir 1 ## famine 1 ## abundance 1 ## and 3## pity 1 ## be 1 ## fairest 1 ## increase 1 ## contracted 1 ## fresh 1 ## else 1 ## we 1 ## light's 1 ## sweet 1 ## within 1 ## due 1 ## foe 1 ## glutton 1

- ## from 1 ## that 2 ## thereby 1 ## beauty's 1 ## eyes 1
- ## making 1

Functions and pointers

- 4.1 Function declaration
- 4.2 Functions parameters
- 4.3 Return values
- 4.4 Error handling
- 4.5 Variadic functions
- 4.6 Iteration and recursion
- 4.7 Anonymous functions
- 4.8 Panic
- 4.9 Pointers
- 4.10 Functions and pointers

```
package main
import "fmt"

// fibonacci returns the nth Fibonacci number.
func fibonacci(n int) int {
```

```
if n < 2 {
       return n
    return fibonacci(n-1) + fibonacci(n-2)
}
// fibonacciSequence changes the int slice to make it contain the Fibonacci
// numbers according to its keys. This function operates on the actual slice,
// that's why it does not return anything.
func fibonacciSequence(slice []int) {
   for n := range slice {
       slice[n] = fibonacci(n)
    }
}
func main() {
    // Create an empty int slice of length 10
    sequence := make([]int, 10)
    // Fill the slice with Fibonacci numbers secuence
    fibonacciSequence(sequence)
    fmt.Println(sequence)
}
```

[0 1 1 2 3 5 8 13 21 34]

Methods

- 5.1 Method declarations
- 5.2 Methods with a pointer receiver
- 5.3 Composing types with structs
- 5.4 Working with struct methods
- 5.5 Method values
- 5.6 Method expressions
- 5.7 Encapsulation

Interfaces

- 6.1 Introduction
- 6.2 Interface types
- 6.3 Satisfaction
- 6.4 flag. Value
- 6.5 Interface values
- 6.6 Sorting with sort. Interface
- 6.7 The error interface
- 6.8 Type assertions
- 6.9 Type switches

Goroutines and channels

- 7.1 What is goroutine
- 7.2 Introduction to concurrency
- 7.3 Channels
- 7.4 Types of channels
- 7.5 Pipelines
- 7.6 Looping in parallel
- 7.7 time.Tick
- 7.8 The select statement
- 7.9 Cancellation

${\bf Module\ project}$

```
package main

import (
    "fmt"
    "math/rand"
    "sync"
    "time"
)
```

```
const (
    NumberOfRacers
    NumberOfLaps
                     = 3
    MaxSleepDuration = 3 // seconds
)
func init() {
    rand.Seed(time.Now().UnixNano())
func race(racer int, start chan struct{}, finish chan int, status chan []int, wg *sync.WaitGroup) {
    defer wg.Done()
    <-start
    for lap := 1; lap <= NumberOfLaps; lap++ {</pre>
        sleep := time.Duration(rand.Intn(MaxSleepDuration))
        time.Sleep(sleep * time.Second)
        go func(racer, lap int) {
            status <- []int{racer, lap}</pre>
        }(racer, lap)
    }
    finish <- racer
}
func main() {
    start := make(chan struct{})
    finish := make(chan int)
    status := make(chan []int)
    done := make(chan struct{})
    var wg sync.WaitGroup
    wg.Add(NumberOfRacers)
    for racer := 1; racer <= NumberOfRacers; racer++ {</pre>
        go race(racer, start, finish, status, &wg)
    }
    go func() {
        wg.Wait()
        close(done)
    }()
    startTime := time.Now()
    close(start)
    ticker := time.NewTicker(time.Second)
    defer ticker.Stop()
    var winners []int
OuterLoop:
    for {
        select {
        case t := <-ticker.C:</pre>
            fmt.Println("Race time:", t.Sub(startTime))
        case s := <-status:</pre>
```

7.9. CANCELLATION 23

```
fmt.Printf("Racer #%d is on lap %d\n", s[0], s[1])
        case finished := <-finish:</pre>
            fmt.Printf("Racer #%d finished!\n", finished)
            if len(winners) < 3 {</pre>
                winners = append(winners, finished)
        case <-done:</pre>
            break OuterLoop
    }
    close(finish)
    close(status)
    fmt.Println("\nWinners:")
    place := 1
    for _, racer := range winners {
        fmt.Printf("%d place: Racer #%d\n", place, racer)
        place++
    }
}
## Racer #10 is on lap 2
## Racer #7 is on lap 1
## Racer #9 is on lap 2
## Racer #9 is on lap 1
## Racer #10 is on lap 1
## Race time: 1.000174895s
## Racer #8 is on lap 1
## Racer #1 finished!
## Racer #1 is on lap 1
## Racer #1 is on lap 2
## Racer #1 is on lap 3
## Racer #7 finished!
## Racer #7 is on lap 2
## Racer #7 is on lap 3
## Racer #6 finished!
## Racer #6 is on lap 1
## Racer #6 is on lap 2
## Racer #6 is on lap 3
## Race time: 2.000160288s
## Racer #2 is on lap 1
## Racer #10 finished!
## Racer #4 is on lap 1
## Racer #3 is on lap 2
## Racer #5 is on lap 1
## Racer #10 is on lap 3
## Racer #3 is on lap 1
## Racer #8 is on lap 2
## Racer #9 finished!
## Racer #9 is on lap 3
## Race time: 3.000149888s
## Racer #5 is on lap 2
## Racer #3 finished!
```

```
## Racer #3 is on lap 3
## Race time: 4.00017553s
## Racer #8 finished!
## Racer #2 is on lap 2
## Racer #4 finished!
## Racer #8 is on lap 3
## Racer #4 is on lap 2
## Racer #4 is on lap 3
## Race time: 5.000275273s
## Racer #5 finished!
## Racer #2 finished!
## Racer #5 is on lap 3
## Racer #2 is on lap 3
##
## Winners:
## 1 place: Racer #1
## 2 place: Racer #7
## 3 place: Racer #6
```