

CLOUD ACCESS CONTROL

LiveU Attendance API

Developer Reference · Version 1.0 · March 23, 2026

A fully cloud-managed REST API for branch operators to manage members and track attendance across all connected ZKTeco devices — no on-premise infrastructure required.

BASE URL

`https://attapi.liveucloud.com/api/v1`AUTHENTICATION HEADER `x-api-key: <YOUR_BRANCH_API_KEY>`

1. Authentication

Every request must include your Branch API key as a request header. The key identifies your branch within the LiveU cloud platform and scopes all responses to your data only.

Field / Parameter	Type	Required	Description
<code>x-api-key</code>	string	Yes	Your unique Branch API key, provided by Live U. Scopes all responses to your branch only.

i Your key only grants access to your own branch data. Records from other branches are never visible or accessible.

EXAMPLE REQUEST

```
curl https://attapi.liveucloud.com/api/v1/members \
-H "x-api-key: your-branch-api-key"
```

2. Members

Members are individuals registered to your branch with access to connected devices. When a member is created or updated via the API, all physical access-control hardware at your branch is configured automatically through the cloud — no manual programming needed.

POST `/members` *Register a new member*

Creates a new member and associates them with your branch. The branch association is derived automatically from your API key — you do not need to supply it.

REQUEST BODY

Field / Parameter	Type	Required	Description
memberId	string	Yes	Your member ID or ZKTeco device PIN. Must be unique within your branch.
name	string	Yes	Full name of the member.
uid	string	No	Optional secondary identifier such as a card number or national ID.
status	string	Optional	Active (default) or Inactive. Inactive members are blocked on all devices immediately.

EXAMPLE REQUEST

```
curl https://attapi.liveucloud.com/api/v1/members \
-X POST \
-H "x-api-key: your-branch-api-key" \
-H "Content-Type: application/json" \
-d '{
  "memberId": "1001",
  "name": "Kasun Perera"
}'
```

RESPONSE · 201 CREATED

```
{
  "success": true,
  "data": {
    "_id": "60d5ec49f72bf0...",
    "memberId": "1001",
    "name": "Kasun Perera",
    "status": "Active",
    "createdAt": "2026-03-22T08:00:00.000Z"
  }
}
```

GET /members *List all members*

Returns all members registered to your branch. Results are not paginated.

EXAMPLE REQUEST

```
curl https://attapi.liveucloud.com/api/v1/members \
-H "x-api-key: your-branch-api-key"
```

RESPONSE · 200 OK

```
{
  "success": true,
  "data": [
    { "_id": "60d5ec...", "memberId": "1001", "name": "Kasun Perera", ... },
    { "_id": "60d5ed...", "memberId": "1002", "name": "Nimal Silva", ... }
  ]
}
```

GET /members/:id *Get a single member*

Returns a single member by their MongoDB `_id`.

PATH PARAMETER

Field / Parameter	Type	Required	Description
id	string	Yes	The member's <code>_id</code> value returned when the member was created.

EXAMPLE REQUEST

```
curl https://attapi.liveucloud.com/api/v1/members/60d5ec49f72bf0... \
-H "x-api-key: your-branch-api-key"
```

PATCH `/members/:id` Update a member

Updates one or more fields on a member. Only include the fields you want to change — all other fields remain unchanged.

PATH PARAMETER

Field / Parameter	Type	Required	Description
id	string	Yes	The member's <code>_id</code> .

REQUEST BODY · ALL FIELDS OPTIONAL

Field / Parameter	Type	Required	Description
name	string	No	Updated full name.
uid	string	No	Updated secondary identifier.
status	string	No	Active or Inactive. Setting Inactive blocks access on all devices immediately. Setting Active restores access instantly.

EXAMPLE REQUEST · DEACTIVATE A MEMBER

```
curl https://attapi.liveucloud.com/api/v1/members/60d5ec... \
-X PATCH \
-H "x-api-key: your-branch-api-key" \
-H "Content-Type: application/json" \
-d '{ "status": "Inactive" }'
```

RESPONSE · 200 OK

```
{
  "success": true,
  "data": {
    "_id": "60d5ec...",
    "memberId": "1001",
    "name": "Kasun Perera",
    "status": "Inactive",
    "updatedAt": "2026-03-22T10:15:00.000Z"
  }
}
```

DELETE `/members/:id` Delete a member

Permanently removes a member from your branch and from all access-control devices.

⚠ This action cannot be undone. To temporarily block access, set status to Inactive rather than deleting. Deletion is permanent and cannot be reversed.

PATH PARAMETER

Field / Parameter	Type	Required	Description
id	string	Yes	The member's _id.

EXAMPLE REQUEST

```
curl https://attapi.liveucloud.com/api/v1/members/60d5ec... \
-X DELETE \
-H "x-api-key: your-branch-api-key"
```

RESPONSE · 200 OK

```
{
  "success": true,
  "message": "Member deleted.",
  "data": { "_id": "60d5ec...", "memberId": "1001", "name": "Kasun Perera" }
}
```

3. Attendance

Attendance records are generated automatically by the LiveU cloud service each time a member scans at one of your connected devices. Every event — check-in, check-out, or access denial — is captured in real time. Branch users have read-only access to these records to preserve log integrity.

GET /attendances *List attendance records*

Returns attendance records for your branch, sorted by date and time with the most recent first. Use the optional query parameters to filter results by member, date range, or event type.

QUERY PARAMETERS · ALL OPTIONAL

Field / Parameter	Type	Required	Description
memberId	string	No	Filter by a member's short ID or ZKTeco PIN. e.g. ?memberId=1001
status	string	No	Filter by event type. Values: In, Out, Attend
access	string	No	Filter by access result. Values: Granted, Denied
from	date	No	Return records with dateTime on or after this value. e.g. ?from=2026-03-01
to	date	No	Return records with dateTime on or before this value. e.g. ?to=2026-03-31

EXAMPLE REQUEST · ALL RECORDS FOR MARCH 2026

```
curl "https://attapi.liveucloud.com/api/v1/attendances
?from=2026-03-01&to=2026-03-31" \
-H "x-api-key: your-branch-api-key"
```

EXAMPLE REQUEST · DENIED ACCESS EVENTS FOR MEMBER 1001

```
curl "https://attapi.liveucloud.com/api/v1/attendances
?memberId=1001&access=Denied" \
```

```
-H "x-api-key: your-branch-api-key"
```

RESPONSE · 200 OK

```
{
  "success": true,
  "data": [
    {
      "_id": "665f1a2b...",
      "memberId": "1001",
      "member": { "name": "Kasun Perera", "memberId": "1001" },
      "device": { "name": "Front Door Reader", "sn": "NYU7254600425" },
      "dateTime": "2026-03-15T08:32:00.000Z",
      "status": "In",
      "access": "Granted"
    }
  ]
}
```

GET `/attendances/:id` *Get a single attendance record*

Returns a single attendance record with fully resolved member and device details.

PATH PARAMETER

Field / Parameter	Type	Required	Description
id	string	Yes	The attendance record's _id.

EXAMPLE REQUEST

```
curl https://attapi.liveucloud.com/api/v1/attendances/665f1a2b... \
-H "x-api-key: your-branch-api-key"
```

4. Error Responses

All responses — both successful and error — follow the same JSON envelope. The success field is always present and indicates whether the operation succeeded.

Status	Meaning	Description
200	OK	Request succeeded.
201	Created	Resource was created successfully.
400	Bad Request	A required field is missing or failed validation.
401	Unauthorized	The x-api-key header is missing or invalid.
403	Forbidden	The resource exists but belongs to a different branch.
404	Not Found	No resource exists with the given ID.
409	Conflict	Duplicate value for a unique field (e.g. memberId).

ERROR RESPONSE SHAPE

```
{
  "success": false,
```

```
"message": "A description of what went wrong"
}
```



LiveU Attendance API · Version 1.0 · Issued by Live U (PVT) Ltd · March 23, 2026

LiveU — Fully Cloud-Managed Access Control & Attendance Tracking · For support, contact your Live U account manager.