

Introduction to Online Learning Algorithms

Yoav Freund

January 7, 2025

Outline

About this Course

Halving Algorithm

Perceptron

Estimating the mean

Class web site

- ▶ All of the class material is available from the github repository
<https://github.com/yoavfreund/2025-online-learning>

Class web site

- ▶ All of the class material is available from the github repository

<https://github.com/yoavfreund/2025-online-learning>



What the class will cover

What the class will cover

What the class will cover

- ▶ Introduction (with Mean)

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms
 - ▶ Hedge

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms
 - ▶ Hedge
 - ▶ Mixability

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms
 - ▶ Hedge
 - ▶ Mixability
 - ▶ Bregman Divergences

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms
 - ▶ Hedge
 - ▶ Mixability
 - ▶ Bregman Divergences

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms
 - ▶ Hedge
 - ▶ Mixability
 - ▶ Bregman Divergences
- ▶ Online learning and Coding

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms
 - ▶ Hedge
 - ▶ Mixability
 - ▶ Bregman Divergences
- ▶ Online learning and Coding
 - ▶ Universal Coding

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms
 - ▶ Hedge
 - ▶ Mixability
 - ▶ Bregman Divergences
- ▶ Online learning and Coding
 - ▶ Universal Coding
 - ▶ Continuous Experts

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms
 - ▶ Hedge
 - ▶ Mixability
 - ▶ Bregman Divergences
- ▶ Online learning and Coding
 - ▶ Universal Coding
 - ▶ Continuous Experts
 - ▶ The Context Algorithm

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms
 - ▶ Hedge
 - ▶ Mixability
 - ▶ Bregman Divergences
- ▶ Online learning and Coding
 - ▶ Universal Coding
 - ▶ Continuous Experts
 - ▶ The Context Algorithm
- ▶ Multiple arm Bandit

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms
 - ▶ Hedge
 - ▶ Mixability
 - ▶ Bregman Divergences
- ▶ Online learning and Coding
 - ▶ Universal Coding
 - ▶ Continuous Experts
 - ▶ The Context Algorithm
- ▶ Multiple arm Bandit
- ▶ Tracking

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms
 - ▶ Hedge
 - ▶ Mixability
 - ▶ Bregman Divergences
- ▶ Online learning and Coding
 - ▶ Universal Coding
 - ▶ Continuous Experts
 - ▶ The Context Algorithm
- ▶ Multiple arm Bandit
- ▶ Tracking
 - ▶ Tracking

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms
 - ▶ Hedge
 - ▶ Mixability
 - ▶ Bregman Divergences
- ▶ Online learning and Coding
 - ▶ Universal Coding
 - ▶ Continuous Experts
 - ▶ The Context Algorithm
- ▶ Multiple arm Bandit
- ▶ Tracking
 - ▶ Tracking
 - ▶ Tracking within a small set of experts

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms
 - ▶ Hedge
 - ▶ Mixability
 - ▶ Bregman Divergences
- ▶ Online learning and Coding
 - ▶ Universal Coding
 - ▶ Continuous Experts
 - ▶ The Context Algorithm
- ▶ Multiple arm Bandit
- ▶ Tracking
 - ▶ Tracking
 - ▶ Tracking within a small set of experts

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms
 - ▶ Hedge
 - ▶ Mixability
 - ▶ Bregman Divergences
- ▶ Online learning and Coding
 - ▶ Universal Coding
 - ▶ Continuous Experts
 - ▶ The Context Algorithm
- ▶ Multiple arm Bandit
- ▶ Tracking
 - ▶ Tracking
 - ▶ Tracking within a small set of experts
- ▶ Online learning and game theory

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms
 - ▶ Hedge
 - ▶ Mixability
 - ▶ Bregman Divergences
- ▶ Online learning and Coding
 - ▶ Universal Coding
 - ▶ Continuous Experts
 - ▶ The Context Algorithm
- ▶ Multiple arm Bandit
- ▶ Tracking
 - ▶ Tracking
 - ▶ Tracking within a small set of experts
- ▶ Online learning and game theory
 - ▶ Repeated Matrix Games

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms
 - ▶ Hedge
 - ▶ Mixability
 - ▶ Bregman Divergences
- ▶ Online learning and Coding
 - ▶ Universal Coding
 - ▶ Continuous Experts
 - ▶ The Context Algorithm
- ▶ Multiple arm Bandit
- ▶ Tracking
 - ▶ Tracking
 - ▶ Tracking within a small set of experts
- ▶ Online learning and game theory
 - ▶ Repeated Matrix Games
 - ▶ Internal regret.

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms
 - ▶ Hedge
 - ▶ Mixability
 - ▶ Bregman Divergences
- ▶ Online learning and Coding
 - ▶ Universal Coding
 - ▶ Continuous Experts
 - ▶ The Context Algorithm
- ▶ Multiple arm Bandit
- ▶ Tracking
 - ▶ Tracking
 - ▶ Tracking within a small set of experts
- ▶ Online learning and game theory
 - ▶ Repeated Matrix Games
 - ▶ Internal regret.
 - ▶ Drifting games

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms
 - ▶ Hedge
 - ▶ Mixability
 - ▶ Bregman Divergences
- ▶ Online learning and Coding
 - ▶ Universal Coding
 - ▶ Continuous Experts
 - ▶ The Context Algorithm
- ▶ Multiple arm Bandit
- ▶ Tracking
 - ▶ Tracking
 - ▶ Tracking within a small set of experts
- ▶ Online learning and game theory
 - ▶ Repeated Matrix Games
 - ▶ Internal regret.
 - ▶ Drifting games
 - ▶ NormalHedge

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms
 - ▶ Hedge
 - ▶ Mixability
 - ▶ Bregman Divergences
- ▶ Online learning and Coding
 - ▶ Universal Coding
 - ▶ Continuous Experts
 - ▶ The Context Algorithm
- ▶ Multiple arm Bandit
- ▶ Tracking
 - ▶ Tracking
 - ▶ Tracking within a small set of experts
- ▶ Online learning and game theory
 - ▶ Repeated Matrix Games
 - ▶ Internal regret.
 - ▶ Drifting games
 - ▶ NormalHedge
- ▶ Online Convex Optimizatio

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms
 - ▶ Hedge
 - ▶ Mixability
 - ▶ Bregman Divergences
- ▶ Online learning and Coding
 - ▶ Universal Coding
 - ▶ Continuous Experts
 - ▶ The Context Algorithm
- ▶ Multiple arm Bandit
- ▶ Tracking
 - ▶ Tracking
 - ▶ Tracking within a small set of experts
- ▶ Online learning and game theory
 - ▶ Repeated Matrix Games
 - ▶ Internal regret.
 - ▶ Drifting games
 - ▶ NormalHedge
- ▶ Online Convex Optimizatio
 - ▶ Follow the regularized leader

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms
 - ▶ Hedge
 - ▶ Mixability
 - ▶ Bregman Divergences
- ▶ Online learning and Coding
 - ▶ Universal Coding
 - ▶ Continuous Experts
 - ▶ The Context Algorithm
- ▶ Multiple arm Bandit
- ▶ Tracking
 - ▶ Tracking
 - ▶ Tracking within a small set of experts
- ▶ Online learning and game theory
 - ▶ Repeated Matrix Games
 - ▶ Internal regret.
 - ▶ Drifting games
 - ▶ NormalHedge
- ▶ Online Convex Optimizatio
 - ▶ Follow the regularized leader
 - ▶ Dual Descent

What the class will cover

- ▶ Introduction (with Mean)
- ▶ Exponential weights algorithms
 - ▶ Hedge
 - ▶ Mixability
 - ▶ Bregman Divergences
- ▶ Online learning and Coding
 - ▶ Universal Coding
 - ▶ Continuous Experts
 - ▶ The Context Algorithm
- ▶ Multiple arm Bandit
- ▶ Tracking
 - ▶ Tracking
 - ▶ Tracking within a small set of experts
- ▶ Online learning and game theory
 - ▶ Repeated Matrix Games
 - ▶ Internal regret.
 - ▶ Drifting games
 - ▶ NormalHedge
- ▶ Online Convex Optimizatio
 - ▶ Follow the regularized leader
 - ▶ Dual Descent
 - ▶ AdaGrad

HW / Evaluation

- ▶ 5 HW assignments for $5 \cdot 15 = 75$ opints

HW / Evaluation

- ▶ 5 HW assignments for $5 \cdot 15 = 75$ opints
- ▶ A final for 25 points.

Example trace for Halving Algorithm

Example trace for Halving Algorithm

expert1
expert2
expert3
expert4
expert5
expert6
expert7
expert8

alg.

Example trace for Halving Algorithm

expert1
expert2
expert3
expert4
expert5
expert6
expert7
expert8

alg.

outcome

Example trace for Halving Algorithm

	$t = 1$
expert1	1
expert2	1
expert3	0
expert4	1
expert5	1
expert6	0
expert7	1
expert8	1

alg.
outcome

Example trace for Halving Algorithm

	$t = 1$
expert1	1
expert2	1
expert3	0
expert4	1
expert5	1
expert6	0
expert7	1
expert8	1
alg.	1
outcome	

Example trace for Halving Algorithm

	$t = 1$
expert1	1
expert2	1
expert3	0
expert4	1
expert5	1
expert6	0
expert7	1
expert8	1
alg.	1
outcome	1

Example trace for Halving Algorithm

	$t = 1$	$t = 2$
expert1	1	1
expert2	1	0
expert3	0	-
expert4	1	0
expert5	1	0
expert6	0	-
expert7	1	1
expert8	1	1
alg.	1	
outcome	1	

Example trace for Halving Algorithm

	$t = 1$	$t = 2$
expert1	1	1
expert2	1	0
expert3	0	-
expert4	1	0
expert5	1	0
expert6	0	-
expert7	1	1
expert8	1	1
alg.	1	0
outcome	1	

Example trace for Halving Algorithm

	$t = 1$	$t = 2$
expert1	1	1
expert2	1	0
expert3	0	-
expert4	1	0
expert5	1	0
expert6	0	-
expert7	1	1
expert8	1	1
alg.	1	0
outcome	1	1

Example trace for Halving Algorithm

	$t = 1$	$t = 2$	$t = 3$
expert1	1	1	1
expert2	1	0	-
expert3	0	-	-
expert4	1	0	-
expert5	1	0	-
expert6	0	-	-
expert7	1	1	1
expert8	1	1	1
alg.	1	0	
outcome	1	1	

Example trace for Halving Algorithm

	$t = 1$	$t = 2$	$t = 3$
expert1	1	1	1
expert2	1	0	-
expert3	0	-	-
expert4	1	0	-
expert5	1	0	-
expert6	0	-	-
expert7	1	1	1
expert8	1	1	1
alg.	1	0	1
outcome	1	1	

Example trace for Halving Algorithm

	$t = 1$	$t = 2$	$t = 3$
expert1	1	1	1
expert2	1	0	-
expert3	0	-	-
expert4	1	0	-
expert5	1	0	-
expert6	0	-	-
expert7	1	1	1
expert8	1	1	1
alg.	1	0	1
outcome	1	1	1

Example trace for Halving Algorithm

	$t = 1$	$t = 2$	$t = 3$	$t = 4$
expert1	1	1	1	1
expert2	1	0	-	-
expert3	0	-	-	-
expert4	1	0	-	-
expert5	1	0	-	-
expert6	0	-	-	-
expert7	1	1	1	1
expert8	1	1	1	0
alg.	1	0	1	
outcome	1	1	1	

Example trace for Halving Algorithm

	$t = 1$	$t = 2$	$t = 3$	$t = 4$
expert1	1	1	1	1
expert2	1	0	-	-
expert3	0	-	-	-
expert4	1	0	-	-
expert5	1	0	-	-
expert6	0	-	-	-
expert7	1	1	1	1
expert8	1	1	1	0
alg.	1	0	1	1
outcome	1	1	1	

Example trace for Halving Algorithm

	$t = 1$	$t = 2$	$t = 3$	$t = 4$
expert1	1	1	1	1
expert2	1	0	-	-
expert3	0	-	-	-
expert4	1	0	-	-
expert5	1	0	-	-
expert6	0	-	-	-
expert7	1	1	1	1
expert8	1	1	1	0
alg.	1	0	1	1
outcome	1	1	1	0

Example trace for Halving Algorithm

	$t = 1$	$t = 2$	$t = 3$	$t = 4$	$t = 5$
expert1	1	1	1	1	-
expert2	1	0	-	-	-
expert3	0	-	-	-	-
expert4	1	0	-	-	-
expert5	1	0	-	-	-
expert6	0	-	-	-	-
expert7	1	1	1	1	-
expert8	1	1	1	0	0
alg.	1	0	1	1	
outcome	1	1	1	0	

Example trace for Halving Algorithm

	$t = 1$	$t = 2$	$t = 3$	$t = 4$	$t = 5$
expert1	1	1	1	1	-
expert2	1	0	-	-	-
expert3	0	-	-	-	-
expert4	1	0	-	-	-
expert5	1	0	-	-	-
expert6	0	-	-	-	-
expert7	1	1	1	1	-
expert8	1	1	1	0	0
alg.	1	0	1	1	0
outcome	1	1	1	0	

Example trace for Halving Algorithm

	$t = 1$	$t = 2$	$t = 3$	$t = 4$	$t = 5$
expert1	1	1	1	1	-
expert2	1	0	-	-	-
expert3	0	-	-	-	-
expert4	1	0	-	-	-
expert5	1	0	-	-	-
expert6	0	-	-	-	-
expert7	1	1	1	1	-
expert8	1	1	1	0	0
alg.	1	0	1	1	0
outcome	1	1	1	0	0

Mistake bound for Halving algorithm

- ▶ Each time algorithm makes a mistakes, the pool of perfect experts is halved (at least).

Mistake bound for Halving algorithm

- ▶ Each time algorithm makes a mistakes, the pool of perfect experts is halved (at least).
- ▶ We assume that at least one expert is perfect.

Mistake bound for Halving algorithm

- ▶ Each time algorithm makes a mistake, the pool of perfect experts is halved (at least).
- ▶ We assume that at least one expert is perfect.
- ▶ Number of mistakes is at most $\log_2 N$.

Mistake bound for Halving algorithm


- ▶ Each time algorithm makes a mistakes, the pool of perfect experts is halved (at least).
- ▶ We assume that at least one expert is perfect.
- ▶ Number of mistakes is at most $\log_2 N$.
- ▶ No stochastic assumptions whatsoever.

Mistake bound for Halving algorithm


- ▶ Each time algorithm makes a mistake, the pool of perfect experts is halved (at least).
- ▶ We assume that at least one expert is perfect.
- ▶ Number of mistakes is at most $\log_2 N$.
- ▶ No stochastic assumptions whatsoever.
- ▶ Proof is based on combining a lower and upper bounds on the number of perfect experts.

The Perceptron Problem


The Perceptron Problem




The Perceptron Problem




The Perceptron Problem




The Perceptron Problem




The Perceptron Problem




The Perceptron Problem




The Perceptron Problem



The Perceptron Problem




The Perceptron Problem




► $\|\vec{V}\| = 1$

The Perceptron Problem




- ▶ $\|\vec{V}\| = 1$
- ▶ Example = (\vec{X}, y) ,
 $y \in \{-1, +1\}$.

The Perceptron Problem



- ▶ $\|\vec{V}\| = 1$
- ▶ Example = (\vec{X}, y) ,
 $y \in \{-1, +1\}$.
- ▶ $\forall \vec{X}, \|\vec{X}\| \leq R$.

The Perceptron Problem



- ▶ $\|\vec{V}\| = 1$
- ▶ Example = (\vec{X}, y) ,
 $y \in \{-1, +1\}$.
- ▶ $\forall \vec{X}, \|\vec{X}\| \leq R$.
- ▶ $\forall (\vec{X}, y),$
 $y(\vec{X} \cdot \vec{V}) \geq g$

The Perceptron learning algorithm

- ▶ An online algorithm. Examples presented one by one.

The Perceptron learning algorithm

- ▶ An online algorithm. Examples presented one by one.
- ▶ start with $\vec{W}_0 = \vec{0}$.


The Perceptron learning algorithm

- ▶ An online algorithm. Examples presented one by one.
- ▶ start with $\vec{W}_0 = \vec{0}$.
- ▶ If mistake: $(\vec{W}_i \cdot \vec{X}_i)y_i \leq 0$


The Perceptron learning algorithm

- ▶ An online algorithm. Examples presented one by one.
- ▶ start with $\vec{W}_0 = \vec{0}$.
- ▶ If mistake: $(\vec{W}_i \cdot \vec{X}_i)y_i \leq 0$
 - ▶ Update $\vec{W}_{i+1} = \vec{W}_i + y_i \vec{X}_i$.


Example trace for the perceptron algorithm




Example trace for the perceptron algorithm




Example trace for the perceptron algorithm




Example trace for the perceptron algorithm



Example trace for the perceptron algorithm



Example trace for the perceptron algorithm



Bound on number of mistakes

- ▶ The number of mistakes that the perceptron algorithm can make is at most $\left(\frac{R}{g}\right)^2$.

Bound on number of mistakes

- ▶ The number of mistakes that the perceptron algorithm can make is at most $\left(\frac{R}{g}\right)^2$.
- ▶ Proof by combining upper and lower bounds on $\|\vec{W}\|$.

Pythagorean Lemma

If $(\vec{W}_i \cdot X_i)y < 0$ then

Pythagorean Lemma


If $(\vec{W}_i \cdot \vec{X}_i)y < 0$ then

$$\|\vec{W}_{i+1}\|^2 = \|\vec{W}_i + y_i \vec{X}_i\|^2 \leq \|\vec{W}_i\|^2 + \|\vec{X}_i\|^2$$

Pythagorean Lemma

If $(\vec{W}_i \cdot \vec{X}_i)y < 0$ then

$$\|\vec{W}_{i+1}\|^2 = \|\vec{W}_i + y_i \vec{X}_i\|^2 \leq \|\vec{W}_i\|^2 + \|\vec{X}_i\|^2$$



Upper bound on $\|\vec{W}_i\|$

Upper bound on $\|\vec{W}_i\|$

Proof by induction

- ▶ Claim: $\|\vec{W}_i\|^2 \leq iR^2$

Upper bound on $\|\vec{W}_i\|$

Proof by induction

- ▶ Claim: $\|\vec{W}_i\|^2 \leq iR^2$
- ▶ Base: $i = 0, \|\vec{W}_0\|^2 = 0$

Upper bound on $\|\vec{W}_i\|$

Proof by induction

- ▶ Claim: $\|\vec{W}_i\|^2 \leq iR^2$
- ▶ Base: $i = 0$, $\|\vec{W}_0\|^2 = 0$
- ▶ Induction step (assume for i and prove for $i + 1$):
$$\begin{aligned}\|\vec{W}_{i+1}\|^2 &\leq \|\vec{W}_i\|^2 + \|\vec{X}_i\|^2 \\ &\leq \|\vec{W}_i\|^2 + R^2 \leq (i + 1)R^2\end{aligned}$$

Lower bound on $\|\vec{W}_i\|$

Lower bound on $\|\vec{W}_i\|$

$$\|\vec{W}_i\| \geq \vec{W}_i \cdot \vec{V} \text{ because } \|\vec{V}\| = 1.$$

Lower bound on $\|\vec{W}_i\|$

$\|\vec{W}_i\| \geq \vec{W}_i \cdot \vec{V}$ because $\|\vec{V}\| = 1$.

Let i denote the number of mistakes made so far.

Lower bound on $\|\vec{W}_i\|$

$\|\vec{W}_i\| \geq \vec{W}_i \cdot \vec{V}$ because $\|\vec{V}\| = 1$.

Let i denote the number of mistakes made so far.

We prove a lower bound on $\vec{W}_i \cdot \vec{V}$ by induction over i

► Claim: $\vec{W}_i \cdot \vec{V} \geq ig$

Lower bound on $\|\vec{W}_i\|$

$\|\vec{W}_i\| \geq \vec{W}_i \cdot \vec{V}$ because $\|\vec{V}\| = 1$.

Let i denote the number of mistakes made so far.

We prove a lower bound on $\vec{W}_i \cdot \vec{V}$ by induction over i

- ▶ Claim: $\vec{W}_i \cdot \vec{V} \geq ig$
- ▶ Base: $i = 0$, $\vec{W}_0 \cdot \vec{V} = 0$

Lower bound on $\|\vec{W}_i\|$

$\|\vec{W}_i\| \geq \vec{W}_i \cdot \vec{V}$ because $\|\vec{V}\| = 1$.

Let i denote the number of mistakes made so far.

We prove a lower bound on $\vec{W}_i \cdot \vec{V}$ by induction over i

- ▶ Claim: $\vec{W}_i \cdot \vec{V} \geq ig$
- ▶ Base: $i = 0$, $\vec{W}_0 \cdot \vec{V} = 0$
- ▶ Induction step (assume for i and prove for $i + 1$):
$$\vec{W}_{i+1} \cdot \vec{V} = \left(\vec{W}_i + \vec{X}_i y_i \right) \vec{V}$$

Lower bound on $\|\vec{W}_i\|$

$\|\vec{W}_i\| \geq \vec{W}_i \cdot \vec{V}$ because $\|\vec{V}\| = 1$.

Let i denote the number of mistakes made so far.

We prove a lower bound on $\vec{W}_i \cdot \vec{V}$ by induction over i

- ▶ Claim: $\vec{W}_i \cdot \vec{V} \geq ig$
- ▶ Base: $i = 0$, $\vec{W}_0 \cdot \vec{V} = 0$
- ▶ Induction step (assume for i and prove for $i + 1$):
$$\vec{W}_{i+1} \cdot \vec{V} = \left(\vec{W}_i + \vec{X}_i y_i \right) \vec{V}$$

Lower bound on $\|\vec{W}_i\|$

$\|\vec{W}_i\| \geq \vec{W}_i \cdot \vec{V}$ because $\|\vec{V}\| = 1$.

Let i denote the number of mistakes made so far.

We prove a lower bound on $\vec{W}_i \cdot \vec{V}$ by induction over i

- ▶ Claim: $\vec{W}_i \cdot \vec{V} \geq ig$
- ▶ Base: $i = 0$, $\vec{W}_0 \cdot \vec{V} = 0$
- ▶ Induction step (assume for i and prove for $i + 1$):
$$\begin{aligned}\vec{W}_{i+1} \cdot \vec{V} &= (\vec{W}_i + \vec{X}_i y_i) \cdot \vec{V} = \vec{W}_i \cdot \vec{V} + y_i \vec{X}_i \cdot \vec{V} \\ &\geq ig + g = (i + 1)g\end{aligned}$$

Combining the upper and lower bounds

Combining the upper and lower bounds

$$(ig)^2 \leq \|\vec{W}_i\|^2 \leq iR^2$$

Combining the upper and lower bounds

$$(ig)^2 \leq \|\vec{W}_i\|^2 \leq iR^2$$

Thus:

$$i \leq \left(\frac{R}{g}\right)^2$$

The mean estimation game

- ▶ An adversary chooses a real number $y_t \in [0, 1]$ and keeps it secret.

The mean estimation game

- ▶ An adversary chooses a real number $y_t \in [0, 1]$ and keeps it secret.
- ▶ You make a guess of the secret number x_t

The mean estimation game

- ▶ An adversary chooses a real number $y_t \in [0, 1]$ and keeps it secret.
- ▶ You make a guess of the secret number x_t
- ▶ The adversary reveals the secret and you pay $(x_t - y_t)^2$

The mean estimation game

- ▶ An adversary chooses a real number $y_t \in [0, 1]$ and keeps it secret.
- ▶ You make a guess of the secret number x_t
- ▶ The adversary reveals the secret and you pay $(x_t - y_t)^2$
- ▶ You want to minimize $\frac{1}{T} \sum_{t=1}^T (x_t - y_t)^2$

The mean estimation game

- ▶ An adversary chooses a real number $y_t \in [0, 1]$ and keeps it secret.
- ▶ You make a guess of the secret number x_t
- ▶ The adversary reveals the secret and you pay $(x_t - y_t)^2$
- ▶ You want to minimize $\frac{1}{T} \sum_{t=1}^T (x_t - y_t)^2$
- ▶ Impossible without additional constraints.

Adversary is a fixed distribution

- ▶ Suppose that the adversary draws y_1, y_2, \dots, y_T IID from a fixed distribution over $[0, 1]$ with mean μ and std σ .

Adversary is a fixed distribution

- ▶ Suppose that the adversary draws y_1, y_2, \dots, y_T IID from a fixed distribution over $[0, 1]$ with mean μ and std σ .
- ▶ Optimal prediction $x_t = \mu$

Adversary is a fixed distribution

- ▶ Suppose that the adversary draws y_1, y_2, \dots, y_T IID from a fixed distribution over $[0, 1]$ with mean μ and std σ .
- ▶ Optimal prediction $x_t = \mu$
- ▶ $E_Y [(\mu - Y)^2] = \sigma^2$

Adversary is a fixed distribution

- ▶ Suppose that the adversary draws y_1, y_2, \dots, y_T IID from a fixed distribution over $[0, 1]$ with mean μ and std σ .
- ▶ Optimal prediction $x_t = \mu$
- ▶ $E_Y [(\mu - Y)^2] = \sigma^2$
- ▶ Online prediction: predict x_{t+1} from $Y^t = \langle Y_1, Y_2, \dots, Y_t \rangle$.

Adversary is a fixed distribution

- ▶ Suppose that the adversary draws y_1, y_2, \dots, y_T IID from a fixed distribution over $[0, 1]$ with mean μ and std σ .
- ▶ Optimal prediction $x_t = \mu$
- ▶ $E_Y [(\mu - Y)^2] = \sigma^2$
- ▶ Online prediction: predict x_{t+1} from $Y^t = \langle Y_1, Y_2, \dots, Y_t \rangle$.
- ▶ **Expected regret**: compare performance of algorithm to $\text{Regret} = E_{Y^T} [(x_t - Y_t)^2] - \sigma^2$

Individual sequence bounds

- ▶ Make no assumption about how the sequence is generated.

Individual sequence bounds

- ▶ Make no assumption about how the sequence is generated.
- ▶ The best constant value for x in hind-sight:

$$x_T^* \doteq \operatorname{argmin}_{x \in [0,1]} \sum_{t=1}^T (x - y_t)^2, \quad x_T^* = \frac{1}{T} \sum_{t=1}^T y_t$$

Individual sequence bounds

- ▶ Make no assumption about how the sequence is generated.
- ▶ The best constant value for x in hind-sight:

$$x_T^* \doteq \operatorname{argmin}_{x \in [0,1]} \sum_{t=1}^T (x - y_t)^2, \quad x_T^* = \frac{1}{T} \sum_{t=1}^T y_t$$

- ▶ Regret: the loss over and above the loss of x_T^* . **for the worst-case sequence**

$$\operatorname{Regret}_T = \sum_{t=1}^T (x_t - y_t)^2 - \sum_{t=1}^T (x_T^* - y_t)^2$$

Individual sequence bounds

- ▶ Make no assumption about how the sequence is generated.
- ▶ The best constant value for x in hind-sight:

$$x_T^* \doteq \operatorname{argmin}_{x \in [0,1]} \sum_{t=1}^T (x - y_t)^2, \quad x_T^* = \frac{1}{T} \sum_{t=1}^T y_t$$

- ▶ **Regret:** the loss over and above the loss of x_T^* . **for the worst-case sequence**

$$\operatorname{Regret}_T = \sum_{t=1}^T (x_t - y_t)^2 - \sum_{t=1}^T (x_T^* - y_t)^2$$

- ▶ **Goal:** sublinear regret $\lim_{T \rightarrow \infty} \frac{\operatorname{Regret}_T}{T} = 0$

Follow the Leader

- ▶ Idea: set x_{t+1} to be the best constant prediction on y_1, \dots, y_t

Follow the Leader

- ▶ Idea: set x_{t+1} to be the best constant prediction on y_1, \dots, y_t
- ▶ $x_{t+1} = \operatorname{argmin}_{x \in [0,1]} \sum_{i=1}^t (x - y_i)^2 = x_t^*$

Follow the Leader

- ▶ Idea: set x_{t+1} to be the best constant prediction on y_1, \dots, y_t
- ▶ $x_{t+1} = \operatorname{argmin}_{x \in [0,1]} \sum_{i=1}^t (x - y_i)^2 = x_t^*$
- ▶ We will prove that the regret of this algorithm is upper bound by $2 + 2 \ln T$

Regret Bound

Theorem

Let $y_t \in [0, 1]$ for $t = 1, \dots, T$ an arbitrary sequence of numbers.

Let the algorithm output be $x_t = x_{t-1}^ = \frac{1}{t-1} \sum_{i=1}^{t-1} y_i$, then*

$$\text{Regret}_T = \sum_{t=1}^T (x_t - y_t)^2 - \sum_{t=1}^T (x_T^* - y_t)^2 \leq 2(1 + \ln T)$$

Lemma

Let x_1, x_2, \dots be the sequence of predictions produced by FTL.
Then for all $u \in R$ (In particular, for $u = x_T^*$):

$$\sum_{t=1}^T \left((x_t - y_t)^2 - (u - y_t)^2 \right) \leq \sum_{t=1}^T \left((x_t - y_t)^2 - (x_t^* - y_t)^2 \right)$$

Proof Sketch:

Subtract $\sum_{t=1}^T (x_t - y_t)^2$ from both sides to get an equivalent claim:

$$\sum_{t=1}^T (x_t^* - y_t)^2 \leq \sum_{t=1}^T (u - y_t)^2$$

The inequality is proven by induction on T .

Proof.

Proof.

- ▶ Base case ($T = 1$): $(x_1^* - y_1)^2 = (y_1 - y_1)^2 = 0 \leq (u - y_1)^2$

Proof.

- ▶ Base case ($T = 1$): $(x_1^* - y_1)^2 = (y_1 - y_1)^2 = 0 \leq (u - y_1)^2$
- ▶ Induction hypothesis: $\sum_{t=1}^{T-1} (x_t^* - y_t)^2 \leq \sum_{t=1}^{T-1} (u - y_t)^2$

Proof.

- ▶ Base case ($T = 1$): $(x_1^* - y_1)^2 = (y_1 - y_1)^2 = 0 \leq (u - y_1)^2$
- ▶ Induction hypothesis: $\sum_{t=1}^{T-1} (x_t^* - y_t)^2 \leq \sum_{t=1}^{T-1} (u - y_t)^2$
- ▶ Induction step:

$$\sum_{t=1}^{T-1} (x_t^* - y_t)^2 \leq \sum_{t=1}^{T-1} (x_{T-1}^* - y_t)^2 \leq \sum_{t=1}^{T-1} (x_T^* - y_t)^2$$

Adding $(x_T^* - y_T)^2$ to both sides gives:

$$\sum_{t=1}^T (x_t^* - y_t)^2 \leq \sum_{t=1}^T (x_T^* - y_t)^2 \leq \sum_{t=1}^T (u - y_t)^2$$

Proof of the theorem

First, note that in FTL we have:

$$x_t = x_{t-1}^* = \frac{1}{t-1} \sum_{i=1}^{t-1} y_i = \frac{t}{t-1} \cdot \left(\frac{1}{t} \sum_{i=1}^t y_i - \frac{y_t}{t} \right) = \frac{t}{t-1} \cdot \left(x_t^* - \frac{y_t}{t} \right)$$

Subtracting x_t^* from both sides, we get $x_t - x_t^* = \frac{x_t^* - y_t}{t-1}$. Then:

$$\begin{aligned} \text{Regret}_T &= \sum_{t=1}^T (x_t - y_t)^2 - \sum_{t=1}^T (x_t^* - y_t)^2 \\ &\leq \sum_{t=1}^T (x_t - y_t)^2 - (x_t^* - y_t)^2 \quad (\text{Lemma}) \\ &= \sum_{t=1}^T (x_t + x_t^* - 2y_t)(x_t - x_t^*) \leq \sum_{t=1}^T \frac{2}{t-1} \leq 2(1 + \ln T) \end{aligned}$$