

CSCI 3675 – Principles of Programming Languages
Fall 2021

Homework 2 – Set operations with Prolog
Due Sunday, September 26, at 11:59 PM

For all problems below, you only need to make sure that the predicates correctly find the first solution, as in the examples provided. You do NOT need to worry about what happens when asking for more solutions (with “;”).

1. (56 pts) Consider an implementation of sets with Prolog lists. A set is an unordered collection of elements, without duplicates.
 - (a) (14 pts) Write the rules for a predicate `isSet(S)`, which succeeds if the list `S` is a set. The following queries show examples of using this predicate:

```
?- isSet([1,2,5]).  
true  
?- isSet([1,2,1,5]).  
false
```
 - (b) (14 pts) Write the rules for a predicate `subset(A,S)`, which succeeds if the set `A` is a subset of the set `S`. The following query shows an example of using this predicate:

```
?- subset([2,5], [1,5,3,2]).  
true
```
 - (c) (14 pts) Write the rules for a predicate `union(A,B,C)`, which succeeds if the union of sets `A` and `B` is the set `C`. The following query shows an example of using this predicate:

```
?- union([2,5,4], [1,5,3,2], C).  
C = [4,1,5,3,2]
```
 - (d) (14 pts) Write the rules for a predicate `intersection(A,B,C)`, which succeeds if the intersection of sets `A` and `B` is the set `C`. The following query shows an example of using this predicate:

```
?- intersection([2,5,4], [1,5,3,2], C).  
C = [2,5]
```
2. (14 pts) Write the rules for a predicate `tally(E,L,N)`, which succeeds if `N` is the number of occurrences of element `E` in list `L`. The following query shows an example of using this predicate:

```
?- tally(3, [1,2,3,1,2,3], N).  
N = 2
```
3. (15 pts) Write the rules for a predicate `subst(X,Y,L,L1)`, which succeeds if list `L1` is identical to list `L` except that all occurrences of `X` in `L` are replaced with `Y` in `L1`. The following query shows an example of using this predicate:

```
?- subst(1, 2, [1,2,3,1,2,3], L1).  
L1 = [2,2,3,2,2,3]
```
4. (15 pts) Write the rules for a predicate `insert(X,L,L1)`, which succeeds if list `L1` is identical to the sorted list `L` with `X` inserted at the correct place. Assume that `L` is already sorted. The following query shows an example of using this predicate:

```
?- insert(5, [1,3,4,7], L1).  
L1 = [1,3,4,5,7]
```
5. (Extra Credit – 10 pts) Write the rules for a predicate `flatten(A,B)`, which succeeds if `A` is a list (possibly containing sublists), and `B` is a list containing all elements in `A` and its sublists, but all at the same level. The following query shows an example of using this predicate:

```
?- flatten([1, [2, [3, 4]], 5], L).  
L = [1, 2, 3, 4, 5]
```

Submission

- Submit your work as one `hw2.pl` file containing all your predicates, via Canvas.
- The file must be able to load (with `consult`) and be tested in the interpreter.
 - Consequently, the file must be in a simple text format; do not submit Word, PDF, RTF, JPG, etc.
 - Also make sure that any auxiliary information (such as your name or question numbers) is commented out.