

Trust Center Demo Script

SWT London 2026

Innovate at Scale: Powering a Secure and Resilient AI Estate

Duration: 10 minutes

Account: SFSEEUROPE-COLM_USWEST

Role: ACCOUNTADMIN

Repo: github.com/sfc-gh-cmoynihan/trust

Act	Topic	Time
1	Trust Center Dashboard - Single Pane of Glass	~2.5 min
2	PII Classification, Data Masking, and Data Security	~3 min
3	AI Security - Enable Live	~2 min
4	Threat Intelligence - Detection Scanners (18 scanners)	~2 min

Pre-flight: Run `5_demo_violations_setup.sql` to populate all Trust Center tabs, OR run `1_demo_setup.sql` for the lighter setup.

Main script: Open `3_demo_trust_center.sql` in a Snowsight worksheet.

Act 1: The Single Pane of Glass

Minutes 0:00 - 2:30

1.1 Open Trust Center Dashboard

[Navigate to Snowsight: Monitoring > Trust Center]

"Let me show you Trust Center -- Snowflake's single pane of glass for security, compliance, and governance. This is where everything comes together."

Point out on screen:

- Severity badges at the top -- Critical, High, Medium, Low counts
- CIS Benchmarks and Security Essentials are enabled
- AI Security and Threat Intelligence not yet enabled

1.2 Show Findings Summary

[Switch to SQL worksheet]

```
SELECT SEVERITY,  
       COUNT(DISTINCT SCANNER_NAME) AS SCANNERS_WITH_FINDINGS,  
       SUM(TOTAL_AT_RISK_COUNT) AS TOTAL_AT_RISK_ENTITIES  
FROM snowflake.trust_center.findings  
WHERE UPPER(STATE) = 'OPEN' AND TOTAL_AT_RISK_COUNT > 0  
GROUP BY SEVERITY;
```

"We have critical findings that need attention. Let us drill in."

1.3 CIS 3.1 -- Network Policy (Critical)

[In Snowsight, click into CIS 3.1 finding. Show severity, at-risk entities, remediation SQL.]

"CIS 3.1 -- we don't have an account-level network policy. That means any IP address can attempt to connect. Trust Center flags this and gives you the exact SQL to fix it."

1.4 CIS 1.14/1.15 -- Admin Privileges (High)

```
SELECT SCANNER_NAME, SEVERITY, TOTAL_AT_RISK_COUNT  
FROM snowflake.trust_center.findings  
WHERE SCANNER_ID IN ('CIS_BENCHMARKS_CIS1_14', 'CIS_BENCHMARKS_CIS1_15',  
                    'CIS_BENCHMARKS_CIS1_16', 'CIS_BENCHMARKS_CIS1_17')  
AND UPPER(STATE) = 'OPEN' AND TOTAL_AT_RISK_COUNT > 0  
QUALIFY ROW_NUMBER() OVER  
        (PARTITION BY SCANNER_ID ORDER BY END_TIMESTAMP DESC) = 1;
```

"41 tasks running with ACCOUNTADMIN. In the agentic world, this is exactly the over-privileged access that creates risk."

>> Transition: But before we remediate, let's talk about protecting the data itself.

Act 2: PII Classification and Data Protection

Minutes 2:30 - 5:00

"One of the top concerns we hear is protecting sensitive data -- especially when agents can access it. Step one: know where it lives."

2.1 Show the HR Data

```
SELECT * FROM DEMO_DB.PUBLIC.HR_DATA LIMIT 5;
```

"Here's an HR table -- names, emails, ages. Let's ask Snowflake to automatically classify what's in it."

2.2 Run Auto-Classification

```
SELECT EXTRACT_SEMANTIC_CATEGORIES( 'DEMO_DB.PUBLIC.HR_DATA' );
```

[Click JSON result to expand. Point out: email, name, age detected.]

"Snowflake identified EMAIL_ADDRESS as email, FNAME and LNAME as names, AGE as a personal identifier. No manual tagging needed."

2.3 Apply Classification Tags

```
CALL ASSOCIATE_SEMANTIC_CATEGORY_TAGS(  
  'DEMO_DB.PUBLIC.HR_DATA',  
  EXTRACT_SEMANTIC_CATEGORIES( 'DEMO_DB.PUBLIC.HR_DATA' )  
);
```

"Tags applied. Every column now has a semantic category and privacy classification. Foundation for protection policies."

2.4 Show Masking in Action

```
SELECT REPORT_ID, ANALYST_NAME, ANALYST_EMAIL, ANALYST_PHONE,  
       TICKER, RECOMMENDATION, PRICE_TARGET, CONFIDENTIAL_NOTES  
FROM RBAC_DEMO_DB.ANALYST_DATA.STOCK_ANALYST_DATA LIMIT 5;
```

"As admin, I see everything -- names, emails, price targets, confidential notes. Switch to a restricted role and masking policies redact the sensitive fields. Same table, same query, different results. Whether it's a human or an agent."

2.5 Connect to Trust Center

```
SELECT SCANNER_NAME, SEVERITY, TOTAL_AT_RISK_COUNT
FROM snowflake.trust_center.findings
WHERE SCANNER_ID = 'CIS_BENCHMARKS_CIS4_10'
      AND UPPER(STATE) = 'OPEN' AND TOTAL_AT_RISK_COUNT > 0 LIMIT 1;
```

"CIS 4.10 flags classified data without masking. Classification finds the data, Trust Center ensures it's protected."

>> Transition: Platform security, data protection -- now let me show you the Data Security tab.

Data Security Tab

Between Acts 2 and 3

"Let me show you the Data Security tab -- this is where classification results come together."

Data Security Dashboard

[Navigate to Trust Center > Data Security tab > Dashboard]

Point out on screen:

- Objects that need review count
- Objects with unmasked sensitive columns count
- Objects by top classification categories chart (NAME, EMAIL, AGE, PHONE)
- Objects by top compliance and regulation standards chart

"Snowflake automatically classified our databases using a classification profile. We can see exactly which objects contain sensitive data, what categories were detected, and which columns still need masking. This is continuous -- new tables get classified automatically."

Show Classified Tags (SQL)

```
SELECT * FROM TABLE(  
    DEMO_DB.INFORMATION_SCHEMA.TAG_REFERENCES_ALL_COLUMNS(  
        'DEMO_DB.PUBLIC.HR_DATA', 'TABLE'))  
WHERE TAG_NAME IN ('SEMANTIC_CATEGORY', 'PRIVACY_CATEGORY')  
ORDER BY COLUMN_NAME;
```

"Every column automatically tagged -- EMAIL, NAME, AGE -- with both semantic and privacy categories. And this feeds directly into the AI Security scanners we're about to enable."

>> Transition: Platform security, data protection, data classification -- now let's turn on agent security.

Act 3: AI Security -- Enable Live

Minutes 5:00 - 7:30

"Now let's turn on agent security. Purpose-built controls for the agentic era."

3.1 Show AI Security is Disabled

```
SELECT ID, NAME, STATE FROM snowflake.trust_center.scanner_packages
WHERE ID = 'AI_SECURITY';
```

[Result: STATE = FALSE]

"AI Security is available but not yet enabled. Let's change that."

3.2 Enable AI Security -- The Live Moment

[Pause for effect before running this]

```
CALL snowflake.trust_center.set_configuration(
    'ENABLED', 'TRUE', 'AI_SECURITY', false);
```

"One command. That's all it takes."

3.3 Show What AI Security Checks

```
SELECT NAME, SHORT_DESCRIPTION FROM snowflake.trust_center.scanners
WHERE SCANNER_PACKAGE_ID = 'AI_SECURITY' ORDER BY NAME;
```

"Four scanners for real-world AI security:"

- **Cortex AI Guardrails** -- prompt injection protection enabled?
- **Cortex Code PAT Usage** -- PATs scoped with role restrictions and network policies?
- **Cortex Search Service Privileged Roles** -- search services owned by admin?
- **Sensitive Data Accessed by Agent** -- agents touching classified data?

"This is agent security -- built into the platform."

3.4 Run AI Security Scanners

```
CALL snowflake.trust_center.execute_scanner('AI_SECURITY');

SELECT SCANNER_NAME, SEVERITY, TOTAL_AT_RISK_COUNT,
       UPPER(STATE) AS STATE
FROM snowflake.trust_center.findings
```

```
WHERE SCANNER_PACKAGE_ID = 'AI_SECURITY'  
ORDER BY END_TIMESTAMP DESC LIMIT 10;
```

"Scanners running. Findings appear alongside CIS and Security Essentials -- all in one place."

>> Transition: The final piece is threat detection.

Act 4: Threat Intelligence -- Detection Scanners

Minutes 7:30 - 10:00

"We've covered platform security, data protection, agent security. The final piece: real-time threat detection."

4.1 Enable Threat Intelligence

```
CALL snowflake.trust_center.set_configuration(
    'ENABLED', 'TRUE', 'THREAT_INTELLIGENCE', false);
```

"Threat Intelligence is now enabled."

4.2 Show Detection Scanners

```
SELECT NAME, SHORT_DESCRIPTION FROM snowflake.trust_center.scanners
WHERE SCANNER_PACKAGE_ID = 'THREAT_INTELLIGENCE' ORDER BY NAME;
```

"18 scanners across four categories -- not configuration checks, active threat detections."

Identity & Auth (6 scanners):

- **Login Protection** -- logins from known malicious IP addresses
- **Dormant User Login** -- inactive accounts suddenly waking up
- **Users with High Volume of Authentication Failures** -- brute force attempts
- **Human User MFA Readiness** -- migrate away from password-only sign-ins
- **Service User Passwordless Readiness** -- legacy service accounts still using passwords
- **Password Sign-In Without MFA** -- users bypassing MFA

Privilege Monitoring (2 scanners):

- **MANAGE GRANTS Privilege Monitoring** -- who can grant access
- **Users with new Admin Privilege Grants** -- new admin escalations

Anomaly Detection (3 scanners):

- **Users with unusual application sessions** -- sessions from unusual apps
- **Users with Long-Running Queries** -- suspicious long-running queries
- **Users with High Volume of Job Failures** -- high job failure rates

Data & Config Protection (7 scanners):

- **Sensitive Parameter Protection** -- data movement safeguards disabled

- **Share Exposure Monitoring** -- new data share exposures
- **SCIM Token Creation Monitoring** -- new SCIM token creations
- **Security Integration Monitoring** -- security integration changes
- **Network Policy Configurations** -- network policy changes
- **Authentication Policy Changes** -- authentication policy modifications
- **Sensitive Policy Changes** -- session and password policy changes

"From knowing what's misconfigured to knowing what's actually happening in your account."

4.3 Run and Show Full Picture

```
CALL snowflake.trust_center.execute_scanner('THREAT_INTELLIGENCE');

SELECT SCANNER_PACKAGE_NAME, SEVERITY,
       COUNT(*) AS FINDING_COUNT,
       SUM(TOTAL_AT_RISK_COUNT) AS TOTAL_AT_RISK
FROM snowflake.trust_center.findings
WHERE UPPER(STATE) = 'OPEN' AND TOTAL_AT_RISK_COUNT > 0
GROUP BY SCANNER_PACKAGE_NAME, SEVERITY
ORDER BY SCANNER_PACKAGE_NAME;
```

"CIS Benchmarks for compliance. Security Essentials for hygiene. AI Security for agent guardrails. Threat Intelligence for real-time detection. All four packages, every at-risk entity, one place. Proactive, enterprise-grade security for data and AI. Built in, not bolted on."

[Switch back to slides -- Slide 7: THANK YOU]