Α	AMPERE	KW	KILOWATT	Т	TUNNEL VISOR	L3S8"	3 SECTION 8"(203.2 mm) RED, YELLOW, GREEN LOUVER ON SIGNAL FACE.
APS	ACCESSIBLE PEDESTRIAN SIGNALS	LGT	LIGHT	TS	TRAFFIC SIGNAL	7040"	
APS-2W	ACCESSIBLE PEDESTRIAN SIGNALS, 2 WIRE SYSTEM.	LUM	LUMINAIRE	TSP	TRANSIT SIGNAL PRIORITY EQUIPMENT	3S12"	3 SECTION 12"(304.8 mm), RED, YELLOW, GREEN
APS-4W	ACCESSIBLE PEDESTRIAN SIGNALS, 4 WIRE SYSTEM.	M	METER	TP	TROLLEY POLE	3S12"LA	3 SECTION 12"(304.8 mm), RED, YELLOW, GREEN (ALL LEFT ARROWS)
ATS	AUTOMATIC TRANSFER SWITCH	MAS	MAST ARM MOUNTED VEHICLE SIGNALS SIDE MOUNTED	V	VOLTAMBEDE	7040"DA	3 SECTION 12"(304.8 mm), RED, YELLOW, GREEN
A.T.&T. AWG	AMERICAN TELEPHONE COMPANY AMERICAN WIRE GAUGE	MAC	MAST ARM MOUNTED VEHICLE SIGNALS	VA VDS	VOLTAMPERE VIDEO DETECTION SYSTEM CAMERA	3S12"RA	(ALL RIGHT ARROWS)
BP	SIGNAL BACKPLATE		WITH CONDULET	U.O.N., UON	UNLESS OTHERWISE NOTED	3S12"GRA	3 SECTION 12"(304.8 mm) RED, YELLOW, GREEN
BSCW	BARE STRANDED COPPER WIRE	METS	MAYOR'S EMERGENCY TELEPHONE SYSTEM	VEH	VEHICLE	7040"004	RIGHT ARROW
С	CONDUIT	mm	MILLIMETER	VMS	VARIABLE MESSAGE SIGN	3S12"GSA	3 SECTION 12"(304.8 mm) RED, YELLOW, GREEN STRAIGHT ARROW
CAB	CABINET	(N)	NEW	w	WATT	3S12"FY	3 SECTION 12"(304.8 mm) RED, YELLOW,
CCTV	CLOSED CIRCUIT TELEVISION CAMERA	NIC NTS	NOT IN CONTRACT NOT TO SCALE				FLASHING YELLOW
CKT	CIRCUIT	NIS OH	OVERHEAD	WM	WALKING MAN	L3S12"	3 SECTION 12"(304.8 mm) RED, YELLOW, GREEN LOUVER ON SIGNAL FACE.
СВ	CIRCUIT BREAKER			WP	WOOD POLE	PV3S12"	PROGRAMMED VISIBILITY, 3 SECTION 12"
CO	CONDUIT ONLY	PAC	PACIFIC BELL CO.	WPR	WEATHERPROOF	. , , , , ,	(304.8 mm), RED, YELLOW, GREEN
CTSP CTSS	STATE OF CALIFORNIA, DEPARTMENT OF TRANSPORTATION, STANDARD PLANS AND	PG&E, PGE	PACIFIC GAS AND ELECTRIC COMPANY	Y	YELLOW	PV3S12"RA	PROGRAMMED VISIBILITY, 3 SECTION 12" (304.8 mm), RED RIGHT ARROW, YELLOW RIGHT A
0122	STANDARD SPECIFICATIONS.	PED	PEDESTRIAN	TV-X	VEHICLE AND PEDESTRIAN SIGNAL POLE		GREEN RIGHT ARROW, TELLOW RIGHT A
DLC	DETECTOR LEAD—IN CABLE	PED(S) XING	PEDESTRIAN CROSSING	SV-X TP-X	MOUNTING DESIGNATIONS. SEE CTSP ES-4A, ES-4B, ES-4C, ES-4D EXCEPT USE U-BOLTS IN	400" \	4 CENTION 9"(007.0) DED VELLOW ODER!
		PPB	PEDESTRIAN PUSH BUTTON	SP-X J	LIEU OF POLE PLATES AS APPLICABLE.	4S8"-X	4 SECTION 8"(203.2 mm), RED, YELLOW, GREEN, AND GREEN "X" FOR MUNI
DLW	DETECTOR LOOP WIRES		PEDESTRIAN PUSH BUTTON POST (POLE)	EB \	TRACCIO DIRECTIONI CUOLI AO CAOT ROUNTS	4S8"GRA	4 SECTION 8"(203.2 mm), RED, YELLOW, GREEN, AND 12"(304.8 mm) GREEN RIGHT ARROW
DTIS	DEPT. OF TELECOMMUNICATIONS AND INFORMATION SERVICES	PPBP	·	WB NB	TRAFFIC DIRECTION SUCH AS EAST BOUND, WEST BOUND, NORTH BOUND AND		AND 12"(304.8 mm) GREEN RIGHT ARROW
DWG	DRAWING	PVC PVC	PROGRAMMED VISIBILITY POLYVINYL CHLORIDE	SB	SOUTH BOUND.	4S12"GLA	4 SECTION 12"(304.8 mm), RED, YELLOW, GREEN
		R	RED	4 4 60	CALTDANC TYPE OF CIONAL CTANDARD		AND GREEN LEFT ARROW
(E) EXT	EXISTING EXTERNAL	R/C	REMOVE FROM SITE OF WORK AS	1-A (X)	CALTRANS TYPE OF SIGNAL STANDARD. SEE CTSP.	L4S12"GLA	4 SECTION 12"(304.8 mm), RED, YELLOW, GREEN GREEN LEFT ARROW. LOUVER ON GREEN BALL ON
			CONTRACTOR'S PROPERTY	12/C	12-CONDUCTOR CABLE	4S12"-GRA,GLA	4 SECTION 12"(304.8 mm), RED, YELLOW, GREEN
FA	FIRE ALARM	RH	RED HAND	XX-X-100	CALTRANS TYPE OF SIGNAL STANDARD WITH	1012 Olvigoth	RIGHT ARROW AND GREEN LEFT ARROW
FC F/I	FULL CIRCLE VISOR FURNISH AND INSTALL UNDER THIS	RLC	RED LIGHT CAMERA		SIGNAL MAST ARM. SEE CTSP.	4S12"GRA	4 SECTION 12"(304.8 mm), RED, YELLOW, GREEN
г/1	CONTRACT	(R)	RELOCATED	1S-IN	1 SECTION INCANDESCENT PEDESTRIAN SIGNAL	40407014	GREEN RIGHT ARROW
FRH	FLASHING RED HAND	R/R	REMOVE AND RELOCATE, OR REMOVE AND REINSTALL AS APPLICABLE	1S-LED	1 SECTION LIGHT EMITTING DIODES (LED)	4S12"GLA	4 SECTION 12"(304.8 mm), RED, YELLOW, GREEN GREEN LEFT ARROW
FUT, (F)	FUTURE	RRFB	RECTANGULAR RAPID FLASHING		PEDESTRIAN SIGNAL	PV4S12"GLA	PROGRAMMED VISIBILITY, 4 SECTION 12"(304.8 mr
HDPE	HIGH DENSITY POLYETHELYNE	IIII D	BEACON			I VISIZ OLA	RED, YELLOW, GREEN, & GREEN LEFT ARROW
HVV	HIGH VOLTAGE VAULT	R/S	REMOVE AND SALVAGE AS CITY'S	1S-COUNT	1 SECTION COUNTDOWN TIMER LED	5S12"GYRA	5 SECTION 12"(304.8 mm), RED, YELLOW, GREEN, YELLOW RIGHT ARROW & GREEN RIGHT ARROW
HPS	HIGH PRESSURE SODIUM	173	PROPERTY	4040°ED	PEDESTRIAN SIGNAL 1 SECTION 12"(304.8mm), FLASHING RED		
HZ	HERTZ	R/W	RIGHT OF WAY	1S12 " FR	· · · · · · · · · · · · · · · · · · ·	5S12"YGLA	5 SECTION 12"(304.8 mm), RED, YELLOW, GREEN YELLOW LEFT ARROW & GREEN LEFT ARROW
G	GREEN	SCGW	STRANDED COPPER GROUND WIRE	1S12"FY 1S12"-GX	1 SECTION 12"(304.8mm), FLASHING YELLOW 1 SECTION 12"(304.8mm), GREEN "X" FOR RAILROAD	PV5S12"YGLA	PROGRAMMED VISIBILITY, 5 SECTION 12"(304.8 mm
GND	GROUND	SL	STREET LIGHT	2S12"-X	2 SECTION 12"(304.8mm), RED "X" AND	FVJS1Z IGLA	RED, YELLOW, GREEN, YELLOW LEFT ARROW,
		SP	SPARE	2312 -7	GREEN "X" FOR RAILROAD		AND GREEN LEFT ARROW
GRSC	GALVANIZED RIGID STEEL CONDUIT			358"	3 SECTION 8"(203.2 mm), RED, YELLOW, GREEN	PV5S12"-GLA,GRA	PROGRAMMED VISIBILITY, 5 SECTION 12"(304.8 mm
IC	INTERSECTION CONTROLLER	SPDPWSF	STANDARD PLAN, DEPARTMENT OF PUBLIC WORKS, CITY AND COUNTY OF SAN FRANCISCO.	3S8"FY	3 SECTION 8"(203.2 mm) RED, YELLOW, FLASHING YELLOW		RED, YELLOW, GREEN, GREEN LEFT ARRÒW, AND GREEN RIGHT ARROW
I/P	IN PLACE OF				I DIGITING I LLLOW		
JB	JUNCTION BOX	SSDPWSF	STANDARD SPECIFICATION, DEPARTMENT OF PUBLIC WORKS, CITY AND COUNTY OF SAN FRANCISCO.				
KVA	KILOVOLTAMPERE						
		SM	SURVEY MONUMENT				
		ST	STEEL POLE				
		SW	SWITCH				
	REFERENCE INFORMATION & FILE NO. OF SURVEYS	AND COUNTY	BUREAU OF ENGINEERING Acting Section Mgr:	o / CHUAO	DESIGNED: DATE: BR 12/2021 SCALE: NONE	MISSION S'	T AND GENEVA AVE SOURC
			CITY & COUNTY OF SAN FRANCISCO	12/2021	DRAWN: DATE: NONE		DRAWIN
		SAN FRAN	Deputy Bureau Mgr:	LESLEY WONG	I Che vao z		
		PUB	SAN FRANCISCO PUBLIC WORKS	12/09/2021	BR 12/2021 NO. E19134 SHEET OF SHEETS		FILE NO

ESH JO: 11711 CONTRACT NO. 10035213